



## Safety Data Sheet

Copyright, 2025, 3M India Limited. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	31-0101-1	<b>Version number:</b>	1.00
<b>Issue Date:</b>	04/02/2025	<b>Supersedes date:</b>	Initial issue.

This Safety Data Sheet has been prepared in accordance with the GHS guidelines & India Hazardous substances (Classification, Labeling & Packaging) Draft Rules 2011.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Finesse-it™ Ultra Fine [100]

#### Product Identification Numbers

60-4402-4017-8      60-4402-4176-2      UU-0127-5526-8

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Industrial use.

#### 1.3. Supplier's details

**Address:** 3M India Limited, plot-48-51, Electronic city, Hosur road, Bangalore-560100  
**Telephone:** 080-45543000, contact Product EHS team  
**E Mail:** productehs.in@mmm.com  
**Website:** <http://solutions.3mindia.co.in>

#### 1.4. Emergency telephone number

080-45543000 (Contact hours: 8:00 AM to 5:00 PM)

### SECTION 2: Hazard identification

Under MSIHC Rules, information is noted below on flammability, acute toxicity and explosivity relevant to this product. In line with international standards, information on other hazard classes and associated precautionary statements relevant to this product are included as well.

#### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2.  
Skin Sensitizer: Category 1A.  
Specific Target Organ Toxicity (single exposure): Category 3.  
Acute Aquatic Toxicity: Category 2.  
Chronic Aquatic Toxicity: Category 2.

#### 2.2. Label elements

##### Signal Word

Warning

**Symbols**

Exclamation mark | Environment |

**Pictograms****HAZARD STATEMENTS:**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS****Prevention:**

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280E	Wear protective gloves.

**Response:**

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

**2.3. Other hazards**

Aspiration classification does not apply due to the viscosity of the product.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>% by Wt</b>
Water	7732-18-5	40 - 60
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	10 - 25
Hydrotreated Heavy Naphtha	64742-48-9	10 - 25
Hydrotreated Light Paraffinic Distillates	64742-55-8	10 - 25
Additive	Trade Secret	1 - 3
Triethanolamine	102-71-6	0.5 - 1.5
Glycerin	56-81-5	0.5 - 1.5
Methylisothiazolinone	2682-20-4	< 0.02

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get

medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable Extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Hydrocarbons.

Carbon monoxide.

Carbon dioxide.

Oxides of nitrogen.

**Condition**

During combustion.

During combustion.

During combustion.

During combustion.

**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use PPE - Exposure Assessment Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate

solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing of dust created by sanding, grinding or machining. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Keep from freezing. Store away from oxidising agents.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Triethanolamine	102-71-6	ACGIH	TWA:5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

To minimise the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Wear appropriate gloves to minimise risk of injury to skin from contact with dust or physical abrasion from grinding or sanding. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

**Respiratory protection**

Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Color</b>	White
<b>Odor</b>	Light Citrus
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	7 - 9
<b>Melting point/Freezing point: NA</b>	<i>Not applicable.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	$\geq 100$ °C
<b>Flash point</b>	No flash point
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	<i>No data available.</i>
<b>Relative density</b>	$\geq 1.1$ [Ref Std: WATER=1]
<b>Water solubility</b>	Negligible
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Kinematic Viscosity</b>	<i>No data available.</i>
<b>Volatile organic compounds (VOC)</b>	20 % weight
<b>Percent volatile</b>	85 % weight [Details: Calculated including water ]
<b>VOC less H2O &amp; exempt solvents</b>	775.3 g/l [Test Method: tested per EPA method 24]

**Bulk density***No data available.***Particle Characteristics***Not applicable.***SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.4 Conditions to avoid**

Sparks and/or flames.

Heat.

**10.5 Incompatible materials**

Strong oxidising agents.

**10.6 Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin contact**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye contact**

Dust created by grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

### Additional Health Effects:

### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

### Additional information:

This document covers only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be considered.

### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Hydrotreated Heavy Naphtha	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Hydrotreated Heavy Naphtha	Dermal	Rabbit	LD50 > 3,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide Mineral (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Heavy Naphtha	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Light Paraffinic Distillates	Dermal	similar compounds	LD50 > 2,000 mg/kg
Hydrotreated Light Paraffinic Distillates	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 5.53 mg/l
Hydrotreated Light Paraffinic Distillates	Ingestion	similar compounds	LD50 > 5,000 mg/kg
Triethanolamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
Triethanolamine	Ingestion	Rat	LD50 9,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Methylisothiazolinone	Dermal	Rat	LD50 242 mg/kg
Methylisothiazolinone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.11 mg/l
Methylisothiazolinone	Ingestion	Rat	LD50 120 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation

Hydrotreated Heavy Naphtha	Rabbit	Irritant
Hydrotreated Light Paraffinic Distillates	similar compounds	No significant irritation
Triethanolamine	Rabbit	Minimal irritation
Glycerin	Rabbit	No significant irritation
Methylisothiazolinone	Rabbit	Corrosive

### Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Hydrotreated Heavy Naphtha	Rabbit	No significant irritation
Hydrotreated Light Paraffinic Distillates	similar compounds	No significant irritation
Triethanolamine	Rabbit	Mild irritant
Glycerin	Rabbit	No significant irritation
Methylisothiazolinone	Rabbit	Corrosive

### Sensitization:

#### Skin Sensitisation

Name	Species	Value
Hydrotreated Heavy Naphtha	Guinea pig	Not classified
Hydrotreated Light Paraffinic Distillates	similar compounds	Not classified
Triethanolamine	Human	Not classified
Glycerin	Guinea pig	Not classified
Methylisothiazolinone	Human and animal	Sensitising

#### Photosensitisation

Name	Species	Value
Methylisothiazolinone	Human and animal	Not sensitizing

### Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide Mineral (non-fibrous)	In Vitro	Not mutagenic
Hydrotreated Heavy Naphtha	In vivo	Not mutagenic
Hydrotreated Heavy Naphtha	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Light Paraffinic Distillates	In Vitro	Not mutagenic
Triethanolamine	In Vitro	Not mutagenic
Triethanolamine	In vivo	Not mutagenic
Methylisothiazolinone	In vivo	Not mutagenic
Methylisothiazolinone	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity



Name	Route	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Inhalation	Rat	Not carcinogenic
Hydrotreated Heavy Naphtha	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Heavy Naphtha	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Triethanolamine	Dermal	Multiple animal species	Not carcinogenic
Triethanolamine	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Methylisothiazolinone	Dermal	Mouse	Not carcinogenic
Methylisothiazolinone	Ingestion	Rat	Not carcinogenic

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrotreated Heavy Naphtha	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
Triethanolamine	Ingestion	Not classified for development	Mouse	NOAEL 1,125 mg/kg/day	during organogenesis
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Methylisothiazolinone	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Methylisothiazolinone	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Methylisothiazolinone	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrotreated Heavy Naphtha	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Heavy Naphtha	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Heavy Naphtha	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Hydrotreated Heavy Naphtha	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Methylisothiazolinone	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydrotreated Heavy Naphtha	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Hydrotreated Heavy Naphtha	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Hydrotreated Heavy Naphtha	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Hydrotreated Heavy Naphtha	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Hydrotreated Heavy Naphtha	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Triethanolamine	Dermal	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,000 mg/kg/day	2 years
Triethanolamine	Dermal	liver	Not classified	Mouse	NOAEL 4,000 mg/kg/day	13 weeks
Triethanolamine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,000 mg/kg/day	2 years
Triethanolamine	Ingestion	liver	Not classified	Guinea pig	NOAEL 1,600 mg/kg/day	24 weeks
Glycerin	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years

**Aspiration Hazard**

Name	Value
Hydrotreated Heavy Naphtha	Aspiration hazard
Hydrotreated Light Paraffinic Distillates	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	N/A	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrotreated Heavy Naphtha	64742-48-9	Fathead minnow	Estimated	96 hours	LL50	8.2 mg/l
Hydrotreated Heavy Naphtha	64742-48-9	Green algae	Estimated	72 hours	EL50	3.1 mg/l
Hydrotreated Heavy Naphtha	64742-48-9	Water flea	Estimated	48 hours	EL50	4.5 mg/l
Hydrotreated Heavy Naphtha	64742-48-9	Green algae	Estimated	72 hours	NOEL	0.5 mg/l
Hydrotreated Heavy Naphtha	64742-48-9	Water flea	Estimated	21 days	NOEL	2.6 mg/l
Hydrotreated Light Paraffinic Distillates	64742-55-8	Fathead minnow	Estimated	96 hours	LL50	>100 mg/l
Hydrotreated Light Paraffinic Distillates	64742-55-8	Water flea	Estimated	48 hours	EL50	>100 mg/l
Hydrotreated Light Paraffinic Distillates	64742-55-8	Green algae	Estimated	72 hours	NOEL	100 mg/l
Hydrotreated Light Paraffinic Distillates	64742-55-8	Water flea	Estimated	21 days	NOEC	10 mg/l
Additive	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Glycerin	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerin	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
Glycerin	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
Triethanolamine	102-71-6	Activated sludge	Experimental	3 hours	IC50	>1,000 mg/l
Triethanolamine	102-71-6	Fathead minnow	Experimental	96 hours	LC50	11,800 mg/l
Triethanolamine	102-71-6	Green algae	Experimental	72 hours	ErC50	512 mg/l
Triethanolamine	102-71-6	Water flea	Experimental	48 hours	EC50	609.98 mg/l
Triethanolamine	102-71-6	Green algae	Experimental	72 hours	ErC10	26 mg/l
Triethanolamine	102-71-6	Water flea	Experimental	21 days	NOEC	16 mg/l
Methylisothiazolin one	2682-20-4	Diatom	Experimental	72 hours	ErC50	0.099 mg/l
Methylisothiazolin one	2682-20-4	Green algae	Experimental	96 hours	ErC50	0.23 mg/l
Methylisothiazolin one	2682-20-4	Mysid Shrimp	Experimental	96 hours	LC50	1.81 mg/l
Methylisothiazolin one	2682-20-4	Sheepshead Minnow	Experimental	96 hours	LC50	25.1 mg/l
Methylisothiazolin one	2682-20-4	Water flea	Experimental	48 hours	LC50	0.934 mg/l
Methylisothiazolin one	2682-20-4	Blackworm	Experimental	28 days	NOEC	25 mg/kg (Dry Weight)
Methylisothiazolin one	2682-20-4	Diatom	Experimental	72 hours	ErC10	0.04 mg/l
Methylisothiazolin	2682-20-4	Fathead minnow	Experimental	33 days	NOEC	2.1 mg/l

one						
Methylisothiazolin one	2682-20-4	Green algae	Experimental	96 hours	NOEC	0.12 mg/l
Methylisothiazolin one	2682-20-4	Water flea	Experimental	21 days	NOEC	0.044 mg/l
Methylisothiazolin one	2682-20-4	Activated sludge	Experimental	3 hours	EC50	41 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Data not available-insufficient	N/A	N/A	N/A	N/A
Hydrotreated Heavy Naphtha	64742-48-9	Estimated Biodegradation	28 days	BOD	10 %BOD/ThOD	OECD 301D - Closed bottle test
Hydrotreated Light Paraffinic Distillates	64742-55-8	Estimated Biodegradation	28 days	CO2 evolution	22 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Additive	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Glycerin	56-81-5	Experimental Biodegradation	14 days	BOD	63 %BOD/ThOD	OECD 301C - MITI test (I)
Triethanolamine	102-71-6	Experimental Biodegradation	19 days	Dissolv. Organic Carbon Deplet	96 %removal of DOC	similar to OECD 301E
Methylisothiazolin one	2682-20-4	Experimental Biodegradation	29 days	CO2 evolution	50 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Methylisothiazolin one	2682-20-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH

## 12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Heavy Naphtha	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Light Paraffinic Distillates	64742-55-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Additive	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerin	56-81-5	Experimental Bioconcentration		Log Kow	-1.75	similar to OECD 107
Triethanolamine	102-71-6	Experimental BCF - Fish	42 days	Bioaccumulation factor	<3.9	similar to OECD 305
Methylisothiazolin one	2682-20-4	Analogous Compound BCF - Fish	56 days	Bioaccumulation factor	5.75	
Methylisothiazolin one	2682-20-4	Experimental Bioconcentration		Log Kow	-0.486	OECD 107 log Kow shke flsk mtd

## 12.4. Mobility in soil

Please contact manufacturer for more details

## 12.5 Other Adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### **13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

The substrate that was abraded must be considered as a factor in the disposal method for this product. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## **SECTION 14: Transport Information**

Not hazardous for transportation.

### **Air Transport (IATA) Regulations**

**UN No** Not applicable

**Proper Shipping Name** Not applicable

**Hazard Class/Division** Not applicable

**Subsidiary Risk** Not applicable

**Packing Group:** Not applicable

### **Marine Transport (IMDG)**

**UN No** Not applicable

**Proper Shipping Name** Not applicable

**Hazard Class/Division** Not applicable

**Subsidiary Risk** Not applicable

**Packing Group:** Not applicable

**Environmental Hazards:** Not applicable

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Global inventory status**

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### **Applicable Environmental, Health and Safety Regulations**

The Manufacture, Storage and Import of Hazardous Chemical Rules, 1989

The following ingredients are listed as hazardous on Part II of Schedule I of the India Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) rules

None.

## **SECTION 16: Other information**

### **NFPA Hazard Classification**

**Health:** 2    **Flammability:** 1    **Instability:** 0    **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision information:**

No revision information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into India, you are responsible to comply with all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

**3M India SDSs are available at <http://solutions.3mindia.co.in>**