



## Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	08-9432-9	<b>Version number:</b>	16.04
<b>Issue Date:</b>	2025/01/20	<b>Supersedes Date:</b>	2024/07/15

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Polyurethane Sealant 540 (Various Colours)

##### Product Identification Numbers

62-5261-5230-1	62-5261-5231-9	62-5261-5235-0	62-5261-5236-8	62-5263-5230-7
62-5263-5231-5	62-5263-5235-6	62-5263-5236-4	62-5484-3530-4	62-5484-3531-2
62-5484-3532-0	62-5484-3533-8	62-5484-3930-6	62-5484-3931-4	62-5484-3932-2
62-5484-3936-3	62-5484-3937-1	62-5484-3938-9	62-5484-5230-9	62-5484-5231-7
62-5484-5232-5	62-5484-5235-8	62-5484-5236-6	62-5484-5237-4	62-5484-5238-2
62-5484-8530-9	62-5484-8531-7	62-5484-9531-6	62-5485-3530-1	62-5485-3531-9
62-5485-3532-7	62-5485-3535-0	62-5485-3536-8	62-5485-3537-6	62-5485-3930-3
62-5485-3931-1	62-5485-3932-9	62-5485-3933-7	62-5485-3935-2	62-5485-3936-0
62-5485-3937-8	62-5485-3938-6	62-5485-5230-6	62-5485-5231-4	62-5485-5232-2
62-5485-5235-5	62-5485-5236-3	62-5485-5237-1	62-5485-5238-9	62-5485-8530-6
62-5485-8531-4	62-5485-9530-5	62-5485-9531-3	62-5485-9532-1	62-5486-3530-9
62-5486-3531-7	62-5486-3532-5	62-5486-3930-1	62-5486-3931-9	62-5486-3932-7
62-5486-3933-5	62-5486-3936-8	62-5486-3937-6	62-5486-5230-4	62-5486-5231-2
62-5486-5232-0	62-5486-5235-3	62-5486-5236-1	62-5486-5237-9	62-5486-5238-7
62-5486-8530-4	62-5486-8531-2	62-5486-9530-3	62-5486-9531-1	DS-2729-9107-8
DS-2729-9108-6	DS-2729-9138-3	DS-2729-9139-1	DS-2729-9143-3	DS-2729-9144-1
DS-2729-9147-4	DS-2729-9148-2	DS-2729-9151-6	DS-2729-9152-4	FI-3000-0000-2
FI-3000-0005-1	FI-3000-0008-5	FI-3000-0148-9	FI-3000-0149-7	FI-3000-0150-5
FI-3000-0151-3	FI-3000-0152-1	FI-3000-0153-9	FI-3000-0154-7	FI-3000-0155-4
FI-3000-0156-2	FI-3000-0177-8	FI-3000-0270-1	FI-3000-0304-8	FI-3000-0305-5
FI-3000-0418-6	FI-3000-7777-8	GT-5000-9014-4	GT-5000-9015-1	GT-5000-9016-9
GT-5000-9017-7	GT-5000-9018-5	HB-0040-9062-5	HB-0040-9071-6	HB-0040-9978-2
HB-0040-9980-8	HB-0040-9981-6	HB-0040-9982-4	HB-0040-9983-2	HB-0040-9984-0
HB-0040-9985-7	HB-0041-0101-8	HB-0041-0102-6	HB-0041-0103-4	HB-0041-0104-2
HB-0041-0105-9	HB-0041-0106-7	HB-0041-0107-5	HB-0041-0108-3	HB-0041-0109-1
HB-0041-0295-8	HB-0041-4883-7	HB-0041-4884-5	HB-0041-5119-5	HB-0041-5120-3
HB-0041-5182-3	HB-0041-5447-0	HB-0041-5448-8	HB-0041-5449-6	HB-0041-5463-7
HB-0041-5464-5	HB-0041-9896-4	JS-3000-5081-7	KS-9990-0648-3	KS-9990-0649-1
KS-9990-0650-9	KS-9990-0651-7	KS-9990-0652-5	XS-0024-0100-7	

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Adhesive

**Specific Use**

General purpose adhesive sealant

**Restrictions on use**

Not applicable

**1.3. Supplier's details**

**Company:** 3M Canada Company  
**Division:** Industrial Adhesives and Tapes Division  
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1  
**Telephone:** (800) 364-3577  
**Website:** www.3M.ca

**1.4. Emergency telephone number**

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

**SECTION 2: Hazard identification**

**2.1. Classification of the substance or mixture**

Respiratory Sensitizer: Category 1.  
Skin Sensitizer: Category 1A.  
Carcinogenicity: Category 2.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

**2.2. Label elements**

**Signal word**

Danger

**Symbols**

Exclamation mark | Health Hazard |

**Pictograms**



**Hazard statements**

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer.

Causes damage to organs: sensory organs |

Causes damage to organs through prolonged or repeated exposure: nervous system |

May cause damage to organs through prolonged or repeated exposure: sensory organs |

**Precautionary statements**

**Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. In case of inadequate ventilation wear respiratory protection. Wear protective

### 3M™ Polyurethane Sealant 540 (Various Colours)

gloves. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

#### Storage:

Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other hazards

None known.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Polyurethane Polymer	Trade Secret	25 - 60	Not Applicable
Plasticizer Mixture	Trade Secret	20 - 40	Not Applicable
Poly(Vinyl Chloride)	9002-86-2	20 - 40	Ethene, chloro-, homopolymer
Xylene	1330-20-7	3 - 7 Trade Secret *	Dimethylbenzene
Calcium Oxide	1305-78-8	< 5	Calcium oxide (CaO)
Hydrotreated Light Petroleum Distillates	64742-47-8	< 5	No Data Available
Titanium Dioxide	13463-67-7	< 5	Titanium oxide (TiO <sub>2</sub> )
Ethylbenzene	100-41-4	0.1 - 1.5 Trade Secret *	Benzene, ethyl-
p,p'-Methylenebis(phenyl isocyanate)	101-68-8	0.1 - 1 Trade Secret *	Benzene, 1,1'-methylenebis[4-isocyanato-
Carbon Black	1333-86-4	< 0.5	Carbon black
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	< 0.1	Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	82919-37-7	< 0.1	Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester

Polyurethane Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

Plasticizer Mixture is a non-hazardous Trade Secret material according to WHMIS criteria.

\*The actual concentration of this ingredient has been withheld as a trade secret.

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

##### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

**5.2. Unsuitable extinguishing media**

None Determined

**5.3. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Carbon monoxide  
Carbon dioxide  
Hydrogen Chloride  
Hydrogen Cyanide  
Oxides of Nitrogen  
Oxides of Sulfur

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.4. Special protection actions for fire-fighters**

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	
p,p'-Methylenebis(phenyl isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
Calcium Oxide	1305-78-8	ACGIH	TWA:2 mg/m3	
Xylene	1330-20-7	ACGIH	TWA:20 ppm	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	SKIN
Poly(Vinyl Chloride)	9002-86-2	ACGIH	TWA(respirable fraction):1 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Solid
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Black, Gray, White
<b>Odour</b>	Mild Xylene
<b>Odour threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point/Freezing point</b>	<i>No Data Available</i>
<b>Boiling point</b>	≥136 °C
<b>Flash Point</b>	No flash point
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapour Pressure</b>	<i>Not Applicable</i>
<b>Relative Vapour Density</b>	<i>Not Applicable</i>
<b>Density</b>	1.17 g/ml
<b>Relative density</b>	1.17 [Ref Std: WATER=1]
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	≥200 °C
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Kinematic Viscosity</b>	256,410 mm <sup>2</sup> /sec
<b>Volatile Organic Compounds</b>	<i>No Data Available</i>
<b>Percent volatile</b>	<i>No Data Available</i>
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	54 g/l [Test Method: tested per EPA method 24]
<b>Molecular weight</b>	<i>No Data Available</i>

<b>Particle Characteristics</b>	<i>Not Applicable</i>
---------------------------------	-----------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Amines  
Alcohols  
Water

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

**Prolonged or repeated exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

<b>Ingredient</b>	<b>CAS No.</b>	<b>Class Description</b>	<b>Regulation</b>
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Additional Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

<b>Name</b>	<b>Route</b>	<b>Species</b>	<b>Value</b>
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Plasticizer Mixture	Dermal	Rat	LD50 > 1,000 mg/kg
Plasticizer Mixture	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Vinyl Chloride)	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(Vinyl Chloride)	Ingestion		LD50 estimated to be > 5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Calcium Oxide	Ingestion	Rat	LD50 > 2,500 mg/kg
Calcium Oxide	Dermal	similar compounds	LD50 > 2,500 mg/kg
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 15,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	similar compounds	LD50 > 5,000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
p,p'-Methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
p,p'-Methylenebis(phenyl isocyanate)	Inhalation-Dust/Mist	Rat	LC50 0.368 mg/l



**3M™ Polyurethane Sealant 540 (Various Colours)**

	(4 hours)		
p,p'-Methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Ingestion	Rat	LD50 3,125 mg/kg
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	Ingestion	Rat	LD50 3,125 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Poly(Vinyl Chloride)	Professional judgement	No significant irritation
Xylene	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation
Calcium Oxide	Human	Corrosive
Hydrotreated Light Petroleum Distillates	similar compounds	Mild irritant
Ethylbenzene	Rabbit	Mild irritant
p,p'-Methylenebis(phenyl isocyanate)	official classification	Irritant
Carbon Black	Rabbit	No significant irritation
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Rabbit	Minimal irritation
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Overall product	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation
Calcium Oxide	Rabbit	Corrosive
Hydrotreated Light Petroleum Distillates	similar compounds	No significant irritation
Ethylbenzene	Rabbit	Moderate irritant
p,p'-Methylenebis(phenyl isocyanate)	official classification	Severe irritant
Carbon Black	Rabbit	No significant irritation
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Rabbit	Mild irritant
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
Titanium Dioxide	Human and animal	Not classified
Hydrotreated Light Petroleum Distillates	similar compounds	Not classified
Ethylbenzene	Human	Not classified

**3M™ Polyurethane Sealant 540 (Various Colours)**

p,p'-Methylenebis(phenyl isocyanate)	Mouse	Sensitizing
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Guinea pig	Sensitizing
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	Guinea pig	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
p,p'-Methylenebis(phenyl isocyanate)	Human	Sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Poly(Vinyl Chloride)	In Vitro	Not mutagenic
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Calcium Oxide	In Vitro	Not mutagenic
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
p,p'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	In vivo	Not mutagenic
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	In vivo	Not mutagenic
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Poly(Vinyl Chloride)	Not Specified	Rat	Some positive data exist, but the data are not sufficient for classification
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
p,p'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
------	-------	-------	---------	-------------	-------------------

**3M™ Polyurethane Sealant 540 (Various Colours)**

Poly(Vinyl Chloride)	Not Specified	Not classified for development	Mouse	NOAEL Not available	during gestation
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	prematuring & during gestation
p,p'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Ingestion	Not classified for development	Rat	NOAEL 209 mg/kg/day	prematuring into lactation
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 804 mg/kg/day	prematuring into lactation
Methyl 1,2,2,6,6-Pentamethyl-4-piperidiny) Sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-Pentamethyl-4-piperidiny) Sebacate	Ingestion	Not classified for development	Rat	NOAEL 209 mg/kg/day	prematuring into lactation
Methyl 1,2,2,6,6-Pentamethyl-4-piperidiny) Sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 804 mg/kg/day	prematuring into lactation

**Lactation**

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
Calcium Oxide	Inhalation	respiratory irritation	May cause respiratory irritation	Not available	NOAEL Not available	occupational exposure
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	

**3M™ Polyurethane Sealant 540 (Various Colours)**

p,p'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
--------------------------------------	------------	------------------------	----------------------------------	-------------------------	---------------------	--

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Poly(Vinyl Chloride)	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.013 mg/l	22 months
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydrotreated Light Petroleum Distillates	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrotreated Light Petroleum Distillates	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Hydrotreated Light Petroleum Distillates	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrotreated Light Petroleum Distillates	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Hydrotreated Light Petroleum Distillates	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
Hydrotreated Light Petroleum Distillates	Ingestion	hematopoietic system   eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for	Mouse	NOAEL 1.1 mg/l	103 weeks

**3M™ Polyurethane Sealant 540 (Various Colours)**

			classification			
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart   immune system   respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
p,p'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	28 days
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Ingestion	gastrointestinal tract   liver   immune system   heart   endocrine system   hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	28 days
Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate	Ingestion	gastrointestinal tract   liver   immune system   heart   endocrine system   hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days

**Aspiration Hazard**

Name	Value
Xylene	Aspiration hazard
Hydrotreated Light Petroleum Distillates	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## **SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Global inventory status**

Contact manufacturer for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

## **SECTION 16: Other information**

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	08-9432-9	<b>Version number:</b>	16.04
<b>Issue Date:</b>	2025/01/20	<b>Supersedes Date:</b>	2024/07/15

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**