



Safety Data Sheet

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 08-9432-9 | Version number: | 16.06 |
| Issue Date: | 2025/08/21 | Supersedes Date: | 2025/06/12 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Polyurethane Sealant 540 (Various Colours)

Product Identification Numbers

| | | | | |
|----------------|----------------|----------------|----------------|----------------|
| 62-5261-5230-1 | 62-5261-5231-9 | 62-5261-5235-0 | 62-5261-5236-8 | 62-5263-5230-7 |
| 62-5263-5231-5 | 62-5263-5235-6 | 62-5263-5236-4 | 62-5484-3530-4 | 62-5484-3531-2 |
| 62-5484-3532-0 | 62-5484-3533-8 | 62-5484-3930-6 | 62-5484-3931-4 | 62-5484-3932-2 |
| 62-5484-3936-3 | 62-5484-3937-1 | 62-5484-3938-9 | 62-5484-5230-9 | 62-5484-5231-7 |
| 62-5484-5232-5 | 62-5484-5235-8 | 62-5484-5236-6 | 62-5484-5237-4 | 62-5484-5238-2 |
| 62-5484-8530-9 | 62-5484-8531-7 | 62-5484-9531-6 | 62-5485-3530-1 | 62-5485-3531-9 |
| 62-5485-3532-7 | 62-5485-3535-0 | 62-5485-3536-8 | 62-5485-3537-6 | 62-5485-3930-3 |
| 62-5485-3931-1 | 62-5485-3932-9 | 62-5485-3933-7 | 62-5485-3935-2 | 62-5485-3936-0 |
| 62-5485-3937-8 | 62-5485-3938-6 | 62-5485-5230-6 | 62-5485-5231-4 | 62-5485-5232-2 |
| 62-5485-5235-5 | 62-5485-5236-3 | 62-5485-5237-1 | 62-5485-5238-9 | 62-5485-8530-6 |
| 62-5485-8531-4 | 62-5485-9530-5 | 62-5485-9531-3 | 62-5485-9532-1 | 62-5486-3530-9 |
| 62-5486-3531-7 | 62-5486-3532-5 | 62-5486-3930-1 | 62-5486-3931-9 | 62-5486-3932-7 |
| 62-5486-3933-5 | 62-5486-3936-8 | 62-5486-3937-6 | 62-5486-5230-4 | 62-5486-5231-2 |
| 62-5486-5232-0 | 62-5486-5235-3 | 62-5486-5236-1 | 62-5486-5237-9 | 62-5486-5238-7 |
| 62-5486-8530-4 | 62-5486-8531-2 | 62-5486-9530-3 | 62-5486-9531-1 | DS-2729-9107-8 |
| DS-2729-9108-6 | DS-2729-9138-3 | DS-2729-9139-1 | DS-2729-9143-3 | DS-2729-9144-1 |
| DS-2729-9147-4 | DS-2729-9148-2 | DS-2729-9151-6 | DS-2729-9152-4 | FI-3000-0000-2 |
| FI-3000-0005-1 | FI-3000-0008-5 | FI-3000-0148-9 | FI-3000-0149-7 | FI-3000-0150-5 |
| FI-3000-0151-3 | FI-3000-0152-1 | FI-3000-0153-9 | FI-3000-0154-7 | FI-3000-0155-4 |
| FI-3000-0156-2 | FI-3000-0177-8 | FI-3000-0270-1 | FI-3000-0304-8 | FI-3000-0305-5 |
| FI-3000-0418-6 | FI-3000-7777-8 | GT-5000-9014-4 | GT-5000-9015-1 | GT-5000-9016-9 |
| GT-5000-9017-7 | GT-5000-9018-5 | HB-0040-9062-5 | HB-0040-9071-6 | HB-0040-9978-2 |
| HB-0040-9980-8 | HB-0040-9981-6 | HB-0040-9982-4 | HB-0040-9983-2 | HB-0040-9984-0 |
| HB-0040-9985-7 | HB-0041-0101-8 | HB-0041-0102-6 | HB-0041-0103-4 | HB-0041-0104-2 |
| HB-0041-0105-9 | HB-0041-0106-7 | HB-0041-0107-5 | HB-0041-0108-3 | HB-0041-0109-1 |
| HB-0041-0295-8 | HB-0041-4883-7 | HB-0041-4884-5 | HB-0041-5119-5 | HB-0041-5120-3 |
| HB-0041-5182-3 | HB-0041-5447-0 | HB-0041-5448-8 | HB-0041-5449-6 | HB-0041-5463-7 |
| HB-0041-5464-5 | HB-0041-9896-4 | JS-3000-5081-7 | KS-9990-0648-3 | KS-9990-0649-1 |
| KS-9990-0650-9 | KS-9990-0651-7 | KS-9990-0652-5 | XS-0024-0100-7 | |

1.2. Recommended use and restrictions on use

Intended Use

Adhesive

Specific Use

General purpose adhesive sealant

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Industrial Adhesives and Tapes Division
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone: (800) 364-3577
Website: www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1A.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard |

Pictograms



Hazard Statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer.

Causes damage to organs: sensory organs.

Causes damage to organs through prolonged or repeated exposure: nervous system.

May cause damage to organs through prolonged or repeated exposure: sensory organs.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fumes. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and respiratory protection. In case of inadequate ventilation wear respiratory protection.

Response:

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical attention. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---|-------------------|--------------------------|--|
| Polyurethane Polymer | Trade Secret | 25 - 60 | Not Applicable |
| Plasticizer Mixture | Trade Secret | 20 - 40 | Not Applicable |
| Poly(Vinyl Chloride) | 9002-86-2 | 20 - 40 | Ethene, chloro-, homopolymer |
| Xylene | 1330-20-7 | 3 - 7 Trade Secret * | Dimethylbenzene |
| Calcium Oxide | 1305-78-8 | 1 - 5 Trade Secret * | Calcium oxide (CaO) |
| Hydrotreated Light Petroleum Distillates | 64742-47-8 | 1 - 5 Trade Secret * | No Data Available |
| Titanium Dioxide | 13463-67-7 | < 4.7 | Titanium oxide (TiO ₂) |
| Ethylbenzene | 100-41-4 | 0.1 - 1.5 Trade Secret * | Benzene, ethyl- |
| p,p'-Methylenebis(phenyl isocyanate) | 101-68-8 | 0.1 - 1 Trade Secret * | Benzene, 1,1'-methylenebis[4-isocyanato- |
| Carbon Black | 1333-86-4 | < 0.3 | Carbon black |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | 41556-26-7 | < 0.1 | Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | 82919-37-7 | < 0.1 | Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester |

Polyurethane Polymer is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

Plasticizer Mixture is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

Poly(Vinyl Chloride) is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Hydrogen Cyanide
Oxides of Nitrogen
Oxides of Sulfur

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide

mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|----------------------|-------------------|---------------|---|----------------------------|
| Ethylbenzene | 100-41-4 | ACGIH | TWA:20 ppm | |
| Calcium Oxide | 1305-78-8 | ACGIH | TWA:2 mg/m3 | |
| Xylene | 1330-20-7 | ACGIH | TWA:20 ppm | |
| Carbon Black | 1333-86-4 | ACGIH | TWA(inhalable fraction):3 mg/m3 | |
| Titanium Dioxide | 13463-67-7 | ACGIH | TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3 | |
| Poly(Vinyl Chloride) | 9002-86-2 | ACGIH | TWA(respirable fraction):1 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|--|--------------------------|
| Physical state | Solid |
| Specific Physical Form: | Paste |
| Colour | Black, Gray, White |
| Odour | Mild Xylene |
| Odour threshold | <i>No Data Available</i> |
| pH | <i>Not Applicable</i> |
| Melting point/Freezing point | <i>No Data Available</i> |
| Boiling point | ≥ 136 °C |
| Flash Point | No flash point |
| Evaporation rate | <i>No Data Available</i> |
| Flammability | Not Applicable |
| Flammable Limits(LEL) | <i>Not Applicable</i> |
| Flammable Limits(UEL) | <i>Not Applicable</i> |
| Vapour Pressure | <i>Not Applicable</i> |
| Relative Vapour Density | <i>Not Applicable</i> |
| Density | 1.17 g/ml |
| Relative density | 1.17 [Ref Std:WATER=1] |
| Water solubility | Nil |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | ≥ 200 °C |

| | |
|--|---|
| Decomposition temperature | <i>No Data Available</i> |
| Kinematic Viscosity | 256,410 mm ² /sec |
| Volatile Organic Compounds | <i>No Data Available</i> |
| Percent volatile | <i>No Data Available</i> |
| VOC Less H₂O & Exempt Solvents | 54 g/l [<i>Test Method: tested per EPA method 24</i>] |
| Molecular weight | <i>No Data Available</i> |

| | |
|---------------------------------|-----------------------|
| Particle Characteristics | <i>Not Applicable</i> |
|---------------------------------|-----------------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Amines
Alcohols
Water

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction

(non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|-------------------|----------------|-------------------------------|---|
| Carbon black | 1333-86-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Ethylbenzene | 100-41-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Titanium dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|-------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Plasticizer Mixture | Dermal | Rat | LD50 > 1,000 mg/kg |
| Plasticizer Mixture | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Poly(Vinyl Chloride) | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Poly(Vinyl Chloride) | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Xylene | Dermal | Rabbit | LD50 > 4,200 mg/kg |
| Xylene | Inhalation-Vapor (4 hours) | Rat | LC50 29 mg/l |
| Xylene | Ingestion | Rat | LD50 3,523 mg/kg |
| Titanium Dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Dioxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium Dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |
| Calcium Oxide | Ingestion | Rat | LD50 > 2,500 mg/kg |
| Calcium Oxide | Dermal | similar compounds | LD50 > 2,500 mg/kg |
| Hydrotreated Light Petroleum Distillates | Ingestion | Rat | LD50 > 15,000 mg/kg |

3M™ Polyurethane Sealant 540 (Various Colours)

| | | | |
|---|--------------------------------|------------------------|--|
| Hydrotreated Light Petroleum Distillates | Dermal | similar compounds | LD50 > 5,000 mg/kg |
| Ethylbenzene | Dermal | Rabbit | LD50 15,433 mg/kg |
| Ethylbenzene | Inhalation-Vapor (4 hours) | Rat | LC50 17.4 mg/l |
| Ethylbenzene | Ingestion | Rat | LD50 4,769 mg/kg |
| p,p'-Methylenebis(phenyl isocyanate) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| p,p'-Methylenebis(phenyl isocyanate) | Ingestion | Rat | LD50 31,600 mg/kg |
| Carbon Black | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Carbon Black | Ingestion | Rat | LD50 > 8,000 mg/kg |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Dermal | Professional judgement | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Ingestion | Rat | LD50 3,125 mg/kg |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | Dermal | Professional judgement | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | Ingestion | Rat | LD50 3,125 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|-------------------------|---------------------------|
| Poly(Vinyl Chloride) | Professional judgement | No significant irritation |
| Xylene | Rabbit | Mild irritant |
| Titanium Dioxide | Rabbit | No significant irritation |
| Calcium Oxide | Human | Corrosive |
| Hydrotreated Light Petroleum Distillates | similar compounds | Mild irritant |
| Ethylbenzene | Rabbit | Mild irritant |
| p,p'-Methylenebis(phenyl isocyanate) | official classification | Irritant |
| Carbon Black | Rabbit | No significant irritation |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Rabbit | Minimal irritation |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|-------------------------|---------------------------|
| Overall product | Rabbit | Mild irritant |
| Xylene | Rabbit | Mild irritant |
| Titanium Dioxide | Rabbit | No significant irritation |
| Calcium Oxide | Rabbit | Corrosive |
| Hydrotreated Light Petroleum Distillates | similar compounds | No significant irritation |
| Ethylbenzene | Rabbit | Moderate irritant |
| p,p'-Methylenebis(phenyl isocyanate) | official classification | Severe irritant |
| Carbon Black | Rabbit | No significant irritation |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Rabbit | Mild irritant |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|---|-------------------|----------------|
| Titanium Dioxide | Human and animal | Not classified |
| Hydrotreated Light Petroleum Distillates | similar compounds | Not classified |
| Ethylbenzene | Human | Not classified |
| p,p'-Methylenebis(phenyl isocyanate) | Mouse | Sensitizing |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Guinea pig | Sensitizing |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | Guinea pig | Sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|--------------------------------------|---------|-------------|
| p,p'-Methylenebis(phenyl isocyanate) | Human | Sensitizing |

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|--|
| Poly(Vinyl Chloride) | In Vitro | Not mutagenic |
| Xylene | In Vitro | Not mutagenic |
| Xylene | In vivo | Not mutagenic |
| Titanium Dioxide | In Vitro | Not mutagenic |
| Titanium Dioxide | In vivo | Not mutagenic |
| Calcium Oxide | In Vitro | Not mutagenic |
| Hydrotreated Light Petroleum Distillates | In Vitro | Not mutagenic |
| Ethylbenzene | In vivo | Not mutagenic |
| Ethylbenzene | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| p,p'-Methylenebis(phenyl isocyanate) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Carbon Black | In Vitro | Not mutagenic |
| Carbon Black | In vivo | Some positive data exist, but the data are not sufficient for classification |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | In vivo | Not mutagenic |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | In vivo | Not mutagenic |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|--------------------------------------|---------------|-------------------------|--|
| Poly(Vinyl Chloride) | Not Specified | Rat | Some positive data exist, but the data are not sufficient for classification |
| Xylene | Dermal | Rat | Not carcinogenic |
| Xylene | Ingestion | Multiple animal species | Not carcinogenic |
| Xylene | Inhalation | Human | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide | Ingestion | Multiple animal species | Not carcinogenic |
| Titanium Dioxide | Inhalation | Rat | Carcinogenic |
| Ethylbenzene | Inhalation | Multiple animal species | Carcinogenic |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | Rat | Some positive data exist, but the data are not |

3M™ Polyurethane Sealant 540 (Various Colours)

| | | | |
|--------------|------------|-------|-------------------------------|
| | | | sufficient for classification |
| Carbon Black | Dermal | Mouse | Not carcinogenic |
| Carbon Black | Ingestion | Mouse | Not carcinogenic |
| Carbon Black | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|---------------|--|-------------------------|-----------------------|--------------------------------|
| Poly(Vinyl Chloride) | Not Specified | Not classified for development | Mouse | NOAEL Not available | during gestation |
| Xylene | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| Xylene | Ingestion | Not classified for development | Mouse | NOAEL Not available | during organogenesis |
| Xylene | Inhalation | Not classified for development | Multiple animal species | NOAEL Not available | during gestation |
| Ethylbenzene | Inhalation | Not classified for development | Rat | NOAEL 4.3 mg/l | prematuring & during gestation |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | Not classified for development | Rat | NOAEL 0.004 mg/l | during organogenesis |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,493 mg/kg/day | 29 days |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | Ingestion | Not classified for development | Rat | NOAEL 209 mg/kg/day | prematuring into lactation |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | Ingestion | Toxic to female reproduction | Rat | NOAEL 804 mg/kg/day | prematuring into lactation |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidiny) Sebacate | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,493 mg/kg/day | 29 days |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidiny) Sebacate | Ingestion | Not classified for development | Rat | NOAEL 209 mg/kg/day | prematuring into lactation |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidiny) Sebacate | Ingestion | Toxic to female reproduction | Rat | NOAEL 804 mg/kg/day | prematuring into lactation |

Lactation

| Name | Route | Species | Value |
|--------|-----------|---------|--|
| Xylene | Ingestion | Mouse | Not classified for effects on or via lactation |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--------|------------|-----------------------------------|--|-------------------------|---------------------|-------------------|
| Xylene | Inhalation | auditory system | Causes damage to organs | Rat | LOAEL 6.3 mg/l | 8 hours |
| Xylene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Xylene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Xylene | Inhalation | eyes | Not classified | Rat | NOAEL 3.5 mg/l | not available |
| Xylene | Inhalation | liver | Not classified | Multiple animal species | NOAEL Not available | |
| Xylene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Multiple animal species | NOAEL Not available | |
| Xylene | Ingestion | eyes | Not classified | Rat | NOAEL 250 | not applicable |

| | | | | | mg/kg | |
|--|------------|-----------------------------------|--|-------------------------|---------------------|-----------------------|
| Calcium Oxide | Inhalation | respiratory irritation | May cause respiratory irritation | Not available | NOAEL Not available | occupational exposure |
| Hydrotreated Light Petroleum Distillates | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| Ethylbenzene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Ethylbenzene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human and animal | NOAEL Not available | |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|------------|--|--|-------------------------|-----------------------|-----------------------|
| Poly(Vinyl Chloride) | Inhalation | respiratory system | Not classified | Multiple animal species | NOAEL 0.013 mg/l | 22 months |
| Xylene | Inhalation | nervous system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.4 mg/l | 4 weeks |
| Xylene | Inhalation | auditory system | May cause damage to organs though prolonged or repeated exposure | Rat | LOAEL 7.8 mg/l | 5 days |
| Xylene | Inhalation | liver | Not classified | Multiple animal species | NOAEL Not available | |
| Xylene | Inhalation | heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system | Not classified | Multiple animal species | NOAEL 3.5 mg/l | 13 weeks |
| Xylene | Ingestion | auditory system | Not classified | Rat | NOAEL 900 mg/kg/day | 2 weeks |
| Xylene | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 1,500 mg/kg/day | 90 days |
| Xylene | Ingestion | liver | Not classified | Multiple animal species | NOAEL Not available | |
| Xylene | Ingestion | heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Titanium Dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium Dioxide | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Hydrotreated Light Petroleum Distillates | Inhalation | liver | Not classified | Rat | NOAEL 6 mg/l | 13 weeks |
| Hydrotreated Light Petroleum Distillates | Inhalation | kidney and/or bladder | Not classified | Rat | LOAEL 1.5 mg/l | 13 weeks |
| Hydrotreated Light Petroleum Distillates | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 6 mg/l | 13 weeks |
| Hydrotreated Light Petroleum Distillates | Ingestion | liver | Not classified | Rat | NOAEL 1,000 | 13 weeks |

3M™ Polyurethane Sealant 540 (Various Colours)

| | | | | | mg/kg/day | |
|---|------------|---|--|-------------------------|-----------------------|-----------------------|
| Hydrotreated Light Petroleum Distillates | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 100 mg/kg/day | 13 weeks |
| Hydrotreated Light Petroleum Distillates | Ingestion | hematopoietic system eyes | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |
| Ethylbenzene | Inhalation | auditory system | May cause damage to organs though prolonged or repeated exposure | Rat | LOAEL 0.9 mg/l | 13 weeks |
| Ethylbenzene | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.1 mg/l | 2 years |
| Ethylbenzene | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 1.1 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 3.4 mg/l | 28 days |
| Ethylbenzene | Inhalation | endocrine system | Not classified | Mouse | NOAEL 3.3 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | gastrointestinal tract | Not classified | Rat | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Inhalation | bone, teeth, nails, and/or hair muscles | Not classified | Multiple animal species | NOAEL 4.2 mg/l | 90 days |
| Ethylbenzene | Inhalation | heart immune system respiratory system | Not classified | Multiple animal species | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Ingestion | liver kidney and/or bladder | Not classified | Rat | NOAEL 680 mg/kg/day | 6 months |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| Carbon Black | Inhalation | pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Ingestion | eyes | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 300 mg/kg/day | 28 days |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Ingestion | gastrointestinal tract liver immune system heart endocrine system hematopoietic system nervous system kidney and/or bladder | Not classified | Rat | NOAEL 1,493 mg/kg/day | 29 days |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | Ingestion | eyes | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 300 mg/kg/day | 28 days |
| Methyl 1,2,2,6,6-Pentamethyl-4-piperidinyl Sebacate | Ingestion | gastrointestinal tract liver immune system heart endocrine system hematopoietic system nervous system kidney and/or bladder | Not classified | Rat | NOAEL 1,493 mg/kg/day | 29 days |

Aspiration Hazard

| Name | Value |
|--|-------------------|
| Xylene | Aspiration hazard |
| Hydrotreated Light Petroleum Distillates | Aspiration hazard |
| Ethylbenzene | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact manufacturer for more information The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|------------------------|-------|
| Document group: | 08-9432-9 | Version number: | 16.06 |
|------------------------|-----------|------------------------|-------|

| | | | |
|--------------------|------------|-------------------------|------------|
| Issue Date: | 2025/08/21 | Supersedes Date: | 2025/06/12 |
|--------------------|------------|-------------------------|------------|

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca