

# Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-8647-1
 Version number:
 13.00

 Revision date:
 04/11/2022
 Supersedes date:
 21/02/2022

Transportation version number:

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

# IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

3M<sup>™</sup> Scotchcast<sup>™</sup> Flexible Power Cable Splicing Kits with 2131 Resin (82-F1, 82-F2, 82-BF1, ALK-8 series)

#### **Product Identification Numbers**

80-6114-6834-1 80-6114-6835-8 80-6114-6836-6

7000006240 7100010200 7100011582

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Electrical

#### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000 tox.uk@mmm.com

Website: www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

28-7650-6, 28-7666-2

#### TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

.....

## KIT LABEL

# 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

#### **CLASSIFICATION:**

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Carcinogenicity, Category 2 - Carc. 2; H351

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### **Symbols**

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

#### **Pictograms**







#### Contains:

4,4'-methylenediphenyl diisocyanate; Polyoxyalkylenes; 1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-

METHYLPHENYL)BUTANE ; methylenediphenyl diisocyanate; 1,1'-Phenyliminodipropan-2-ol; 1,1'-

Methylenebis[isocyanatobenzene], homopolymer

#### **HAZARD STATEMENTS:**

H315 Causes skin irritation. H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure:

respiratory system |

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P261G Avoid breathing vapours or dust.

P280B Wear protective gloves and eye/face protection.

Page: 2 of

#### 3MTM ScotchcastTM Flexible Power Cable Splicing Kits with 2131 Resin (82-F1, 82-F2, 82-BF1, ALK-8 series)

#### **Response:**

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

#### For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

#### <=125 ml Hazard statements

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure: respiratory system.

#### <=125 ml Precautionary statements

#### **Prevention:**

P261G Avoid breathing vapours or dust.

P280B Wear protective gloves and eye/face protection.

#### Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

#### Information required per Regulation (EU) 2020/1149 as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information can be found at feica.eu/Puinfo

#### **Revision information:**

Kit: Component document group number(s) information was modified.

Section 2: <125ml Precautionary - Prevention information was modified.

Label: CLP Precautionary - Prevention information was modified.



# Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-7650-6
 Version number:
 15.00

 Revision date:
 02/05/2025
 Supersedes date:
 24/04/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotchcast<sup>TM</sup> Flame-Retardant Compound 2131 (Part A)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Electrical

#### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

#### **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

#### **CLASSIFICATION:**

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Carcinogenicity, Category 2 - Carc. 2; H351

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

\_\_\_\_\_

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

For full text of H phrases, see Section 16.

#### 2.2. Label elements

#### The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### SIGNAL WORD

DANGER.

#### **Symbols**

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

#### **Pictograms**





Ingredient	CAS Nbr	EC No.	% by Wt
Polyoxyalkylenes	154517-54-1		35 - 45
4,4'-methylenediphenyl diisocyanate	101-68-8	202-966-0	15 - 40
1,1'-Methylenebis[isocyanatobenzene], homopolymer	39310-05-9		10 - 30
methylenediphenyl diisocyanate	26447-40-5	247-714-0	1 - 5

#### **HAZARD STATEMENTS:**

H315	Causes skin irritation.
H319	Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure: respiratory system.

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P261A Avoid breathing vapours.

P280K Wear protective gloves and respiratory protection.

**Response:** 

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

#### For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

#### <=125 ml Hazard statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

#### <=125 ml Precautionary statements

**Prevention:** 

P261A Avoid breathing vapours.

P280K Wear protective gloves and respiratory protection.

**Response:** 

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

Contains 45% of components with unknown hazards to the aquatic environment.

Information required per Regulation (EU) 2020/1149, amendment to REACH Regualtion (1907/2006) as amended for Great Britain, as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information can be found at feica.eu/Puinfo

## 2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Ingredient	Identifier(s)	0%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Polyoxyalkylenes	(CAS-No.) 154517-54-1	35 - 45	Resp. Sens. 1, H334 Skin Sens. 1, H317
4,4'-methylenediphenyl diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0	15 - 40	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Nota 2,C
1,1'-Methylenebis[isocyanatobenzene], homopolymer	(CAS-No.) 39310-05-9	10 - 30	
Diundecyl phthalate	(CAS-No.) 3648-20-2	< 15	Aquatic Chronic 3, H412

	(EC-No.) 222-884-9		
methylenediphenyl diisocyanate	(CAS-No.) 26447-40-5 (EC-No.) 247-714-0	1- 5	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Nota 2,C
triethyl phosphate	(CAS-No.) 78-40-0 (EC-No.) 201-114-5	< 1.2	Acute Tox. 4, H302 Eye Irrit. 2, H319

Please see section 16 for the full text of any H statements referred to in this section

#### **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
methylenediphenyl diisocyanate	(CAS-No.) 26447-40-5 (EC-No.) 247-714-0	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335
1,1'-Methylenebis[isocyanatobenzene], homopolymer	(CAS-No.) 39310-05-9	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335
4,4'-methylenediphenyl diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Target organ effects. See Section 11 for additional details.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### **Hazardous Decomposition or By-Products**

Substance	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.

#### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with

fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Protect from sunlight. Store away from heat. Store away from strong bases. Store away from areas where product may come into contact with food or pharmaceuticals. Store in a dry place.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Free isocyanates	101-68-8	UK HSE	TWA(as NCO):0.02 mg/m3;STEL(as NCO):0.07 mg/m3	Respiratory Sensitizer
Free isocyanates	26447-40-5	UK HSE	TWA(as NCO):0.02 mg/m3;STEL(as NCO):0.07 mg/m3	Respiratory Sensitizer
Free isocyanates	39310-05-9	UK HSE	TWA(as NCO):0.02 mg/m3;STEL(as NCO):0.07 mg/m3	Respiratory Sensitizer

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### **Biological limit values**

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
Free isocyanates	101-68- 8	UK EH40 BMGVs	Isocyanate- derived diamine	Creatinine in urine	EPE	1 umol/mol	
Free isocyanates	26447- 40-5	UK EH40 BMGVs	Isocyanate- derived diamine	Creatinine in urine	EPE	1 umol/mol	
Free isocyanates	39310-	UK EH40	Isocyanate-	Creatinine in	EPE	1 umol/mol	

05-9 BMGVs derived diamine

urine

UK EH40 BMGVs: UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EPE: At the end of the period of exposure.

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.	
Colour	Light Straw	
Odor	Pungent Petroleum	
Odour threshold	No data available.	
Melting point/freezing point	Not applicable.	
Boiling point/boiling range	>=148.9 °C	
Flammability	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Flash point	>=148.9 °C [Test Method:Closed Cup]	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
pH	substance/mixture is non-soluble (in water)	
Kinematic Viscosity	741 mm <sup>2</sup> /sec	
Water solubility	Nil	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Vapour pressure	No data available.	
Density	No data available.	
Relative density	1.08 [ <i>Ref Std</i> :WATER=1]	
Relative Vapour Density	No data available.	
Particle Characteristics	Not applicable.	

#### 9.2. Other information

#### 9.2.2 Other safety characteristics

Average particle sizeNo data available.Bulk densityNo data available.EU Volatile Organic CompoundsNo data available.Evaporation rateNo data available.Molecular weightNo data available.Softening pointNo data available.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

#### 10.4 Conditions to avoid

None known.

#### 10.5 Incompatible materials

Strong bases.

#### 3M™ Scotchcast™ Flame-Retardant Compound 2131 (Part A)

Alcohols.

Water

#### 10.6 Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

#### Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### **Additional Health Effects:**

#### Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

#### **Additional information:**

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyoxyalkylenes	Dermal		LD50 estimated to be > 5,000 mg/kg

Polyoxyalkylenes	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Inhalation- Dust/Mist	Rat	LC50 0.368 mg/l
	(4 hours)		
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
1,1'-Methylenebis[isocyanatobenzene], homopolymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,1'-Methylenebis[isocyanatobenzene], homopolymer	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
1,1'-Methylenebis[isocyanatobenzene], homopolymer	Ingestion	Rat	LD50 31,600 mg/kg
Diundecyl phthalate	Dermal	Rabbit	LD50 > 7,900 mg/kg
Diundecyl phthalate	Ingestion	Rat	LD50 > 15,000 mg/kg
methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
methylenediphenyl diisocyanate	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
triethyl phosphate	Dermal	Guinea	LD50 > 21,400 mg/kg
		pig	
triethyl phosphate	Inhalation-	Rat	LC50 > 8.8 mg/l
	Dust/Mist		
	(4 hours)		
triethyl phosphate	Ingestion	Rat	LD50 1,131 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	official classificat ion	Irritant
1,1'-Methylenebis[isocyanatobenzene], homopolymer	official classificat ion	Irritant
methylenediphenyl diisocyanate	official classificat ion	Irritant
triethyl phosphate	Rabbit	No significant irritation

Serious Eve Damage/Irritation

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	official classificat ion	Severe irritant
1,1'-Methylenebis[isocyanatobenzene], homopolymer	official classificat ion	Severe irritant
methylenediphenyl diisocyanate	official classificat ion	Severe irritant
triethyl phosphate	Rabbit	Severe irritant

## **Skin Sensitisation**

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	Mouse	Sensitising
1,1'-Methylenebis[isocyanatobenzene], homopolymer	Mouse	Sensitising
methylenediphenyl diisocyanate	Mouse	Sensitising
triethyl phosphate	Mouse	Not classified

# **Respiratory Sensitisation**

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	Human	Sensitising
1,1'-Methylenebis[isocyanatobenzene], homopolymer	Human	Sensitising
methylenediphenyl diisocyanate	Human	Sensitising

**Germ Cell Mutagenicity** 

Name	Route Value		
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification	
1,1'-Methylenebis[isocyanatobenzene], homopolymer	In Vitro	Some positive data exist, but the data are not sufficient for classification	
methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification	

Carcinogenicity

Name	Route	Species	Value
4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
1,1'-Methylenebis[isocyanatobenzene], homopolymer	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure
	110410	, mad	Species	1000100010	Duration
4,4'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL	during
		_		0.004 mg/l	organogenesis
1,1'-Methylenebis[isocyanatobenzene],	Inhalation	Not classified for development	Rat	NOAEL	during
homopolymer		_		0.004 mg/l	organogenesis
methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL	during
, , ,				0.004 mg/l	organogenesis

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
1,1'- Methylenebis[isocyanatobe nzene], homopolymer	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
triethyl phosphate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
1,1'- Methylenebis[isocyanatob enzene], homopolymer	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

\_\_\_\_\_

methylenediphenyl	Inhalation	respiratory system	Causes damage to organs through	Rat	LOAEL	13 weeks
diisocyanate			prolonged or repeated exposure		0.004 mg/l	

#### **Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

#### 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Туре	Exposure	Test endpoint	Test result
Polyoxyalkylenes	154517-54-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
4,4'- methylenediphenyl diisocyanate	101-68-8	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
4,4'- methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
4,4'- methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
4,4'- methylenediphenyl diisocyanate	101-68-8	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
4,4'- methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
4,4'- methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	21 days	NOEC	10 mg/l
1,1'- Methylenebis[isocy anatobenzene], homopolymer	39310-05-9	Water flea	Analogous Compound	24 hours	EC50	>100 mg/l
Diundecyl phthalate	3648-20-2	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Diundecyl phthalate	3648-20-2	Water flea	Experimental	21 days	NOEC	0.35 mg/l
methylenediphenyl diisocyanate		Green algae	Analogous Compound	72 hours	EC50	>1,640 mg/l
methylenediphenyl diisocyanate	26447-40-5	Water flea	Analogous Compound	24 hours	EC50	>1,000 mg/l
methylenediphenyl diisocyanate	26447-40-5	Zebra Fish	Analogous Compound	96 hours	LC50	>1,000 mg/l
methylenediphenyl diisocyanate	26447-40-5	Green algae	Analogous Compound	72 hours	NOEC	1,640 mg/l

methylenediphenyl diisocyanate	26447-40-5	Water flea	Analogous Compound	21 days	NOEC	10 mg/l
methylenediphenyl diisocyanate	26447-40-5	Activated sludge	Analogous Compound	3 hours	EC50	>100 mg/l
methylenediphenyl diisocyanate	26447-40-5	Lettuce	Analogous Compound	17 days	NOEC	1,000 mg/kg (Dry Weight)
methylenediphenyl diisocyanate	26447-40-5	Redworm	Analogous Compound	14 days	LC50	>1,000 mg/kg (Dry Weight)
triethyl phosphate	78-40-0	Activated sludge	Experimental	5 hours	EC50	5,000 mg/l
triethyl phosphate	78-40-0	Bacteria	Experimental	30 minutes	EC10	2,985 mg/l
triethyl phosphate	78-40-0	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
triethyl phosphate	78-40-0	Green algae	Experimental	72 hours	EbC50	900 mg/l
triethyl phosphate	78-40-0	Water flea	Experimental	48 hours	EC50	350 mg/l
triethyl phosphate	78-40-0	Water flea	Experimental	21 days	NOEC	31.6 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polyoxyalkylenes	154517-54-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
4,4'- methylenediphenyl diisocyanate	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	
1,1'- Methylenebis[isocy anatobenzene], homopolymer	39310-05-9	Hydrolysis product Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
1,1'- Methylenebis[isocy anatobenzene], homopolymer	39310-05-9	Analogous Compound Hydrolysis		Hydrolytic half-life (pH 7)	<2 hours (t 1/2)	
Diundecyl phthalate	3648-20-2	Experimental Biodegradation	28 days	CO2 evolution	76 %CO2 evolution/THCO2 evolution	similar to OECD 301B
methylenediphenyl diisocyanate	26447-40-5	Analogous Compound Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
methylenediphenyl diisocyanate	26447-40-5	Analogous Compound Aquatic Inherent Biodegrad.	28 days	BOD	0 %BOD/ThOD	OECD 302C - Modified MITI (II)
methylenediphenyl diisocyanate	26447-40-5	Analogous Compound Hydrolysis		Hydrolytic half-life (pH 7)	<2 hours (t 1/2)	
triethyl phosphate	78-40-0	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	97 %removal of DOC	835.3200 Zhan-Wellens
triethyl phosphate	78-40-0	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
triethyl phosphate	78-40-0	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	EC C.7 Hydrolysis at pH

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Polyoxyalkylenes	154517-54-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-	101-68-8	Experimental BCF	28 days	Bioaccumulation	200	OECD305-Bioconcentration
methylenediphenyl		- Fish		factor		

diisocyanate						
1,1'- Methylenebis[isocy anatobenzene], homopolymer	39310-05-9	Analogous Compound BCF - Fish	28 days	Bioaccumulation factor	200	
Diundecyl phthalate	3648-20-2	Modeled Bioconcentration		Bioaccumulation factor	7.4	Catalogic™
methylenediphenyl diisocyanate	26447-40-5	Analogous Compound BCF - Fish	28 days	Bioaccumulation factor	200	OECD305-Bioconcentration
methylenediphenyl diisocyanate	26447-40-5	Analogous Compound Bioconcentration		Log Kow		OECD 117 log Kow HPLC method
triethyl phosphate	78-40-0	Experimental BCF - Fish		Bioaccumulation factor	<1.3	OECD305-Bioconcentration

#### 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
4,4'- methylenediphenyl diisocyanate	101-68-8	Estimated Mobility in Soil	Koc	34,000 l/kg	Episuite <sup>TM</sup>
methylenediphenyl diisocyanate	26447-40-5	Modeled Mobility in Soil	Koc	300,000 l/kg	Episuite <sup>TM</sup>
triethyl phosphate	78-40-0	Modeled Mobility in Soil	Koc	30 l/kg	Episuite <sup>TM</sup>

#### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

#### 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

#### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

## **SECTION 14: Transportation information**

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

rcino		

<u>Ingredient</u>	<u>CAS Nbr</u>	Classification	Regulation
methylenediphenyl diisocyanate	26447-40-5	Carc. 2	The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain, UK Mandatory Classification and Labelling list
methylenediphenyl diisocyanate	26447-40-5	Gr. 3: Not classifiable	International Agency for Research on Cancer
1,1'-Methylenebis[isocyanatobenzene],	39310-05-9	Carc. 2	3M classified

Page: 15 of 17

#### 3M™ Scotchcast™ Flame-Retardant Compound 2131 (Part A)

homopolymer			according to the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain
4,4'-methylenediphenyl diisocyanate	101-68-8	Carc. 2	The retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain, UK Mandatory
			Classification and Labelling list
4,4'-methylenediphenyl diisocyanate	101-68-8	Gr. 3: Not classifiable	International Agency for Research on Cancer

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	CAS Nbr
methylenediphenyl diisocyanate	26447-40-5
4,4'-methylenediphenyl diisocyanate	101-68-8

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

### **Authorisation status under UK REACH:**

The following substance/s contained in this product might be or is/are subject to authorisation in accordance with UK REACH:

<u>Ingredient</u>	CAS Nbr
Diundecyl phthalate	3648-20-2

norization status: listed in UK REACH Annex XIV ("Authorization")

<u>Ingredient</u>	CAS Nbr
Diundecyl phthalate	3648-20-2

Authorisation status: listed in the UK REACH Candidate List of Substances of Very High Concern for Authorisation

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2 None

#### Regulation (EU) No 649/2012, as amended for GB

Chemical	Identifier(s)	Annex I
Diundecyl phthalate	3648-20-2	Part 1 and Part 2

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

### **SECTION 16: Other information**

#### List of relevant H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H412	Harmful to aquatic life with long lasting effects

#### **Revision information:**

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

#### 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



# Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-7666-2
 Version number:
 12.01

 Revision date:
 05/10/2023
 Supersedes date:
 27/07/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M Scotchcast<sup>™</sup> Flame Retardant Resin 2131 (Part B)

#### **Product Identification Numbers**

80-6114-6841-6

7000058848

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Electrical

#### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 E Mail: tox.uk@mmm.com Website: www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

#### **CLASSIFICATION:**

#### 3M Scotchcast™ Flame Retardant Resin 2131 (Part B)

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### SIGNAL WORD

DANGER.

#### **Symbols**

GHS05 (Corrosion)

#### **Pictograms**



Ingredient CAS Nbr EC No. % by Wt

1,1'-Phenyliminodipropan-2-ol 3077-13-2 221-360-7 4 - 10

#### **HAZARD STATEMENTS:**

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P280A Wear eye/face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

#### For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

#### <=125 ml Precautionary statements

**Prevention:** 

P280A Wear eye/face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

4% of the mixture consists of components of unknown acute oral toxicity.

Contains 8% of components with unknown hazards to the aquatic environment.

#### 2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
1,3-Butadiene, homopolymer, hydroxyterminated	(CAS-No.) 69102-90-5	20 - 30	Substance not classified as hazardous
1,1'-(Ethane-1,2-diyl)bis[pentabromobenzene]	(CAS-No.) 84852-53-9 (EC-No.) 284-366-9	22 - 25	Substance not classified as hazardous
Diundecyl phthalate, branched and linear	(CAS-No.) 85507-79-5 (EC-No.) 287-401-6	10 - 20	Substance not classified as hazardous
Silicic acid, aluminum potassium sodium salt	(CAS-No.) 12736-96-8 (EC-No.) 235-787-1	1 - 10	Substance not classified as hazardous
Propane-1,2-diol, propoxylated	(CAS-No.) 25322-69-4	5 - 10	Acute Tox. 4, H302
Diantimony pentoxide	(CAS-No.) 1314-60-9 (EC-No.) 215-237-7	5 - 10	Aquatic Chronic 2, H411
Castor oil	(CAS-No.) 8001-79-4 (EC-No.) 232-293-8	1 - 10	Substance not classified as hazardous
1,1'-Phenyliminodipropan-2-ol	(CAS-No.) 3077-13-2 (EC-No.) 221-360-7	4 - 10	Eye Dam. 1, H318
Oxydipropanol	(CAS-No.) 25265-71-8 (EC-No.) 246-770-3	3 - 6	Substance not classified as hazardous
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	<= 2	Substance with a national occupational exposure limit
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	(CAS-No.) 68909-20-6 (EC-No.) 272-697-1	<= 1	Substance with a national occupational exposure limit
1,4-diazabicyclooctane	(CAS-No.) 280-57-9	<= 1	Acute Tox. 4, H302

#### 3M Scotchcast™ Flame Retardant Resin 2131 (Part B)

(EC-No.) 205-999-9	Eye Dam. 1, H318

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Wash with soap and water. If you feel unwell, get medical attention.

#### **Eve contact**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.
Oxides of antimony.	During combustion.

#### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation

to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (eg. gloves, respirators...) as required.

#### 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Keep cool. Store away from heat. Store in a dry place.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

**Ingredient** Additional comments CAS Nbr Limit type Agency

Carbon black TWA: 3.5 mg/m<sup>3</sup>; STEL: 7 1333-86-4 UK HSC

 $mg/m^3$ 

Silicon dioxide 68909-20-6 UK HSC TWA(as respirable dust):2.4

mg/m3;TWA(as inhalable

dust):6 mg/m3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### 8.2. Exposure controls

## 8.2.1. Engineering controls

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

#### Skin/hand protection

No chemical protective gloves are required.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state Liquid. Colour Black Odor Pungent Odor

**Odour threshold** No data available. Melting point/freezing point Not applicable. Boiling point/boiling range > 143.3 °C Flammability (solid, gas) Not applicable. Flammable Limits(LEL) No data available.

Flammable Limits(UEL) No data available.

Flash point > 143.3 °C [Test Method: Closed Cup]

**Autoignition temperature** No data available. **Decomposition temperature** No data available.

pН substance/mixture is non-soluble (in water)

**Kinematic Viscosity** 4.264 mm<sup>2</sup>/sec Nil

Water solubility

**Solubility- non-water** No data available. Partition coefficient: n-octanol/water No data available.

Vapour pressure < 186,158.4 Pa [@ 55 °C]

**Density** No data available.

1.29 [*Ref Std*:WATER=1] Relative density

**Relative Vapour Density** No data available.

#### 9.2. Other information

#### 9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNo data available.Molecular weightNo data available.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

#### 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

None known.

## 10.5 Incompatible materials

None known.

#### 10.6 Hazardous decomposition products

Substance

None known.

**Condition** 

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May cause additional health effects (see below).

#### Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

#### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### **Additional Health Effects:**

#### Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
1,3-Butadiene, homopolymer, hydroxy-terminated	Dermal		LD50 estimated to be > 5,000 mg/kg
1,3-Butadiene, homopolymer, hydroxy-terminated	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Diundecyl phthalate, branched and linear	Dermal	Rat	LD50 > 2,000 mg/kg
Diundecyl phthalate, branched and linear	Ingestion	Rat	LD50 > 15,800 mg/kg
Propane-1,2-diol, propoxylated	Dermal	Rabbit	LD50 > 10,000 mg/kg
Propane-1,2-diol, propoxylated	Ingestion	Rat	LD50 > 1,000 mg/kg
1,1'-Phenyliminodipropan-2-ol	Dermal	Rabbit	LD50 > 2,000 mg/kg
1,1'-Phenyliminodipropan-2-ol	Ingestion	Rat	LD50 3,800 mg/kg
Castor oil	Dermal		LD50 estimated to be > 5,000
Castor oil	Ingestion		LD50 estimated to be > 5,000
Oxydipropanol	Dermal	Rabbit	LD50 > 5,010 mg/kg
Oxydipropanol	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.34 mg/l
Oxydipropanol	Ingestion	Rat	LD50 > 14,800 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
1,4-diazabicyclooctane	Dermal	Rabbit	LD50 > 3,200 mg/kg
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	Rat	LD50 > 2,000 mg/kg
1,4-diazabicyclooctane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.05 mg/l
1,4-diazabicyclooctane	Ingestion	Rat	LD50 1,870 mg/kg
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Diundecyl phthalate, branched and linear	Rabbit	No significant irritation
Propane-1,2-diol, propoxylated	Not available	No significant irritation
1,1'-Phenyliminodipropan-2-ol	Professio nal	Minimal irritation

D 0 C 17

## 3M Scotchcast<sup>TM</sup> Flame Retardant Resin 2131 (Part B)

	judgemen	
	t	
Castor oil	Human	Minimal irritation
Oxydipropanol	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Rabbit	No significant irritation
1,4-diazabicyclooctane	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Diundecyl phthalate, branched and linear	Rabbit	Mild irritant
Propane-1,2-diol, propoxylated	Not	Mild irritant
	available	
1,1'-Phenyliminodipropan-2-ol	Professio	Corrosive
	nal	
	judgemen	
	t	
Castor oil	Rabbit	Mild irritant
Oxydipropanol	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Rabbit	No significant irritation
1,4-diazabicyclooctane	Rabbit	Corrosive

#### **Skin Sensitisation**

Name	Species	Value
Diundecyl phthalate, branched and linear	Human	Not classified
Propane-1,2-diol, propoxylated	Human	Not classified
	and	
	animal	
Castor oil	Human	Not classified
Oxydipropanol	Guinea	Not classified
	pig	
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Guinea	Not classified
	pig	

# **Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value		
Diundecyl phthalate, branched and linear	In Vitro	Not mutagenic		
Propane-1,2-diol, propoxylated	In Vitro	Not mutagenic		
Castor oil	In Vitro	Not mutagenic		
Castor oil	In vivo	Not mutagenic		
Oxydipropanol	In Vitro	Not mutagenic		
Oxydipropanol	In vivo	Not mutagenic		
Carbon black	In Vitro	Not mutagenic		
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification		
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	In Vitro	Not mutagenic		

Carcinogenicity

Carcinogenicity			
Name	Route	Species	Value
Oxydipropanol	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

\_\_\_\_\_

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Diundecyl phthalate, branched and linear	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,100 mg/kg/day	21 days
Diundecyl phthalate, branched and linear	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Oxydipropanol	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesis
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure
For the component/components, either no data is currently available or the data is not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Diundecyl phthalate, branched and linear	Ingestion	liver	Not classified	Rat	NOAEL 2,100 mg/kg/day	21 days
Castor oil	Ingestion	heart   hematopoietic system   liver	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks
Castor oil	Ingestion	kidney and/or bladder	Not classified	Mouse	NOAEL 13,000 mg/kg/day	13 weeks
Oxydipropanol	Ingestion	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 470 mg/kg/day	105 weeks
Oxydipropanol	Ingestion	heart	Not classified	Rat	NOAEL 470 mg/kg/day	105 weeks
Oxydipropanol	Ingestion	endocrine system   liver	Not classified	Rat	NOAEL 3,040 mg/kg/day	105 weeks
Oxydipropanol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 115 mg/kg/day	105 weeks
Oxydipropanol	Ingestion	skin   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   vascular system	Not classified	Rat	NOAEL 3,040 mg/kg/day	105 weeks
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Silanamine, 1,1,1- trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.035 mg/l	13 weeks
Silanamine, 1,1,1- trimethyl-N-	Inhalation	hematopoietic system   kidney	Not classified	Rat	NOAEL 0.035 mg/l	13 weeks

(trimethylsilyl)-,		and/or bladder				
hydrolysis products with						
silica						
Silanamine, 1,1,1-	Ingestion	liver	Not classified	Rat	NOAEL	5 weeks
trimethyl-N-					1,000	
(trimethylsilyl)-,					mg/kg/day	
hydrolysis products with						
silica						

#### **Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

#### 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
1,1'-(Ethane-1,2-diyl)bis[pentabrom obenzene]	84852-53-9	Activated sludge	Experimental	3 hours	NOEC	10 mg/l
1,1'-(Ethane-1,2-diyl)bis[pentabrom obenzene]	84852-53-9	Green algae	Experimental	96 hours	EC50	>100 mg/l
1,1'-(Ethane-1,2-diyl)bis[pentabrom obenzene]	84852-53-9	Rainbow trout	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
1,1'-(Ethane-1,2-diyl)bis[pentabrom obenzene]	84852-53-9	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
1,1'-(Ethane-1,2-diyl)bis[pentabrom obenzene]	84852-53-9	Green algae	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Diundecyl phthalate, branched and linear	85507-79-5	Green algae	Estimated	72 hours	EC50	>100 mg/l
Diundecyl phthalate, branched and linear	85507-79-5	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Diundecyl phthalate, branched and linear	85507-79-5	Sheepshead Minnow	Estimated	96 hours	LC50	>100 mg/l
Diundecyl phthalate, branched and linear	85507-79-5	Green algae	Estimated	72 hours	NOEC	100 mg/l
Diundecyl phthalate, branched and linear	85507-79-5	Rainbow trout	Estimated	155 days	NOEC	100 mg/l

Stitick and   12736-96-8   Zebra Fish	0.1 1	12736-96-8	IC 1	le e e e	061	ECCO	L 100 //
Destination socion   Silicic acid, alturnium potassium socion   Silicic acid, alturnium potassium socion   Silicic acid, alturnium potassium socion   Silicic acid, alturnium   Silicic acid, alturniu	Silicic acid, aluminum	12/36-96-8	Green algae	Estimated	96 hours	EC50	>100 mg/l
2736-96-8   Zebra Fish	potassium sodium						
Statistical and   Statistica	salt						
Description Sodium solum sails		12736-96-8	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Salt							
Stitical cand, alumnium potential processium sodium salt	salt						
Diantimony   Dia	Silicic acid,	12736-96-8	Green algae	Estimated	72 hours	NOEC	100 mg/l
Salt	aluminum						
Silicic acid, alluminum potassium sodium soll unimour potassium sodium soll unimour potassium sodium soll unimour petentoxide   Stimated   St	•						
Stimutor		12726 06 0	W . C		21.1	NOEG	100 //
Diantimony   peteroxide   Diantimony   peteroxide   Diantimony   peteroxide   Diantimony   petroxide   Diantimony   Diantimony   Diantimony   petroxide   Diantimony	,	12/36-96-8	Water flea	Estimated	21 days	NOEC	100 mg/I
Dantimony pertoxide   Dantimony							
Dantimony pentoxide   Dantimony   Dantimony pentoxide   Dantimony   Dantim	salt						
Dantimony   1314-60-9   Fish   Estimated   96 hours   LC50   9.2 mg/l	Diantimony	1314-60-9	Fathead minnow	Estimated	96 hours	LC50	19.1 mg/l
Diantimony pentoxide   Diantimony   1314-60-9   Invertebrate   Estimated   28 days   NOEC   149 mg/kg (Dry Weight)	pentoxide						
Dantimony   1314-60-9   Green algae   Estimated   72 hours   ErC50   >48.6 mg/l		1314-60-9	Fish	Estimated	96 hours	LC50	9.2 mg/l
Diantimony   1314-60-9   Estimated   Diantimony   1314-60-9   Estimated   Pathogram   Pa	1	1214 60 0		The state of the s		D 050	100
Diantimony   1314-60-9   Invertebrate   Estimated   96 hours   LC50   2.35 mg/l		1314-60-9	Green algae	Estimated	72 hours	ErC50	>48.6 mg/I
Dentition   Dent		1314-60-9	Invertebrate	Estimated	96 hours	I C50	2 35 mg/l
Dantimony   1314-60-9   Estimated   28 days   NOEC   149 mg/kg (Dry Weight)		1514 00 )	Inverteblate	Estimated	) o nours	Leso	2.33 mg/1
Dentining   1314-60-9   Fathead minnow   Estimated   28 days   NOEC   1.5 mg/l	Diantimony	1314-60-9	Blackworm	Estimated	28 days	NOEC	149 mg/kg (Dry Weight)
Dentoxide	pentoxide						
Diantimony   1314-60-9   Green algae   Estimated   72 hours   NOEC   2.8 mg/l	Diantimony	1314-60-9	Fathead minnow	Estimated	28 days	NOEC	1.5 mg/l
Diantimony   1314-60-9   Water flea   Estimated   21 days   NOEC   2.31 mg/l							
Diantimony   1314-60-9   Water flea   Estimated   21 days   NOEC   2.31 mg/l		1314-60-9	Green algae	Estimated	72 hours	NOEC	2.8 mg/l
Diantimony   1314-60-9   Barley   Estimated   4 hours   EC50   36 mg/l		1314 60 0	Water flee	Estimated	21 days	NOEC	2.31 mg/l
Diantimony pentoxide   Diantimony pentony pentoxide   Diantimony pentoxide   Diantimony pentoxide   Diantimony pentony pentoxide   Diantimony pentony pentony pentoxide   Diantimony pentony penton		1314-00-9	water frea	Estimated	21 days	NOEC	2.31 mg/1
Diantimony   Dia		1314-60-9	Activated sludge	Estimated	4 hours	EC50	36 mg/l
Diantimony   Dia	pentoxide						
Diantimony   1314-60-9   Soil microbes   Estimated   7 days   NOEC   3,900 mg/kg (Dry Weight)	Diantimony	1314-60-9	Barley	Estimated	5 days	EC50	9,230 mg/kg (Dry Weight)
Diantimony   Diantimony   Diantimony   Estimated   Estimated   28 days   NOEC   1,330 mg/kg (Dry Weight)		10111500		<u> </u>		1,1000	
Diantimony pentoxide		1314-60-9	Soil microbes	Estimated	/ days	NOEC	3,900 mg/kg (Dry Weight)
Dentoxide   Castor oil   Record   Rec		1314-60-9	Springtail	Estimated	28 days	NOEC	1 330 mg/kg (Dry Weight)
Castor oil   8001-79-4   Bacteria   Analogous   Compound   Compo		1314 00 7	Springuin	Estimated	20 days	Note	1,550 mg/kg (Biy Weight)
Compound   Castor oil   8001-79-4   Zebra Fish   Analogous   Compound   Com	Castor oil	8001-79-4	Bacteria	Analogous	16 hours	NOEC	10,000 mg/l
Compound   N/A				Compound			, ,
1,1'-	Castor oil	8001-79-4	Zebra Fish		96 hours	LC50	>100 mg/l
Phenyliminodiprop an-2-ol			1277	<del> </del>	27/	2.77	127.1
an-2-ol Propane-1,2-diol, propoxylated Propane-1,2-diol, propo	,	3077-13-2	N/A		N/A	N/A	N/A
Propane-1,2-diol, propoxylated	, , ,						
Propane-1,2-diol, propoxylated		25322-69-4	Green algae		72 hours	ErC50	>100 mg/l
Compound   Propane-1,2-diol, propoxylated   Propane-1,2-diol, pr	propoxylated	20322 05 .	oreen argue		72 110 415		l 100 mg l
Propane-1,2-diol, propoxylated Oxydipropanol Propane-1,2-diol, propoxylated	Propane-1,2-diol,	25322-69-4	Water flea		48 hours	EC50	105.8 mg/l
propoxylated Compound Propane-1,2-diol, propoxylated Propanel Prop	propoxylated						
Propane-1,2-diol, propoxylated25322-69-4Green algaeAnalogous Compound72 hoursNOEC100 mg/lPropane-1,2-diol, propoxylated25322-69-4Water fleaAnalogous Compound21 daysNOEC>=10 mg/lPropane-1,2-diol, propoxylated25322-69-4Activated sludge Analogous Compound3 hoursEC50>1,000 mg/lOxydipropanol25265-71-8GoldfishExperimental96 hoursLC50>5,000 mg/lOxydipropanol25265-71-8Green algaeExperimental72 hoursEC50>100 mg/lOxydipropanol25265-71-8Water fleaExperimental48 hoursEC50>100 mg/l		25322-69-4	Zebra Fish		96 hours	LC50	>100 mg/l
propoxylated Compound Propane-1,2-diol, propoxylated Compound Propane-1,2-diol, propoxylated Propane-1,2-diol, propoxylated Propane-1,2-diol, propoxylated Compound Propane-1,2-diol, propoxylated Compound Propoxylated Oxydipropanol 25265-71-8 Goldfish Experimental 96 hours LC50 >5,000 mg/l Oxydipropanol 25265-71-8 Green algae Experimental 72 hours EC50 >100 mg/l Oxydipropanol 25265-71-8 Water flea Experimental 48 hours EC50 >100 mg/l		25222 (0.4	C		72 1	NOEC	100//
Propane-1,2-diol, propoxylated25322-69-4Water fleaAnalogous Compound21 daysNOEC>=10 mg/lPropane-1,2-diol, propoxylated25322-69-4Activated sludge CompoundAnalogous Compound3 hoursEC50>1,000 mg/lOxydipropanol25265-71-8GoldfishExperimental96 hoursLC50>5,000 mg/lOxydipropanol25265-71-8Green algaeExperimental72 hoursEC50>100 mg/lOxydipropanol25265-71-8Water fleaExperimental48 hoursEC50>100 mg/l	1 /	23322-69-4	Green algae		/2 nours	NOEC	100 mg/1
propoxylated Compound Propane-1,2-diol, propoxylated Oxydipropanol 25265-71-8 Green algae Experimental Paper EC50 S1,000 mg/l Oxydipropanol 25265-71-8 Water flea Experimental 48 hours EC50 S100 mg/l		25322-69-4	Water flea		21 days	NOEC	>=10 mg/l
Propane-1,2-diol, propoxylated	propoxylated					1.020	
propoxylated Compound Coxydipropanol 25265-71-8 Goldfish Experimental 96 hours LC50 >5,000 mg/l Oxydipropanol 25265-71-8 Green algae Experimental 72 hours EC50 >100 mg/l Oxydipropanol 25265-71-8 Water flea Experimental 48 hours EC50 >100 mg/l	Propane-1,2-diol,	25322-69-4	Activated sludge	<del></del>	3 hours	EC50	>1,000 mg/l
Oxydipropanol 25265-71-8 Green algae Experimental 72 hours EC50 >100 mg/l Oxydipropanol 25265-71-8 Water flea Experimental 48 hours EC50 >100 mg/l	propoxylated				ļ		
Oxydipropanol 25265-71-8 Water flea Experimental 48 hours EC50 >100 mg/l	Oxydipropanol	25265-71-8	Goldfish	Experimental	96 hours	LC50	>5,000 mg/l
Oxydipropanol 25265-71-8 Water flea Experimental 48 hours EC50 >100 mg/l	Odiam-	25265 71 9	C1	Ei	72 1	ECEC	> 100/1
	Oxygipropanol	23203-71-8	Green algae	Experimental	/2 nours	EC30	>100 mg/1
	Oxydipropanol	25265-71-8	Water flea	Experimental	48 hours	EC50	>100 mg/l
Oxydipropanol 25265-71-8 Green algae Experimental 72 hours NOEC 100 mg/l	2.1.j a.propanoi				.0 110415		100
	Oxydipropanol	25265-71-8	Green algae	Experimental	72 hours	NOEC	100 mg/l
	• • •						

Oxydipropanol	25265-71-8	Bacteria	Experimental	18 hours	EC10	1,000 mg/l
Oxydipropanol	25265-71-8	Bobwhite quail	Experimental	14 days	LD50	>2,000 mg per kg of bodyweight
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	EC50	>=100 mg/l
Carbon black	1333-86-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Silanamine, 1,1,1- trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	68909-20-6	Algae or other aquatic plants	Estimated	72 hours	EC50	>100 mg/l
1,4- diazabicyclooctane	280-57-9	Bacteria	Experimental	17 hours	EC50	356 mg/l
1,4- diazabicyclooctane	280-57-9	Common Carp	Experimental	96 hours	LC50	>100 mg/l
1,4- diazabicyclooctane	280-57-9	Green algae	Experimental	72 hours	ErC50	180 mg/l
1,4- diazabicyclooctane	280-57-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
1,4- diazabicyclooctane	280-57-9	Green algae	Experimental	72 hours	ErC10	79 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	Data not availblinsufficient	N/A	N/A	N/A	N/A
1,1'-(Ethane-1,2-diyl)bis[pentabrom obenzene]	84852-53-9	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
Diundecyl phthalate, branched and linear	85507-79-5	Experimental Biodegradation	28 days	CO2 evolution	66 %CO2 evolution/THCO2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2
Silicic acid, aluminum potassium sodium salt	12736-96-8	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Diantimony pentoxide	1314-60-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Castor oil	8001-79-4	Analogous Compound Biodegradation	28 days	BOD	64 %BOD/ThOD	OECD 301D - Closed bottle test
1,1'- Phenyliminodiprop an-2-ol	3077-13-2	Modeled Biodegradation	28 days	BOD	6 %BOD/ThOD	Catalogic™
Propane-1,2-diol, propoxylated	25322-69-4	Experimental Biodegradation	28 days	BOD	93.6 %BOD/ThOD	OECD 301F - Manometric respirometry
Oxydipropanol	25265-71-8	Experimental Biodegradation	28 days	BOD	84.4 %BOD/ThOD	OECD 301F - Manometric respirometry
Oxydipropanol	25265-71-8	Experimental Aquatic Inherent Biodegrad.	42 days	Dissolv. Organic Carbon Deplet	83.6 %removal of DOC	OECD 302A - Modified SCAS Test
Oxydipropanol	25265-71-8	Experimental Biodegradation	64 days	Dissolv. Organic Carbon Deplet	23.6 %removal of DOC	OECD 306(Misc)-Biodegrad. Seaw
Carbon black	1333-86-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Silanamine, 1,1,1- trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	68909-20-6	Data not availbl- insufficient	N/A	N/A	N/A	N/A

# 3M Scotchcast<sup>TM</sup> Flame Retardant Resin 2131 (Part B)

1,4-	280-57-9	Experimental	28 days	CO2 evolution	7 %CO2	OECD 301B - Modified
diazabicyclooctane		Biodegradation	-		evolution/THCO2	sturm or CO2
					evolution	

## 12.3 : Bioaccumulative potential

homopolymer, hydroxy-terminated	1852-53-9	Data not available or insufficient for classification  Experimental	N/A	N/A	N/A	N/A
, , , , , , , , , , , , , , , , , , , ,		Experimental				
obenzene]		Bioconcentration		Log Kow	3.55	
Diundecyl 855 phthalate, branched and linear		Modeled Bioconcentration		Bioaccumulation factor	7.4	Catalogic <sup>TM</sup>
Diundecyl 855 phthalate, branched and linear		Experimental Bioconcentration		Log Kow	10.33	
Silicic acid, aluminum potassium sodium salt		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diantimony pentoxide 131		Analogous Compound BCF - Fish	23 days	Bioaccumulation factor	<=28.6	
Castor oil 800		Modeled Bioconcentration		Bioaccumulation factor	7.4	Catalogic <sup>TM</sup>
1,1'- Phenyliminodiprop an-2-ol		Modeled Bioconcentration		Bioaccumulation factor	2.8	Catalogic <sup>TM</sup>
Propane-1,2-diol, propoxylated 253		Experimental Bioconcentration		Log Kow	≤1.13	EC A.8 Partition Coefficient
Oxydipropanol 252	5265-71-8	Experimental BCF - Fish	42 days	Bioaccumulation factor	4.6	OECD305-Bioconcentration
Oxydipropanol 252		Experimental Bioconcentration		Log Kow	-0.462	EC A.8 Partition Coefficient
Carbon black 133		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	ı	Data not available or insufficient for classification		N/A	N/A	N/A
1,4- diazabicyclooctane 280	30-57-9	Experimental BCF - Fish	42 days	Bioaccumulation factor	<13	OECD305-Bioconcentration

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
1,1'- Phenyliminodipropa n-2-ol	3077-13-2	Modeled Mobility in Soil	Koc	150 l/kg	ACD/Labs ChemSketch™
Propane-1,2-diol, propoxylated	25322-69-4	Experimental Mobility in Soil	Koc	<17.8 l/kg	OECD 121 Estim. of Koc by HPLC
Oxydipropanol	25265-71-8	Modeled Mobility in Soil	Koc	1 l/kg	Episuite <sup>TM</sup>
1,4- diazabicyclooctane	280-57-9	Modeled Mobility in Soil	Koc	3 l/kg	Episuite <sup>TM</sup>

#### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

#### 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product—that has been completely cured or polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

#### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

# SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.

Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	CAS Nbr	<u>Classification</u>	Regulation
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### Global inventory status

Contact 3M for more information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2 None

#### Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

#### **SECTION 16: Other information**

#### List of relevant H statements

H302	Harmful if swallowed.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### 3M Scotchcast™ Flame Retardant Resin 2131 (Part B)

#### **Revision information:**

- Section 4: First aid for skin contact information information was modified.
- Section 7: Precautions safe handling information information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Carcinogenicity Table information was modified.
- Section 11: Health Effects Inhalation information information was modified.
- Section 11: Prolonged or repeated exposure may cause standard phrases information was added.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

#### 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.