

# Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 11-8904-2
 Version Number:
 23.00

 Issue Date:
 03/28/25
 Supercedes Date:
 08/28/24

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Process Color 990-06 Orange

# **Product Identification Numbers**

42-0016-3985-7, 75-0300-8075-0 7000004844

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Ink

## 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Commercial Branding and Transportation Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

# 2.1. Hazard classification

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1A.

Reproductive Toxicity: Category 1B.

Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 1. Specific Target Organ Toxicity (single exposure): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1.

# 2.2. Label elements

### Signal word

Danger

#### **Symbols**

Flame | Corrosion | Exclamation mark | Health Hazard |

### **Pictograms**



#### **Hazard Statements**

Flammable liquid and vapor.

Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

May cause cancer.

Causes damage to organs:

sensory organs

Causes damage to organs through prolonged or repeated exposure:

nervous system

May cause damage to organs through prolonged or repeated exposure:

sensory organs

# **Precautionary Statements**

### **Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

#### **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### **Storage:**

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

## Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

16% of the mixture consists of ingredients of unknown acute inhalation toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
1-Methoxy-2-propyl acetate	108-65-6	10 - 30 Trade Secret *
Cyclohexanone	108-94-1	10 - 30 Trade Secret *
Dipropylene glycol methyl ether acetate	88917-22-0	10 - 30 Trade Secret *
Vinyl polymer (NJTSR # 04499600-5238P	Trade Secret*	10 - 30 Trade Secret *
2,3,4,5- Tetrachloro-6-cyanobenzoic acid,methyl	106276-79-3	1 - 5 Trade Secret *
ester,reaction products with 2-methyl-1,3-		
benzenediamine and sodium methoxide		
Xylene	1330-20-7	1 - 5 Trade Secret *
Alkyd resin 3261 (NJTSR # 04499600-6267P)	Trade Secret*	1 - 5 Trade Secret *
Organic pigment (NJTSR # 04499600-5836P)	Trade Secret*	1 - 5 Trade Secret *
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione	68511-62-6	0.5 - 2 Trade Secret *
complexes		
Ethylbenzene	100-41-4	< 0.9 Trade Secret *
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	52829-07-9	< 0.5 Trade Secret *
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-	104810-48-2	< 0.3 Trade Secret *
2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-		
oxopropyl]omegahydroxy-		
Polymeric Benzotriazole	104810-47-1	< 0.3 Trade Secret *
Calcium 2-ethylhexanoate	136-51-6	< 0.2 Trade Secret *
Dibutyltin dilaurate	77-58-7	< 0.2 Trade Secret *
Zinc 2-ethylhexanoate	136-53-8	< 0.2 Trade Secret *
Nickel salts of naphthenic acids	61788-71-4	< 0.03 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

# **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

#### **Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

# 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

# **Hazardous Decomposition or By-Products**

Substance	Condition
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

# 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or

To larger spins, cover arange and outer areas to prevent enary into sewer systems of

bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal
				carcin., Ototoxicant
Ethylbenzene	100-41-4	OSHA	TWA:435 mg/m3(100 ppm)	
1-Methoxy-2-propyl acetate	108-65-6	AIHA	TWA:50 ppm	
Cyclohexanone	108-94-1	ACGIH	TWA:20 ppm;STEL:50 ppm	A3: Confirmed animal
				carcin., Danger of
				cutaneous absorption
Cyclohexanone	108-94-1	OSHA	TWA:200 mg/m3(50 ppm)	
Xylene	1330-20-7	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcin
Xylene	1330-20-7	OSHA	TWA:435 mg/m3(100 ppm)	
NICKEL, SOLUBLE	61788-71-4	OSHA	TWA(as Ni):1 mg/m3	
COMPOUNDS				
NICKEL, INSOLUBLE	68511-62-6	OSHA	TWA(as Ni):1 mg/m3	
COMPOUNDS				
TIN, ORGANIC COMPOUNDS	77-58-7	ACGIH	TWA(as Sn):0.1	A4: Not class. as human

19

				carcin, Danger of cutaneous absorption
TIN, ORGANIC COMPOUNDS	77-58-7	OSHA	TWA(as Sn):0.1 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

# 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

## 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

**Indirect Vented Goggles** 

# Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical stateLiquidColorOrange

**Specific Physical Form:** liquid

OdorModerate SolventOdor thresholdNo Data Available

pH Not Applicable
Melting point Not Applicable
Boiling Point >=281 °F

Flash Point 109 °F [Test Method: Tagliabue Closed Cup]

**Evaporation rate** <=1 [Ref Std:BUOAC=1]

Flammability (solid, gas) Not Applicable

Flammable Limits(LEL) 1 % Flammable Limits(UEL) 9.4 %

 Vapor Pressure
 <=5.1 mmHg [@ 68 °F]</td>

 Vapor Density
 >=3.4 [Ref Std: AIR=1]

 Density
 0.97 g/ml [@ 20 °C]

 Specific Gravity
 0.97 [Ref Std: WATER=1]

 Solubility In Water
 No Data Available

Solubility- non-water

Partition coefficient: n-octanol/ water

Autoignition temperature

No Data Available
No Data Available
No Data Available
No Data Available

**Decomposition temperature**No Data Available**Viscosity**900 - 1,500 centipoise

Volatile Organic Compounds 700 - 800 g/l [Details: As Packaged.]

**Percent volatile VOC Less H2O & Exempt Solvents**65 - 80 % weight

No Data Available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Sparks and/or flames

# 10.5. Incompatible materials

Strong oxidizing agents

# 10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1. Information on Toxicological effects

# Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### **Skin Contact:**

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

## **Eve Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

### **Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

### **Additional Health Effects:**

# Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

# Prolonged or repeated exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### **Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Nickel Compounds (except alloys)	61788-71-4	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Nickel Compounds (except alloys)	68511-62-6	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Nickel compounds	61788-71-4	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Nickel compounds	68511-62-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Acute Toxicity	Donat	C	V-l
Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Cyclohexanone	Dermal	Rabbit	LD50 >794, <3160 mg/kg
Cyclohexanone	Inhalation- Vapor (4 hours)	Rat	LC50 > 6.2 mg/l
Cyclohexanone	Ingestion	Rat	LD50 1,296 mg/kg
1-Methoxy-2-propyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
1-Methoxy-2-propyl acetate	Inhalation- Vapor (4 hours)	Rat	LC50 > 28.8 mg/l
1-Methoxy-2-propyl acetate	Ingestion	Rat	LD50 8,532 mg/kg
Vinyl polymer (NJTSR # 04499600-5238P	Dermal	Rabbit	LD50 > 8,000 mg/kg
Vinyl polymer (NJTSR # 04499600-5238P	Ingestion	Rat	LD50 > 8,000 mg/kg
Dipropylene glycol methyl ether acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Dipropylene glycol methyl ether acetate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Dipropylene glycol methyl ether acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Alkyd resin 3261 (NJTSR # 04499600-6267P)	Dermal		LD50 estimated to be > 5,000 mg/kg
Alkyd resin 3261 (NJTSR # 04499600-6267P)	Ingestion		LD50 estimated to be > 5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation- Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Organic pigment (NJTSR # 04499600-5836P)	Dermal	Rat	LD50 > 2,000 mg/kg
Organic pigment (NJTSR # 04499600-5836P)	Ingestion	Rat	LD50 > 5,000 mg/kg
2,3,4,5- Tetrachloro-6-cyanobenzoic acid,methyl ester,reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide	Ingestion	Rat	LD50 > 5,000 mg/kg
2,3,4,5- Tetrachloro-6-cyanobenzoic acid,methyl ester,reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide	Dermal	similar compoun ds	LD50 > 2,500 mg/kg
2,3,4,5- Tetrachloro-6-cyanobenzoic acid,methyl ester,reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide	Inhalation- Dust/Mist (4 hours)	similar compoun ds	LC50 > 1.04 mg/l
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.222 mg/l
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Ingestion	Rat	LD50 > 5,000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation- Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Dermal	Rat	LD50 > 3,170 mg/kg
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.5 mg/l

Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Ingestion	Rat	LD50 3,700 mg/kg
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Dermal	Rat	LD50 > 2,000 mg/kg
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.8 mg/l
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Ingestion	Rat	LD50 > 5,000 mg/kg
Polymeric Benzotriazole	Dermal	Rat	LD50 > 2,000 mg/kg
Polymeric Benzotriazole	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.8 mg/l
Polymeric Benzotriazole	Ingestion	Rat	LD50 > 5,000 mg/kg
Dibutyltin dilaurate	Dermal	Rat	LD50 > 2,000 mg/kg
Dibutyltin dilaurate	Ingestion	Rat	LD50 1,290 mg/kg
Zinc 2-ethylhexanoate	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc 2-ethylhexanoate	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium 2-ethylhexanoate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Calcium 2-ethylhexanoate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.2 mg/l
Calcium 2-ethylhexanoate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nickel salts of naphthenic acids	Ingestion	Rat	LD50 419 mg/kg

ATE = acute toxicity estimate

# **Skin Corrosion/Irritation**

Name	Species	Value
Cyclohexanone	Rabbit	Irritant
1-Methoxy-2-propyl acetate	Rabbit	No significant irritation
Vinyl polymer (NJTSR # 04499600-5238P	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Dipropylene glycol methyl ether acetate	Rabbit	No significant irritation
Xylene	Rabbit	Mild irritant
Organic pigment (NJTSR # 04499600-5836P)	Rabbit	No significant irritation
2,3,4,5- Tetrachloro-6-cyanobenzoic acid,methyl ester,reaction products with 2-	Rabbit	No significant irritation
methyl-1,3-benzenediamine and sodium methoxide		
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Mild irritant
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Rabbit	No significant irritation
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	Rabbit	No significant irritation
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-		
Polymeric Benzotriazole	Rabbit	No significant irritation
Dibutyltin dilaurate	Rabbit	Corrosive
Zinc 2-ethylhexanoate	Rabbit	Mild irritant
Calcium 2-ethylhexanoate	Rabbit	No significant irritation
Nickel salts of naphthenic acids	Professio	Minimal irritation
	nal	
	judgeme	
	nt	

**Serious Eye Damage/Irritation** 

Name	Species	Value
Cyclohexanone	In vitro data	Corrosive
1-Methoxy-2-propyl acetate	Rabbit	Mild irritant
Vinyl polymer (NJTSR # 04499600-5238P	Professio nal judgeme	No significant irritation

**Page** 10 **of** 19

	nt	
Dipropylene glycol methyl ether acetate	Rabbit	No significant irritation
Xylene	Rabbit	Mild irritant
Organic pigment (NJTSR # 04499600-5836P)	Rabbit	No significant irritation
2,3,4,5- Tetrachloro-6-cyanobenzoic acid,methyl ester,reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide	Rabbit	No significant irritation
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Moderate irritant
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Rabbit	Corrosive
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Rabbit	No significant irritation
Polymeric Benzotriazole	Rabbit	No significant irritation
Dibutyltin dilaurate	Rabbit	Corrosive
Zinc 2-ethylhexanoate	Rabbit	Severe irritant
Calcium 2-ethylhexanoate	Rabbit	Corrosive
Nickel salts of naphthenic acids	Professio	Mild irritant
	nal	
	judgeme	
	nt	

# **Skin Sensitization**

Name	Species	Value
Cyclohexanone	Guinea	Not classified
•	pig	
1-Methoxy-2-propyl acetate	Guinea	Not classified
	pig	
Dipropylene glycol methyl ether acetate	Guinea	Not classified
	pig	
Organic pigment (NJTSR # 04499600-5836P)	Mouse	Not classified
2,3,4,5- Tetrachloro-6-cyanobenzoic acid, methyl ester, reaction products with 2-	Mouse	Not classified
methyl-1,3-benzenediamine and sodium methoxide		
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	similar	Sensitizing
	compoun	
	ds	
Ethylbenzene	Human	Not classified
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Guinea	Not classified
	pig	
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	Guinea	Sensitizing
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	pig	
Polymeric Benzotriazole	Guinea	Sensitizing
	pig	
Dibutyltin dilaurate	Guinea	Sensitizing
	pig	
Nickel salts of naphthenic acids	similar	Sensitizing
	compoun	
	ds	

# **Photosensitization**

Name	Species	Value
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Guinea	Not sensitizing
	pig	

**Respiratory Sensitization** 

Name	Species	Value
Nickel salts of naphthenic acids	Professio nal judgeme nt	Sensitizing

**Germ Cell Mutagenicity** 

Germ Gen Wataugemeity		
Name	Route	Value

Cyclohexanone	In Vitro	Not mutagenic
Cyclohexanone	In vivo	Not mutagenic
1-Methoxy-2-propyl acetate	In Vitro	Not mutagenic
Dipropylene glycol methyl ether acetate	In Vitro	Not mutagenic
Dipropylene glycol methyl ether acetate	In vivo	Not mutagenic
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Organic pigment (NJTSR # 04499600-5836P)	In Vitro	Not mutagenic
2,3,4,5- Tetrachloro-6-cyanobenzoic acid,methyl ester,reaction products with 2-	In Vitro	Not mutagenic
methyl-1,3-benzenediamine and sodium methoxide		
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	In Vitro	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	In Vitro	Not mutagenic
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	In Vitro	Not mutagenic
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-		
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	In vivo	Not mutagenic
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-		
Polymeric Benzotriazole	In Vitro	Not mutagenic
Polymeric Benzotriazole	In vivo	Not mutagenic
Dibutyltin dilaurate	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Dibutyltin dilaurate	In vivo	Mutagenic
Calcium 2-ethylhexanoate	In Vitro	Not mutagenic
Nickel salts of naphthenic acids	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Nickel salts of naphthenic acids	In vivo	Mutagenic

Carcinogenicity

Name	Route	Species	Value
Cyclohexanone	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes	Not Specified	similar compoun ds	Carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
Nickel salts of naphthenic acids	Inhalation	similar compoun ds	Carcinogenic

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name Name	Route	Value	Species	Test Result	Exposure Duration
Cyclohexanone	Inhalation	Not classified for female reproduction	Rat	NOAEL 4 mg/l	2 generation
Cyclohexanone	Ingestion	Not classified for development	Rabbit	NOAEL 500 mg/kg/day	during gestation
Cyclohexanone	Inhalation	Not classified for male reproduction	Rat	NOAEL 2 mg/l	2 generation
Cyclohexanone	Inhalation	Not classified for development	Rat	NOAEL 2.6 mg/l	during gestation
1-Methoxy-2-propyl acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during

**Page** 12 **of** 19

					gestation
1-Methoxy-2-propyl acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-Methoxy-2-propyl acetate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-Methoxy-2-propyl acetate	Inhalation	Not classified for development	Rat	NOAEL 21.6 mg/l	during organogenesi s
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesi s
Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Organic pigment (NJTSR # 04499600-5836P)	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Organic pigment (NJTSR # 04499600- 5836P)	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Organic pigment (NJTSR # 04499600- 5836P)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)- pyrimidinetrione complexes	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 430 mg/kg/day	2 generation
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Ingestion	Not classified for development	Rat	NOAEL 130 mg/kg/day	2 generation
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 130 mg/kg/day	2 generation
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	premating into lactation
Poly(oxy-1,2-ethanediyl), alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Ingestion	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	115 days
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Ingestion	Not classified for development	Rat	NOAEL 2 mg/kg/day	premating into lactation
Polymeric Benzotriazole	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	premating into lactation
Polymeric Benzotriazole	Ingestion	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	115 days
Polymeric Benzotriazole	Ingestion	Not classified for development	Rat	NOAEL 2 mg/kg/day	premating into lactation
Dibutyltin dilaurate	Ingestion	Toxic to female reproduction	Rat	NOAEL 2 mg/kg/day	premating into lactation
Dibutyltin dilaurate	Ingestion	Toxic to development	Rat	NOAEL 2.5 mg/kg/day	during gestation
Zinc 2-ethylhexanoate	Ingestion	Not classified for female reproduction	similar compoun ds	NOAEL 800 mg/kg/day	2 generation
Zinc 2-ethylhexanoate	Ingestion	Not classified for male reproduction	similar compoun ds	NOAEL 800 mg/kg/day	2 generation
Zinc 2-ethylhexanoate	Ingestion	Toxic to development	similar compoun ds	NOAEL 100 mg/kg/day	during gestation
Calcium 2-ethylhexanoate	Ingestion	Not classified for female reproduction	similar	NOAEL 800	2 generation

**Page** 13 **of** 19

			compoun ds	mg/kg/day	
Calcium 2-ethylhexanoate	Ingestion	Not classified for male reproduction	similar compoun ds	NOAEL 800 mg/kg/day	2 generation
Calcium 2-ethylhexanoate	Ingestion	Toxic to development	similar compoun ds	NOAEL 100 mg/kg/day	during gestation
Nickel salts of naphthenic acids	Ingestion	Toxic to development	similar compoun ds	NOAEL not available	2 generation

# Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) |

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Cyclohexanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Guinea pig	LOAEL 16.1 mg/l	6 hours
Cyclohexanone	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	
Cyclohexanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
1-Methoxy-2-propyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1-Methoxy-2-propyl acetate	Ingestion	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL not available	
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Dermal	photoirritation	Not classified	Mouse	NOAEL not available	
Bis(2,2,6,6-tetramethyl-4-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL not	

**Page** 14 **of** 19

piperidinyl) sebacate			data are not sufficient for	health	available	
			classification	hazards		
Dibutyltin dilaurate	Ingestion	immune system	Causes damage to organs	Rat	LOAEL 5	
					mg/kg	
Zinc 2-ethylhexanoate	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL not	
			data are not sufficient for	health	available	
			classification	hazards		
Calcium 2-ethylhexanoate	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL not	
			data are not sufficient for	health	available	
			classification	hazards		

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Cyclohexanone	Inhalation	liver   kidney and/or bladder   heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles   nervous system   eyes   respiratory system   vascular system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Ingestion	hematopoietic system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 407 mg/kg/day	3 months
1-Methoxy-2-propyl acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 16.2 mg/l	9 days
1-Methoxy-2-propyl acetate	Inhalation	olfactory system	Not classified	Mouse	LOAEL 1.62 mg/l	9 days
1-Methoxy-2-propyl acetate	Inhalation	blood	Not classified	Multiple animal species	NOAEL 16.2 mg/l	9 days
1-Methoxy-2-propyl acetate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	44 days
Dipropylene glycol methyl ether acetate	Ingestion	liver   heart   endocrine system   hematopoietic system   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days

**Page** 15 **of** 19

Xylene	Ingestion	liver	Not classified	Multiple animal	NOAEL Not available	
Xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Organic pigment (NJTSR # 04499600-5836P)	Ingestion	heart   endocrine system   gastrointestinal tract   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Nickel, 5,5'-azobis- 2,4,6(1H,3H,5H)- pyrimidinetrione complexes	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart   immune system   respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Bis(2,2,6,6-tetramethyl-4-piperidinyl) sebacate	Ingestion	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 261 mg/kg/day	90 days
Poly(oxy-1,2- ethanediyl), .alpha[3-[3- (2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4- hydroxyphenyl]-1- oxopropyl]omega	Ingestion	liver   endocrine system   hematopoietic system   eyes   kidney and/or bladder   respiratory	Not classified	Rat	NOAEL 50 mg/kg/day	90 days

**Page** 16 **of** 19

hydroxy-		system				
Polymeric Benzotriazole	Ingestion	liver   endocrine system   hematopoietic system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 50 mg/kg/day	90 days
Dibutyltin dilaurate	Ingestion	liver	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 2 mg/kg/day	2 weeks
Dibutyltin dilaurate	Ingestion	immune system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 mg/kg/day	28 days
Nickel salts of naphthenic acids	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	similar compoun ds	NOAEL not available	13 weeks

**Aspiration Hazard** 

Name		Value		
Xylene		Aspiration hazard		
Ethylbenzene		Aspiration hazard		

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

## **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D018 (Benzene)

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

# 15.1. US Federal Regulations

Contact 3M for more information.

### **EPCRA 311/312 Hazard Classifications:**

Physical Hazards	
Flammable (gases, aerosols, liquids, or solids)	

Health Hazards	
Carcinogenicity	
Reproductive toxicity	
Respiratory or Skin Sensitization	
Serious eye damage or eye irritation	
Skin Corrosion or Irritation	
Specific target organ toxicity (single or repeated exposure)	

# Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	<u>% by Wt</u>
Xylene	1330-20-7	Trade Secret 1 - 5
Xylene (Benzene, dimethyl-)	1330-20-7	Trade Secret 1 - 5
Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione	68511-62-6	Trade Secret 0.5 - 2
complexes (NICKEL COMPOUNDS)		
Ethylbenzene	100-41-4	Trade Secret < 0.9
Nickel salts of naphthenic acids (NICKEL	61788-71-4	Trade Secret < 0.03
COMPOUNDS)		

# 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. One or more chemical components of this material have been commercialized under the TSCA polymer exemption at 40CFR723.250. Polymers subject to this exemption are not listed on the TSCA Inventory, but are in compliance with TSCA requirements.

Contact 3M for more information.

# 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

# NFPA Hazard Classification

Health: 3 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:11-8904-2Version Number:23.00Issue Date:03/28/25Supercedes Date:08/28/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com