

# **Safety Data Sheet**

Copyright, 2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 07-3297-4
 Version number:
 9.01

 Issue Date:
 2025/06/05
 Supercedes Date:
 2015/12/31

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Wire Pulling Lubricant Wintergrade WLW Series (WLW-QT, WLW-1, WLW-5)

**Product Identification Numbers** 

80-6108-3368-5 80-6108-3369-3 80-6108-3370-1

#### 1.2. Recommended use and restrictions on use

**Intended Use** 

WIRE PULLING LUBRICANT

**Specific Use** 

WIRE PULLING LUBRICANT

#### Restrictions on use

Not applicable

#### 1.3. Supplier's details

**Company:** 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

## 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

## **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

#### 2.2. Label elements

#### Signal word

Not applicable.

### 3MTM Wire Pulling Lubricant Wintergrade WLW Series (WLW-QT, WLW-1, WLW-5)

#### **Symbols**

Not applicable

#### **Pictograms**

Not applicable

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Water	7732-18-5	75 - 80	Water
PROPYLENE GLYCOL	57-55-6	15 - 19	1,2-Propanediol
GLYCOLS, POLYPROPYLENE	25322-69-4	0.1 - 2	Poly[oxy(methyl-1,2-ethanediyl)], .alphahydroomegahydroxy-
Polyethylene Glycol	25322-68-3	0.1 - 2	Poly(oxy-1,2-ethanediyl), .alpha hydroomegahydroxy-
SODIUM POLYACRYLATE	9003-04-7	0.1 - 1	2-Propenoic acid, homopolymer, sodium salt

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

#### Skin Contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

#### 5.2. Unsuitable extinguishing media

None Determined

#### 5.3. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

**Substance** 

Carbon monoxide Carbon dioxide

#### **Condition**

**During Combustion During Combustion** 

#### 5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Ventilate the area with fresh air. Observe precautions from other sections.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

#### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Polyethylene Glycol	25322-68-3	AIHA	TWA:10 mg/m3	
GLYCOLS, POLYPROPYLENE	25322-69-4	AIHA	TWA(as aerosol):10 mg/m3	
PROPYLENE GLYCOL	57-55-6	AIHA	TWA(as aerosol):10 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

D 2 C

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

No protective gloves required.

#### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

information on basic physical and chemical pro	operties	
Physical state	Liquid	
Specific Physical Form:	Gel	
Colour	Light Green	
Odour	Odourless	
Odour threshold	No Data Available	
pH	6.5 - 8.5	
Melting point/Freezing point	-12.2 °C	
<b>Boiling point</b>	>=100 °C	
Flash Point	No flash point	
Evaporation rate	Approximately 1 Units not available or not applicable [Ref	
	Std:WATER=1]	
Flammability	Not Applicable	
Flammable Limits(LEL)	No Data Available	
Flammable Limits(UEL)	No Data Available	
Vapour Pressure	Approximately 2,399.8 Pa [Details:@20C.]	
Relative Vapour Density	0.9 - 1.1 [ <i>Ref Std</i> :AIR=1]	
Density	Not Applicable	
Relative density	Approximately 1.01 [Ref Std:WATER=1]	
Water solubility	Complete	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	Not Applicable	

Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Kinematic Viscosity	89,109 mm2/sec
Volatile Organic Compounds	18 %
Percent volatile	97 % weight
VOC Less H2O & Exempt Solvents	18 %
Average particle size	Not Applicable
Bulk density	Not Applicable
Molecular weight	Not Applicable
Softening point	Not Applicable

Particle Characteristics	Not Applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

#### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

## 10.4. Conditions to avoid

None known.

# 10.5. Incompatible materials

None known.

Not Applicable

#### 10.6. Hazardous decomposition products

Substance Aldehydes Condition

Oxidation, heat or reaction

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

No known health effects.

\_\_\_\_\_

#### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

Contact with the eyes during product use is not expected to result in significant irritation.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
PROPYLENE GLYCOL	Dermal	Rabbit	LD50 20,800 mg/kg
PROPYLENE GLYCOL	Ingestion	Rat	LD50 22,000 mg/kg
GLYCOLS, POLYPROPYLENE	Dermal	Rabbit	LD50 > 10,000 mg/kg
Polyethylene Glycol	Dermal	Rabbit	LD50 > 20,000 mg/kg
GLYCOLS, POLYPROPYLENE	Ingestion	Rat	LD50 > 1,000 mg/kg
Polyethylene Glycol	Ingestion	Rat	LD50 32,770 mg/kg
SODIUM POLYACRYLATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
SODIUM POLYACRYLATE	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
PROPYLENE GLYCOL	Rabbit	No significant irritation
GLYCOLS, POLYPROPYLENE	Not	No significant irritation
	available	
Polyethylene Glycol	Rabbit	Minimal irritation
SODIUM POLYACRYLATE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
PROPYLENE GLYCOL	Rabbit	No significant irritation
GLYCOLS, POLYPROPYLENE	Not	Mild irritant
	available	
Polyethylene Glycol	Rabbit	Mild irritant
SODIUM POLYACRYLATE	Rabbit	No significant irritation

#### **Skin Sensitization**

Name	Species	Value
PROPYLENE GLYCOL	Human	Not classified
GLYCOLS, POLYPROPYLENE	Human and	Not classified
	animal	
Polyethylene Glycol	Guinea	Not classified
	pig	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

	Name	Route	Value
--	------	-------	-------

PROPYLENE GLYCOL	In Vitro	Not mutagenic
PROPYLENE GLYCOL	In vivo	Not mutagenic
GLYCOLS, POLYPROPYLENE	In Vitro	Not mutagenic
Polyethylene Glycol	In Vitro	Not mutagenic
Polyethylene Glycol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
PROPYLENE GLYCOL	Dermal	Mouse	Not carcinogenic
PROPYLENE GLYCOL	Ingestion	Multiple animal species	Not carcinogenic
Polyethylene Glycol	Ingestion	Rat	Not carcinogenic

## Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
PROPYLENE GLYCOL	Ingestion	Not classified for female reproduction	Mouse	NOAEL 10,100 mg/kg/day	2 generation
PROPYLENE GLYCOL	Ingestion	Not classified for male reproduction	Mouse	NOAEL 10,100 mg/kg/day	2 generation
PROPYLENE GLYCOL	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,230 mg/kg/day	during organogenesi s
Polyethylene Glycol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
Polyethylene Glycol	Ingestion	Not classified for male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days
Polyethylene Glycol	Not Specified	Not classified for reproduction and/or development		NOEL N/A	
Polyethylene Glycol	Ingestion	Not classified for development	Mouse	NOAEL 562 mg/animal/da y	during gestation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Specific Target Organ Toxicity - single exposure						
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
PROPYLENE GLYCOL	Ingestion	central nervous system depression	Not classified	Human and animal	NOAEL Not available	
Polyethylene Glycol	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
PROPYLENE GLYCOL	Ingestion	hematopoietic system	Not classified	Multiple animal species	NOAEL 1,370 mg/kg/day	117 days
PROPYLENE GLYCOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 5,000 mg/kg/day	104 weeks
Polyethylene Glycol	Inhalation	respiratory system	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks
Polyethylene Glycol	Ingestion	kidney and/or bladder   heart	Not classified	Rat	NOAEL 5,640	13 weeks

Page: 7 of 9

3M™ Wire Pulling Lubricant Wintergrade WLW Series (WLW-QT, WLW-1, WLW-5)							
						1	
		endocrine system			mg/kg/day		
		hematonoietic					

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

system | liver |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

## Health: 0 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	07-3297-4	Version number:	9.01
Issue Date:	2025/06/05	Supercedes Date:	2015/12/31

#### Reason for Reissue

Conversion to GHS format SDS.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca