



Safety Data Sheet

Copyright, 2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	18-5798-6	Version number:	5.08
Issue Date:	2026/02/02	Supersedes Date:	2025/12/03

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M(TM) SCOTCH-WELD(TM) 2214 REGULAR EPOXY ADHESIVE

Product Identification Numbers

62-2214-2930-1	62-2214-2932-7	62-2214-2935-0	62-2214-6530-5	62-2214-7530-4
62-2214-8530-3	H0-0021-5153-0			

1.2. Recommended use and restrictions on use

Intended Use
Adhesive

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Industrial Adhesives and Tapes Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2B.
Skin Sensitizer: Category 1.

2.2. Label elements

Signal word
Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

Causes eye irritation. May cause an allergic skin reaction.

Precautionary statements

Prevention:

Avoid breathing fumes. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical advice. Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Aluminum Pigments	7429-90-5	15 - 40	Aluminum
Epoxy Resin 1	25068-38-6	15 - 40 Trade Secret *	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
Amorphous Silica	67762-90-7	1 - 5	Siloxanes and Silicones, di-Me, reaction products with silica
Dicyandiamide	461-58-5	1 - 5	Guanidine, cyano-
Epoxy Resin 2	41638-13-5	1 - 5 Trade Secret *	Oxirane, 2,2'-[oxybis[(methyl-2,1-ethanediyl)oxymethylene]]bis-
p-Chlorophenyl-Dimethylurea	150-68-5	1 - 5 Trade Secret *	Urea, N'-(4-chlorophenyl)-N,N-dimethyl-
Synthetic Elastomer	Trade Secret	1 - 5	Not Applicable
1,4-bis[(2,3-epoxypropoxy)methyl]cyclohexane	14228-73-0	0.1 - 1 Trade Secret *	Oxirane, 2,2'-[1,4-cyclohexanedylbis(methyleneoxymethylene)]bis-

Synthetic Elastomer is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes

Chlorine

Carbon monoxide

Carbon dioxide

Hydrogen Chloride

Hydrogen Cyanide

Ammonia

Oxides of Nitrogen

Condition

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

5.4. Special protection actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing

bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store in a dry place. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
p-Chlorophenyl-Dimethylurea	150-68-5	Manufacturer determined	TWA(Inhalable aerosol)(8 hours):1 mg/m ³	
Aluminum metal and insoluble compounds, respirable fraction	7429-90-5	ACGIH	TWA(respirable fraction):1 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	7429-90-5	ACGIH	TWA(inhalable particulates):10 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	7429-90-5	ACGIH	TWA(respirable particles):3 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

Provide appropriate local exhaust when product is heated.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Colour	Gray
Odour	Mild Epoxy
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	>=260 °C
Flash Point	248.9 °C [Test Method: Closed Cup]
Evaporation rate	Negligible
Flammability	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapour Pressure	No Data Available
Relative Vapour Density	No Data Available

Density	1.44 g/ml [Ref Std: WATER=1]
Relative density	1.44 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	694,444 mm ² /sec
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H ₂ O & Exempt Solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]
VOC Less H ₂ O & Exempt Solvents	0 % [Test Method:calculated per CARB title 2]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Pigments	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Pigments	Ingestion		LD50 estimated to be > 5,000 mg/kg
Aluminum Pigments	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.888 mg/l
Epoxy Resin 1	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin 1	Ingestion	Rat	LD50 > 1,000 mg/kg
Dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Epoxy Resin 2	Dermal	Rabbit	LD50 > 2,000 mg/kg
Dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg
Epoxy Resin 2	Ingestion	Rat	LD50 > 2,000 mg/kg
Synthetic Elastomer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Synthetic Elastomer	Ingestion	Rat	LD50 > 30,000 mg/kg
p-Chlorophenyl-Dimethylurea	Dermal	Rabbit	LD50 > 2,500 mg/kg
p-Chlorophenyl-Dimethylurea	Ingestion	Rat	LD50 1,480 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
1,4-bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Rat	LD50 1,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Pigments	Rabbit	No significant irritation
Epoxy Resin 1	Rabbit	Mild irritant
Dicyandiamide	Human and animal	Minimal irritation
Epoxy Resin 2	Rabbit	No significant irritation
Synthetic Elastomer	Professional judgement	No significant irritation

3M(TM) SCOTCH-WELD(TM) 2214 REGULAR EPOXY ADHESIVE

p-Chlorophenyl-Dimethylurea	similar compounds	Mild irritant
Amorphous Silica	Rabbit	No significant irritation
1,4-bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro data	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Pigments	Rabbit	No significant irritation
Epoxy Resin 1	Rabbit	Moderate irritant
Dicyandiamide	Professional judgement	Mild irritant
Epoxy Resin 2	Rabbit	Moderate irritant
Synthetic Elastomer	Professional judgement	No significant irritation
p-Chlorophenyl-Dimethylurea	similar compounds	Moderate irritant
Amorphous Silica	Rabbit	No significant irritation
1,4-bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro data	No significant irritation

Skin Sensitization

Name	Species	Value
Aluminum Pigments	Guinea pig	Not classified
Epoxy Resin 1	Human and animal	Sensitizing
Dicyandiamide	Guinea pig	Not classified
Epoxy Resin 2	Guinea pig	Sensitizing
Amorphous Silica	Human and animal	Not classified
1,4-bis[(2,3-epoxypropoxy)methyl]cyclohexane	similar compounds	Sensitizing

Respiratory Sensitization

Name	Species	Value
Aluminum Pigments	Human	Not classified
Epoxy Resin 1	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Pigments	In Vitro	Not mutagenic
Epoxy Resin 1	In vivo	Not mutagenic
Epoxy Resin 1	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	In Vitro	Not mutagenic
Epoxy Resin 2	In Vitro	Some positive data exist, but the data are not sufficient for classification
p-Chlorophenyl-Dimethylurea	In Vitro	Some positive data exist, but the data are not sufficient for classification

3M(TM) SCOTCH-WELD(TM) 2214 REGULAR EPOXY ADHESIVE

p-Chlorophenyl-Dimethylurea	In vivo	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	In Vitro	Not mutagenic
1,4-bis[(2,3-epoxypropoxy)methyl]cyclohexane	In Vitro	Mutagenic; structurally related to germ cell mutagens

Carcinogenicity

Name	Route	Species	Value
Epoxy Resin 1	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	Ingestion	Rat	Not carcinogenic
p-Chlorophenyl-Dimethylurea	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Epoxy Resin 1	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin 1	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin 1	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin 1	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Dicyandiamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dicyandiamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
Dicyandiamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
p-Chlorophenyl-Dimethylurea	Ingestion	Not classified for development	Mouse	LOAEL 215 mg/kg/day	during gestation
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Epoxy Resin 1	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Epoxy Resin 2	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL not available	
p-Chlorophenyl-Dimethylurea	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar compounds	NOAEL Not available	
p-Chlorophenyl-Dimethylurea	Ingestion	methemoglobinemia	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	not applicable
1,4-bis[(2,3-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	

3M(TM) SCOTCH-WELD(TM) 2214 REGULAR EPOXY ADHESIVE

epoxypropoxy)methyl]cyclohexane			data are not sufficient for classification	health hazards	available	
---------------------------------	--	--	--	----------------	-----------	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum Pigments	Inhalation	nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Aluminum Pigments	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Epoxy Resin 1	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin 1	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin 1	Ingestion	auditory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy Resin 1	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy Resin 1	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy Resin 1	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy Resin 1	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy Resin 1	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy Resin 1	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Dicyandiamide	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks
p-Chlorophenyl-Dimethylurea	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 800 mg/kg/day	103 weeks
p-Chlorophenyl-Dimethylurea	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 65 mg/kg/day	103 weeks
p-Chlorophenyl-Dimethylurea	Ingestion	immune system	Not classified	Rat	LOAEL 520 mg/kg/day	13 weeks
Amorphous Silica	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Amorphous Silica	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	18-5798-6	Version number:	5.08
Issue Date:	2026/02/02	Supersedes Date:	2025/12/03

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE,

COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca