



Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-3682-9	Version number:	6.00
Revision date:	19/12/2024	Supersedes date:	03/02/2022
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™ Aerospace Sealant AC-251 Black B-2

Product Identification Numbers

70-0052-0957-5 70-0052-4364-0

7010372247 7100169376

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000

E Mail: tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

30-3448-5, 30-3193-7

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H302

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



HAZARD STATEMENTS:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
------	--

H410	Very toxic to aquatic life with long lasting effects.
------	---

PRECAUTIONARY STATEMENTS

Prevention:

P260A	Do not breathe vapours.
P273	Avoid release to the environment.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P391	Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Precautionary statements

Prevention:

P260A

Do not breathe vapours.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

GB Kit Information: CLP Percent Unknown information was added.

Label: CLP Percent Unknown - Kit information was deleted.

Kit Information: CLP Target Organ Hazard Statement information was deleted.

Label: CLP Ingredients - kit components information was deleted.

Section 1: Product use information information was modified.

Section 2: <125ml Hazard - Health information was deleted.

Section 2: <125ml Precautionary - Prevention information was modified.

Section 2: <125ml Precautionary - Response information was deleted.

Section 02: CLP Physical and Health Hazard Statements information was modified.

Label: CLP Classification information was modified.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.

Label: CLP Target Organ Hazard Statement information was added.

Label: Signal Word information was modified.

Section 02: SDS Elements: CLP Supplemental Precautionary Statements information was deleted.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-3193-7	Version number:	10.01
Revision date:	07/02/2025	Supersedes date:	19/12/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Aerospace Sealant AC-251 Black B-2 Catalyst

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Hardener

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H302
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



HAZARD STATEMENTS:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260A	Do not breathe vapours.
P273	Avoid release to the environment.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P391	Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Precautionary statements

Prevention:

P260A	Do not breathe vapours.
-------	-------------------------

10% of the mixture consists of components of unknown acute oral toxicity.

Contains 49% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Contains a substance identified as an endocrine disrupter in the list established in accordance with REACH Article 59(1), as amended by UK REACH Regulations SI 2019/758. Contains a substance that meets the criteria for vPvB according to Regulation (EC) No 1907/2006, Annex XIII, as amended by UK REACH Regulations SI 2019/758.

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
manganese dioxide	(CAS-No.) 1313-13-9 (EC-No.) 215-202-6	30 - 50	Acute Tox. 4, H332 Acute Tox. 4, H302 EUH031 STOT RE 2, H373
Hydrogenated terphenyl	(CAS-No.) 61788-32-7 (EC-No.) 262-967-7	30 - 45	Aquatic Chronic 2, H411
Zeolites	(CAS-No.) 1318-02-1 (EC-No.) 215-283-8	5 - 10	Substance with a national occupational exposure limit
Polyphenyls, quater- and higher, partially hydrogenated	(CAS-No.) 68956-74-1 (EC-No.) 273-316-1	1 - 10	Substance not classified as hazardous
Terphenyl	(CAS-No.) 26140-60-3 (EC-No.) 247-477-3	1 - 5	Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	0.1 - 3	Substance not classified as hazardous
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	0.1 - 3	Substance with a national occupational exposure limit
sodium hydroxide	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5	< 2	Skin Corr. 1A, H314 Eye Dam. 1, H318 Met. Corr. 1, H290
ferbam (ISO)	(CAS-No.) 14484-64-1 (EC-No.) 238-484-2	0.1 - 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=100 Acute Tox. 2, H330
lead powder; [particle diameter < 1 mm]	(CAS-No.) 7439-92-1 (EC-No.) 231-100-4	<= 0.06	Repr. 1A, H360FD Lact., H362 STOT SE 2, H371 STOT RE 2, H373 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=10 Repr. 1A, H360FD
Branched-nonylphenol, ethoxylate	(CAS-No.) 68412-54-4 (EC-No.) 500-209-1	< 0.02	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400,M=1

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
lead powder; [particle diameter < 1 mm]	(CAS-No.) 7439-92-1 (EC-No.) 231-100-4	(C >= 0.03%) Repr. 1A, H360D
sodium hydroxide	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5	(C >= 5%) Skin Corr. 1A, H314 (2% =< C < 5%) Skin Corr. 1B, H314 (0.5% =< C < 2%) Skin Irrit. 2, H315 (C >= 2%) Eye Dam. 1, H318 (0.5% =< C < 2%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include: Irritation to the skin (localized redness, swelling, itching, and dryness). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Harmful if swallowed. Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.
Oxides of Lead	During combustion.
Oxides of sulphur.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Avoid contact during pregnancy/while nursing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
sodium hydroxide	1310-73-2	UK HSE	STEL:2 mg/m ³	
Manganese, inorganic compounds	1313-13-9	UK HSE	TWA(as Mn, respirable fraction):0.05 mg/m ³	
Aluminium oxides	1318-02-1	UK HSE	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	
Carbon black	1333-86-4	UK HSE	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³	
Terphenyl	26140-60-3	UK HSE	STEL:4.8 mg/m ³ (0.5 ppm)	
Hydrogenated terphenyl	61788-32-7	UK HSE	TWA:19 mg/m ³ (2 ppm);STEL:48 mg/m ³ (5 ppm)	
lead powder; [particle diameter < 1 mm]	7439-92-1	UK HSE	TWA(as Pb):0.15 mg/m ³	

UK HSE : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
POLYNUCLEAR AROMATIC HYDROCARBONS	26140-60-3	UK EH40 BMGVs	1-Hydroxypyrene	urine	EOS	4 umol/mol	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EOS: End of shift.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions.

Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter type P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Black
Odor	Slight Earthy
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	No data available.
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	≥ 93.3 °C [Test Method: Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	No data available.
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	1.59 g/ml
Relative density	1.59 [Ref Std: WATER=1]
Relative Vapour Density	≥ 1 [Ref Std: AIR=1]
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Reducing agents.

Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which may interfere with lactation or be harmful to breastfed children.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
manganese dioxide	Dermal	Rat	LD50 2,000 mg/kg
manganese dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.5 mg/l
manganese dioxide	Ingestion	Rat	LD50 > 2,197 mg/kg
Hydrogenated terphenyl	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrogenated terphenyl	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.7 mg/l
Hydrogenated terphenyl	Ingestion	Rat	LD50 > 10,000 mg/kg
Zeolites	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zeolites	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.57 mg/l
Zeolites	Ingestion	Rat	LD50 > 5,000 mg/kg
Terphenyl	Dermal	Rabbit	LD50 > 5,000 mg/kg
Terphenyl	Inhalation-Dust/Mist (4 hours)	Rat	LD50 > 3.8 mg/l
Terphenyl	Ingestion	Rat	LD50 2,304 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
ferbam (ISO)	Dermal	Rabbit	LD50 > 4,000 mg/kg
ferbam (ISO)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.4 mg/l
ferbam (ISO)	Ingestion	Rat	LD50 1,130 mg/kg
lead powder; [particle diameter < 1 mm]	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Branched-nonylphenol, ethoxylate	Ingestion	similar compounds	LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
manganese dioxide	Rabbit	No significant irritation
Hydrogenated terphenyl	Rabbit	No significant irritation

3M Aerospace Sealant AC-251 Black B-2 Catalyst

Zeolites	Rabbit	No significant irritation
Terphenyl	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
sodium hydroxide	Rabbit	Corrosive
ferbam (ISO)	Rabbit	No significant irritation
lead powder; [particle diameter < 1 mm]	similar compounds	No significant irritation
Branched-nonylphenol, ethoxylate	similar compounds	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
manganese dioxide	Rabbit	Mild irritant
Hydrogenated terphenyl	Rabbit	No significant irritation
Zeolites	Rabbit	Mild irritant
Terphenyl	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
sodium hydroxide	Rabbit	Corrosive
ferbam (ISO)	Rabbit	Severe irritant
lead powder; [particle diameter < 1 mm]	similar compounds	Mild irritant
Branched-nonylphenol, ethoxylate	similar compounds	Severe irritant

Skin Sensitisation

Name	Species	Value
manganese dioxide	Mouse	Not classified
Hydrogenated terphenyl	Human	Not classified
sodium hydroxide	Human	Not classified
ferbam (ISO)	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
manganese dioxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
manganese dioxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Hydrogenated terphenyl	In Vitro	Not mutagenic
Hydrogenated terphenyl	In vivo	Not mutagenic
Terphenyl	In Vitro	Not mutagenic
Terphenyl	In vivo	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
sodium hydroxide	In Vitro	Not mutagenic
lead powder; [particle diameter < 1 mm]	In vivo	Some positive data exist, but the data are not sufficient for classification
Branched-nonylphenol, ethoxylate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
------	-------	---------	-------

3M Aerospace Sealant AC-251 Black B-2 Catalyst

Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
ferbam (ISO)	Ingestion	Rat	Not carcinogenic
lead powder; [particle diameter < 1 mm]	Not specified.	official classification	Carcinogenic.

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
manganese dioxide	Inhalation	Not classified for female reproduction	Rat	NOAEL 20 mg/m ³	2 generation
manganese dioxide	Inhalation	Not classified for male reproduction	Rabbit	LOAEL 250 mg/kg	1 days
manganese dioxide	Ingestion	Not classified for development	Rat	LOAEL 354 mg/kg/day	prematuring into lactation
manganese dioxide	Inhalation	Not classified for development	Rat	LOAEL 61 mg/m ³	gestation into lactation
Hydrogenated terphenyl	Ingestion	Not classified for female reproduction	Rat	NOAEL 81 mg/kg/day	2 generation
Hydrogenated terphenyl	Ingestion	Not classified for male reproduction	Rat	NOAEL 62 mg/kg/day	2 generation
Hydrogenated terphenyl	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	during organogenesis
ferbam (ISO)	Ingestion	Not classified for female reproduction	Rat	NOAEL 25 mg/kg/day	3 generation
ferbam (ISO)	Ingestion	Not classified for male reproduction	Rat	NOAEL 25 mg/kg/day	3 generation
ferbam (ISO)	Ingestion	Not classified for development	Rat	NOAEL 11 mg/kg/day	during organogenesis
lead powder; [particle diameter < 1 mm]	Not specified.	Toxic to female reproduction	Human	LOAEL 10 ug/dl blood	
lead powder; [particle diameter < 1 mm]	Not specified.	Toxic to male reproduction	Human	LOAEL 37 ug/dl blood	
lead powder; [particle diameter < 1 mm]	Not specified.	Toxic to development	Human	NOAEL Not available	
Branched-nonylphenol, ethoxylate	Ingestion	Not classified for reproduction and/or development	similar compounds	NOAEL Not available	

Lactation

Name	Route	Species	Value
ferbam (ISO)	Ingestion	Rat	Causes effects on or via lactation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
sodium hydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	
lead powder; [particle diameter < 1 mm]	Ingestion	nervous system	May cause damage to organs	Human	LOAEL 90 ug/dl blood	poisoning and/or abuse
lead powder; [particle diameter < 1 mm]	Ingestion	heart	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Branched-nonylphenol, ethoxylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

3M Aerospace Sealant AC-251 Black B-2 Catalyst

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
manganese dioxide	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Monkey	LOAEL 1.1 mg/m ³	10 months
manganese dioxide	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hydrogenated terphenyl	Dermal	skin	Not classified	Rabbit	NOAEL 500 mg/kg/day	3 weeks
Hydrogenated terphenyl	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 2,000 mg/kg/day	3 weeks
Hydrogenated terphenyl	Inhalation	liver hematopoietic system eyes	Not classified	Rat	NOAEL 0.5 mg/l	13 weeks
Hydrogenated terphenyl	Ingestion	hematopoietic system kidney and/or bladder liver eyes respiratory system	Not classified	Rat	NOAEL 120 mg/kg/day	14 weeks
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 60 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 50 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	gastrointestinal tract	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
lead powder; [particle diameter < 1 mm]	Inhalation	heart endocrine system immune system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
lead powder; [particle diameter < 1 mm]	Ingestion	bone, teeth, nails, and/or hair	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 20 ug/dl blood	3 months
lead powder; [particle diameter < 1 mm]	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.5 mg/kg/day	20 days
lead powder; [particle diameter < 1 mm]	Ingestion	hematopoietic system kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 40 ug/dl blood	environmental exposure
lead powder; [particle diameter < 1 mm]	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	LOAEL 11 ug/dl blood	environmental exposure
lead powder; [particle diameter < 1 mm]	Ingestion	auditory system heart endocrine system vascular system	Not classified	Human	NOAEL Not available	environmental exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
manganese dioxide	1313-13-9	Rainbow trout	Endpoint not reached	96 hours	LC50	>100 mg/l
manganese dioxide	1313-13-9	Green algae	Experimental	72 hours	EC50	>100 mg/l
manganese dioxide	1313-13-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
manganese dioxide	1313-13-9	Green algae	Experimental	72 hours	EC10	100 mg/l
manganese dioxide	1313-13-9	Water flea	Experimental	8 days	NOEC	100 mg/l
Hydrogenated terphenyl	61788-32-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrogenated terphenyl	61788-32-7	Activated sludge	Experimental	3 hours	NOEC	103 mg/l
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Zeolites	1318-02-1	African clawed frog	Analogous Compound	96 hours	LC50	1,800 mg/l
Zeolites	1318-02-1	Fathead minnow	Analogous Compound	96 hours	LC50	>680 mg/l
Zeolites	1318-02-1	Green algae	Analogous Compound	72 hours	EC50	130 mg/l
Zeolites	1318-02-1	Sediment organism	Analogous Compound	22 days	EC50	364.9 mg/l
Zeolites	1318-02-1	Water flea	Analogous Compound	48 hours	EC50	>100 mg/l
Zeolites	1318-02-1	Fathead minnow	Analogous Compound	30 days	NOEC	86.7 mg/l
Zeolites	1318-02-1	Green algae	Analogous Compound	72 hours	NOEC	18 mg/l
Zeolites	1318-02-1	Water flea	Analogous Compound	21 days	NOEC	32 mg/l
Zeolites	1318-02-1	Bacteria	Experimental	16 hours	EC50	950 mg/l
Zeolites	1318-02-1	Radish	Experimental	23 days	EC50	4,000 mg/kg (Dry Weight)
Terphenyl	26140-60-3	Water flea	Analogous Compound	48 hours	EC50	0.022 mg/l
Terphenyl	26140-60-3	Green algae	Experimental	72 hours	ErC50	0.102 mg/l
Terphenyl	26140-60-3	Rainbow trout	Experimental	96 hours	LC50	27 mg/l
Terphenyl	26140-60-3	Fathead minnow	Experimental	34 days	NOEC	0.064 mg/l
Terphenyl	26140-60-3	Green algae	Experimental	72 hours	NOEC	0.00322 mg/l
Terphenyl	26140-60-3	Water flea	Experimental	21 days	NOEC	0.005 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l

3M Aerospace Sealant AC-251 Black B-2 Catalyst

Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l
sodium hydroxide	1310-73-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
ferbam (ISO)	14484-64-1	Green algae	Experimental	96 hours	ErC50	2.4 mg/l
ferbam (ISO)	14484-64-1	Guppy	Experimental	96 hours	LC50	0.09 mg/l
ferbam (ISO)	14484-64-1	Water flea	Experimental	48 hours	LC50	0.09 mg/l
ferbam (ISO)	14484-64-1	Rainbow trout	Experimental	60 days	NOEC	0.00056 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Fathead minnow	Analogous Compound	96 hours	LC50	0.0408 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Green algae	Analogous Compound	72 hours	ErC50	0.0205 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Water flea	Analogous Compound	48 hours	EC50	0.026 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	N/A	Analogous Compound	30 days	EC10	0.0017 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Green algae	Analogous Compound	72 hours	ErC10	0.0061 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Rainbow trout	Analogous Compound	578 days	NOEC	0.003 mg/l
lead powder; [particle diameter < 1 mm]	7439-92-1	Activated sludge	Analogous Compound	24 hours	EC50	9 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Fathead minnow	Experimental	96 hours	LC50	0.218 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Green algae	Experimental	72 hours	ErC50	>3 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Mysid Shrimp	Experimental	48 hours	LC50	0.11 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Water flea	Experimental	48 hours	EC50	0.328 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Green algae	Experimental	72 hours	NOEC	1.5 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Medaka	Experimental	100 days	NOEC	0.035 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Mysid Shrimp	Experimental	28 days	NOEC	0.0077 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Water flea	Experimental	21 days	NOEC	0.1 mg/l
Branched-nonylphenol, ethoxylate	68412-54-4	Activated sludge	Experimental	3 hours	EC20	>1,000 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
----------	---------	-----------	----------	------------	-------------	----------

3M Aerospace Sealant AC-251 Black B-2 Catalyst

manganese dioxide	1313-13-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Hydrogenated terphenyl	61788-32-7	Experimental Biodegradation	35 days	CO2 evolution	1 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Hydrogenated terphenyl	61788-32-7	Experimental Photolysis		Photolytic half-life(in water)	86 days (t 1/2)	
Hydrogenated terphenyl	61788-32-7	Experimental Soil Metabolism Aerobic		Half-life (t 1/2)	202 days (t 1/2)	
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Zeolites	1318-02-1	Analogous Compound Hydrolysis		Hydrolytic half-life	60 days (t 1/2)	
Terphenyl	26140-60-3	Experimental Biodegradation	14 days	BOD	0.5 %BOD/ThOD	OECD 301C - MITI test (I)
Carbon black	1333-86-4	Data not availbl-insufficient	N/A	N/A	N/A	N/A
sodium hydroxide	1310-73-2	Data not availbl-insufficient	N/A	N/A	N/A	N/A
ferbam (ISO)	14484-64-1	Analogous Compound Biodegradation	14 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
ferbam (ISO)	14484-64-1	Experimental Hydrolysis		Hydrolytic half-life	≤31 minutes (t 1/2)	
lead powder; [particle diameter < 1 mm]	7439-92-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Branched-nonylphenol, ethoxylate	68412-54-4	Experimental Biodegradation	28 days	BOD	25.9 %BOD/ThOD	OECD 301F - Manometric respirometry

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
manganese dioxide	1313-13-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrogenated terphenyl	61788-32-7	Analogous Compound BCF - Fish	42 days	Bioaccumulation factor	5200	similar to OECD 305
Hydrogenated terphenyl	61788-32-7	Experimental Bioconcentration		Log Kow	>5.3	OECD 117 log Kow HPLC method
Polyphenyls, quater- and higher, partially hydrogenated	68956-74-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Zeolites	1318-02-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Terphenyl	26140-60-3	Analogous Compound BCF - Fish	56 days	Bioaccumulation factor	12993	OECD305-Bioconcentration
Terphenyl	26140-60-3	Estimated Bioconcentration		Log Kow	5.86	
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
sodium hydroxide	1310-73-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ferbam (ISO)	14484-64-1	Experimental Bioconcentration		Log Kow	-1.597	OECD 107 log Kow shke flask mtd

3M Aerospace Sealant AC-251 Black B-2 Catalyst

lead powder; [particle diameter < 1 mm]	7439-92-1	Experimental BCF - Other		Bioaccumulation factor	1322	
Branched- nonylphenol, ethoxylate	68412-54-4	Experimental Bioconcentration		Log Kow	4.21	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Hydrogenated terphenyl	61788-32-7	Experimental Mobility in Soil	Koc	≥8400 l/kg	OECD 121 Estim. of Koc by HPLC
Terphenyl	26140-60-3	Estimated Mobility in Soil	Koc	≥1.8E+04 l/kg	
Branched- nonylphenol, ethoxylate	68412-54-4	Modeled Mobility in Soil	Koc	3,020 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

Ingredient	CAS Nbr	PBT/vPvB status
Hydrogenated terphenyl	61788-32-7	Meets UK REACH vPvB criteria

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(FERBAM;	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(FERBAM;	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(FERBAM; TERPHENYL)

	TERPHENYL)	TERPHENYL)	
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
ferbam (ISO)	14484-64-1	Gr. 3: Not classifiable	International Agency for Research on Cancer
Zeolites	1318-02-1	Gr. 3: Not classifiable	International Agency for Research on Cancer
lead powder; [particle diameter < 1 mm]	7439-92-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
-------------------	----------------

Branched-nonylphenol, ethoxylate

68412-54-4

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

Authorisation status under UK REACH:

The following substance/s contained in this product might be or is/are subject to authorisation in accordance with UK REACH:

<u>Ingredient</u>	<u>CAS Nbr</u>
Branched-nonylphenol, ethoxylate	68412-54-4
Hydrogenated terphenyl	61788-32-7
lead powder; [particle diameter < 1 mm]	7439-92-1

Authorisation status: listed in the UK REACH Candidate List of Substances of Very High Concern for Authorisation

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E1 Hazardous to the Aquatic environment	100	200

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
ferbam (ISO)	14484-64-1	100	200
lead powder; [particle diameter < 1 mm]	7439-92-1	100	200

Regulation (EU) No 649/2012, as amended for GB

Chemical	Identifier(s)	Annex I
Branched-nonylphenol, ethoxylate	68412-54-4	Part 1 and Part 2
ferbam (ISO)	14484-64-1	Part 1 and Part 2
lead powder; [particle diameter < 1 mm]	7439-92-1	Part 1

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

EUH031	Contact with acid liberates toxic gas.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360FD	May damage fertility. May damage the unborn child.
H362	May cause harm to breast-fed children.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

GB Section 15: Carcinogenicity information information was modified.
Section 6: Accidental release personal information information was modified.
BLV Reg Agency Desc information was added.
Section 8: BLV table information was added.
Section 8: BLV information was deleted.
Legend description information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-3448-5	Version number:	4.04
Revision date:	06/01/2025	Supersedes date:	05/12/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Aerospace Sealant AC-251 B-1/2, B-1, and B-2 Black Base

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended for Great Britain, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

Not applicable

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH210

Safety data sheet available on request.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	(CAS-No.) 68611-50-7	55 - 65	Substance not classified as hazardous
Calcium carbonate	(CAS-No.) 471-34-1 (EC-No.) 207-439-9	30 - 40	Substance with a national occupational exposure limit
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	(CAS-No.) 68611-50-7	1 - 1.9	Aquatic Chronic 2, H411
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	< 0.5	Substance with a national occupational exposure limit
Quartz	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	< 0.5	STOT RE 1, H372
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 0.3	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

formaldehyde

Carbon monoxide

Carbon dioxide.

Hydrogen Chloride

Condition

During combustion.

During combustion.

During combustion.

During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	UK HSE	TWA: 191 mg/m ³ (50 ppm); STEL: 384 mg/m ³ (100 ppm)	SKIN
Carbon black	1333-86-4	UK HSE	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³	
Quartz	14808-60-7	UK HSE	TWA(respirable):0.1 mg/m ³	
DUST, INERT OR NUISANCE	471-34-1	UK HSE	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	

UK HSE : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Black
Odor	Pungent Sulphuric
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	<i>Not applicable.</i>
Flammability	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	>=93.3 °C [<i>Test Method:Closed Cup</i>]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	1.61 g/ml
Relative density	1.61 [<i>Ref Std: WATER=1</i>]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information**9.2.2 Other safety characteristics**

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Percent volatile	0.1 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Reducing agents.

Strong acids.

Strong bases.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	Dermal	Rat	LD50 > 7,800 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	Dermal	Rat	LD50 > 7,800 mg/kg
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	Rabbit	No significant irritation
Calcium carbonate	Rabbit	No significant irritation
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation
Quartz	Professional judgement	No significant irritation
toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	Rabbit	No significant irritation
Calcium carbonate	Rabbit	No significant irritation
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	Rabbit	No significant irritation

3M Aerospace Sealant AC-251 B-1/2, B-1, and B-2 Black Base

Carbon black	Rabbit	No significant irritation
toluene	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced		Not classified
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)		Not classified
toluene	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
Quartz	Inhalation	Human and animal	Carcinogenic.
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Calcium carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	68611-50-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Calcium carbonate	471-34-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Calcium carbonate	471-34-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Calcium carbonate	471-34-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Calcium carbonate	471-34-1	Green algae	Experimental	72 hours	EC10	100 mg/l
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	68611-50-7	Green algae	Experimental	72 hours	EC50	17 mg/l
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	68611-50-7	Water flea	Experimental	48 hours	EC50	4.71 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l
Quartz	14808-60-7	Green algae	Estimated	72 hours	EC50	440 mg/l
Quartz	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l

3M Aerospace Sealant AC-251 B-1/2, B-1, and B-2 Black Base

Quartz	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l
Quartz	14808-60-7	Green algae	Estimated	72 hours	NOEC	60 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	68611-50-7	Data not available - insufficient	N/A	N/A	N/A	N/A
Calcium carbonate	471-34-1	Data not available - insufficient	N/A	N/A	N/A	N/A
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	68611-50-7	Data not available - insufficient	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available - insufficient	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available - insufficient	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced	68611-50-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Calcium carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propane, 1,2,3-trichloro-, polymer with 1,1'-[methylenebis(oxy)]bis[2-chloroethane] and sodium sulfide (Na ₂ (Sx)), reduced (MW<1800)	68611-50-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC

and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 10

Waste adhesives and sealants other than those mentioned in 08 04 09

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity****Ingredient****CAS Nbr****Classification****Regulation**

Carbon black

1333-86-4

Grp. 2B: Possible human International Agency

Quartz	14808-60-7	carc. Grp. 1: Carcinogenic to humans	for Research on Cancer International Agency for Research on Cancer
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
toluene	108-88-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

Regulation UK regulation 2023/63 (marketing and use of explosive precursors and poisons)

This product contains a reportable substance according to UK legislation 1972/66: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see UK Regulation 2023/63 for further details.

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
toluene	108-88-3	10	50

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 3: Composition/ Information of ingredients table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.