



Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 45-3307-1
Issue Date: 10/22/24

Version Number: 1.00
Supersedes Date: Initial Issue

Product identifier

3M™ Aerospace Sealant AC-251 Black B-2

Recommended use

Sealant

Supplier's details

MANUFACTURER: 3M
DIVISION: Automotive and Aerospace Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

30-3448-5, 45-3052-3

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	30-3448-5	Version Number:	4.00
Issue Date:	12/03/24	Supersedes Date:	04/18/23

SECTION 1: Identification

1.1. Product identifier

3M™ Aerospace Sealant AC-251 B-1/2, B-1, and B-2 Black Base

Product Identification Numbers

LC-B100-1135-5, LC-B100-1135-6, LC-B100-1135-7, LC-B100-1135-8, LC-B100-1135-9, LC-B100-1136-0, LC-B100-1136-1, LC-B100-1955-0, 41-4901-0207-0, 42-0044-2103-0, 42-0044-2104-8, 42-0044-2105-5, 70-0052-1972-3
7010333032

1.2. Recommended use and restrictions on use

Recommended use

For industrial or professional use only., Sealant

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive and Aerospace Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Reproductive Toxicity: Category 1B.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard |

Pictograms

**Hazard Statements**

May damage fertility or the unborn child.

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.

Response:

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
POLYSULFIDE RUBBER	68611-50-7	55 - 65
CALCIUM CARBONATE	471-34-1	30 - 40
POLYSULFIDE RUBBER (MW<1800)	68611-50-7	1 - 2
CARBON BLACK	1333-86-4	< 0.5 Trade Secret *
QUARTZ SILICA	14808-60-7	< 0.5 Trade Secret *
Toluene	108-88-3	< 0.3 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
CARBON BLACK	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
CARBON BLACK	1333-86-4	OSHA	TWA:3.5 mg/m3	
QUARTZ SILICA	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
QUARTZ SILICA	14808-60-7	OSHA	TWA Table Z-1(respirable):0.05 mg/m3;TWA Table Z-3(respirable):0.1 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.)	
DUST, INERT OR NUISANCE	471-34-1	OSHA	TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part

of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Black

Specific Physical Form:

Paste

Odor

Pungent Sulfuric

Odor threshold

No Data Available

pH

No Data Available

Melting point

Not Applicable

Boiling Point

Not Applicable

Flash Point

≥ 200 °F [*Test Method: Closed Cup*]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density

1.61 g/ml

Specific Gravity

1.61 [*Ref Std: WATER=1*]

Solubility in Water

Nil

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Volatile Organic Compounds

2.5 g/l

Percent volatile

0.1 %

VOC Less H₂O & Exempt Solvents

2.5 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Reducing agents

Strong acids

Strong bases

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
Silica, Crystalline (Respirable Size)	14808-60-7	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Soot (as found in occupational exposure of chimney sweeps)	1333-86-4	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Soots	1333-86-4	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Silica dust, crystalline, in the form of quartz or cristobalite	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
POLYSULFIDE RUBBER	Dermal	Rat	LD50 > 7,800 mg/kg
POLYSULFIDE RUBBER	Ingestion	Rat	LD50 > 5,000 mg/kg
CALCIUM CARBONATE	Dermal	Rat	LD50 > 2,000 mg/kg
CALCIUM CARBONATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
CALCIUM CARBONATE	Ingestion	Rat	LD50 6,450 mg/kg
POLYSULFIDE RUBBER (MW<1800)	Dermal	Rat	LD50 > 7,800 mg/kg
POLYSULFIDE RUBBER (MW<1800)	Ingestion	Rat	LD50 > 5,000 mg/kg
CARBON BLACK	Dermal	Rabbit	LD50 > 3,000 mg/kg
CARBON BLACK	Ingestion	Rat	LD50 > 8,000 mg/kg
QUARTZ SILICA	Dermal		LD50 estimated to be > 5,000 mg/kg
QUARTZ SILICA	Ingestion		LD50 estimated to be > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
POLYSULFIDE RUBBER	Rabbit	No significant irritation
CALCIUM CARBONATE	Rabbit	No significant irritation
POLYSULFIDE RUBBER (MW<1800)	Rabbit	No significant irritation
CARBON BLACK	Rabbit	No significant irritation
QUARTZ SILICA	Professional judgement	No significant irritation
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
POLYSULFIDE RUBBER	Rabbit	No significant irritation
CALCIUM CARBONATE	Rabbit	No significant irritation
POLYSULFIDE RUBBER (MW<1800)	Rabbit	No significant irritation
CARBON BLACK	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
POLYSULFIDE RUBBER		Not classified
POLYSULFIDE RUBBER (MW<1800)		Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

CARBON BLACK	In Vitro	Not mutagenic
CARBON BLACK	In vivo	Some positive data exist, but the data are not sufficient for classification
QUARTZ SILICA	In Vitro	Some positive data exist, but the data are not sufficient for classification
QUARTZ SILICA	In vivo	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
CARBON BLACK	Dermal	Mouse	Not carcinogenic
CARBON BLACK	Ingestion	Mouse	Not carcinogenic
CARBON BLACK	Inhalation	Rat	Carcinogenic
QUARTZ SILICA	Inhalation	Human and animal	Carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CALCIUM CARBONATE	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

CALCIUM CARBONATE	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
CARBON BLACK	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
QUARTZ SILICA	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Reproductive toxicity

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 30-3448-5
Issue Date: 12/03/24

Version Number: 4.00
Supersedes Date: 04/18/23

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	45-3052-3	Version Number:	1.01
Issue Date:	11/05/24	Supersedes Date:	10/10/24

SECTION 1: Identification

1.1. Product identifier

Aerospace Sealant AC-251 B-2 Catalyst

1.2. Recommended use and restrictions on use

Recommended use

Curing Agent, For Professional Use Only

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive and Aerospace Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Acute Toxicity (oral): Category 4.
 Serious Eye Damage/Irritation: Category 1.
 Skin Corrosion/Irritation: Category 2.
 Carcinogenicity: Category 2.
 Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms

**Hazard Statements**

Harmful if swallowed.
Causes serious eye damage.
Causes skin irritation.
Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:
nervous system |
respiratory system |

Precautionary Statements**Prevention:**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves and eye/face protection.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF ON SKIN: Wash with plenty of soap and water.
Immediately call a POISON CENTER or doctor/physician.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Rinse mouth.
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

1% of the mixture consists of ingredients of unknown acute oral toxicity.
5% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Manganese Dioxide	1313-13-9	15 - 60 Trade Secret *
Ethanol, 2,2'-oxybis-,dibenzoate	120-55-8	15 - 45
Dibenzoate Propanol	27138-31-4	< 15
Zeolites	1318-02-1	1 - 10
Silica	7631-86-9	< 5
Aluminum Oxide	1344-28-1	< 3

Sodium Oxide	1313-59-3	< 3 Trade Secret *
Carbon Black	1333-86-4	< 2.5 Trade Secret *
Potassium Oxide	12136-45-7	< 2 Trade Secret *
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	68909-20-6	< 2 Trade Secret *
Heterocyclic Organic Compound	Trade Secret*	< 2
Sodium Hydroxide	1310-73-2	< 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

DO NOT USE WATER In case of fire: Use a fire fighting agent suitable for water-reactives such as dry chemical to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Oxides of Nitrogen
Oxides of Sulfur

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Sodium Hydroxide	1310-73-2	ACGIH	CEIL:2 mg/m3	
Sodium Hydroxide	1310-73-2	OSHA	TWA:2 mg/m3	
MANGANESE COMPOUNDS	1313-13-9	OSHA	CEIL(as Mn):5 mg/m3	
MANGANESE, INORGANIC COMPOUNDS	1313-13-9	ACGIH	TWA(as Mn, respirable fraction):0.02 mg/m3;TWA(as Mn, inhalable fraction):0.1 mg/m3	A4: Not class. as human carcin
Aluminum, insoluble compounds	1318-02-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m3	
Aluminum Oxide	1344-28-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable	

			fraction):5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m3	
SILICA, AMORPHOUS	68909-20-6	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
DUST, INERT OR NUISANCE	7631-86-9	OSHA	TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	7631-86-9	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	7631-86-9	ACGIH	TWA(respirable particles):3 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half mask or full facepiece air-purifying respirator with N100 particulate filters

Half facepiece or full facepiece air-purifying respirator suitable for particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Black-Brown

Odor

No Data Available

Odor threshold

No Data Available

pH

10

Melting point

Not Applicable

Boiling Point

No Data Available

Flash Point

Flash point > 93 °C (200 °F)

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density

13.4 lb/gal

Specific Gravity

1.61

Solubility In Water

Not Applicable

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

100,000 centipoise

Volatile Organic Compounds

12.3 g/l

Percent volatile

0.8 % weight

VOC Less H2O & Exempt Solvents

12.5 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Reducing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Soot (as found in occupational exposure of chimney sweeps)	1333-86-4	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Soots	1333-86-4	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens

Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
--------------	-----------	-------------------------------	---

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
Manganese Dioxide	Dermal	Rat	LD50 2,000 mg/kg
Manganese Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.5 mg/l
Manganese Dioxide	Ingestion	Rat	LD50 > 2,197 mg/kg
Dibenzoate Propanol	Dermal	Rat	LD50 > 2,000 mg/kg
Dibenzoate Propanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Dibenzoate Propanol	Ingestion	Rat	LD50 3,295 mg/kg
Zeolites	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zeolites	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.57 mg/l
Zeolites	Ingestion	Rat	LD50 > 5,000 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Sodium Oxide	Ingestion	Professional judgement	LD50 estimated to be 50 - 300 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Heterocyclic Organic Compound	Ingestion	Rat	LD50 > 5,000 mg/kg
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	Rat	LD50 > 2,000 mg/kg
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Manganese Dioxide	Rabbit	No significant irritation
Dibenzoate Propanol	Rabbit	No significant irritation
Zeolites	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
Sodium Oxide	similar compounds	Corrosive
Carbon Black	Rabbit	No significant irritation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Rabbit	No significant irritation

Potassium Oxide	official classification	Corrosive
Sodium Hydroxide	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Manganese Dioxide	Rabbit	Mild irritant
Dibenzoate Propanol	Rabbit	No significant irritation
Zeolites	Rabbit	Mild irritant
Silica	Rabbit	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
Sodium Oxide	similar compounds	Corrosive
Carbon Black	Rabbit	No significant irritation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Rabbit	No significant irritation
Potassium Oxide	similar health hazards	Corrosive
Sodium Hydroxide	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Manganese Dioxide	Mouse	Not classified
Dibenzoate Propanol	Guinea pig	Not classified
Silica	Human and animal	Not classified
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Guinea pig	Not classified
Sodium Hydroxide	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Manganese Dioxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Manganese Dioxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Dibenzoate Propanol	In Vitro	Not mutagenic
Silica	In Vitro	Not mutagenic
Aluminum Oxide	In Vitro	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
Heterocyclic Organic Compound	In Vitro	Not mutagenic
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	In Vitro	Not mutagenic
Sodium Hydroxide	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Manganese Dioxide	Inhalation	Not classified for female reproduction	Rat	NOAEL 20 mg/m3	2 generation
Manganese Dioxide	Inhalation	Not classified for male reproduction	Rabbit	LOAEL 250 mg/kg	1 days
Manganese Dioxide	Ingestion	Not classified for development	Rat	LOAEL 354 mg/kg/day	premating into lactation
Manganese Dioxide	Inhalation	Not classified for development	Rat	LOAEL 61 mg/m3	gestation into lactation
Dibenzoate Propanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Dibenzoate Propanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Dibenzoate Propanol	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Sodium Oxide	Inhalation	respiratory irritation	May cause respiratory irritation	Professional judgement	NOAEL Not available	
Potassium Oxide	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
Sodium Hydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Manganese Dioxide	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Monkey	LOAEL 1.1 mg/m3	10 months
Manganese Dioxide	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Dibenzoate Propanol	Ingestion	hematopoietic system liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Aluminum Oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not	occupational

					available	exposure
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.035 mg/l	13 weeks
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Inhalation	hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 0.035 mg/l	13 weeks
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	5 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Acute toxicity

Carcinogenicity

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient

Manganese Dioxide (MANGANESE COMPOUNDS)
Aluminum Oxide

C.A.S. No

1313-13-9
1344-28-1

% by Wt

Trade Secret 15 - 60
< 3

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** Reacts with Water

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 45-3052-3
Issue Date: 11/05/24

Version Number: 1.01
Supersedes Date: 10/10/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness

or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com