



Safety Data Sheet

Copyright, 2025, Meguiar's Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 28-5727-4 | Version Number: | 6.03 |
| Issue Date: | 05/29/25 | Supersedes Date: | 12/17/24 |

SECTION 1: Identification

1.1. Product identifier

Hot Shine Tire Coating (High Gloss) G138 [G13815]

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Tire coating/maintenance product

1.3. Supplier's details

| | |
|----------------------|-------------------------------------|
| MANUFACTURER: | Meguiar's, Inc. |
| DIVISION: | Meguiar's |
| ADDRESS: | 213 Technology Dr, Irvine, CA 92618 |
| Telephone: | 1-800-347-5700 |

1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Aerosol: Category 2.
Gas Under Pressure: Liquefied gas.
Serious Eye Damage/Irritation: Category 2A.
Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Warning

Symbols

Flame | Gas cylinder | Exclamation mark |

Pictograms**Hazard Statements**

Flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|-------------|-------------------------|
| METHYL ACETATE | 79-20-9 | 30 - 50 Trade Secret * |
| ACETONE | 67-64-1 | 10 - 20 Trade Secret * |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | 64742-47-8 | 5 - 13 Trade Secret * |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | 426260-76-6 | 5 - < 10 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons
Formaldehyde
Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2

and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------------------|-------------|--------|---|--------------------------------|
| Heptane, all isomers | 426260-76-6 | ACGIH | TWA:400 ppm;STEL:500 ppm | |
| MINERAL OILS, HIGHLY-REFINED OILS | 64742-47-8 | ACGIH | TWA(inhalable fraction):5 mg/m ³ | A4: Not class. as human carcin |
| ACETONE | 67-64-1 | ACGIH | TWA:250 ppm;STEL:500 ppm | A4: Not class. as human carcin |
| ACETONE | 67-64-1 | OSHA | TWA:2400 mg/m ³ (1000 ppm) | |
| METHYL ACETATE | 79-20-9 | ACGIH | TWA:200 ppm;STEL:250 ppm | |
| METHYL ACETATE | 79-20-9 | OSHA | TWA:610 mg/m ³ (200 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Clear Colorless

Specific Physical Form:

Aerosol

Odor

Weak Grape

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

Not Applicable

Flash Point

20 °F [*Test Method*:Pensky-Martens Closed Cup] [*Details*:D93-90]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

| | |
|---|---|
| Density | 0.865 g/cm ³ |
| Specific Gravity | 0.87 [Ref Std: WATER=1] |
| Solubility in Water | Nil |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity | 2.2992 mm ² /sec [@ 100 °F] [Details:Kinematic viscosity] |
| Molecular weight | No Data Available |
| Volatile Organic Compounds | 9.8 % weight [Test Method:calculated per CARB] |
| Volatile Organic Compounds | 172.4 g/l [Test Method:calculated SCAQMD rule 443.1] |
| VOC Less H ₂ O & Exempt Solvents | 398.2 g/l |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
|------------------|------------------|

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|----------------------------|-------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| METHYL ACETATE | Dermal | Rat | LD50 > 2,000 mg/kg |
| METHYL ACETATE | Inhalation-Vapor (4 hours) | Rat | LC50 > 49 mg/l |
| METHYL ACETATE | Ingestion | Rat | LD50 > 5,000 mg/kg |
| ACETONE | Dermal | Rabbit | LD50 > 15,688 mg/kg |
| ACETONE | Inhalation-Vapor (4 hours) | Rat | LC50 76 mg/l |
| ACETONE | Ingestion | Rat | LD50 5,800 mg/kg |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Ingestion | Rat | LD50 > 15,000 mg/kg |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Dermal | similar compounds | LD50 > 5,000 mg/kg |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Dermal | Rabbit | LD50 > 2,920 mg/kg |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Inhalation-Vapor (4 hours) | Rat | LC50 > 23.3 mg/l |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Ingestion | Rat | LD50 > 5,840 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-------------------|---------------------------|
| METHYL ACETATE | Rabbit | No significant irritation |
| ACETONE | Mouse | Minimal irritation |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | similar compounds | Mild irritant |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Rabbit | Irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|-------------------|---------------------------|
| METHYL ACETATE | Rabbit | Moderate irritant |
| ACETONE | Rabbit | Severe irritant |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | similar compounds | No significant irritation |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|--|-------------------|----------------|
| METHYL ACETATE | Human | Not classified |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | similar compounds | Not classified |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Guinea pig | Not classified |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| METHYL ACETATE | In Vitro | Not mutagenic |
| METHYL ACETATE | In vivo | Not mutagenic |
| ACETONE | In vivo | Not mutagenic |
| ACETONE | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | In Vitro | Not mutagenic |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---------|---------------|-------------------------|------------------|
| ACETONE | Not Specified | Multiple animal species | Not carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--------------------------------------|---------------|--|---------|-----------------------|----------------------|
| ACETONE | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,700 mg/kg/day | 13 weeks |
| ACETONE | Inhalation | Not classified for development | Rat | NOAEL 5.2 mg/l | during organogenesis |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Not Specified | Not classified for female reproduction | Rat | NOAEL Not available | 2 generation |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Not Specified | Not classified for male reproduction | Rat | NOAEL Not available | 2 generation |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Not Specified | Not classified for development | Rat | NOAEL Not available | 2 generation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure |
|------|-------|-----------------|-------|---------|-------------|----------|
|------|-------|-----------------|-------|---------|-------------|----------|

| | | | | | | Duration |
|--|------------|-----------------------------------|--|------------------------|---------------------|------------------------|
| METHYL ACETATE | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| METHYL ACETATE | Inhalation | respiratory irritation | May cause respiratory irritation | Human and animal | NOAEL Not available | |
| METHYL ACETATE | Inhalation | blindness | Not classified | | NOAEL Not available | |
| METHYL ACETATE | Ingestion | central nervous system depression | May cause drowsiness or dizziness | | NOAEL Not available | |
| ACETONE | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| ACETONE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| ACETONE | Inhalation | immune system | Not classified | Human | NOAEL 1.19 mg/l | 6 hours |
| ACETONE | Inhalation | liver | Not classified | Guinea pig | NOAEL Not available | |
| ACETONE | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|----------------|------------|---|--|------------|-----------------------|-------------------|
| METHYL ACETATE | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.1 mg/l | 28 days |
| METHYL ACETATE | Inhalation | endocrine system hematopoietic system liver immune system kidney and/or bladder | Not classified | Rat | NOAEL 6.1 mg/l | 28 days |
| ACETONE | Dermal | eyes | Not classified | Guinea pig | NOAEL Not available | 3 weeks |
| ACETONE | Inhalation | hematopoietic system | Not classified | Human | NOAEL 3 mg/l | 6 weeks |
| ACETONE | Inhalation | immune system | Not classified | Human | NOAEL 1.19 mg/l | 6 days |
| ACETONE | Inhalation | kidney and/or bladder | Not classified | Guinea pig | NOAEL 119 mg/l | not available |
| ACETONE | Inhalation | heart liver | Not classified | Rat | NOAEL 45 mg/l | 8 weeks |
| ACETONE | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 900 mg/kg/day | 13 weeks |
| ACETONE | Ingestion | heart | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| ACETONE | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 200 mg/kg/day | 13 weeks |
| ACETONE | Ingestion | liver | Not classified | Mouse | NOAEL 3,896 mg/kg/day | 14 days |
| ACETONE | Ingestion | eyes | Not classified | Rat | NOAEL 3,400 mg/kg/day | 13 weeks |
| ACETONE | Ingestion | respiratory system | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |

| | | | | | | |
|--|------------|---|----------------|-------|------------------------------|----------|
| ACETONE | Ingestion | muscles | Not classified | Rat | NOAEL 2,500 mg/kg | 13 weeks |
| ACETONE | Ingestion | skin bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 11,298 mg/kg/day | 13 weeks |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Inhalation | liver | Not classified | Rat | NOAEL 6 mg/l | 13 weeks |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Inhalation | kidney and/or bladder | Not classified | Rat | LOAEL 1.5 mg/l | 13 weeks |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 6 mg/l | 13 weeks |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Ingestion | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 100 mg/kg/day | 13 weeks |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Ingestion | hematopoietic system eyes | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |

Aspiration Hazard

| Name | Value |
|--|-------------------|
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Aspiration hazard |
| HEPTANE, BRANCHED, CYCLIC AND LINEAR | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

| |
|---|
| Physical Hazards |
| Flammable (gases, aerosols, liquids, or solids) |
| Gas under pressure |

| |
|--|
| Health Hazards |
| Serious eye damage or eye irritation |
| Specific target organ toxicity (single or repeated exposure) |

15.2. State Regulations

Contact manufacturer for more information

California Proposition 65

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>Listing</u> |
|--|-------------------|----------------|
| Soots, tars, and mineral oils (untreated and mildly treated oils and used engine oils) | None | Carcinogen |

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 4 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 28-5727-4 | Version Number: | 6.03 |
| Issue Date: | 05/29/25 | Supersedes Date: | 12/17/24 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's Inc. product, some of which are uniquely within the user's knowledge and control, it is

essential that the user evaluate the Meguiar's Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com