



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-2507-1	Version number:	28.00
Revision date:	02/04/2025	Supersedes date:	13/06/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld AF-163-2 Structural Adhesive Film

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural Film Adhesive.

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone:	+353 1 280 3555
E Mail:	tox.uk@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The eye damage/irritation classification is not applied due to the nature of this product (adhesive film).

This material has been tested for skin corrosion/irritation and the test results do not meet the criteria for classification.

This material has been tested for skin sensitization and the test results do not meet the criteria for classification.

CLASSIFICATION:

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Symbols

GHS09 (Environment) |

Pictograms**HAZARD STATEMENTS:**

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH208 Contains Adipohydrazide. | bis-[4-(2,3-epoxipropoxy)phenyl]propane. May produce an allergic reaction.

60% of the mixture consists of components of unknown acute oral toxicity.

Contains 60% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction product of CASRNs 25068-38-6, 79-94-7, 80-05-7, and 27417-83-0	None	45 - 65	Substance not classified as hazardous
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26	15 - 40	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Dicyandiamide	(CAS-No.) 461-58-5 (EC-No.) 207-312-8 (REACH-No.) 01-	< 5	Substance not classified as hazardous

	2119474914-28		
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	(CAS-No.) 17526-94-2 (EC-No.) 241-523-6 (REACH-No.) 01-2119966132-41	< 1.5	Substance not classified as hazardous
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDI-	(CAS-No.) 6386-73-8 (EC-No.) 228-988-0	< 1	Aquatic Acute 1, H400,M=1 Aquatic Chronic 2, H411
Adipohydrazide	(CAS-No.) 1071-93-8 (EC-No.) 213-999-5 (REACH-No.) 01-2119962900-36	< 1	Aquatic Chronic 2, H411 Skin Sens. 1B, H317
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2	< 1	Eye Dam. 1, H318 Aquatic Chronic 3, H412
Dye	Trade Secret	< 0.2	Substance not classified as hazardous
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	(CAS-No.) 358-23-6 (EC-No.) 206-616-8	<= 0.01	EUH014 Ox. Liq. 2, H272 Met. Corr. 1, H290 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxypropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

Skin contact

If exposed, wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products**Substance**

Aldehydes.
Carbon monoxide
Carbon dioxide.
Hydrogen Chloride
Hydrogen cyanide.
Hydrogen Fluoride
Ammonia
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Ventilate the area with fresh air.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid breathing of vapours created during the cure cycle. Avoid inhalation of thermal decomposition products. Avoid

breathing of dust created by cutting, sanding, grinding or machining. For industrial/occupational use only. Not for consumer sale or use. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Short-term exposure, Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	12.3 mg/m ³
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Short-term exposure, Systemic effects	12.3 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater	0.003 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Intermittent releases to water	0.013 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water	0.0003 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water sediments	0.5 mg/kg d.w.

bis-[4-(2,3-epoxipropoxy)phenyl]propane		Sewage Treatment Plant	10 mg/l
---	--	------------------------	---------

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

No protective gloves required.

Respiratory protection

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Film
Colour	Red
Odor	Odourless
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	<i>Not applicable.</i>
Flammability	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Flash point	No flash point

Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>Not applicable.</i>
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Density	1.27 g/ml
Relative density	1.27 [Ref Std: WATER=1]
Relative Vapour Density	<i>Not applicable.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	Negligible % [Test Method: Estimated]
Evaporation rate	<i>Not applicable.</i>
Molecular weight	<i>No data available.</i>
Percent volatile	Negligible

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Amines.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from

internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No known health effects.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg
N,N'-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	Dermal	Rat	LD50 > 2,000 mg/kg
N,N'-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	Ingestion	Rat	LD50 > 2,000 mg/kg
Adipohydrazide	Ingestion	Mouse	LD50 > 5,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	Ingestion	Rat	LD50 1,012 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Multiple animal species	No significant irritation
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Rabbit	Mild irritant
Dicyandiamide	Human and animal	Minimal irritation
N,N'-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	Rabbit	No significant irritation
Adipohydrazide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
------	---------	-------

bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Moderate irritant
Dicyandiamide	Professional judgement	Mild irritant
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	similar health hazards	Corrosive

Skin Sensitisation

Name	Species	Value
Overall product	Guinea pig	Not classified
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human and animal	Sensitising
Dicyandiamide	Guinea pig	Not classified
Adipohydrazide	Guinea pig	Sensitising
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	In Vitro	Not mutagenic
Adipohydrazide	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Some positive data exist, but the data are not sufficient for classification
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	Ingestion	Rat	Not carcinogenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation

3M Scotch-Weld AF-163-2 Structural Adhesive Film

bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Dicyandiamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dicyandiamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
Dicyandiamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
TRIFLUOROMETHANES ULFONIC ACID ANHYDRIDE	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Dicyandiamide	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Dicyandiamide	461-58-5	Bluegill	Experimental	96 hours	LC50	>1,000 mg/l
Dicyandiamide	461-58-5	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Dicyandiamide	461-58-5	Water flea	Experimental	48 hours	EC50	3,177 mg/l
Dicyandiamide	461-58-5	Green algae	Experimental	72 hours	NOEC	310 mg/l
Dicyandiamide	461-58-5	Water flea	Experimental	21 days	NOEC	25 mg/l
Dicyandiamide	461-58-5	Redworm	Experimental	14 days	LC50	>3,200 mg/kg (Dry Weight)
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Green algae	Experimental	72 hours	ErC50	>100 mg/l
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Green algae	Experimental	72 hours	NOEC	100 mg/l

3M Scotch-Weld AF-163-2 Structural Adhesive Film

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Adipohydrazide	1071-93-8	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Adipohydrazide	1071-93-8	Common Carp	Experimental	96 hours	LC50	>100 mg/l
Adipohydrazide	1071-93-8	Green algae	Experimental	72 hours	ErC50	8.7 mg/l
Adipohydrazide	1071-93-8	Water flea	Experimental	48 hours	EC50	>=106 mg/l
Adipohydrazide	1071-93-8	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDIMETHYL-	6386-73-8	Diatom	Analogous Compound	72 hours	EC50	0.43 mg/l
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDIMETHYL-	6386-73-8	Fathead minnow	Analogous Compound	96 hours	LC50	0.54 mg/l
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDIMETHYL-	6386-73-8	Green algae	Analogous Compound	72 hours	EC50	>1.9 mg/l
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDIMETHYL-	6386-73-8	Water flea	Analogous Compound	48 hours	EC50	0.96 mg/l
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDIMETHYL-	6386-73-8	Fathead minnow	Analogous Compound	35 days	NOEC	0.16 mg/l
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDIMETHYL-	6386-73-8	Green algae	Analogous Compound	72 hours	NOEC	0.5 mg/l
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDIMETHYL-	6386-73-8	Water flea	Analogous Compound	21 days	NOEC	0.3 mg/l
Dye	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	358-23-6	Green algae	Hydrolysis Product	72 hours	ErC50	48 mg/l
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	358-23-6	Rainbow trout	Hydrolysis Product	96 hours	LC50	>100 mg/l
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	358-23-6	Water flea	Hydrolysis Product	48 hours	EC50	>100 mg/l

3M Scotch-Weld AF-163-2 Structural Adhesive Film

TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	358-23-6	Green algae	Hydrolysis Product	72 hours	ErC10	5.8 mg/l
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	358-23-6	Activated sludge	Hydrolysis Product	3 hours	EC50	>1,000 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Dicyandiamide	461-58-5	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	0 %removal of DOC	OECD 301E - Modif. OECD Screen
Dicyandiamide	461-58-5	Experimental Aquatic Inherent Biodegrad.	14 days	Dissolv. Organic Carbon Deplet	0 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
Dicyandiamide	461-58-5	Experimental Biodegradation	61 days	CO2 evolution	1.1 %CO2 evolution/THC O2 evolution	OECD 309 Aero Sim Biod Water
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Experimental Aquatic Inherent Biodegrad.	28 days	Dissolv. Organic Carbon Deplet	10 %removal of DOC (does not pass 10-day window)	similar to OECD 302B
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	33 days (t 1/2)	OECD 111 Hydrolysis func of pH
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Adipohydrazide	1071-93-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	62.1 %removal of DOC	OECD 301E - Modif. OECD Screen
Adipohydrazide	1071-93-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDI-	6386-73-8	Modeled Biodegradation	28 days	BOD	16 %BOD/ThOD	Catalogic™
Dye	Trade Secret	Modeled Biodegradation	28 days	CO2 evolution	41.8 %CO2 evolution/THC O2 evolution	Catalogic™
TRIFLUOROMETHANESULFONIC ACID ANHYDRIDE	358-23-6	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	≤2 minutes (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Dicyandiamide	461-58-5	Experimental BCF - Fish	42 days	Bioaccumulation factor	≤3.1	OECD305-Bioconcentration
Dicyandiamide	461-58-5	Experimental Bioconcentration		Log Kow	-0.52	OECD 107 log Kow shke flask mtd
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Experimental Bioconcentration		Log Kow	<0.23	OECD 117 log Kow HPLC method
[3-(2,3-epoxypropoxy)propyl]trime	2530-83-8	Experimental Bioconcentration		Log Kow	0.5	Episuite™

thoxysilane						
Adipohydrazide	1071-93-8	Experimental Bioconcentration		Log Kow	-2.7	OECD 107 log Kow shke flsk mtd
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDI-	6386-73-8	Modeled Bioconcentration		Bioaccumulation factor	410	Catalogic™
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDI-	6386-73-8	Modeled Bioconcentration		Log Kow	6.3	Episuite™
Dye	Trade Secret	Modeled Bioconcentration		Bioaccumulation factor	500	Catalogic™
Dye	Trade Secret	Modeled Bioconcentration		Log Kow	5.7	Episuite™
TRIFLUOROMETHANES ULFONIC ACID ANHYDRIDE	358-23-6	Hydrolysis product Bioconcentration		Log Kow	<0.3	similar to OECD 117

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite™
Dicyandiamide	461-58-5	Modeled Mobility in Soil	Koc	9 l/kg	Episuite™
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite™
Adipohydrazide	1071-93-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite™
PHENOL, 2,2',6-TRIBROMO-4,4'-ISOPROPYLIDENEDI-	6386-73-8	Modeled Mobility in Soil	Koc	170,000 l/kg	Episuite™
Dye	Trade Secret	Modeled Mobility in Soil	Koc	29,000 l/kg	Episuite™
TRIFLUOROMETHANES ULFONIC ACID ANHYDRIDE	358-23-6	Modeled Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the

respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH014	Reacts violently with water.
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 1: Product identification numbers information was deleted.
Section 01: SAP Material Numbers information was deleted.
Contains statement for sensitizers information was added.
Label: CLP Supplemental Hazard Statements information was deleted.
List of sensitizers information was added.
Section 3: Composition/ Information of ingredients table information was modified.
Section 5: Fire - Special hazards information information was modified.
Section 5: Hazardous combustion products table information was modified.
Section 6: Accidental release personal information information was modified.
Section 7: Conditions safe storage information was modified.
Section 7: Precautions safe handling information information was modified.
Section 8: Appropriate Engineering controls information information was modified.
Section 8: Personal Protection - Respiratory Information information was added.
Section 8: Respiratory protection information information was deleted.
Section 9: Flammability (solid, gas) information information was deleted.
Section 09: Flammability information information was added.
Section 09: Particle Characteristics N/A information was added.
Section 10: Hazardous Decomposition Products information information was added.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Specific Target Organ Toxicity - single exposure text information was deleted.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was added.
Section 12: Component ecotoxicity information information was modified.
Section 12: Mobility in soil information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material.
information was modified.

Annex

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxy)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
Exposure Scenario Name	Industrial Use of Adhesives

Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article
Processes, tasks and activities covered	Application of product with a roller or brush. Application of product with applicator gun. Application with a wipe. Transfers without dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: 220 days/year; Frequency of exposure at workplace [for one worker]: 5 days/week;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com