Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	42-7905-5	**Version number:**	1.05
Revision date:	08/02/2023	**Supersedes date:**	24/11/2022
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier
3M™ Scotch-Weld™ Epoxy Structural Adhesive DP410 Off-White

Product Identification Numbers

UU-0114-7504-1	UU-0114-7505-8	UU-0116-1335-1
7100261679	7100261739	4100059983

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Adhesive

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com

Website: www.3M.com

1.4. Emergency telephone number
Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

07-7184-0, 42-7068-2

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture
CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:
Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements
CLP REGULATION (EC) No 1272/2008

SIGNAL WORD
DANGER.

Symbols
GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Contains:
2,4,6-tris(dimethylaminomethyl)phenol.; Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane; Nitric acid, calcium salt, tetrahydrate; bis-[4-(2,3-epoxipropoxi)phenyl]propane; 3,3'-Oxybis(ethyleneoxy)bis(propylamine)

HAZARD STATEMENTS:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260A	Do not breathe vapours.
P273	Avoid release to the environment.
P280B	Wear protective gloves and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P260A	Do not breathe vapours.
P280B	Wear protective gloves and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:
Label: CLP Ingredients - kit components information was modified.
Section 2: <125ml Precautionary - Prevention information was modified.
Label: CLP Precautionary - Prevention information was modified.

Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	07-7184-0	**Version number:**	18.01
Revision date:	24/02/2025	**Supersedes date:**	19/07/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
3M™ Scotch-Weld™ Epoxy Structural Adhesive DP410 Off-White: Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone:	+353 1 280 3555
E Mail:	tox.uk@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number
Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:
Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

2.2. Label elements
CLP REGULATION (EC) No 1272/2008

SIGNAL WORD
DANGER.

Symbols
GHS05 (Corrosion) |GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	30 - 70
Nitric acid, calcium salt, tetrahydrate	13477-34-4	233-332-1	7 - 13
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	202-013-9	7 - 13

HAZARD STATEMENTS:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P260A	Do not breathe vapours.
P280D	Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P260A	Do not breathe vapours.
P280D	Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

25% of the mixture consists of components of unknown acute oral toxicity.

Contains 27% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2 (REACH-No.) 01-2119963377-26	30 - 70	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Amine terminated adduct	Trade Secret	10 - 30	Substance not classified as hazardous
Nitric acid, calcium salt, tetrahydrate	(CAS-No.) 13477-34-4 (EC-No.) 233-332-1 (REACH-No.) 01-2119495093-35	7 - 13	Acute Tox. 4, H302 Eye Dam. 1, H318
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9 (REACH-No.) 01-2119560597-27	7 - 13	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318
Bis[(dimethylamino)methyl]phenol	(CAS-No.) 71074-89-0 (EC-No.) 275-162-0	< 5	Acute Tox. 4, H302 Skin Corr. 1C, H314

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact
Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact
Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed
Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed
The most important symptoms and effects based on the CLP classification include:
Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required
Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes.	During combustion.
Amine compounds.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters
When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus,tunic and trousers (leggings),bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities
Store away from heat. Store away from acids.

7.3. Specific end use(s)
See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values
No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Long-term exposure (8 hours), Local effects	1 mg/m³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	59 mg/m³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Short-term exposure, Local effects	13 mg/m³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Short-term exposure, Systemic effects	176 mg/m³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Freshwater	0.22 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Freshwater sediments	0.809 mg/kg d.w.
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Intermittent releases to water	2.2 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Marine water	0.022 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Marine water sediments	0.0809 mg/kg d.w.
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Sewage Treatment Plant	125 mg/l

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls
Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Full face shield.
Indirect vented goggles.

Applicable Norms/Standards
Use eye/face protection conforming to EN 166

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.7	=>8 hours

Neoprene.	0.5	=>8 hours
Nitrile rubber.	0.4	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Neoprene apron.
Apron – Nitrile

Respiratory protection

In case of inadequate ventilation wear respiratory protection.
An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls
Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Thixotropic paste
Colour	Off-White
Odor	Amine
Odour threshold	*No data available.*
Melting point/freezing point	*Not applicable.*
Boiling point/boiling range	*Not applicable.*
Flammability	Not applicable.
Flammable Limits(LEL)	*Not applicable.*
Flammable Limits(UEL)	*Not applicable.*
Flash point	>=100 ºC [*Test Method:*Closed Cup]
Autoignition temperature	*Not applicable.*
Decomposition temperature	*No data available.*
pH	*substance/mixture is non-soluble (in water)*
Kinematic Viscosity	*No data available.*
Water solubility	Negligible
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	*Not applicable.*

Density	1.09 - 1.12 g/ml
Relative density	1.09 - 1.12 [*Ref Std:*WATER=1]
Relative Vapour Density	*Not applicable.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	*No data available.*
Evaporation rate	*Not applicable.*
Percent volatile	<=1 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity
This material is considered to be non reactive under normal use conditions

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
Heat.
Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials
Strong acids.

10.6 Hazardous decomposition products

Substance	**Condition**
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose

and throat pain.

Skin contact
May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact
Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion
Harmful if swallowed.
Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:
Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness.

Additional information:
Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
Nitric acid, calcium salt, tetrahydrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Dermal	similar compounds	LD50 > 2,000 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
Bis[(dimethylamino)methyl]phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Nitric acid, calcium salt, tetrahydrate	similar compounds	No significant irritation
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compounds	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Nitric acid, calcium salt, tetrahydrate	Rabbit	Corrosive
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compounds	Corrosive

Skin Sensitisation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professional judgement	Sensitising
Nitric acid, calcium salt, tetrahydrate	similar compounds	Not classified
2,4,6-tris(dimethylaminomethyl)phenol	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
Nitric acid, calcium salt, tetrahydrate	In Vitro	Not mutagenic
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	premating into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for female reproduction	similar compounds	NOAEL 1,500 mg/kg/day	premating into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for male reproduction	similar compounds	NOAEL 1,500 mg/kg/day	28 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for development	similar compounds	NOAEL 1,500 mg/kg/day	premating into lactation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Ingestion	methemoglobinemia	Causes damage to organs	Human	NOAEL Not available	environmental exposure
2,4,6-tris(dimethylaminomethyl) phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	gastrointestinal tract | heart | endocrine system | bone, teeth, nails, and/or hair | hematopoietic system | liver | immune system | muscles | nervous system | eyes | kidney and/or bladder | respiratory system | vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	heart | skin | endocrine system | bone, teeth, nails, and/or hair | hematopoietic system | liver | immune system | nervous system | eyes | kidney and/or bladder | respiratory system | vascular system	Not classified	similar compounds	NOAEL 1,500 mg/kg/day	28 days
2,4,6-tris(dimethylaminomethyl) phenol	Dermal	skin	Not classified	Rat	NOAEL 25 mg/kg/day	4 weeks
2,4,6-tris(dimethylaminomethyl) phenol	Dermal	liver | nervous system | auditory system | hematopoietic system | eyes	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6-tris(dimethylaminomethyl) phenol	Ingestion	heart | endocrine system | hematopoietic system | liver | muscles | nervous system | kidney and/or bladder | respiratory system | vascular system | auditory system | skin | gastrointestinal tract | bone, teeth, nails, and/or hair |	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

		immune system | eyes				

Aspiration Hazard
For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Amine terminated adduct	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Guppy	Estimated	96 hours	LC50	1,378 mg/l
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Fathead minnow	Estimated	30 days	NOEC	58 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l

Bis[(dimethylamino)methyl]phenol	71074-89-0	N/A	Data not available or insufficient for classification	N/A	N/A	NA

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
Amine terminated adduct	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not availbl-insufficient	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Biodegradation	28 days	BOD	41 %CO2 evolution/THCO2 evolution	Catalogic™

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
Amine terminated adduct	Trade Secret	Estimated Bioconcentration		Bioaccumulation factor	2.9	
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Bioconcentration		Log Kow	-2.34	ACD/Labs ChemSketch™

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Modeled Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)
08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3263	UN3263	UN3263
14.2 UN proper shipping name	CORROSIVE SOLID, BASIC, ORGANIC, N.O.S.(3,3'-OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE))	CORROSIVE SOLID, BASIC, ORGANIC, N.O.S.(3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE))	CORROSIVE SOLID, BASIC, ORGANIC, N.O.S.(3,3'-OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE))
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	II	II	II
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.

Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	C8	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	18 - ALKALIS

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status
Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU
Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Revision information:
Section 2: Other hazards phrase information was modified.
Section 6: Accidental release personal information information was modified.
Section 7: Conditions safe storage information was modified.
Section 8: Appropriate Engineering controls information information was modified.
Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.
Section 09: Particle Characteristics N/A information was added.
Section 11: Health Effects - Additional Information information was added.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.

Annex

1. Title	
Substance identification	
Exposure Scenario Name	Formulation
Lifecycle Stage	Formulation or re-packing
Contributing activities	PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Batch manufacture of a chemical substance or formulation (including polymerisation reactions).
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Duration of use: 8 hours/day; Emission days per year: <= 225 days per year;
Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:** **Human health:** Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; **Environmental:** Waste Water treatment - Incineration;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent leaks and prevent soil / water pollution caused by leaks;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
Exposure Scenario Name	Industrial Transfer
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Transfer of substance/mixture with dedicated engineering controls.
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week;

	Processing Temperature:: 20 degree Celsius;
Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:** **Human health:** Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; **Environmental:** None needed;
Waste management measures	Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 06d -Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
Processes, tasks and activities covered	Application of product through a mixing nozzle
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Processing Temperature:: 20 degree Celsius;
Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:** **Human health:** Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; **Environmental:** None needed;
Waste management measures	Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-

	dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article
Processes, tasks and activities covered	Application of product with a roller or brush. Application of product with applicator gun. Application with a wipe. Transfers without dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Duration of use: 8 hours/day; Emission days per year: 220 days/year; Frequency of exposure at workplace [for one worker]: 5 days/week;
Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:** **Human health:** Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; **Environmental:** None needed;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	
Exposure Scenario Name	Professional Use of Adhesives
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor) ERC 08f -Widespread use leading to inclusion into/onto article (outdoor)
Processes, tasks and activities covered	Application of product with applicator gun.
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Application Temperature:: <= 40 degree Celsius; Duration of use: 8 hours/day; Indoors with good general ventilation;
Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:** **Human health:** Goggles - Chemical resistant; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; **Environmental:** Industrial Sewage Treatment Plant;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and

	PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com

Safety Data Sheet

Copyright,2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	42-7068-2	**Version number:**	3.00
Revision date:	29/10/2026	**Supersedes date:**	23/12/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
3M™ Scotch-Weld™ Epoxy Structural Adhesive DP410 Off-White: Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Industrial use.

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone:	+353 1 280 3555
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number
Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements
CLP REGULATION (EC) No 1272/2008

SIGNAL WORD
WARNING.

Symbols
GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	Identifier(s)	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	< 75
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	29407-84-9		7 - 13

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

25% of the mixture consists of components of unknown acute oral toxicity.

Contains 39% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01-2119456619-26	< 75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Acrylic copolymer 1	Trade Secret	< 15	Substance not classified as hazardous
Acrylic copolymer 2	Trade Secret	< 15	Substance not classified as hazardous
Acrylic copolymer 3	Trade Secret	< 15	Substance not classified as hazardous
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	(CAS-No.) 29407-84-9	7 - 13	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	1 - 2	Substance not classified as hazardous
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2 (REACH-No.) 01-2119513212-58	1 - 2	Eye Dam. 1, H318 Aquatic Chronic 3, H412
2,6-Di-tert-butyl-p-cresol	(CAS-No.) 128-37-0 (EC-No.) 204-881-4 (REACH-No.) 01-2119555270-46,01-2119565113-46	< 0.3	Aquatic Chronic 1, H410,M=1 Aquatic Acute 1, H400,M=1
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	(CAS-No.) 36443-68-2 (EC-No.) 253-039-2	< 0.025	Aquatic Chronic 1, H410,M=10

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
The most important symptoms and effects based on the CLP classification include:
Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Advice for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or

bodies of water.

6.3. Methods and material for containment and cleaning up
Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)
See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	Identifier(s)	Agency	Limit type	Additional comments
2,6-Di-tert-butyl-p-cresol	128-37-0	Ireland OELs	TWA(8 hours):2 mg/m3	

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values
No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Worker	Dermal, Short-term exposure, Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-		Worker	Inhalation, Long-term	12.3 mg/m³

epoxipropoxi)phenyl]propane			exposure (8 hours), Systemic effects	
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Worker	Inhalation, Short-term exposure, Systemic effects	12.3 mg/m³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Freshwater	0.003 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Freshwater sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Intermittent releases to water	0.013 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Marine Water	0.0003 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Marine water sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Sewage Treatment Plant	10 mg/l

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.
Indirect vented goggles.

Applicable Norms/Standards
Use eye protection conforming to EN 16321

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions.

Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136
Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls
Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Beige
Odor	Epoxy
Odour threshold	*No data available.*
Melting point/freezing point	*No data available.*
Boiling point/boiling range	>=200 ºC
Flammability	Not applicable.
Flammable Limits(LEL)	*Not applicable.*
Flammable Limits(UEL)	*Not applicable.*
Flash point	Flash point > 93 °C (200 °F) [*Test Method:*Closed Cup]
Autoignition temperature	*No data available.*
Decomposition temperature	*No data available.*
pH	*substance/mixture is non-soluble (in water)*
Kinematic Viscosity	*No data available.*
Water solubility	*No data available.*
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	*Not applicable.*
Density	1.15 g/cm3

Relative density	1.11 - 1.15
Relative Vapour Density	*Not applicable.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	*No data available.*
Evaporation rate	*Not applicable.*
Percent volatile	*No data available.*

SECTION 10: Stability and reactivity

10.1 Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
Heat.
Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials
Strong acids.
Strong oxidising agents.

10.6 Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose

and throat pain.

Skin contact
Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact
Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion
Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Acrylic copolymer 1	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylic copolymer 1	Ingestion	Rat	LD50 > 5,000 mg/kg
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Ingestion	similar compounds	LD50 estimated to be > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Dermal	Rat	LD50 > 2,000 mg/kg
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Ingestion	Rat	LD50 > 7,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Professional judgement	Irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
2,6-Di-tert-butyl-p-cresol	Human and animal	Minimal irritation
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-	Rabbit	No significant irritation

METHYLPHENYL)PROPIONATE]		

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Professional judgement	Severe irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human and animal	Sensitising
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Professional judgement	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified
2,6-Di-tert-butyl-p-cresol	Human	Not classified
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Some positive data exist, but the data are not sufficient for classification
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]prop	Dermal	liver	Not classified	Rat	NOAEL 1,000	2 years

ane					mg/kg/day	
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	auditory system | heart | endocrine system | hematopoietic system | liver | eyes | kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system | silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	heart | endocrine system | bone, teeth, nails, and/or hair | hematopoietic system | liver | immune system | nervous system | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-Di-tert-butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 110 mg/kg/day	90 days
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Ingestion	liver	Not classified	Rat	NOAEL 100 mg/kg/day	24 months
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	Ingestion	hematopoietic system	Not classified	Monkey	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard
For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	Identifier(s)	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Acrylic copolymer 1	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	29407-84-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Siloxanes and Silicones, di-Me, reaction products with	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

silica						
2,6-Di-tert-butyl-p-cresol	128-37-0	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC10	0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Bluegill	Endpoint not reached	96 hours	LC50	>100 mg/l
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Fathead minnow	Experimental	32 days	NOEC	0.0088 mg/l
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Water flea	Experimental	21 days	NOEC	0.0055 mg/l
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Redworm	Experimental	56 days	NOEC	1,000 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Acrylic copolymer 1	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	29407-84-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
2,6-Di-tert-butyl-p-cresol	128-37-0	Data not availbl-insufficient	N/A	N/A	N/A	N/A
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Experimental Biodegradation	28 days	CO2 evolution	8 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH

12.3 : Bioaccumulative potential

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Acrylic copolymer 1	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	29407-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Bioconcentration		Log Kow	0.5	Episuite™
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,6-Di-tert-butyl-p-cresol	128-37-0	Experimental BCF - Fish	56 days	Bioaccumulation factor	1277	OECD305-Bioconcentration
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	8.0	OECD305-Bioconcentration
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROP	36443-68-2	Experimental Bioconcentration		Log Kow	4.7	OECD 117 log Kow HPLC method

IONATE]						

12.4. Mobility in soil

Material	Identifier(s)	Test type	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite™
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite™
TRIETHYLENE GLYCOL BIS[3-(3-TERT-BUTYL-4-HYDROXY-5-METHYLPHENYL)PROPIONATE]	36443-68-2	Modeled Mobility in Soil	Koc	3,500 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects
No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)
08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	UN3082	UN3082	UN3082

14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable.	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient	Identifier(s)	Classification	Regulation
2,6-Di-tert-butyl-p-cresol	128-37-0	Gr. 3: Not classifiable	International Agency for Research on Cancer
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:
The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingredient	Identifier(s)
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3

Restriction status: listed in REACH Annex XVII
Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

Ingredient	%
3902 Polymers of propylene or of other olefins	<= 16
3906 Acrylic polymers	<= 13

Global inventory status
Contact 3M for more information.

DIRECTIVE 2012/18/EU
Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:
EU Section 14 - Table Data information was added.
EU Section 14 - Table Headers information was added.
Formulation: Section 16: Annex information was modified.
Industrial Use of Adhesives: Section 16: Annex information was modified.
Professional Use of Adhesives: Section 16: Annex information was modified.
CLP: Ingredient table information was modified.
Label: CLP Percent Unknown information was modified.
Label: CLP Precautionary - Prevention information was modified.

Label: Graphic information was modified.
Section 3: Composition/ Information of ingredients table information was modified.
Section 5: Hazardous combustion products table information was modified.
Section 6: Accidental release personal information information was modified.
Section 8: Eye/face protection information information was modified.
Section 8: glove data value information was deleted.
Section 8: glove data value information was modified.
Section 8: PNEC table row information was modified.
Section 8: Respiratory protection - recommended respirators information information was modified.
Section 9: Vapour pressure value information was added.
Section 9: Vapour pressure value information was deleted.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Mobility in soil information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12:Bioccumulative potential information information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.
Section 14 Classification Code – Main Heading information was deleted.
Section 14 Classification Code – Regulation Data information was deleted.
Section 14 Control Temperature – Main Heading information was deleted.
Section 14 Control Temperature – Regulation Data information was deleted.
Section 14 Emergency Temperature – Main Heading information was deleted.
Section 14 Emergency Temperature – Regulation Data information was deleted.
Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.
Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.
Section 14 Other Dangerous Goods – Main Heading information was deleted.
Section 14 Other Dangerous Goods – Regulation Data information was deleted.
Section 14 Packing Group – Main Heading information was deleted.
Section 14 Packing Group – Regulation Data information was deleted.
Section 14 Proper Shipping Name information was deleted.
Section 14 Regulations – Main Headings information was deleted.
Section 14 Segregation – Regulation Data information was deleted.
Section 14 Segregation Code – Main Heading information was deleted.
Section 14 Special Precautions – Main Heading information was deleted.
Section 14 Special Precautions – Regulation Data information was deleted.
Section 14 Transport in bulk – Regulation Data information was deleted.
Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was deleted.
Section 14 UN Number Column data information was deleted.
Section 14 UN Number information was deleted.
Section 15: Microparticles Header information was added.
Section 15: Microparticles Statement information was added.
Section 15: Microplastics Table information was added.

Annex

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxi)phenyl]propane; EC No. 216-823-5;

	Identifier(s) 1675-54-3;
Exposure Scenario Name	Formulation
Lifecycle Stage	Formulation or re-packing
Contributing activities	PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Batch manufacture of a chemical substance or formulation (including polymerisation reactions).
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Duration of use: 8 hours/day; Emission days (in days per year): <= 225 days per year;
Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:** **Human health:** Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; **Environmental:** Waste Water treatment - Incineration;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent leaks and prevent soil / water pollution caused by leaks;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxi)phenyl]propane; EC No. 216-823-5; Identifier(s) 1675-54-3;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 05 -Mixing or blending in batch processes PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article
Processes, tasks and activities covered	Application of product with a roller or brush. (PROC 10) Application of product with applicator gun. (PROC 13) Application with a wipe. (PROC 10) Transfers without dedicated controls, including loading, filling, dumping, bagging. (PROC 8a)
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Duration of use: 8 hours/day; Emission days (in days per year): 220 days/year; Frequency of exposure at workplace: 5 days/week;
Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:**

	Human health: Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; **Environmental:** None needed;
Waste management measures	Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	bis-[4-(2,3-epoxipropoxi)phenyl]propane; EC No. 216-823-5; Identifier(s) 1675-54-3;
Exposure Scenario Name	Professional Use of Adhesives
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor) ERC 08f -Widespread use leading to inclusion into/onto article (outdoor)
Processes, tasks and activities covered	Application of product with applicator gun. (PROC 13)
2. Operational conditions and risk management measures	
Operating Conditions	**Physical state:**Liquid. **General operating conditions:** Application Temperature:: <= 40 degree Celsius; Duration of use: 8 hours/day; Indoors with good general ventilation;
Risk management measures	Under the operational conditions described above the following risk management measures apply: **General risk management measures:** **Human health:** Goggles - Chemical resistant; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; **Environmental:** Industrial Sewage Treatment Plant;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com