



## Safety Data Sheet

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 45-1677-9  
**Issue Date:** 15/06/2025

**Version number:** 1.00  
**Supersedes date:** Initial issue.

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ VHB™ Tape Max Promoter Clear

##### Product Identification Numbers

7100362728	7100363011	7100363048
70-0111-4567-2	70-0111-4565-6	70-0111-4566-4

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesion promoter.

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.  
Serious Eye Damage/Irritation: Category 2.  
Skin Sensitizer: Category 1B.  
Specific Target Organ Toxicity (single exposure): Category 3

## 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

### Signal word

Danger

### Symbols

Flame | Exclamation mark |

### Pictograms



### Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.

### Precautionary statements

#### Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash exposed skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280E	Wear protective gloves.

#### Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### Storage:

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

None known.

**2.4. Other hazards which do not result in classification**

May be harmful if swallowed.

Causes mild skin irritation.

May be harmful if inhaled.

Toxic to aquatic life.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>% by Weight</b>
Propan-1-ol	71-23-8	40 - 80
Dimethyl Carbonate	616-38-6	10 - 30
d-limonene	5989-27-5	< 10
Acrylate Polymer	Trade Secret	< 5
Polyamide Resin	Trade Secret	< 5
Isopropyl Alcohol	67-63-0	< 2

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable.

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products****Substance**

Hydrocarbons.  
Carbon monoxide.  
Carbon dioxide.  
Irritant vapours or gases.  
Oxides of nitrogen.

**Condition**

During combustion.  
During combustion.  
During combustion.  
During combustion.  
During combustion.

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**Hazchem Code:** 3YE

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work

clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

## 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
d-limonene	5989-27-5	AIHA	TWA:165.5 mg/m <sup>3</sup> (30 ppm)	
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcin
Isopropyl Alcohol	67-63-0	Australia OELs	TWA(8 hours):983 mg/m <sup>3</sup> (400 ppm);STEL(15 minutes):1230 mg/m <sup>3</sup> (500 ppm)	
Propan-1-ol	71-23-8	ACGIH	TWA:100 ppm	A4: Not class. as human carcin
Propan-1-ol	71-23-8	Australia OELs	TWA(8 hours): 492 mg/m <sup>3</sup> (200 ppm); STEL(15 minutes): 614 mg/m <sup>3</sup> (250 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Nitrile rubber.

Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile  
Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Liquid.
<b>Colour</b>	Yellow
<b>Odour</b>	Orange
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	6
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	93.2 °C [ <i>@ 101,324.72 Pa</i> ]
<b>Flash point</b>	19 °C [ <i>Test Method:Closed Cup</i> ]
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability</b>	Flammable Liquid: Category 2.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	3,333.1 Pa [ <i>@ 20 °C</i> ]
<b>Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	0.85 g/ml
<b>Relative density</b>	0.85 [ <i>Ref Std:WATER=1</i> ]
<b>Water solubility</b>	1 %
<b>Solubility- non-water</b>	<i>No data available.</i>

Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Kinematic Viscosity	No data available.
Volatile organic compounds (VOC)	630 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:Low Solids Calculation]
Volatile organic compounds (VOC)	73 % [Test Method:calculated SCAQMD rule 443.1] [Details:weight percent]
Percent volatile	93 % weight [Details:measured]
VOC less H2O & exempt solvents	745 g/l [Test Method:calculated SCAQMD rule 443.1]
Molecular weight	No data available.
Solids content	7 %

Particle Characteristics	Not applicable.
--------------------------	-----------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

Sparks and/or flames.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May be harmful if inhaled. May cause additional health effects (see below).

**Skin contact**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Propan-1-ol	Dermal	Rabbit	LD50 4,000 mg/kg
Propan-1-ol	Inhalation-Vapour (4 hours)	Rat	LC50 > 34 mg/l
Propan-1-ol	Ingestion	Rat	LD50 estimated to be 2,000 - 5,000 mg/kg
Dimethyl Carbonate	Dermal		estimated to be > 5,000 mg/kg
Dimethyl Carbonate	Inhalation-Dust/Mist		estimated to be > 12.5 mg/l
Dimethyl Carbonate	Inhalation-Vapour		estimated to be > 50 mg/l
Dimethyl Carbonate	Ingestion		estimated to be > 5,000 mg/kg
d-limonene	Inhalation-Vapour (4 hours)	Mouse	LC50 > 3.14 mg/l
d-limonene	Dermal	Rabbit	LD50 > 5,000 mg/kg
d-limonene	Ingestion	Rat	LD50 4,400 mg/kg
Polyamide Resin	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Polyamide Resin	Ingestion	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Acrylate Polymer	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Acrylate Polymer	Ingestion	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-Vapour (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg

ATE = acute toxicity estimate



**Skin Corrosion/Irritation**

Name	Species	Value
Propan-1-ol	Rabbit	Minimal irritation
d-limonene	Rabbit	Irritant
Polyamide Resin	Professional judgement	No significant irritation
Acrylate Polymer	Professional judgement	No significant irritation
Isopropyl Alcohol	Multiple animal species	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Propan-1-ol	Rabbit	Severe irritant
d-limonene	Rabbit	Mild irritant
Polyamide Resin	Professional judgement	No significant irritation
Acrylate Polymer	Professional judgement	No significant irritation
Isopropyl Alcohol	Rabbit	Severe irritant

**Skin Sensitisation**

Name	Species	Value
Propan-1-ol	Guinea pig	Not classified
d-limonene	Mouse	Sensitising
Polyamide Resin	Professional judgement	Not classified
Acrylate Polymer	Professional judgement	Not classified
Isopropyl Alcohol	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Propan-1-ol	In Vitro	Some positive data exist, but the data are not sufficient for classification
d-limonene	In Vitro	Not mutagenic
d-limonene	In vivo	Not mutagenic
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Propan-1-ol	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
d-limonene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Propan-1-ol	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.6 mg/l	6 weeks
Propan-1-ol	Inhalation	Not classified for	Rat	NOAEL 8.6	during gestation

		development		mg/l	
d-limonene	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	pre mating & during gestation
d-limonene	Ingestion	Not classified for development	Multiple animal species	NOAEL 591 mg/kg/day	during organogenesis
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Propan-1-ol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Mouse	NOAEL 5 mg/l	4 hours
Propan-1-ol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	
Propan-1-ol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
d-limonene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
d-limonene	Ingestion	nervous system	Not classified		NOAEL Not available	
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Propan-1-ol	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 70 mg/kg/day	83 weeks
Propan-1-ol	Ingestion	liver	Not classified	Rat	LOAEL 70 mg/kg/day	83 weeks
d-limonene	Ingestion	kidney and/or	Not classified	Rat	LOAEL 75	103 weeks

		bladder			mg/kg/day	
d-limonene	Ingestion	liver	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
d-limonene	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	103 weeks
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks

**Aspiration Hazard**

Name	Value
d-limonene	Aspiration hazard

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not Determined

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Propan-1-ol	71-23-8	Activated sludge	Experimental	3 hours	IC50	>1,000 mg/l
Propan-1-ol	71-23-8	Algae or other aquatic plants	Experimental	96 hours	EC50	4,480 mg/l
Propan-1-ol	71-23-8	Fathead minnow	Experimental	96 hours	LC50	4,555 mg/l
Propan-1-ol	71-23-8	Fish	Experimental	96 hours	LC50	3,000 mg/l
Propan-1-ol	71-23-8	Water flea	Experimental	48 hours	EC50	3,642 mg/l
Propan-1-ol	71-23-8	Water flea	Experimental	21 days	NOEC	100 mg/l
Dimethyl	616-38-6	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l

Carbonate						
Dimethyl Carbonate	616-38-6	Green algae	Experimental	72 hours	ErC50	>100 mg/l
Dimethyl Carbonate	616-38-6	Water flea	Experimental	48 hours	EC50	>100 mg/l
Dimethyl Carbonate	616-38-6	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Dimethyl Carbonate	616-38-6	Green algae	Experimental	72 hours	NOEC	100 mg/l
Dimethyl Carbonate	616-38-6	Water flea	Experimental	21 days	NOEC	25 mg/l
d-limonene	5989-27-5	Fathead minnow	Experimental	96 hours	LC50	0.702 mg/l
d-limonene	5989-27-5	Green algae	Experimental	72 hours	ErC50	0.32 mg/l
d-limonene	5989-27-5	Water flea	Experimental	48 hours	EC50	0.307 mg/l
d-limonene	5989-27-5	Fathead minnow	Experimental	8 days	EC10	0.32 mg/l
d-limonene	5989-27-5	Green algae	Experimental	72 hours	ErC10	0.174 mg/l
d-limonene	5989-27-5	Water flea	Experimental	21 days	NOEC	0.153 mg/l
Acrylate Polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A % weight
Polyamide Resin	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Isopropyl Alcohol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Invertebrate	Experimental	24 hours	LC50	>10,000 mg/l
Isopropyl Alcohol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Propan-1-ol	71-23-8	Experimental Biodegradation	20 days	BOD	73 %BOD/ThOD	OECD 301D - Closed bottle test
Dimethyl Carbonate	616-38-6	Experimental Biodegradation	28 days	BOD	86 %BOD/ThOD	OECD 301C - MITI test (I)
d-limonene	5989-27-5	Experimental Biodegradation	14 days	BOD	98 %BOD/ThOD	OECD 301C - MITI test (I)
d-limonene	5989-27-5	Experimental Biodegradation	14 days	Dissolv. Organic Carbon Deplet	>93.8 %removal of DOC	OECD 303A - Simulated Aerobic
Acrylate Polymer	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Polyamide Resin	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Isopropyl Alcohol	67-63-0	Experimental Biodegradation	14 days	BOD	86 %BOD/ThOD	OECD 301C - MITI test (I)

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Propan-1-ol	71-23-8	Experimental Bioconcentration		Log Kow	0.2	
Dimethyl Carbonate	616-38-6	Experimental Bioconcentration		Log Kow	0.354	OECD 107 log Kow shke flsk mtd
d-limonene	5989-27-5	Modeled Bioconcentration		Bioaccumulation factor	2100	Catalogic™
d-limonene	5989-27-5	Experimental		Log Kow	4.57	

		Bioconcentration				
Acrylate Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyamide Resin	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Isopropyl Alcohol	67-63-0	Experimental Bioconcentration		Log Kow	0.05	

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

## SECTION 13: Disposal considerations

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility.

## SECTION 14: Transport Information

**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Hazchem Code: 3YE

IERG: 14

**International Air Transport Association (IATA) - Air Transport**

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Marine Pollutant: Not applicable.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Australian Inventory Status:

One or more ingredient/s in this product is not listed on the inventory. To meet compliance requirements of the Industrial Chemicals Act 2019, an importer is required to have an import mechanism in place for import of these ingredient/s prior to import of the product. Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## **SECTION 16: Other information**

### **Revision information:**

Initial issue.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**