



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 24-1026-4
Issue Date: 10/06/25

Version Number: 10.00
Supersedes Date: 02/04/25

SECTION 1: Identification

1.1. Product identifier

3M™ Dyneon™ Fluoroplastic PFA 6515TZ

Product Identification Numbers

97-5000-1371-5
7100090852

1.2. Recommended use and restrictions on use

Recommended use

Fluoropolymer for industrial processing

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Advanced Materials Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable

Pictograms

Not applicable

Hazard Statements

Precautionary statements**2.3. Hazards not otherwise classified**

May cause polymer fume fever.

Supplemental Information:

May cause thermal burns. The health hazards of this material are not completely known. See the SDS.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Perfluoropropanoic acid (unintentional impurity)	422-64-0	<= 0.0000483
Hexafluoropropylene oxide dimer acid (unintentional impurity)	13252-13-6	<= 0.0000117
Perfluoro-3-methoxypropanoic acid (unintentional impurity)	377-73-1	<= 0.0000102
Perfluorobutanoic acid (unintentional impurity)	375-22-4	<= 0.00000294
Perfluorohexanoic acid (unintentional impurity)	307-24-4	<= 0.00000289
Perfluorooctanoic acid (unintentional impurity)	335-67-1	<= 0.00000052
Perfluorononanoic acid (unintentional impurity)	375-95-1	<= 0.00000037
Perfluorodecanoic acid (unintentional impurity)	335-76-2	<= 0.00000023
Perfluorododecanoic acid (unintentional impurity)	307-55-1	<= 0.00000023
Perfluorotetradecanoic acid (unintentional impurity)	376-06-7	<= 0.00000021
Tetrafluoroethylene-Perfluoro(Propyl Vinyl Ether) Copolymer	26655-00-5	100

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

Eye Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid eye contact. Do not breathe thermal decomposition products. For industrial/occupational use only. Not for consumer sale or use. Store work clothes separately from other clothing, food and tobacco products. Avoid skin contact. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Perfluorooctanoic acid (unintentional impurity)	335-67-1	Manufacturer determined	TWA:0.01 mg/m3	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Local exhaust required above 400 C.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Neoprene, Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Coarse Powder
Color	White

Odor	Odorless
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	300 - 320 °C [<i>Test Method:</i> Tested per ASTM protocol] [<i>Details:</i> D 3307]
Boiling point/Initial boiling point/Boiling range	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>Not Applicable</i>
Flammability	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Relative Vapor Density	<i>Not Applicable</i>
Density	2.14 - 2.18 g/cm3
Relative Density	2.14 - 2.18 [<i>Ref Std:</i> WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	<i>Not Applicable</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Percent volatile as Text	Negligible
VOC Less H2O & Exempt Solvents	<i>Not Applicable</i>
Molecular weight	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
---------------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Alkali and alkaline earth metals

Reactions with metals in powder form occur from 370 degrees C onwards.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Hexafluoropropylene	At Elevated Temperatures
Carbonyl Fluoride	At Elevated Temperatures
Carbon monoxide	At Elevated Temperatures
Carbon dioxide	At Elevated Temperatures

Hydrogen Fluoride
 Perfluoroisobutylene (PFIB)
 Toxic Vapor, Gas, Particulate

At Elevated Temperatures
 At Elevated Temperatures
 At Elevated Temperatures

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

During heating:

Polymer Fume Fever: Sign/symptoms may include chest pain or tightness, shortness of breath, malaise, muscle aches, increased heart rate, fever, chills, sweats, nausea and headache.

Skin Contact:

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eye Contact:

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion:

No known health effects.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Perfluorooctanoic acid	335-67-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Additional Information:

The health hazards of this material are not completely known. Conservative safe handling measures should be followed (as described in sections 7 and 8), and appropriate first aid measures (as described in section 4) should be taken if exposure occurs.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
------	-------	---------	-------

Tetrafluoroethylene-Perfluoro(Propyl Vinyl Ether) Copolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Tetrafluoroethylene-Perfluoro(Propyl Vinyl Ether) Copolymer	Ingestion		LD50 estimated to be > 5,000 mg/kg
Perfluoropropanoic acid (unintentional impurity)	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
Perfluoropropanoic acid (unintentional impurity)	Inhalation-Vapor (4 hours)	Rat	LC50 > 11 mg/l
Perfluorohexanoic acid (unintentional impurity)	Ingestion	Rat	LD50 500-1000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Serious Eye Damage/Irritation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Skin Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Perfluoropropanoic acid (unintentional impurity)	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Perfluorohexanoic acid (unintentional impurity)	Ingestion	Not classified for reproduction and/or development	Rat	LOEL 500 mg/kg	
Perfluorohexanoic acid (unintentional impurity)	Ingestion	Not classified for male reproduction	Rat	LOAEL 500 mg/kg	not applicable

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Perfluoropropanoic acid (unintentional impurity)	Ingestion	liver heart endocrine system hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 320 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not Applicable.

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Perfluoropropanoic acid (unintentional impurity)	422-64-0	<= 0.0000483
Hexafluoropropylene oxide dimer acid (unintentional impurity)	13252-13-6	<= 0.0000117
Perfluoro-3-methoxypropanoic acid (unintentional impurity)	377-73-1	<= 0.0000102
Perfluorobutanoic acid (unintentional impurity)	375-22-4	<= 0.00000294
Perfluorohexanoic acid (unintentional impurity)	307-24-4	<= 0.00000289
Perfluorooctanoic acid (unintentional impurity)	335-67-1	<= 0.00000052
Perfluorononanoic acid (unintentional impurity)	375-95-1	<= 0.00000037
Perfluorododecanoic acid (unintentional impurity)	307-55-1	<= 0.00000023

Perfluorodecanoic acid (unintentional impurity)	335-76-2	<= 0.00000023
Perfluorotetradecanoic acid (unintentional impurity)	376-06-7	<= 0.00000021

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
Perfluorododecanoic acid (unintentional impurity)	307-55-1	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable
Perfluorooctanoic acid (unintentional impurity)	335-67-1	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable
Perfluorodecanoic acid (unintentional impurity)	335-76-2	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable
Perfluorononanoic acid (unintentional impurity)	375-95-1	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable
Perfluorotetradecanoic acid (unintentional impurity)	376-06-7	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable

This material contains a chemical regulated by an EPA Significant New Use Rule (TSCA Section 5)

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Reference</u>
Perfluorododecanoic acid (unintentional impurity)	307-55-1	40 CFR 721.10536
Perfluorooctanoic acid (unintentional impurity)	335-67-1	40 CFR 721.10536
Perfluorodecanoic acid (unintentional impurity)	335-76-2	40 CFR 721.10536
Perfluorononanoic acid (unintentional impurity)	375-95-1	40 CFR 721.10536
Perfluorotetradecanoic acid (unintentional impurity)	376-06-7	40 CFR 721.10536

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride and Perfluoroisobutylene (PFIB). During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

HMIS Hazard Classification

Health: 0 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	24-1026-4	Version Number:	10.00
Issue Date:	10/06/25	Supersedes Date:	02/04/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com