Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	26-5804-5	**Version number:**	14.00
Revision date:	03/11/2025	**Supersedes date:**	31/10/2025
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier
3M Scotchcast™ Electrical Resin 281 (A & B)

Product Identification Numbers
80-6116-2515-5

7100150444

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Electrical

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number
+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

20-4047-5, 20-4030-1

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD
WARNING.

Symbols
GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Contains:
reaction product: bisphenol-A-(epichlorhydrin); Dihydro-3-(tetrapropenyl)furan-2,5-dione

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

No revision information

Safety Data Sheet

Copyright,2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	20-4030-1	**Version number:**	10.00
Revision date:	12/11/2026	**Supersedes date:**	13/05/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
3M™ Scotchcast™ Electrical Resin 281 Part A

Product Identification Numbers
80-6116-2516-3

7100150608

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Electrical

1.3. Details of the supplier of the safety data sheet

Address:	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone:	+44 (0)1344 858 000
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com/uk

1.4. Emergency telephone number
+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD
WARNING.

Symbols
GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredient	Identifier(s)	EC No.	% by Wt
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	500-033-5	45 - 65

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

2.3. Other hazards

None known.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
reaction product: bisphenol-A-(epichlorhydrin)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5	45 - 65	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Talc	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	35 - 55	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
reaction product: bisphenol-A-(epichlorhydrin)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:
Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.

5.3. Advice for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities
No special storage requirements.

7.3. Specific end use(s)
See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	Identifier(s)	Agency	Limit type	Additional comments
Talc	14807-96-6	UK HSE	TWA(as respirable dust):1 mg/m³	

UK HSE : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values
No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls
No engineering controls required.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.
Indirect vented goggles.

Applicable Norms/Standards
Use eye protection conforming to EN 16321

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection
None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Green-Gray
Odor	Moderate Amine
Odour threshold	*No data available.*
Melting point/freezing point	*No data available.*
Boiling point/boiling range	>= 177.2 ºC
Flammability	Not applicable.
Flammable Limits(LEL)	*Not applicable.*
Flammable Limits(UEL)	*Not applicable.*
Flash point	> 176.7 ºC [*Test Method:*Closed Cup]
Autoignition temperature	*No data available.*
Decomposition temperature	*No data available.*
pH	*substance/mixture is non-soluble (in water)*
Kinematic Viscosity	170,886 mm²/sec
Water solubility	Negligible
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	*No data available.*
Density	1.58 g/ml
Relative density	1.58 [*Ref Std:*WATER=1]
Relative Vapour Density	*No data available.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

Average particle size	*No data available.*
Bulk density	*No data available.*
EU Volatile Organic Compounds	0 g/l [*Details:*Parts A and B as mixed]
Evaporation rate	*Not applicable.*
Molecular weight	*No data available.*
Percent volatile	*No data available.*
Percent volatile	Negligible
Softening point	*No data available.*

SECTION 10: Stability and reactivity

10.1 Reactivity
This material is considered to be non reactive under normal use conditions

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
None known.

10.5 Incompatible materials
None known.

No data available.

10.6 Hazardous decomposition products

Substance	Condition
Aldehydes.	Oxidative Degradation

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
No known health effects.

Skin contact
Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact
Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion
Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
reaction product: bisphenol-A-(epichlorhydrin)	Dermal	Rat	LD50 > 1,600 mg/kg
reaction product: bisphenol-A-(epichlorhydrin)	Ingestion	Rat	LD50 > 1,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Rabbit	Moderate irritant
Talc	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Human and animal	Sensitising

Respiratory Sensitisation

Name	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Human	Not classified
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
reaction product: bisphenol-A-(epichlorhydrin)	In vivo	Not mutagenic
reaction product: bisphenol-A-(epichlorhydrin)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Talc	Dermal	Human	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
reaction product: bisphenol-A-(epichlorhydrin)	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
reaction product: bisphenol-A-(epichlorhydrin)	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
reaction product: bisphenol-A-(epichlorhydrin)	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
reaction product: bisphenol-A-(epichlorhydrin)	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
reaction product: bisphenol-A-(epichlorhydrin)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
reaction product: bisphenol-A-(epichlorhydrin)	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
reaction product: bisphenol-A-(epichlorhydrin)	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
reaction product: bisphenol-A-(epichlorhydrin)	Ingestion	auditory system | heart | endocrine system | hematopoietic system | liver | eyes | kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Talc	Inhalation	pneumoconiosis	Repeated and prolonged exposure to large amounts of talc dust can cause lung injury	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis | respiratory system	Not classified	Rat	NOAEL 18 mg/m³	113 weeks

Aspiration Hazard
For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	Identifier(s)	Organism	Type	Exposure	Test endpoint	Test result
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Water flea	Estimated	48 hours	LC50	1.8 mg/l
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Green algae	Experimental	72 hours	EC50	>11 mg/l

reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
Talc	14807-96-6	Data not availbl-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	Experimental Bioconcentration		Log Kow	3.242	
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are

complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable.	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient	Identifier(s)	Classification	Regulation
Talc	14807-96-6	Grp. 2A: Probable human carc.	International Agency for Research on Cancer

Global inventory status
Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483
Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012, as amended for GB
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Revision information:
EU Section 14 - Table Data information was added.
EU Section 14 - Table Headers information was added.

GBSDS Section 14 Transport in bulk - Main Heading information was deleted.
GBSDS Section 14 UN Number information was deleted.
Label: CLP Precautionary - Prevention information was modified.
Label: Graphic information was modified.
Section 08: Personal Protection - Apron Statement information was added.
Section 8: Personal Protection - Skin/body information information was deleted.
Section 8: Skin protection - protective clothing information information was deleted.
Section 9: Vapour pressure value information was added.
Section 9: Vapour pressure value information was deleted.
Section 11: Carcinogenicity Table information was modified.
Section 11: Specific Target Organ Toxicity - single exposure text information was deleted.
Section 11: Target Organs - Single Table information was added.
Section 13: Standard Phrase Category Waste GHS information was modified.
Section 14 Classification Code – Main Heading information was deleted.
Section 14 Classification Code – Regulation Data information was deleted.
Section 14 Control Temperature – Main Heading information was deleted.
Section 14 Control Temperature – Regulation Data information was deleted.
Section 14 Emergency Temperature – Main Heading information was deleted.
Section 14 Emergency Temperature – Regulation Data information was deleted.
Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.
Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.
Section 14 Other Dangerous Goods – Main Heading information was deleted.
Section 14 Other Dangerous Goods – Regulation Data information was deleted.
Section 14 Packing Group – Main Heading information was deleted.
Section 14 Packing Group – Regulation Data information was deleted.
Section 14 Proper Shipping Name information was deleted.
Section 14 Regulations – Main Headings information was deleted.
Section 14 Segregation – Regulation Data information was deleted.
Section 14 Segregation Code – Main Heading information was deleted.
Section 14 Special Precautions – Main Heading information was deleted.
Section 14 Special Precautions – Regulation Data information was deleted.
Section 14 Transport in bulk – Regulation Data information was deleted.
Section 14 UN Number Column data information was deleted.
Section 15: Seveso Substance Text information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk
For Northern Ireland documents, please contact your 3M representative to obtain a copy.

Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	20-4047-5	**Version number:**	13.00
Revision date:	03/11/2025	**Supersedes date:**	31/10/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
3M™ Scotchcast™ Electrical Resin 281 Part B

Product Identification Numbers
80-6116-2517-1

7100150607

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Electrical

1.3. Details of the supplier of the safety data sheet

Address:	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone:	+44 (0)1344 858 000
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com/uk

1.4. Emergency telephone number
+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 4 - Aquatic Chronic 4; H413

For full text of H phrases, see Section 16.

2.2. Label elements
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD
WARNING.

Symbols
GHS07 (Exclamation mark) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	247-781-6	20 - 35

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H413	May cause long lasting harmful effects to aquatic life.

PRECAUTIONARY STATEMENTS

Prevention:

P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

33% of the mixture consists of components of unknown acute oral toxicity.
33% of the mixture consists of components of unknown acute dermal toxicity.

Contains 33% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Talc	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	30 - 45	Substance with a national occupational exposure limit
Castor oil, oligomeric reaction products with maleic anhydride	(CAS-No.) 68308-83-8 (EC-No.) 500-202-3	20 - 35	Substance not classified as hazardous
Dihydro-3-(tetrapropenyl)furan-2,5-dione	(CAS-No.) 26544-38-7 (EC-No.) 247-781-6	20 - 35	Aquatic Chronic 4, H413 Eye Irrit. 2, H319 Skin Sens. 1A, H317
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9	< 3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
The most important symptoms and effects based on the GB CLP classification include:
Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities
No special storage requirements.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Talc	14807-96-6	UK HSE	TWA(as respirable dust):1 mg/m³	

UK HSE : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values
No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.
Indirect vented goggles.

Applicable Norms/Standards
Use eye protection conforming to EN 166

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Buff
Odor	Mild Maleic Anhydride
Odour threshold	*No data available.*
Melting point/freezing point	*No data available.*
Boiling point/boiling range	>= 177.2 ºC
Flammability	Not applicable.
Flammable Limits(LEL)	*No data available.*
Flammable Limits(UEL)	*No data available.*
Flash point	> 176.7 ºC [*Test Method:*Tagliabue closed cup]
Autoignition temperature	*No data available.*
Decomposition temperature	*No data available.*
pH	*substance/mixture is non-soluble (in water)*
Kinematic Viscosity	19,259 mm²/sec
Water solubility	Nil
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	< 186,158.4 Pa [*Details:*@ 131 F]
Density	1.35 g/ml
Relative density	1.35 [*Ref Std:*WATER=1]
Relative Vapour Density	*Not applicable.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

Bulk density	*No data available.*
EU Volatile Organic Compounds	0 g/l [*Details:*Parts A and B as mixed]
Evaporation rate	*No data available.*
Molecular weight	*No data available.*
Percent volatile	*No data available.*
Softening point	*No data available.*

SECTION 10: Stability and reactivity

10.1 Reactivity
This material is considered to be non reactive under normal use conditions

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
None known.

10.5 Incompatible materials
None known.

10.6 Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin contact
Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact
Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion
Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Dihydro-3-(tetrapropenyl)furan-2,5-dione	Dermal	Rabbit	LD50 > 6,200 mg/kg
Dihydro-3-(tetrapropenyl)furan-2,5-dione	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.2 mg/l
Dihydro-3-(tetrapropenyl)furan-2,5-dione	Ingestion	Rat	LD50 2,900 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Dihydro-3-(tetrapropenyl)furan-2,5-dione	Rabbit	Mild irritant
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Dihydro-3-(tetrapropenyl)furan-2,5-dione	Rabbit	Severe irritant
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Dihydro-3-(tetrapropenyl)furan-2,5-dione	similar compounds	Sensitising
2,4,6-tris(dimethylaminomethyl)phenol	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified
Dihydro-3-(tetrapropenyl)furan-2,5-dione	similar compounds	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Dihydro-3-(tetrapropenyl)furan-2,5-dione	In Vitro	Not mutagenic
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Talc	Dermal	Human	Some positive data exist, but the data are not sufficient for classification

Talc	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dihydro-3-(tetrapropenyl)furan-2,5-dione	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2,4,6-tris(dimethylaminomethyl) phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Repeated and prolonged exposure to large amounts of talc dust can cause lung injury	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis | respiratory system	Not classified	Rat	NOAEL 18 mg/m³	113 weeks
Dihydro-3-(tetrapropenyl)furan-2,5-dione	Ingestion	heart | endocrine system | hematopoietic system | liver | immune system | nervous system | kidney and/or bladder	Not classified	Rat	NOAEL 300 mg/kg/day	14 days
2,4,6-tris(dimethylaminomethyl) phenol	Dermal	skin	Not classified	Rat	NOAEL 25 mg/kg/day	4 weeks
2,4,6-tris(dimethylaminomethyl) phenol	Dermal	liver | nervous system | auditory system | hematopoietic system | eyes	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6-tris(dimethylaminomethyl) phenol	Ingestion	heart | endocrine system | hematopoietic system | liver | muscles | nervous system | kidney and/or bladder | respiratory system | vascular system | auditory system | skin | gastrointestinal tract | bone, teeth, nails, and/or hair |	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

		immune system | eyes				

Aspiration Hazard
For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Castor oil, oligomeric reaction products with maleic anhydride	68308-83-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Activated sludge	Experimental	3 hours	EC50	800 mg/l
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Green algae	Experimental	96 hours	ErC50	110 mg/l
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Water flea	Hydrolysis Product	48 hours	EC50	>100 mg/l
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Green algae	Experimental	96 hours	NOEC	33 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Talc	14807-96-6	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Castor oil, oligomeric reaction products with maleic anhydride	68308-83-8	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Experimental Biodegradation	28 days	BOD	9.9 %BOD/ThOD	OECD 301D - Closed bottle test
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Experimental Hydrolysis		Hydrolytic half-life	22 minutes (t 1/2)	OECD 111 Hydrolysis func of pH
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Castor oil, oligomeric reaction products with maleic anhydride	68308-83-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Experimental Bioconcentration		Log Kow	≥4.39	OECD 107 log Kow shke flsk mtd
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Dihydro-3-(tetrapropenyl)furan-2,5-dione	26544-38-7	Experimental Mobility in Soil	Koc	825 l/kg	OECD 106 Adsp-Desb Batch Equil

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for

transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09*	Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27*	Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient	CAS Nbr	Classification	Regulation
Talc	14807-96-6	Grp. 2A: Probable human carc.	International Agency for Research on Cancer

Global inventory status
Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483
Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012, as amended for GB
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H413	May cause long lasting harmful effects to aquatic life.

Revision information:
Section 3: Composition/ Information of ingredients table information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our

knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk
For Northern Ireland documents, please contact your 3M representative to obtain a copy.