



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 11-2708-3
Issue Date: 08/26/25

Version Number: 21.01
Supersedes Date: 01/04/24

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive EC-2214

Product Identification Numbers

62-2214-0540-0, 62-2214-2940-0, 62-2214-6540-4, 62-2214-7540-3, 62-2214-8540-2
7000046355, 7100083322

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Automotive and Aerospace Solutions Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms

**Hazard Statements**

Causes eye irritation.
May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wear protective gloves and eye/face protection.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Epoxy Resin A	25068-38-6	30 - 60 Trade Secret *
Aluminum Pigments	7429-90-5	15 - 40
Amorphous Silica	67762-90-7	1 - 5
Dicyandiamide	461-58-5	1 - 5
Epoxy Resin B	41638-13-5	1 - 5 Trade Secret *
Synthetic Elastomer (NJTS Reg No 04499600-5706P)	Trade Secret*	1 - 5
p-Chlorophenyl-Dimethylurea	150-68-5	< 2.5
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	14228-73-0	< 1 Trade Secret *
Acetone	67-64-1	<= 0.99

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Aldehydes
Chlorine
Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Hydrogen Cyanide
Ammonia
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
p-Chlorophenyl-Dimethylurea	150-68-5	Manufacturer determined	TWA(Inhalable aerosol)(8 hours):1 mg/m3	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcin
Acetone	67-64-1	OSHA	TWA:2400 mg/m3(1000 ppm)	
SILICA, AMORPHOUS	67762-90-7	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Aluminum Pigments	7429-90-5	OSHA	TWA(as Al total dust):15 mg/m3;TWA(as Al, respirable fraction):5 mg/m3	
CAS NO M~AL~F	7429-90-5	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	7429-90-5	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	7429-90-5	ACGIH	TWA(respirable particles):3 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust when product is heated.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Solid

Color

Gray

Specific Physical Form:

Paste

Odor

Faint Epoxy

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

>=260 °C

Flash Point

480 °F [Test Method: Closed Cup]

Evaporation rate

Negligible

Flammability (solid, gas)

Not Classified

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure	No Data Available
Vapor Density	No Data Available
Density	1.44 g/ml [Ref Std: WATER=1]
Specific Gravity	1.44 [Ref Std: WATER=1]
Solubility in Water	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	>= 1,000,000 centipoise [@ 73.4 °F]
Hazardous Air Pollutants	0 % weight [Test Method: Calculated]
Molecular weight	No Data Available
Volatile Organic Compounds	<=65 g/l [Test Method: calculated SCAQMD rule 443.1]
Percent volatile	<=5 % weight
VOC Less H2O & Exempt Solvents	<=65 g/l [Test Method: calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

10.5. Incompatible materials

Strong oxidizing agents

Strong acids

Strong bases

Amines

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Epoxy Resin A	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin A	Ingestion	Rat	LD50 > 1,000 mg/kg
Aluminum Pigments	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Pigments	Ingestion		LD50 estimated to be > 5,000 mg/kg
Aluminum Pigments	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.888 mg/l
Dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Epoxy Resin B	Dermal	Rabbit	LD50 > 2,000 mg/kg
Dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg
Epoxy Resin B	Ingestion	Rat	LD50 > 2,000 mg/kg
Synthetic Elastomer (NJTS Reg No 04499600-5706P)	Dermal	Rabbit	LD50 > 15,000 mg/kg
Synthetic Elastomer (NJTS Reg No 04499600-5706P)	Ingestion	Rat	LD50 > 30,000 mg/kg
p-Chlorophenyl-Dimethylurea	Dermal	Rabbit	LD50 > 2,500 mg/kg
p-Chlorophenyl-Dimethylurea	Ingestion	Rat	LD50 1,480 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Rat	LD50 1,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Epoxy Resin A	Rabbit	Mild irritant
Aluminum Pigments	Rabbit	No significant irritation

Dicyandiamide	Human and animal	Minimal irritation
Epoxy Resin B	Rabbit	No significant irritation
Synthetic Elastomer (NJTS Reg No 04499600-5706P)	Professional judgement	No significant irritation
p-Chlorophenyl-Dimethylurea	similar compounds	Mild irritant
Amorphous Silica	Rabbit	No significant irritation
Acetone	Mouse	Minimal irritation
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro data	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Epoxy Resin A	Rabbit	Moderate irritant
Aluminum Pigments	Rabbit	No significant irritation
Dicyandiamide	Professional judgement	Mild irritant
Epoxy Resin B	Rabbit	Moderate irritant
Synthetic Elastomer (NJTS Reg No 04499600-5706P)	Professional judgement	No significant irritation
p-Chlorophenyl-Dimethylurea	similar compounds	Moderate irritant
Amorphous Silica	Rabbit	No significant irritation
Acetone	Rabbit	Severe irritant
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro data	No significant irritation

Skin Sensitization

Name	Species	Value
Epoxy Resin A	Human and animal	Sensitizing
Aluminum Pigments	Guinea pig	Not classified
Dicyandiamide	Guinea pig	Not classified
Epoxy Resin B	Guinea pig	Sensitizing
Amorphous Silica	Human and animal	Not classified
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	similar compounds	Sensitizing

Respiratory Sensitization

Name	Species	Value
Epoxy Resin A	Human	Not classified
Aluminum Pigments	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

Epoxy Resin A	In vivo	Not mutagenic
Epoxy Resin A	In Vitro	Some positive data exist, but the data are not sufficient for classification
Aluminum Pigments	In Vitro	Not mutagenic
Dicyandiamide	In Vitro	Not mutagenic
Epoxy Resin B	In Vitro	Some positive data exist, but the data are not sufficient for classification
p-Chlorophenyl-Dimethylurea	In Vitro	Some positive data exist, but the data are not sufficient for classification
p-Chlorophenyl-Dimethylurea	In vivo	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	In Vitro	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In Vitro	Mutagenic; structurally related to germ cell mutagens

Carcinogenicity

Name	Route	Species	Value
Epoxy Resin A	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	Ingestion	Rat	Not carcinogenic
p-Chlorophenyl-Dimethylurea	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Acetone	Not Specified	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Epoxy Resin A	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin A	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin A	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin A	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Dicyandiamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematings & during gestation
Dicyandiamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
Dicyandiamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematings & during gestation
p-Chlorophenyl-Dimethylurea	Ingestion	Not classified for development	Mouse	LOAEL 215 mg/kg/day	during gestation
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks

Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
---------	------------	--------------------------------	-----	----------------	----------------------

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Epoxy Resin B	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL not available	
p-Chlorophenyl-Dimethylurea	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar compounds	NOAEL Not available	
p-Chlorophenyl-Dimethylurea	Ingestion	methemoglobinemia	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	not applicable
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Epoxy Resin A	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin A	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin A	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Aluminum Pigments	Inhalation	nervous system respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Dicyandiamide	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks
p-Chlorophenyl-Dimethylurea	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 800 mg/kg/day	103 weeks
p-Chlorophenyl-Dimethylurea	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 65 mg/kg/day	103 weeks
p-Chlorophenyl-Dimethylurea	Ingestion	immune system	Not classified	Rat	LOAEL 520 mg/kg/day	13 weeks
Amorphous Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks

Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Aluminum Pigments	7429-90-5	15 - 40
Aluminum Pigments (Aluminum)	7429-90-5	15 - 40
p-Chlorophenyl-Dimethylurea	150-68-5	< 2.5

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	11-2708-3	Version Number:	21.01
Issue Date:	08/26/25	Supersedes Date:	01/04/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com