Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	42-3931-5	**Version number:**	3.00
Revision date:	29/04/2025	**Supersedes date:**	06/11/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
3M™ Famous Finish 51677, 51678

Product Identification Numbers
UU-0108-8137-1

7100225048

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Automotive.

1.3. Details of the supplier of the safety data sheet

Address:	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone:	+44 (0)1344 858 000
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com/uk

1.4. Emergency telephone number
+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.
The aspiration hazard classification is not required due to the product's viscosity.

CLASSIFICATION:
Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

2.2. Label elements
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD
WARNING.

Symbols
GHS07 (Exclamation mark) |

Pictograms



HAZARD STATEMENTS:

H317	May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P280E	Wear protective gloves.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

1% of the mixture consists of components of unknown acute oral toxicity.

2.3. Other hazards

None known.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Non-Hazardous Ingredients	Mixture	40 - 70	Substance not classified as hazardous
Aluminium oxide	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6	5 - 15	Substance with a national occupational exposure limit
White mineral oil (petroleum)	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8	1 - 10	Asp. Tox. 1, H304

Aluminium Oxide (non-fibrous)	(CAS-No.) 1344-28-1 (EC-No.) 215-691-6	3 - 7	Substance with a national occupational exposure limit
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	(EC-No.) 920-114-2	3 - 7	Asp. Tox. 1, H304 EUH066
Glycerol	(CAS-No.) 56-81-5 (EC-No.) 200-289-5	1 - 5	Substance with a national occupational exposure limit
Alcohols, C16-18 and C18-unsatd.	(CAS-No.) 68002-94-8 (EC-No.) 268-106-1	0.5 - 1.5	Substance not classified as hazardous
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	< 0.05	Acute Tox. 2, H330(LC50 = 0.21 mg/l **ATE values per GB MCL**) Acute Tox. 4, H302(LD50 = 450 mg/kg **ATE values per GB MCL**) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9	(C >= 0.036%) Skin Sens. 1A, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

Skin contact
If exposed, wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:
Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Keep out of reach of children. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities
Store away from heat.

7.3. Specific end use(s)
See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium oxide	1344-28-1	UK HSE	TWA(as respirable dust):4 mg/m3;TWA(as inhalable dust):10 mg/m3	
Aluminium Oxide (non-fibrous)	1344-28-1	UK HSE	TWA(as respirable dust):4 mg/m3;TWA(as inhalable dust):10 mg/m3	
Glycerol	56-81-5	UK HSE	TWA(as mist):10 mg/m3	

UK HSE : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values
No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls
No engineering controls required.

8.2.2. Personal protective equipment (PPE)

Eye/face protection
None required.

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Nitrile rubber.	0.11	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Respiratory protection
None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Liquid.
Colour	White
Odor	Low Odour
Odour threshold	*No data available.*
Melting point/freezing point	*No data available.*
Boiling point/boiling range	*No data available.*
Flammability	Not applicable.
Flammable Limits(LEL)	*No data available.*
Flammable Limits(UEL)	*No data available.*
Flash point	93.9 ºC [*Test Method:*Closed Cup] [*Details:*Estimated]
Autoignition temperature	*No data available.*
Decomposition temperature	*No data available.*
pH	8.2 - 8.6
Kinematic Viscosity	2,703 - 3,604 mm²/sec
Water solubility	*No data available.*
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	*No data available.*
Density	*No data available.*
Relative density	1.11 - 1.13 [@ 20 ºC] [*Ref Std:*WATER=1]
Relative Vapour Density	*No data available.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	*No data available.*
Evaporation rate	*No data available.*

SECTION 10: Stability and reactivity

10.1 Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
Heat.

10.5 Incompatible materials
None known.

10.6 Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
No known health effects.

Skin contact
Contact with the skin during product use is not expected to result in significant irritation.

Eye contact
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion
Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg

Aluminium Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Glycerol	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerol	Ingestion	Rat	LD50 > 5,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-benzisothiazol-3(2H)-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.21 mg/l
1,2-benzisothiazol-3(2H)-one	Ingestion	Rat	LD50 450 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminium oxide	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	No significant irritation
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Rabbit	No significant irritation
Glycerol	Rabbit	No significant irritation
1,2-benzisothiazol-3(2H)-one	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Aluminium oxide	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
Glycerol	Rabbit	No significant irritation
1,2-benzisothiazol-3(2H)-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
White mineral oil (petroleum)	Guinea pig	Not classified
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Guinea pig	Not classified
Glycerol	Guinea pig	Not classified
1,2-benzisothiazol-3(2H)-one	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminium oxide	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Aluminium Oxide (non-fibrous)	In Vitro	Not mutagenic
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic

Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In vivo	Not mutagenic
1,2-benzisothiazol-3(2H)-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminium oxide	Inhalation	Rat	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Aluminium Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Glycerol	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	gestation into lactation
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
Glycerol	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 112 mg/kg/day	2 generation
1,2-benzisothiazol-3(2H)-one	Ingestion	Not classified for development	Rat	NOAEL 112 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
1,2-benzisothiazol-3(2H)-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration

Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver | immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Aluminium Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Glycerol	Inhalation	respiratory system | heart | liver | kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerol	Ingestion	endocrine system | hematopoietic system | liver | kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
1,2-benzisothiazol-3(2H)-one	Ingestion	liver | hematopoietic system | eyes | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 322 mg/kg/day	90 days
1,2-benzisothiazol-3(2H)-one	Ingestion	heart | endocrine system | nervous system	Not classified	Rat	NOAEL 150 mg/kg/day	28 days

Aspiration Hazard

Name	Value
White mineral oil (petroleum)	Aspiration hazard
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l

Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	N/A	Experimental	96 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Fish	Estimated	96 hours	LL50	>1,028 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Green algae	Estimated	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Green algae	Estimated	72 hours	NOEL	1,000 mg/l
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Water flea	Estimated	21 days	NOEL	5 mg/l
Glycerol	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerol	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
Glycerol	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
Alcohols, C16-18 and C18-unsatd.	68002-94-8	Water flea	Experimental	48 hours	EC50	70 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	ErC50	0.11 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Sheepshead Minnow	Experimental	96 hours	LC50	16.7 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	2.9 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Green algae	Experimental	72 hours	NOEC	0.0403 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Activated sludge	Experimental	3 hours	EC50	12.8 mg/l
1,2-benzisothiazol-3(2H)-one	2634-33-5	Bobwhite quail	Experimental	14 days	LD50	617 mg per kg of bodyweight
1,2-benzisothiazol-3(2H)-one	2634-33-5	Cabbage	Experimental	14 days	EC50	200 mg/kg (Dry Weight)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Redworm	Experimental	14 days	LC50	>410.6 mg/kg (Dry Weight)

1,2-benzisothiazol-3(2H)-one	2634-33-5	Soil microbes	Experimental	28 days	EC50	>811.5 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium oxide	1344-28-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Aluminium Oxide (non-fibrous)	1344-28-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Estimated Biodegradation	28 days	BOD	82 %BOD/ThOD	OECD 301F - Manometric respirometry
Glycerol	56-81-5	Experimental Biodegradation	14 days	BOD	63 %BOD/ThOD	OECD 301C - MITI test (I)
Alcohols, C16-18 and C18-unsatd.	68002-94-8	Experimental Biodegradation	28 days	BOD	87 %BOD/ThOD	OECD 301D - Closed bottle test
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Aquatic Inherent Biodegrad.	34 days	Dissolv. Organic Carbon Deplet	17 %removal of DOC	OECD 302A - Modified SCAS Test
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	21 days	Dissolv. Organic Carbon Deplet	80 %removal of DOC	OECD 303A - Simulated Aerobic
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation		Half-life (t 1/2)	4 hours (t 1/2)	
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Hydrolysis		Hydrolytic half-life	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	920-114-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol	56-81-5	Experimental Bioconcentration		Log Kow	-1.75	similar to OECD 107
Alcohols, C16-18 and C18-unsatd.	68002-94-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental BCF - Fish	56 days	Bioaccumulation factor	6.62	similar to OECD 305
1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Glycerol	56-81-5	Modeled Mobility in Soil	Koc	<1 l/kg	Episuite™

1,2-benzisothiazol-3(2H)-one	2634-33-5	Experimental Mobility in Soil	Koc	9.33 l/kg	OECD 121 Estim. of Koc by HPLC

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)
080112 Waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and	No data available.	No data available.	No data available.

IBC Code			
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status
Contact 3M for more information.

COMAH Regulation, SI 2015/483
Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
1,2-benzisothiazol-3(2H)-one	2634-33-5	50	200

Regulation (EU) No 649/2012, as amended for GB
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Revision information:
GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was added.
GB Section 04: Information on toxicological effects information was modified.
Section 1: E-mail address information was modified.
Section 02: CLP Physical and Health Hazard Statements information was added.
Contains statement for sensitizers information was deleted.
Section 02: GB Classification Statements information was deleted.
Section 2: H phrase reference information was added.
Label: CLP Classification information was added.
Label: CLP Precautionary - Prevention information was added.
Label: CLP Precautionary - Response information was added.
Label: CLP Supplemental Hazard Statements information was deleted.
Section 02: Label Elements: GB Percent Unknown information was added.
Label: Graphic information was added.
Label: Signal Word information was added.
List of sensitizers information was deleted.
Section 3: Composition/ Information of ingredients table information was modified.
Section 03: SCL table information was modified.
Section 6: Accidental release personal information information was modified.
Section 8: glove data value information was added.
Section 8: Personal Protection - Skin/body information information was added.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 8: Skin protection - protective clothing information information was added.
Section 8: Skin protection - recommended gloves text information was added.
Section 11: Acute Toxicity table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Mobility in soil information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12:Bioccumulative potential information information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk
For Northern Ireland documents, please contact your 3M representative to obtain a copy.