



## Safety Data Sheet

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	10-0286-4	<b>Version number:</b>	11.00
<b>Issue Date:</b>	07/01/2025	<b>Supersedes date:</b>	28/11/2022

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Edge Sealer 3950

#### Product Identification Numbers

75-34-1519-8 (Legacy ID)

7010303382 (SAP ID)

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Edge Sealer for Screen Printing Inks and Graphic Films, Sealant.

For Industrial or Professional use only.

#### 1.3. Supplier's details

<b>Address:</b>	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
<b>Telephone:</b>	136 136
<b>E Mail:</b>	productinfo.au@mmm.com
<b>Website:</b>	www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Flammable liquid: Category 3.

Serious Eye Damage/Irritation: Category 2.

Carcinogenicity: Category 2.

Reproductive Toxicity: Category 1.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3

## 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

### Signal word

Danger

### Symbols

Flame | Exclamation mark | Health Hazard |

### Pictograms



### Hazard statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs: sensory organs.
H372	Causes damage to organs through prolonged or repeated exposure: nervous system.
H373	May cause damage to organs through prolonged or repeated exposure: sensory organs.

### Precautionary statements

#### Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280F	Wear respiratory protection.

#### Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
--------------------	--

P304 + P340

P305 + P351 + P338

P308 + P313

P312

P337 + P313

P370 + P378

with water or shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTRE or doctor/physician if you feel unwell.

IF eye irritation persists: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

P403 + P233

P403 + P235

P405

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:**

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

Aspiration classification does not apply due to the viscosity of the product.

**2.4. Other hazards which do not result in classification**

May be harmful if swallowed.

May be harmful in contact with skin.

Causes mild skin irritation.

May be harmful if inhaled.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>% by Weight</b>
Xylene	1330-20-7	40 - 50
Modified acrylic resin	Trade Secret	40 - 50
Ethylbenzene	100-41-4	7 - 13
Toluene	108-88-3	< 1

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

#### **4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## **SECTION 5: Fire-fighting measures**

### **5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### **5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

### **5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**Hazchem Code:** •3Y

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### **6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin., Ototoxicant
Ethylbenzene	100-41-4	Australia OELs	TWA(8 hours):434 mg/m <sup>3</sup> (100 ppm);STEL(15 minutes):543 mg/m <sup>3</sup> (125 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcinogen, Ototoxicant
Toluene	108-88-3	Australia OELs	TWA(8 hours):191 mg/m <sup>3</sup> (50 ppm);STEL(15 minutes):574 mg/m <sup>3</sup> (150 ppm)	SKIN
Xylene	1330-20-7	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
Xylene	1330-20-7	Australia OELs	TWA(8 hours):350 mg/m <sup>3</sup> (80 ppm);STEL(15 minutes):655 mg/m <sup>3</sup> (150 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

## 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polymer laminate

Select and use gloves according to AS/NZ 2161.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Colour</b>	Colourless
<b>Odour</b>	Slight Solvent
<b>Odour threshold</b>	No data available.
<b>pH</b>	Not applicable.
<b>Melting point/Freezing point</b>	Not applicable.
<b>Boiling point/Initial boiling point/Boiling range</b>	>=136.1 °C
<b>Flash point</b>	25 °C [Test Method: Tagliabue closed cup]
<b>Evaporation rate</b>	<=1 [Ref Std: BUOAC=1]
<b>Flammability</b>	Flammable liquid: Category 3.
<b>Flammable Limits(LEL)</b>	1 %
<b>Flammable Limits(UEL)</b>	7 %
<b>Vapour pressure</b>	<=946.6 Pa [@ 20 °C]
<b>Relative Vapour Density</b>	>=1 [Ref Std: AIR=1]
<b>Density</b>	0.97 g/ml
<b>Relative density</b>	0.97 [Test Method: Tested per ASTM protocol] [Ref

	<i>Std: WATER=1]</i>
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	$\geq 432.2$ °C
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Kinematic Viscosity</b>	412 mm <sup>2</sup> /sec
<b>Volatile organic compounds (VOC)</b>	$\leq 525$ g/l
<b>Percent volatile</b>	50 - 60 % weight
<b>VOC less H<sub>2</sub>O &amp; exempt solvents</b>	$\leq 525$ g/l
<b>Molecular weight</b>	<i>No data available.</i>

<b>Particle Characteristics</b>	<i>Not applicable.</i>
---------------------------------	------------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

Heat.

Sparks and/or flames.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.5 Incompatible materials

Strong oxidising agents.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

May be harmful in contact with skin.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye contact**

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Prolonged or repeated exposure may cause target organ effects:**

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-Vapour (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapour (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**



Name	Species	Value
Xylene	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Mild irritant
Toluene	Rabbit	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Xylene	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Moderate irritant
Toluene	Rabbit	Moderate irritant

**Skin Sensitisation**

Name	Species	Value
Ethylbenzene	Human	Not classified
Toluene	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic.
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis

Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	prematuring & during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

### Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004	3 hours

					mg/l	
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs through prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine	Not classified	Mouse	NOAEL 3.3	103 weeks

		system			mg/l	
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart   immune system   respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

**Aspiration Hazard**

Name	Value
Xylene	Aspiration hazard
Ethylbenzene	Aspiration hazard
Toluene	Aspiration hazard

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not Determined

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Xylene	1330-20-7	Activated sludge	Estimated	3 hours	NOEC	157 mg/l
Xylene	1330-20-7	Green algae	Estimated	72 hours	EC50	4.36 mg/l
Xylene	1330-20-7	Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Xylene	1330-20-7	Water flea	Estimated	48 hours	EC50	3.82 mg/l
Xylene	1330-20-7	Green algae	Estimated	72 hours	NOEC	0.44 mg/l
Xylene	1330-20-7	Rainbow trout	Estimated	56 days	NOEC	>1.3 mg/l
Xylene	1330-20-7	Water flea	Estimated	7 days	NOEC	0.96 mg/l
Ethylbenzene	100-41-4	Green algae	Estimated	73 hours	EC50	4.36 mg/l
Ethylbenzene	100-41-4	Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Ethylbenzene	100-41-4	Water flea	Estimated	48 hours	EC50	3.82 mg/l
Ethylbenzene	100-41-4	Activated sludge	Experimental	49 hours	EC50	130 mg/l
Ethylbenzene	100-41-4	Green algae	Estimated	73 hours	NOEC	0.44 mg/l
Ethylbenzene	100-41-4	Rainbow trout	Estimated	56 days	NOEC	>1.3 mg/l
Ethylbenzene	100-41-4	Water flea	Estimated	7 days	NOEC	0.96 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Xylene	1330-20-7	Experimental Biodegradation	28 days	BOD	90-98 %BOD/ThOD	OECD 301F - Manometric respirometry

Xylene	1330-20-7	Experimental Photolysis		Photolytic half-life (in air)	1.4 days (t 1/2)	
Ethylbenzene	100-41-4	Experimental Biodegradation	28 days	BOD	90-98 %BOD/ThOD	OECD 301F - Manometric respirometry
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

### 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Xylene	1330-20-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	25.9	
Ethylbenzene	100-41-4	Experimental BCF - Fish	56 days	Bioaccumulation factor	25.9	
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility.

## SECTION 14: Transport Information

### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN1866

Proper shipping name: RESIN SOLUTION

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Limited quantity may apply

Hazchem Code: •3Y

IERG: 14

### International Air Transport Association (IATA) - Air Transport

UN No.: UN1866

Proper shipping name: RESIN SOLUTION

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: III

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1866

Proper shipping name: RESIN SOLUTION

**Class/Division:** 3

**Sub Risk:** Not applicable.

**Packing Group:** III

**Marine Pollutant:** Not applicable.

**Special Instructions:** Limited quantity may apply

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Australian Inventory Status:**

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## SECTION 16: Other information

**Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**