Safety Data Sheet

Copyright,2026, Meguiar's Inc.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	46-4408-4	**Version Number:**	1.00
Issue Date:	04/20/26	**Supersedes Date:**	Initial Issue

Product identifier
Meguiar's® Hot Shine Quarter Pallet G55261

Recommended use
Automotive

Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	213 Technology Dr, Irvine, CA 92618
Telephone:	1-800-347-5700

Emergency telephone number
CHEMTREC 1-800-424-9300 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

28-5727-4, 41-3255-1, 37-6016-2

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's Inc. makes no representations as to its

completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com

Safety Data Sheet

Copyright,2025, Meguiar's Inc.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	41-3255-1	**Version Number:**	4.00
Issue Date:	10/07/25	**Supersedes Date:**	03/05/24

SECTION 1: Identification

1.1. Product identifier
Hot Shine Tire Foam G139 [G13919]

1.2. Recommended use and restrictions on use

Recommended use
Automotive, Clean Shine and Protect Tires

1.3. Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	213 Technology Dr, Irvine, CA 92618
Telephone:	1-800-347-5700

1.4. Emergency telephone number
CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification
Aerosol Category 1
Reproductive Toxicity: Category 2.
Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Flame |Health Hazard |

Pictograms



Hazard Statements
Extremely flammable aerosol.
Pressurized container: may burst if heated.

Suspected of damaging fertility or the unborn child.
Causes damage to organs: cardiovascular system.

Precautionary statements
General:
Keep out of reach of children.

Prevention:
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not breathe vapor or spray.
Wash exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves.

Response:
IF exposed or concerned: Call a POISON CENTER or doctor.

Storage:
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

Notes to Physician:
Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
BUTANE	106-97-8	3 - 7 Trade Secret *
ETHOXYLATED C9-11 ALCOHOLS	68439-46-3	1 - < 5 Trade Secret *
PROPANE	74-98-6	1 - 5 Trade Secret *
MORPHOLINE	110-91-8	0.1 - < 0.5 Trade Secret *
SODIUM NITRITE	7632-00-0	< 0.5

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. Get medical attention.

Skin Contact:
Wash with soap and water. If you feel unwell, get medical attention.

Eye Contact:
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required
Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Special protective actions for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Natural gas	106-97-8	ACGIH	Limit value not established:	simple asphyxiant
MORPHOLINE	110-91-8	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Danger of cutaneous absorption
MORPHOLINE	110-91-8	OSHA	TWA:70 mg/m3(20 ppm)	SKIN
PROPANE	74-98-6	ACGIH	Limit value not established:	simple asphyxiant
PROPANE	74-98-6	OSHA	TWA:1800 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Butyl Rubber, Polymer laminate

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Color	White
Odor	Weak Orange
Odor threshold	*No Data Available*
pH	9 - 10
Melting point/Freezing point	*No Data Available*
Boiling point/Initial boiling point/Boiling range	*No Data Available*
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	*No Data Available*
Flammability	Flammable Aerosol: Category 1.
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*
Relative Vapor Density	*No Data Available*
Density	1 g/ml
Relative Density	1 [*Ref Std:*WATER=1]
Water solubility	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	15 mm2/sec

Volatile Organic Compounds	9.7 % weight
Percent volatile	*No Data Available*
VOC Less H2O & Exempt Solvents	348.7 g/l
Molecular weight	*Not Applicable*

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat
Sparks and/or flames

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	**Condition**
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
May cause additional health effects (see below).

Skin Contact:
Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:
May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:
Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Nitrate or nitrite (ingested) under conditions that result in endogenous nitrosation	7632-00-0	Grp. 2A: Probable human carc.	International Agency for Research on Cancer

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
BUTANE	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
PROPANE	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
ETHOXYLATED C9-11 ALCOHOLS	Dermal	similar compounds	LD50 > 2,000 mg/kg
ETHOXYLATED C9-11 ALCOHOLS	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 1.6 mg/l
ETHOXYLATED C9-11 ALCOHOLS	Ingestion	similar compounds	LD50 3,488 mg/kg
SODIUM NITRITE	Ingestion	Rat	LD50 180 mg/kg
MORPHOLINE	Dermal	Rabbit	LD50 500 mg/kg
MORPHOLINE	Inhalation-Vapor	Rat	LC50 estimated to be 10 - 20 mg/l
MORPHOLINE	Ingestion	Rat	LD50 1,680 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
BUTANE	Professional judgement	No significant irritation
PROPANE	Rabbit	Minimal irritation
ETHOXYLATED C9-11 ALCOHOLS	similar compounds	Minimal irritation
SODIUM NITRITE	Rabbit	No significant irritation
MORPHOLINE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	In vitro data	No significant irritation
BUTANE	Rabbit	No significant irritation
PROPANE	Rabbit	Mild irritant
ETHOXYLATED C9-11 ALCOHOLS	Professional judgement	Moderate irritant
SODIUM NITRITE	Rabbit	Severe irritant
MORPHOLINE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
ETHOXYLATED C9-11 ALCOHOLS	Guinea pig	Not classified
MORPHOLINE	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
BUTANE	In Vitro	Not mutagenic
PROPANE	In Vitro	Not mutagenic
ETHOXYLATED C9-11 ALCOHOLS	In Vitro	Not mutagenic
SODIUM NITRITE	In Vitro	Some positive data exist, but the data are not sufficient for classification
SODIUM NITRITE	In vivo	Some positive data exist, but the data are not sufficient for classification
MORPHOLINE	In Vitro	Some positive data exist, but the data are not sufficient for classification
MORPHOLINE	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
SODIUM NITRITE	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
MORPHOLINE	Ingestion	Multiple animal species	Not carcinogenic
MORPHOLINE	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
ETHOXYLATED C9-11 ALCOHOLS	Dermal	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	2 generation
ETHOXYLATED C9-11 ALCOHOLS	Dermal	Not classified for development	Rat	NOAEL 250 mg/kg/day	2 generation
ETHOXYLATED C9-11 ALCOHOLS	Dermal	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	2 generation
SODIUM NITRITE	Ingestion	Not classified for female reproduction	Mouse	NOAEL 425	2 generation

				mg/kg/day	
SODIUM NITRITE	Ingestion	Not classified for male reproduction	Mouse	NOAEL 425 mg/kg/day	2 generation
SODIUM NITRITE	Ingestion	Not classified for development	Rat	NOAEL 50 mg/kg/day	gestation into lactation
MORPHOLINE	Ingestion	Not classified for development		NA	
MORPHOLINE	Ingestion	Toxic to male reproduction	similar compounds	NOAEL 60 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BUTANE	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
BUTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
BUTANE	Inhalation	heart	Not classified	Dog	NOAEL 5,000 ppm	25 minutes
BUTANE	Inhalation	respiratory irritation	Not classified	Rabbit	NOAEL Not available	
PROPANE	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
PROPANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
PROPANE	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
ETHOXYLATED C9-11 ALCOHOLS	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
SODIUM NITRITE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
SODIUM NITRITE	Ingestion	methemoglobinemia	Causes damage to organs	Human	NOAEL Not available	
MORPHOLINE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BUTANE	Inhalation	kidney and/or bladder | blood	Not classified	Rat	NOAEL 4,489 ppm	90 days
ETHOXYLATED C9-11 ALCOHOLS	Dermal	kidney and/or bladder | heart | hematopoietic system | liver | nervous system | respiratory system	Not classified	Rat	NOAEL 125 mg/kg/day	13 weeks
SODIUM NITRITE	Ingestion	skin | gastrointestinal tract | hematopoietic system | eyes | kidney and/or bladder | heart | endocrine system | bone, teeth, nails, and/or hair | liver | immune system | muscles | nervous system | respiratory system	Not classified	Rat	NOAEL 310 mg/kg/day	14 weeks

MORPHOLINE	Dermal	liver | kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	LOAEL 900 mg/kg/day	13 days
MORPHOLINE	Dermal	hematopoietic system	Not classified	Guinea pig	NOAEL 900 mg/kg/day	13 days
MORPHOLINE	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
MORPHOLINE	Inhalation	pulmonary fibrosis	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.09 mg/l	13 weeks
MORPHOLINE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 64 mg/l	5 days
MORPHOLINE	Inhalation	liver	Not classified	Rat	LOAEL 64 mg/l	5 days
MORPHOLINE	Inhalation	heart | endocrine system	Not classified	Rat	NOAEL 0.9 mg/l	13 weeks
MORPHOLINE	Inhalation	gastrointestinal tract | nervous system	Not classified	Rat	NOAEL 0.53 mg/l	104 weeks
MORPHOLINE	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 160 mg/kg/day	30 days
MORPHOLINE	Ingestion	liver | respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 160 mg/kg/day	30 days
MORPHOLINE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 800 mg/kg/day	30 days
MORPHOLINE	Ingestion	endocrine system	Not classified	Rat	NOAEL 323 mg/kg/day	4 weeks

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Flammable (gases, aerosols, liquids, or solids)

Health Hazards
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	C.A.S. No	Regulation	Status
SODIUM NITRITE	7632-00-0	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable

This material contains a chemical regulated by an EPA Significant New Use Rule (TSCA Section 5)

Ingredient (Category if applicable)	C.A.S. No	Reference
SODIUM NITRITE	7632-00-0	40CFR721.4740

15.2. State Regulations

Contact manufacturer for more information

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	41-3255-1	**Version Number:**	4.00
Issue Date:	10/07/25	**Supersedes Date:**	03/05/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com

Safety Data Sheet

Copyright,2025, Meguiar's Inc.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	37-6016-2	**Version Number:**	2.15
Issue Date:	04/17/25	**Supercedes Date:**	08/26/24

SECTION 1: Identification

1.1. Product identifier
Hot Shine Tire Spray (High Gloss) G120 [G12024 G12064]

1.2. Recommended use and restrictions on use

Recommended use
Automotive, Protective Tire Coating

1.3. Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	213 Technology Dr, Irvine, CA 92618
Telephone:	1-800-347-5700

1.4. Emergency telephone number
CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification
Aspiration Hazard: Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Health Hazard |

Pictograms



Hazard Statements
May be fatal if swallowed and enters airways.

Precautionary Statements
General:
Keep out of reach of children.

Response:
Do NOT induce vomiting.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Storage:
Store locked up.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	80 - 100 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

If Swallowed:
Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish. Water spray or fog may be used. Do not use straight streams.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Do not use in a confined area with minimal air exchange. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used:Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	Clear Colorless
Odor	Very Slight Naphtha
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*Not Applicable*
Boiling Point	450 ºF
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	*No Data Available*

Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*
Vapor Density	*No Data Available*
Density	0.83 g/l
Specific Gravity	0.83 [*Ref Std:*WATER=1]
Solubility In Water	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Viscosity	50 centipoise
Hazardous Air Pollutants	0 lb HAPS/lb solids
Molecular weight	*No Data Available*
Volatile Organic Compounds	0.00 % weight [*Test Method:*calculated per CARB title 2]
Percent volatile	79 % weight [*Test Method:*Estimated]
VOC Less H2O & Exempt Solvents	5.61 lb/gal [*Test Method:*calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity
This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
Strong acids
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:
Sprayed material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 15,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	similar compounds	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	No significant irritation

Skin Sensitization

Name	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	Not classified

Respiratory Sensitization
For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value

HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic

Carcinogenicity
For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects
For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	hematopoietic system | eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks

Aspiration Hazard

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations
Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable

Health Hazards
Aspiration Hazard

15.2. State Regulations
Contact manufacturer for more information

15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations
Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	37-6016-2	**Version Number:**	2.15
Issue Date:	04/17/25	**Supercedes Date:**	08/26/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com

Safety Data Sheet

Copyright,2026, Meguiar's Inc.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	28-5727-4	**Version Number:**	7.00
Issue Date:	09/09/26	**Supersedes Date:**	05/29/25

SECTION 1: Identification

1.1. Product identifier
Hot Shine Tire Coating (High Gloss) G138 [G13815]

1.2. Recommended use and restrictions on use

Recommended use
Automotive, Tire coating/maintenance product

1.3. Supplier's details

MANUFACTURER:	Meguiar's, Inc.
DIVISION:	Meguiar's
ADDRESS:	213 Technology Dr, Irvine, CA 92618
Telephone:	1-800-347-5700

1.4. Emergency telephone number
CHEMTREC 1-800-424-9300 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification
Aerosol Category 2
Serious Eye Damage/Irritation: Category 2A.
Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements
Signal word
Warning

Symbols
Flame |Exclamation mark |

Pictograms



Hazard Statements
Flammable aerosol.
Pressurized container: may burst if heated.

Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause respiratory irritation.

Precautionary statements
General:
Keep out of reach of children.

Prevention:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing vapor or spray.
Wash exposed skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear eye protection.

Response:
IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice.

Storage:
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
METHYL ACETATE	79-20-9	15 - 40 Trade Secret *
ACETONE	67-64-1	10 - 20 Trade Secret *
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	7 - 13 Trade Secret *
HEPTANE, BRANCHED, CYCLIC AND LINEAR	426260-76-6	5 - < 10 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons	During Combustion
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

5.3. Special protective actions for fire-fighters
Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and

could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Heptane, straight and branched isomers	426260-76-6	ACGIH	TWA:200 ppm;STEL:400 ppm	Ototoxicant
Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction	64742-47-8	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
ACETONE	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcin

ACETONE	67-64-1	OSHA	TWA:2400 mg/m3(1000 ppm)	
METHYL ACETATE	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
METHYL ACETATE	79-20-9	OSHA	TWA:610 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates
Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Color	Clear Colorless
Odor	Weak Grape
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*Not Applicable*
Boiling Point	*Not Applicable*

Flash Point	20 ºF [*Test Method:*Pensky-Martens Closed Cup] [*Details:*D93-90]
Evaporation rate	*No Data Available*
Flammability	Flammable Aerosol: Category 2.
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*
Relative Vapor Density	*No Data Available*
Density	0.865 g/l
Relative Density	0.86 - 0.866 [*Ref Std:*WATER=1]
Solubility in Water	Nil
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	2.3 mm2/sec [@ 100 ºF]
Molecular weight	*No Data Available*
Volatile Organic Compounds	9.8 % weight [*Test Method:*calculated per CARB]
Volatile Organic Compounds	172.4 g/l [*Test Method:*calculated SCAQMD rule 443.1]
VOC Less H2O & Exempt Solvents	398.2 g/l

Particle Characteristics *Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat
Sparks and/or flames

10.5. Incompatible materials
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:
Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:
Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
METHYL ACETATE	Dermal	Rat	LD50 > 2,000 mg/kg
METHYL ACETATE	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
METHYL ACETATE	Ingestion	Rat	LD50 > 5,000 mg/kg
ACETONE	Dermal	Rabbit	LD50 > 15,688 mg/kg
ACETONE	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
ACETONE	Ingestion	Rat	LD50 5,800 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 15,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	similar compounds	LD50 > 5,000 mg/kg
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Dermal	Rabbit	LD50 > 2,920 mg/kg
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Inhalation-Vapor (4 hours)	Rat	LC50 > 23.3 mg/l
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Ingestion	Rat	LD50 > 5,840 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
METHYL ACETATE	Rabbit	No significant irritation
ACETONE	Mouse	Minimal irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	Mild irritant
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
METHYL ACETATE	Rabbit	Moderate irritant
ACETONE	Rabbit	Severe irritant
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	No significant irritation
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
METHYL ACETATE	Human	Not classified
HYDROTREATED LIGHT PETROLEUM DISTILLATES	similar compounds	Not classified
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
METHYL ACETATE	In Vitro	Not mutagenic
METHYL ACETATE	In vivo	Not mutagenic
ACETONE	In vivo	Not mutagenic
ACETONE	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
HEPTANE, BRANCHED, CYCLIC AND LINEAR	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
ACETONE	Not Specified	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
ACETONE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
ACETONE	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	2 generation

HEPTANE, BRANCHED, CYCLIC AND LINEAR	Not Specified	Not classified for development	Rat	NOAEL Not available	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
METHYL ACETATE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
METHYL ACETATE	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
METHYL ACETATE	Inhalation	blindness	Not classified		NOAEL Not available	
METHYL ACETATE	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
ACETONE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ACETONE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ACETONE	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
ACETONE	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
ACETONE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
METHYL ACETATE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
METHYL ACETATE	Inhalation	endocrine system	Not classified	Rat	NOAEL 6.1 mg/l	28 days
METHYL ACETATE	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6.1 mg/l	28 days
METHYL ACETATE	Inhalation	liver	Not classified	Rat	NOAEL 6.1 mg/l	28 days
METHYL ACETATE	Inhalation	immune system	Not classified	Rat	NOAEL 6.1 mg/l	28 days
METHYL ACETATE	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
ACETONE	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
ACETONE	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
ACETONE	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
ACETONE	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
ACETONE	Inhalation	heart	Not classified	Rat	NOAEL 45 mg/l	8 weeks
ACETONE	Inhalation	liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
ACETONE	Ingestion	kidney and/or	Not classified	Rat	NOAEL 900	13 weeks

		bladder			mg/kg/day	
ACETONE	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
ACETONE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
ACETONE	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
ACETONE	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
ACETONE	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
ACETONE	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
ACETONE	Ingestion	skin	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
ACETONE	Ingestion	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks

Aspiration Hazard

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
HEPTANE, BRANCHED, CYCLIC AND LINEAR	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations
Contact manufacturer for more information

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Flammable (gases, aerosols, liquids, or solids)

Health Hazards
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations
Contact manufacturer for more information

15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact manufacturer for more information

15.4. International Regulations
Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	28-5727-4	**Version Number:**	7.00
Issue Date:	09/09/26	**Supersedes Date:**	05/29/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's Inc.

Meguiar's, Inc. USA SDSs are available at www.Meguiars.com