



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	41-2317-0	Version Number:	2.00
Issue Date:	04/15/2025	Supersedes Date:	10/20/2023

This Safety Data Sheet has been prepared in accordance with the DENR Administrative Order No. 2015-09 Rules and Procedures for the Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Preparation of Safety Data Sheet (SDS) and Labelling Requirements of Toxic Chemical Substances.

SECTION 1: Identification

1.1. Product identifier

3M™ Ceramic Coating, 39901

Product Identification Numbers

60-4551-1058-9

1.2. Recommended use and restrictions on use

Recommended use

Automotive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS:	3M Philippines, Inc., 18th Floor, Bonifacio Stopover Corporate Center, 31st Street corner, 2nd Avenue, Bonifacio Global City, Taguig City, 1635 Philippines
Telephone:	+632 827 11680
E Mail:	mcvillalva@mmm.com
Website:	www.3m.com/ph

1.4. Emergency telephone number

+632 827 11680

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 3.

Skin Corrosion/Irritation: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Specific Target Organ Toxicity (single exposure): Category 3.

Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word

Warning

Symbols

Flame | Exclamation mark |

Pictograms**Hazard statements**

H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

P501	Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.
------	---

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Siloxane Polymer	Trade Secret	60 - 90
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	10 - 30
BIS(TRIMETHOXYSILYLPROPYL)AMINE	82985-35-1	< 3
Methyl Alcohol	67-56-1	< 0.2

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Formaldehyde
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Methyl Alcohol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	Danger of cutaneous absorption
Methyl Alcohol	67-56-1	Philippines OELs	TWA(8 hours):260 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Philippines OELs : Philippines. Threshold Limit Values for Airborne Contaminants

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Colorless
Odor	Slight Minty
Odor threshold	No Data Available
pH	No Data Available
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	155.5 °C
Flash Point	47.2 °C [Test Method: Closed Cup]
Evaporation rate	<=1 [Ref Std: BUOAC=1]
Flammability	Flammable Liquid: Category 3.
Flammable Limits(LEL)	0.92 % volume
Flammable Limits(UEL)	16 % volume
Vapor Pressure	<=133 Pa [Ref Std: AIR=1]
Relative Vapor Density	>=1 [Ref Std: AIR=1]
Density	0.97 g/ml [Ref Std: WATER=1]
Relative Density	0.97 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	267 °C
Decomposition temperature	No Data Available
Kinematic Viscosity	206 mm ² /sec
Volatile Organic Compounds	223 g/l [Test Method: Tested per ASTM protocol]
Percent volatile	No Data Available
VOC Less H₂O & Exempt Solvents	223 g/l [Test Method: Tested per ASTM protocol]

Average particle size	<i>No Data Available</i>
Bulk density	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Softening point	<i>No Data Available</i>
Maximum Storage Temperature	72 °F

* The values noted with an asterisk (*) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at a facility, including further changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct characterization testing based on the use factors at the specific facility.

Particle Characteristics	<i>Not Applicable</i>
---------------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Not determined

No Data Available

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. May cause additional health effects (see below).

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Inhalation-Vapor (4 hours)	Rat	LC50 > 11 mg/l
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Ingestion	Rat	LD50 > 2,000 mg/kg
BIS(TRIMETHOXSILYLPROPYL)AMINE	Dermal	Rabbit	LD50 11,865 mg/kg
BIS(TRIMETHOXSILYLPROPYL)AMINE	Ingestion	Rat	LD50 3,780 mg/kg
Methyl Alcohol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methyl Alcohol	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
Methyl Alcohol	Ingestion		LD50 estimated to be 50 - 300 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Rabbit	Irritant
BIS(TRIMETHOXSILYLPROPYL)AMINE	Rabbit	Mild irritant
Methyl Alcohol	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Rabbit	No significant irritation
BIS(TRIMETHOXSILYLPROPYL)AMINE	Rabbit	Corrosive
Methyl Alcohol	Rabbit	Moderate irritant

Sensitization:**Skin Sensitization**

Name	Species	Value
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Guinea pig	Not classified
BIS(TRIMETHOXSILYLPROPYL)AMINE	Guinea pig	Not classified
Methyl Alcohol	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	In Vitro	Not mutagenic
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	In vivo	Not mutagenic
BIS(TRIMETHOXSILYLPROPYL)AMINE	In vivo	Not mutagenic
BIS(TRIMETHOXSILYLPROPYL)AMINE	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Methyl Alcohol	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Methyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
Methyl Alcohol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
Methyl Alcohol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL not available	
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL not available	
Methyl Alcohol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methyl Alcohol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BIS(TRIMETHOXYSIYL LPROPYL)AMINE	Ingestion	endocrine system gastrointestinal tract hematopoietic system heart bone, teeth, nails, and/or hair liver immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methyl Alcohol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
Methyl Alcohol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
Methyl Alcohol	Ingestion	liver nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Siloxane Polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Green algae	Experimental	72 hours	EC50	>1,170 mg/l
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Water flea	Experimental	48 hours	EC50	>864 mg/l
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Green algae	Experimental	72 hours	NOEC	221 mg/l
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Activated sludge	Analogous Compound	3 hours	NOEC	1,000 mg/l
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Cress	Experimental	17 days	NOEC	>=100 mg/kg (Dry Weight)
BIS(TRIMETHOXYDILYLPROPYL)AMINE	82985-35-1	Activated sludge	Experimental	3 hours	EC10	270 mg/l
BIS(TRIMETHOXYDILYLPROPYL)AMINE	82985-35-1	Green algae	Experimental	72 hours	EC50	36 mg/l
BIS(TRIMETHOXYDILYLPROPYL)AMINE	82985-35-1	Medaka	Experimental	96 hours	LC50	>100 mg/l
BIS(TRIMETHOXYDILYLPROPYL)AMINE	82985-35-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
BIS(TRIMETHOXYDILYLPROPYL)AMINE	82985-35-1	Green algae	Experimental	72 hours	NOEC	8.3 mg/l
Methyl Alcohol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	EC50	16.9 mg/l
Methyl Alcohol	67-56-1	Bay mussel	Experimental	96 hours	LC50	15,900 mg/l
Methyl Alcohol	67-56-1	Bluegill	Experimental	96 hours	LC50	15,400 mg/l
Methyl Alcohol	67-56-1	Green algae	Experimental	96 hours	ErC50	22,000 mg/l
Methyl Alcohol	67-56-1	Sediment organism	Experimental	96 hours	LC50	54,890 mg/l
Methyl Alcohol	67-56-1	Water flea	Experimental	48 hours	LC50	3,289 mg/l
Methyl Alcohol	67-56-1	Green algae	Experimental	96 hours	NOEC	9.96 mg/l
Methyl Alcohol	67-56-1	Medaka	Experimental	8.33 days	NOEC	158,000 mg/l
Methyl Alcohol	67-56-1	Water flea	Experimental	21 days	NOEC	122 mg/l
Methyl Alcohol	67-56-1	Activated sludge	Experimental	3 hours	IC50	>1,000 mg/l
Methyl Alcohol	67-56-1	Barley	Experimental	14 days	EC50	15,492 mg/kg (Dry Weight)

Methyl Alcohol	67-56-1	Redworm	Experimental	63 days	EC50	26,646 mg/kg (Dry Weight)
Methyl Alcohol	67-56-1	Springtail	Experimental	28 days	EC50	5,683 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Siloxane Polymer	Trade Secret	Data not available - insufficient	N/A	N/A	N/A	N/A
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Experimental Biodegradation	28 days	Carbon dioxide evolution	47 %CO ₂ evolution/THCO ₂ evolution	OECD 301B - Mod. Sturm or CO ₂
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Transformation product Biodegradation	14 days	Biological Oxygen Demand	92 %BOD/ThOD	OECD 301C - MITI (I)
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Modeled Hydrolysis		Hydrolytic half-life	4.1 hours (t 1/2)	Catalogic™
BIS(TRIMETHOXYSILYLPROPYL)AMINE	82985-35-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	17 %BOD/ThOD	OECD 301D - Closed Bottle Test
Methyl Alcohol	67-56-1	Experimental Biodegradation	3 days	Percent degraded	91 %degraded	
Methyl Alcohol	67-56-1	Experimental Biodegradation	14 days	Biological Oxygen Demand	92 %BOD/ThOD	OECD 301C - MITI (I)
Methyl Alcohol	67-56-1	Experimental Photolysis		Photolytic half-life (in air)	35 days (t 1/2)	
Methyl Alcohol	67-56-1	Experimental Soil Metabolism Aerobic	5 days	Carbon dioxide evolution	53.4 %CO ₂ evolution/THCO ₂ evolution	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Siloxane Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Transformation product Bioconcentration		Log of Octanol/H ₂ O part. coeff	-0.77	
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Modeled Bioconcentration		Log of Octanol/H ₂ O part. coeff	0.7	Episuite™
SILANE, TRIMETHOXY(2-METHYLPROPYL)-	18395-30-7	Transformation product Bioconcentration		Log of Octanol/H ₂ O part. coeff	-1.0	Episuite™
BIS(TRIMETHOXYSILYLPROPYL)AMINE	82985-35-1	Experimental BCF - Fish	28 days	Bioaccumulation Factor	4.2	
Methyl Alcohol	67-56-1	Experimental BCF - Fish	3 days	Bioaccumulation Factor	<4.5	
Methyl Alcohol	67-56-1	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	-0.77	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information**Marine Transport (IMDG)**

UN Number:UN1866

Proper Shipping Name:RESIN SOLUTION

Technical Name:None assigned.

Hazard Class/Division:3

Subsidiary Risk:None assigned.

Packing Group:III

Limited Quantity:Yes

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN1866

Proper Shipping Name:RESIN SOLUTION

Technical Name:None assigned.

Hazard Class/Division:3

Subsidiary Risk:None assigned.

Packing Group:III

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Global inventory status**

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information**Revision information:**

Section 01: Address information was modified.
Section 01: Product identification numbers information was added.
Section 01: Recommended Use information was modified.
Section 02: PH Precautionary - Disposal information was modified.
Section 02: PH Precautionary - Prevention information was modified.
Section 02: PH Precautionary - Response information was modified.
Section 02: PH Precautionary - Storage information was deleted.
Section 03: Material is a mixture standard phrase information was added.
Section 06: Accidental release personal information information was modified.
Section 07: Conditions safe storage information was modified.
Section 09: Flammability (solid, gas) information information was deleted.
Section 09: Flammability information information was added.
Section 09: Kinematic Viscosity information information was added.
Section 09: Particle Characteristics N/A information was added.
Section 09: Vapor Density Value information was modified.
Section 09: Viscosity information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Philippines SDSs are available at www.3m.com/ph