

# Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 34-8339-3
 Version number:
 6.00

 Revision date:
 01/08/2025
 Supersedes date:
 27/06/2025

Transportation version number:

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive EC-3542 B/A FR

#### **Product Identification Numbers**

87-3300-0130-3

7100142520

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

2-part, semi-structural adhesive, Industrial use.

# 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000

**E Mail:** ner-productstewardship@mmm.com

Website: www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

36-6157-6, 36-6156-8

# TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

# KIT LABEL

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### **CLASSIFICATION:**

Substance or Mixture Corrosive to Metals, Category 1 - Met. Corr. 1; H290

Skin Corrosion/Irritation, Category 1C - Skin Corr. 1C; H314

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317 Germ Cell Mutagenicity, Category 2 - Muta. 2; H341 Reproductive Toxicity, Category 1B - Repr. 1B; H360F

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

#### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### SIGNAL WORD

DANGER.

#### **Symbols**

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

#### **Pictograms**









#### **Contains:**

m-Xylene-.alpha.alpha'.-diamine; 1,2-Ethanediamine, phosphate; bis-[4-(2,3-epoxipropoxi)phenyl]propane; Epichlorhydrin - trimethylolpropane copolymer; 3,3'-Oxybis(ethyleneoxy)bis(propylamine)

#### HAZARD STATEMENTS:

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

### **Prevention:**

P201 Obtain special instructions before use.
P260G Do not breathe vapours or dust.

P280J Wear protective gloves, protective clothing, respiratory protection, eye protection, and face

protection.

### **Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

# SUPPLEMENTAL INFORMATION:

# **Supplemental Hazard Statements:**

EUH071 Corrosive to the respiratory tract.

# **Supplemental Precautionary Statements:**

Restricted to professional users.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

# **Revision information:**

No revision information



# Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 36-6156-8
 Version number:
 7.00

 Revision date:
 27/06/2025
 Supersedes date:
 27/06/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M<sup>™</sup> Scotch-Weld<sup>™</sup> Epoxy Adhesive EC-3542 B/A FR Part A

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Part A of a 2-part Epoxy Adhesive, Industrial use.

#### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

# 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

This material has been tested for skin corrosion/irritation and the test results are reflected in the assigned classification.

#### **CLASSIFICATION:**

Substance or Mixture Corrosive to Metals, Category 1 - Met. Corr. 1; H290 Skin Corrosion/ Irritation, Category 1C - Skin Corr. 1C; H314 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### SIGNAL WORD

DANGER.

#### **Symbols**

GHS05 (Corrosion) |GHS07 (Exclamation mark) |

#### **Pictograms**



Ingredient	CAS Nbr	EC No.	% by Wt
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	10 - 30
1,2-Ethanediamine, phosphate	14852-17-6	238-914-9	10 - 30
m-Xylenealpha.alpha'diamine	1477-55-0	216-032-5	5 - 10

#### **HAZARD STATEMENTS:**

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P260G Do not breathe vapours or dust.

P280D Wear protective gloves, protective clothing, and eye/face protection.

**Response:** 

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

# SUPPLEMENTAL INFORMATION:

# **Supplemental Hazard Statements:**

EUH071 Corrosive to the respiratory tract.

15% of the mixture consists of components of unknown acute oral toxicity.

Contains 15% of components with unknown hazards to the aquatic environment.

#### 2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

Not applicable

# 3.2. Mixtures

Ingredient	Identifier(s)	9/0	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	20 - 30	Substance with a national occupational exposure limit
1,2-Ethanediamine, phosphate	(CAS-No.) 14852-17-6 (EC-No.) 238-914-9	10 - 30	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2	10 - 30	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
UNDISCLOSED MATERIAL	Trade Secret	5 - 20	Substance not classified as hazardous
Silane, trimethoxyoctyl-, hydrolysis products with silica	(CAS-No.) 92797-60-9 (EC-No.) 296-597-2	1 - 10	Substance with a national occupational exposure limit
m-Xylenealpha.alpha'diamine	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5	5 - 10	EUH071 Acute Tox. 4, H332 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
Urea, N,N'-bis[3-(dimethylamino)propyl]-	(CAS-No.) 52338-87-1 (EC-No.) 257-861-2	1 - < 3	Eye Dam. 1, H318 Aquatic Chronic 3, H412
Nitric acid, calcium salt, tetrahydrate	(CAS-No.) 13477-34-4 (EC-No.) 233-332-1	1 - < 3	Acute Tox. 4, H302 Eye Dam. 1, H318
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	<= 0.99	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Corrosive to respiratory tract (severe nose and throat pain, chest tightness and pain, wheezing, and breathlessness). Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

### 4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

# **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxideDuring combustion.Carbon dioxide.During combustion.Irritant vapours or gases.During combustion.

#### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

# **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralise spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralising agent until reaction stops. Let cool before collecting. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

# 7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from acids.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

IngredientCAS Nbr<br/>tolueneAgency<br/>108-88-3Limit type<br/>UK HSEAdditional comments<br/>TWA: 191 mg/m³ (50 ppm);Additional comments<br/>SKIN

STEL: 384 mg/m<sup>3</sup> (100 ppm)

DUST, INERT OR NUISANCE 65997-17-3 UK HSE TWA(as respirable dust):4

mg/m3;TWA(as inhalable

dust):10 mg/m3

Oxide glass chemicals 65997-17-3 Manufacturer TWA(as non-fibrous,

determined respirable)(8 hours):3

mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10

mg/m3

Silicon dioxide 92797-60-9 UK HSE TWA(as respirable dust):2.4

mg/m3;TWA(as inhalable

dust):6 mg/m3

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### 8.2. Exposure controls

# 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	<b>Breakthrough Time</b>
Butyl rubber.	0.5	=>8 hours
Neoprene.	0.5	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Neoprene apron.

# Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Specific Physical Form:  Colour  Grey  Odor  Slight Amine  Odour threshold  Melting point/freezing point  Boiling point/boiling range  Flammability  Not applicable.  Flammable Limits(LEL)  Flammable Limits(UEL)  Flash point  Flash point  Flash point  Flash point  Flash point  Autoignition temperature  Decomposition temperature  No data available.	information on basic physical and chemical properties			
Colour Grey Odor Slight Amine Odour threshold No data available. Melting point/freezing point Not applicable. Boiling point/boiling range No data available. Flammability Not applicable. Flammable Limits(LEL) No data available. Flash point Flash point Plash point Plash point Plash point Plash point No data available. Flash point Flash point Plash plash point Plash plash point Plash point Plash point Plash point Plash point Plash	Physical state	Liquid.		
Odor Slight Amine Odour threshold No data available. Melting point/freezing point Not applicable. Boiling point/boiling range No data available. Flammability Not applicable. Flammable Limits(LEL) No data available. Flammable Limits(UEL) No data available. Flash point Flash point Plash point Plash point Plash point No data available. Flooring No data available. Flo	Specific Physical Form:	Thixotropic paste		
Odour threshold       No data available.         Melting point/freezing point       Not applicable.         Boiling point/boiling range       No data available.         Flammability       Not applicable.         Flammable Limits(LEL)       No data available.         Flash point       Flash point > 93 °C (200 °F) [Test Method: Closed Cup]         Autoignition temperature       No data available.         Decomposition temperature       No data available.         OH       substance/mixture is non-soluble (in water)         Kinematic Viscosity       No data available.         Water solubility       Negligible         Solubility- non-water       No data available.         Partition coefficient: n-octanol/water       No data available.         Vapour pressure       No data available.         Density       0.65 [Ref Std: WATER=1]	Colour	Grey		
Melting point/freezing point Boiling point/boiling range No data available. Not applicable. Not applicable. Not applicable. Not applicable. Not applicable.  Flammability No data available. Flammable Limits(LEL) No data available. Flash point Flash point Flash point > 93 °C (200 °F) [Test Method: Closed Cup] Autoignition temperature No data available. Decomposition temperature No data available. Substance/mixture is non-soluble (in water) No data available. Water solubility Negligible Solubility- non-water No data available. Partition coefficient: n-octanol/water No data available. Vapour pressure No data available. Vapour pressure No data available.	Odor	Slight Amine		
No data available.	Odour threshold	No data available.		
Flammable Limits(LEL)  Flammable Limits(UEL)  Flash point  Autoignition temperature  Decomposition temperature  No data available.  Partition coefficient: n-octanol/water  No data available.	Melting point/freezing point	Not applicable.		
Flammable Limits(LEL)  No data available. Flash point  Flash point  Flash point  Flash point  No data available. Flash point  No data available.	Boiling point/boiling range	No data available.		
Flash point Flash point Flash point Flash point Flash point > 93 °C (200 °F) [Test Method:Closed Cup] Autoignition temperature No data available. Decomposition temperature No data available.  Substance/mixture is non-soluble (in water) No data available. Water solubility Negligible Solubility- non-water No data available. Partition coefficient: n-octanol/water No data available. Vapour pressure No data available. Vapour pressure No data available.	Flammability	Not applicable.		
Flash point Flash point Flash point Flash point Flash point > 93 °C (200 °F) [Test Method:Closed Cup] Autoignition temperature No data available. Decomposition temperature No data available.  Substance/mixture is non-soluble (in water) No data available. Water solubility Negligible Solubility- non-water No data available. Partition coefficient: n-octanol/water No data available. Vapour pressure No data available. Vapour pressure No data available.				
Flash point  Autoignition temperature  No data available.  Decomposition temperature  No data available.  No data available.  Substance/mixture is non-soluble (in water)  No data available.  Water solubility  Negligible  Solubility- non-water  No data available.  Partition coefficient: n-octanol/water  No data available.  Vapour pressure  No data available.	Flammable Limits(LEL)	No data available.		
Autoignition temperature  Decomposition temperature  No data available.  No data available.  Substance/mixture is non-soluble (in water)  No data available.  No data available.  No data available.  Negligible  Solubility- non-water  No data available.  Partition coefficient: n-octanol/water  No data available.  Oensity  O.65 g/ml  Relative density  O.65 [Ref Std:WATER=1]	Flammable Limits(UEL)	No data available.		
Decomposition temperature  Decomposition temperature  No data available.  Substance/mixture is non-soluble (in water)  No data available.  Negligible  Solubility- non-water  No data available.  Partition coefficient: n-octanol/water  No data available.  Oensity  O.65 g/ml  Relative density  O.65 [Ref Std:WATER=1]	Flash point	Flash point > 93 °C (200 °F) [Test Method:Closed Cup]		
Substance/mixture is non-soluble (in water)  No data available.  Negligible  Solubility- non-water  Partition coefficient: n-octanol/water  No data available.  Relative density  0.65 g/ml  Relative density  0.65 [Ref Std:WATER=1]	Autoignition temperature	No data available.		
Kinematic Viscosity  No data available.  Water solubility  Negligible  Solubility- non-water  No data available.  Partition coefficient: n-octanol/water  No data available.  Vapour pressure  No data available.  No data available.  Oensity  0.65 g/ml  Relative density  0.65 [Ref Std:WATER=1]	Decomposition temperature	No data available.		
Water solubility Negligible Solubility- non-water No data available. Partition coefficient: n-octanol/water No data available. Vapour pressure No data available. Density 0.65 g/ml Relative density 0.65 [Ref Std:WATER=1]	рН	substance/mixture is non-soluble (in water)		
No data available.     Partition coefficient: n-octanol/water   No data available.     Vapour pressure   No data available.     No data available.     No data available.     No data available.     Oensity   O.65 g/ml     Relative density   O.65 [Ref Std:WATER=1]	Kinematic Viscosity	No data available.		
Partition coefficient: n-octanol/water  No data available.  No data available.  No data available.  Oensity  0.65 g/ml  Relative density  0.65 [Ref Std:WATER=1]	Water solubility	Negligible		
Vapour pressure       No data available.         Density       0.65 g/ml         Relative density       0.65 [Ref Std:WATER=1]	Solubility- non-water	No data available.		
Density 0.65 g/ml Relative density 0.65 [Ref Std:WATER=1]	Partition coefficient: n-octanol/water	No data available.		
Relative density 0.65 [Ref Std:WATER=1]	Vapour pressure	No data available.		
	Density	0.65 g/ml		
Relative Vapour Density No data available.	Relative density	0.65 [Ref Std:WATER=1]		
1 V	Relative Vapour Density	No data available.		
Particle Characteristics Not applicable.	Particle Characteristics	Not applicable.		

#### 9.2. Other information

9.2.2 Other safety characteristics

**EU Volatile Organic Compounds Evaporation rate**  No data available. No data available.

# 3M™ Scotch-Weld™ Epoxy Adhesive EC-3542 B/A FR Part A

Molecular weight No data available.

Percent volatile 3.7 %
Percent volatile Negligible

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5 Incompatible materials

None known.

# 10.6 Hazardous decomposition products

Substance

None known.

**Condition** 

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

# Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

#### **Additional Health Effects:**

# Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness.

# Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### **Additional information:**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
1,2-Ethanediamine, phosphate	Inhalation- Vapour	Professio nal judgeme nt	LC50 estimated to be > 50 mg/l
1,2-Ethanediamine, phosphate	Dermal	Rat	LD50 > 2,000  mg/kg
1,2-Ethanediamine, phosphate	Ingestion	Rat	LD50 > 2,000  mg/kg
m-Xylenealpha.alpha'diamine	Dermal	Rabbit	LD50 > 2,000  mg/kg
m-Xylenealpha.alpha'diamine	Inhalation- Dust/Mist (4 hours)	Rat	LC50 1.2 mg/l
m-Xylenealpha.alpha'diamine	Ingestion	Rat	LD50 980 mg/kg
Silane, trimethoxyoctyl-, hydrolysis products with silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane, trimethoxyoctyl-, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,340 mg/kg
Urea, N,N'-bis[3-(dimethylamino)propyl]-	Dermal	Rat	LD50 > 2,050 mg/kg
Urea, N,N'-bis[3-(dimethylamino)propyl]-	Ingestion	Rat	LD50 5,125 mg/kg
Nitric acid, calcium salt, tetrahydrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Dermal	similar compoun ds	LD50 > 2,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation- Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Nama	L'anguige	l Valua
Name	Species	i value

Overall product	In vitro	Corrosive
	data	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
1,2-Ethanediamine, phosphate	Rabbit	No significant irritation
m-Xylenealpha.alpha'diamine	Rat	Corrosive
Urea, N,N'-bis[3-(dimethylamino)propyl]-	Rabbit	No significant irritation
Nitric acid, calcium salt, tetrahydrate	similar	No significant irritation
	compoun	
	ds	
toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
1,2-Ethanediamine, phosphate	Rabbit	No significant irritation
m-Xylenealpha.alpha'diamine	Rabbit	Corrosive
Urea, N,N'-bis[3-(dimethylamino)propyl]-	Rabbit	Corrosive
Nitric acid, calcium salt, tetrahydrate	Rabbit	Corrosive
toluene	Rabbit	Moderate irritant

# **Skin Sensitisation**

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professio nal judgemen t	Sensitising
1,2-Ethanediamine, phosphate	similar compoun ds	Sensitising
m-Xylenealpha.alpha'diamine	Guinea pig	Sensitising
Urea, N,N'-bis[3-(dimethylamino)propyl]-	Guinea pig	Not classified
Nitric acid, calcium salt, tetrahydrate	similar compoun ds	Not classified
toluene	Guinea pig	Not classified

# **Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,2-Ethanediamine, phosphate	In Vitro	Not mutagenic
1,2-Ethanediamine, phosphate	In vivo	Not mutagenic
m-Xylenealpha.alpha'diamine	In Vitro	Not mutagenic
m-Xylenealpha.alpha'diamine	In vivo	Not mutagenic

# 3M™ Scotch-Weld™ Epoxy Adhesive EC-3542 B/A FR Part A

Urea, N,N'-bis[3-(dimethylamino)propyl]-	In Vitro	Not mutagenic
Urea, N,N'-bis[3-(dimethylamino)propyl]-	In vivo	Not mutagenic
Nitric acid, calcium salt, tetrahydrate	In Vitro	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Oxide glass chemicals	Inhalation	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	
toluene	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not
			sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not
			sufficient for classification

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	premating into lactation
1,2-Ethanediamine, phosphate	Ingestion	Not classified for female reproduction	Rat	NOAEL 150 mg/kg/day	premating into lactation
1,2-Ethanediamine, phosphate	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	33 days
1,2-Ethanediamine, phosphate	Ingestion	Not classified for development	Rat	NOAEL 150 mg/kg/day	premating into lactation
m-Xylenealpha.alpha'diamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 450 mg/kg/day	premating into lactation
m-Xylenealpha.alpha'diamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 450 mg/kg/day	48 days
m-Xylenealpha.alpha'diamine	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	premating into lactation
Urea, N,N'-bis[3-(dimethylamino)propyl]-	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	during gestation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for female reproduction	similar compoun ds	NOAEL 1,500 mg/kg/day	premating into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for male reproduction	similar compoun ds	NOAEL 1,500 mg/kg/day	28 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for development	similar compoun ds	NOAEL 1,500 mg/kg/day	premating into lactation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

realite Route Farget Organ(s) Value Species Test result Exposure	Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
--	------	-------	-----------------	-------	---------	-------------	----------

Page: 11 of 20

						Duration
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
m-Xylenealpha.alpha' diamine	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not avaliable	
Urea, N,N'-bis[3- (dimethylamino)propyl]-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available.	
Nitric acid, calcium salt, tetrahydrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Ingestion	methemoglobinemi a	Causes damage to organs	Human	NOAEL Not available	environmental exposure
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Ingestion	gastrointestinal tract   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
1,2-Ethanediamine, phosphate	Ingestion	heart   endocrine system   hematopoietic system   liver   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	28 days
m-Xylenealpha.alpha' diamine	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.005 mg/l	13 weeks
m-Xylenealpha.alpha' diamine	Inhalation	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   vascular system	Not classified	Rat	NOAEL 0.03 mg/l	13 weeks
m-Xylenealpha.alpha' diamine	Ingestion	endocrine system   hematopoietic system	Not classified	Rat	NOAEL 600 mg/kg/day	28 days

m-Xylenealpha.alpha' diamine	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	28 days
m-Xylenealpha.alpha' diamine	Ingestion	heart   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	28 days
Urea, N,N'-bis[3- (dimethylamino)propyl]-	Ingestion	blood   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	28 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	similar compoun ds	NOAEL 1,500 mg/kg/day	28 days
toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

# **Aspiration Hazard**

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

# 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
1,2-Ethanediamine, phosphate	14852-17-6	Green algae	Experimental	72 hours	ErC50	>400 mg/l
1,2-Ethanediamine, phosphate	14852-17-6	Water flea	Experimental	48 hours	EC50	12.5 mg/l
1,2-Ethanediamine, phosphate	14852-17-6	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
1,2-Ethanediamine, phosphate	14852-17-6	Water flea	Experimental	21 days	EC10	0.25 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Activated sludge	Experimental	30 minutes	EC50	>1,000 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Bacteria	Experimental	16 hours	EC10	24 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Green algae	Experimental	72 hours	ErC50	28 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Medaka	Experimental	96 hours	LC50	87.6 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Water flea	Experimental	48 hours	EC50	15.2 mg/l
m- Xylenealpha.alph a'diamine	1477-55-0	Green algae	Experimental	72 hours	NOEC	9.8 mg/l

r	1	1	1		1	
m- Xylenealpha.alph a'diamine	1477-55-0	Water flea	Experimental	21 days	NOEC	4.7 mg/l
Silane, trimethoxyoctyl-, hydrolysis products with silica	92797-60-9	Algae or other aquatic plants	Experimental	72 hours	EC50	>=10,000 mg/l
Silane, trimethoxyoctyl-, hydrolysis products	92797-60-9	Water flea	Experimental	24 hours	EL50	>10,000 mg/l
with silica Silane,	92797-60-9	Zebra Fish	Experimental	96 hours	LC50	>10,000 mg/l
trimethoxyoctyl-, hydrolysis products with silica						, ,
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Guppy	Estimated	96 hours	LC50	1,378 mg/l
Nitric acid, calcium salt, tetrahydrate		Fathead minnow	Estimated	30 days	NOEC	58 mg/l
Urea, N,N'-bis[3- (dimethylamino)pr opyl]-	52338-87-1	Activated sludge	Analogous Compound	3 hours	NOEC	180 mg/l
Urea, N,N'-bis[3- (dimethylamino)pr opyl]-	52338-87-1	Green algae	Analogous Compound	72 hours	ErC50	>100 mg/l
Urea, N,N'-bis[3- (dimethylamino)pr opyl]-	52338-87-1	Medaka	Analogous Compound	96 hours	LC50	>1,000 mg/l
Urea, N,N'-bis[3- (dimethylamino)pr opyl]-	52338-87-1	Water flea	Experimental	48 hours	EC50	93 mg/l
Urea, N,N'-bis[3- (dimethylamino)pr opyl]-	52338-87-1	Green algae	Analogous Compound	72 hours	ErC10	>100 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
3,3'-	4246-51-9	Experimental	25 days	CO2 evolution	-8 %CO2	OECD 301B - Modified

Oxybis(ethyleneox y)bis(propylamine)		Biodegradation			evolution/THCO2 evolution	sturm or CO2
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
1,2-Ethanediamine, phosphate	14852-17-6	Experimental Biodegradation	28 days	BOD	74 %BOD/ThOD	OECD 301D - Closed bottle test
Oxide glass chemicals	65997-17-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A
m- Xylenealpha.alph a'diamine	1477-55-0	Experimental Biodegradation	28 days	CO2 evolution	49 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
m- Xylenealpha.alph a'diamine	1477-55-0	Experimental Aquatic Inherent Biodegrad.	28 days	BOD	22 %BOD/ThOD	OECD 302C - Modified MITI (II)
Silane, trimethoxyoctyl-, hydrolysis products with silica	92797-60-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Urea, N,N'-bis[3- (dimethylamino)pr opyl]-	52338-87-1	Analogous Compound Biodegradation	28 days	BOD	1 %BOD/ThOD	OECD 301C - MITI test (I)
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
1,2-Ethanediamine, phosphate	14852-17-6	Experimental Bioconcentration		Log Kow	1.865	OECD 117 log Kow HPLC method
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
m- Xylenealpha.alph a'diamine	1477-55-0	Experimental BCF - Fish	42 days	Bioaccumulation factor	<2.7	OECD305-Bioconcentration
m- Xylenealpha.alph a'diamine	1477-55-0	Extrapolated Bioconcentration		Log Kow	0.18	OECD 107 log Kow shke flsk mtd
Silane, trimethoxyoctyl-, hydrolysis products with silica	92797-60-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Urea, N,N'-bis[3- (dimethylamino)pr opyl]-	52338-87-1	Analogous Compound BCF - Fish	28 days	Bioaccumulation factor	≤2.3	OECD305-Bioconcentration
Urea, N,N'-bis[3- (dimethylamino)pr opyl]-	52338-87-1	Analogous Compound Bioconcentration		Log Kow	-0.085	OECD 107 log Kow shke flsk mtd
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
3,3'- Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Modeled Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™
1,2-Ethanediamine, phosphate	14852-17-6	Experimental Mobility in Soil	Koc	28.2 l/kg	OECD 121 Estim. of Koc by HPLC
m- Xylenealpha.alpha 'diamine	1477-55-0	Modeled Mobility in Soil	Koc	<1 l/kg	ACD/Labs ChemSketch™
Urea, N,N'-bis[3- (dimethylamino)pro pyl]-	52338-87-1	Modeled Mobility in Soil	Koc	4 l/kg	Episuite <sup>TM</sup>
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

#### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

#### 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

#### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

# **SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN2735	UN2735	UN2735
14.2 UN proper shipping name	OF DIETHYLENE GLYCOL; META-	AMINES, LIQUID, CORROSIVE, N.O.S.(BIS(3- AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL; META- XYLENEDIAMINE)	AMINES, LIQUID, CORROSIVE, N.O.S.(BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL; META- XYLENEDIAMINE)

14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	III	III	III
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	C7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	18 - ALKALIS

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	•		• • .
( '9	rcino	oen:	icity
~ "	1 (1111	5011	icit,

<u>Ingredient</u>	CAS Nbr	<b>Classification</b>	Regulation
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

# Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<b>Ingredient</b>	<u>CAS Nbr</u>
toluene	108-88-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of

\_\_\_\_\_\_

# Restriction

#### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

### COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
toluene	108-88-3	10	50

# Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

# **SECTION 16: Other information**

### List of relevant H statements

EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### **Revision information:**

GB Section 02: CLP Ingredient table information was modified.

GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was modified.

Label: CLP Classification information was modified.

Label: CLP Environmental Hazard Statements information was added.

Label: CLP Supplemental Hazard Statements information was added.

OEL Reg Agency Desc information was modified.

Section 09: Flammability information information was added.

Section 09: Particle Characteristics N/A information was added.

Section 1: E-mail address information was modified.

Section 11: Reproductive Toxicity Table information was modified.

# 3M™ Scotch-Weld™ Epoxy Adhesive EC-3542 B/A FR Part A

- Section 11: Target Organs Repeated Table information was modified.
- Section 11: Target Organs Single Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Mobility in soil information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.
- Section 3: Composition/Information of ingredients table information was modified.
- Section 5: Hazardous combustion products table information was modified.
- Section 6: Accidental release personal information information was modified.
- Section 7: Conditions safe storage information was modified.
- Section 8: glove data value information was modified.
- Section 8: Occupational exposure limit table information was modified.
- Section 8: Respiratory protection recommended respirators information information was modified.
- Section 9: Flammability (solid, gas) information information was deleted.
- Section 9: Property description for optional properties information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

#### 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



# Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 36-6157-6
 Version number:
 6.00

 Revision date:
 01/08/2025
 Supersedes date:
 14/12/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M<sup>™</sup> Scotch-Weld<sup>™</sup> Epoxy Adhesive EC-3542 B/A FR Part B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Part B of a 2-part Epoxy Adhesive, Industrial use.

#### 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

# 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

# **CLASSIFICATION:**

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Germ Cell Mutagenicity, Category 2 - Muta. 2; H341

Reproductive Toxicity, Category 1B - Repr. 1B; H360F

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

#### 2.2. Label elements

#### The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

### SIGNAL WORD

DANGER.

#### **Symbols**

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

#### **Pictograms**



Ingredient	CAS Nbr	EC No.	% by Wt
Epichlorhydrin - trimethylolpropane copolymer	30499-70-8		20 - 40
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	20 - 35

#### **HAZARD STATEMENTS:**

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H317 May cause an allergic skin reaction.
 H341 Suspected of causing genetic defects.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P201 Obtain special instructions before use.
P273 Avoid release to the environment.

P280I Wear protective gloves, eye protection, face protection, and respiratory protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

# SUPPLEMENTAL INFORMATION:

### **Supplemental Precautionary Statements:**

Restricted to professional users.

#### 2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

Not applicable

# 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Epichlorhydrin - trimethylolpropane copolymer	(CAS-No.) 30499-70-8	20 - 40	Aquatic Chronic 2, H411 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 Muta. 2, H341 Repr. 1B, H360F
Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	20 - 40	Substance with a national occupational exposure limit
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	20 - 35	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
1,2-Ethanediamine, phosphate	(CAS-No.) 14852-17-6 (EC-No.) 238-914-9	1 - 20	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Silane, trimethoxyoctyl-, hydrolysis products with silica	(CAS-No.) 92797-60-9 (EC-No.) 296-597-2	< 10	Substance with a national occupational exposure limit
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2	< 5	Eye Dam. 1, H318 Aquatic Chronic 3, H412
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	< 1	Carc. 2, H351 (inhalation)
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 0.3	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412

Please see section 16 for the full text of any H statements referred to in this section

# **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
		(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eve contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

SubstanceConditionAldehydes.During combustion.Carbon monoxideDuring combustion.Carbon dioxide.During combustion.Hydrogen ChlorideDuring combustion.

#### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE

listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

# **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

# 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	<b>Additional comments</b>
toluene	108-88-3	UK HSE	TWA: 191 mg/m³ (50 ppm);	SKIN
			STEL: 384 mg/m <sup>3</sup> (100 ppm)	
Titanium dioxide	13463-67-7	UK HSE	TWA(respirable):4	
			mg/m3;TWA(Inhalable):10	
DUGT DIEDT OD MUGANICE	65007 17 3	III HOD	mg/m3	
DUST, INERT OR NUISANCE	65997-17-3	UK HSE	TWA(as respirable dust):4	
			mg/m3;TWA(as inhalable	
0:1 1 1 : 1	65007 17 3	N. C	dust):10 mg/m3	
Oxide glass chemicals	6599/-17-3	Manufacturer	TWA(as non-fibrous,	

# 3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive EC-3542 B/A FR Part B

determined respirable)(8 hours):3

mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10

mg/m3

Silicon dioxide 92797-60-9 UK HSE TWA(as respirable dust):2.4

mg/m3;TWA(as inhalable

dust):6 mg/m3

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

# Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

# 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

The following protective clothing material(s) are also recommended:

# Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following

respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

. Information on basic physical and chemical properties			
Physical state	Liquid.		
Colour	White		
Odor	Slight Epoxy		
Odour threshold	No data available.		
Melting point/freezing point	Not applicable.		
Boiling point/boiling range	No data available.		
Flammability	Not applicable.		
Flammable Limits(LEL)	Not applicable.		
Flammable Limits(UEL)	Not applicable.		
Flash point	Flash point > 93 °C (200 °F) [Test Method: Closed Cup]		
Autoignition temperature	No data available.		
Decomposition temperature	No data available.		
pH	substance/mixture is non-soluble (in water)		
Kinematic Viscosity	No data available.		
Water solubility	Negligible		
Solubility- non-water	No data available.		
Partition coefficient: n-octanol/water	No data available.		
Vapour pressure	No data available.		
Density	0.65 g/ml		
Relative density	0.68 - 0.7 [Ref Std:WATER=1]		
Relative Vapour Density	No data available.		
Particle Characteristics	Not applicable.		

#### 9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNo data available.Molecular weightNo data available.Percent volatileNegligible

# **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5 Incompatible materials

Amines.

# 10.6 Hazardous decomposition products

**Substance** 

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eve contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

#### Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Epichlorhydrin - trimethylolpropane copolymer	Dermal	Rat	LD50 > 3,170 mg/kg
Epichlorhydrin - trimethylolpropane copolymer	Ingestion	Rat	LD50 3,398 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
1,2-Ethanediamine, phosphate	Inhalation-	Professio	LC50 estimated to be > 50 mg/l
	Vapour	nal	
		judgeme	
		nt	
1,2-Ethanediamine, phosphate	Dermal	Rat	LD50 > 2,000 mg/kg
1,2-Ethanediamine, phosphate	Ingestion	Rat	LD50 > 2,000 mg/kg
Silane, trimethoxyoctyl-, hydrolysis products with silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane, trimethoxyoctyl-, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,340 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation-	Rat	LC50 > 5.3 mg/l
	Dust/Mist		
	(4 hours)		
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-	Rat	LC50 > 6.82 mg/l
	Dust/Mist		
	(4 hours)		
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapour (4		
	hours)		
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant		
Epichlorhydrin - trimethylolpropane copolymer	In vitro data	Irritant		
Oxide glass chemicals	Professio nal judgemen t	No significant irritation		
1,2-Ethanediamine, phosphate	Rabbit	No significant irritation		
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant		
Titanium dioxide	Rabbit	No significant irritation		
toluene	Rabbit	Irritant		

Serious Eve Damage/Irritation

Name		Species	Value
	bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant

\_\_\_\_\_

Epichlorhydrin - trimethylolpropane copolymer		Corrosive
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
1,2-Ethanediamine, phosphate	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
Titanium dioxide	Rabbit	No significant irritation
toluene	Rabbit	Moderate irritant

# **Skin Sensitisation**

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Sensitising
	and	
	animal	
Epichlorhydrin - trimethylolpropane copolymer	similar	Sensitising
	compoun	
	ds	
1,2-Ethanediamine, phosphate	similar	Sensitising
	compoun	
	ds	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea	Not classified
	pig	
Titanium dioxide	Human	Not classified
	and	
	animal	
toluene	Guinea	Not classified
	pig	

**Respiratory Sensitisation** 

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route	Value		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Epichlorhydrin - trimethylolpropane copolymer	In Vitro	Some positive data exist, but the data are not sufficient for classification		
Epichlorhydrin - trimethylolpropane copolymer	In vivo	Mutagenic		
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification		
1,2-Ethanediamine, phosphate	In Vitro	Not mutagenic		
1,2-Ethanediamine, phosphate	In vivo	Not mutagenic		
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification		
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Some positive data exist, but the data are not sufficient for classification		
Titanium dioxide	In Vitro	Not mutagenic		
Titanium dioxide	In vivo	Not mutagenic		
toluene	In Vitro	Not mutagenic		
toluene	In vivo	Not mutagenic		

Carcinogenicity

Caremogenicity			
Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Oxide glass chemicals	Inhalation	Multiple animal	Some positive data exist, but the data are not sufficient for classification

Dogg. 10 of 20

		species	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic
Titanium dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.
toluene	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not
			sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not
			sufficient for classification

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Epichlorhydrin - trimethylolpropane copolymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	premating into lactation
Epichlorhydrin - trimethylolpropane copolymer	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	premating into lactation
Epichlorhydrin - trimethylolpropane copolymer	Ingestion	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	14 days
1,2-Ethanediamine, phosphate	Ingestion	Not classified for female reproduction	Rat	NOAEL 150 mg/kg/day	premating into lactation
1,2-Ethanediamine, phosphate	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	33 days
1,2-Ethanediamine, phosphate	Ingestion	Not classified for development	Rat	NOAEL 150 mg/kg/day	premating into lactation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Epichlorhydrin - trimethylolpropane copolymer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
toluene	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	

		system depression	dizziness		available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
			data are not sufficient for		available	
			classification			
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL	3 hours
					0.004 mg/l	
toluene	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning
		system depression	dizziness		available	and/or abuse

Specific Target Organ Toxicity - repeated exposure

Specific Target Organ Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	Duration 2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epichlorhydrin - trimethylolpropane copolymer	Ingestion	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 300 mg/kg/day	43 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
1,2-Ethanediamine, phosphate	Ingestion	heart   endocrine system   hematopoietic system   liver   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	28 days
[3-(2,3- epoxypropoxy)propyl]trim ethoxysilane	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the	Rat	LOAEL 2.3	15 months

			data are not sufficient for classification		mg/l	
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

**Aspiration Hazard** 

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

# 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Туре	Exposure	Test endpoint	Test result
Epichlorhydrin - trimethylolpropane copolymer	30499-70-8	Bacteria	Experimental	18 hours	EC50	>10,000 mg/l
Epichlorhydrin - trimethylolpropane copolymer	30499-70-8	Common Carp	Experimental	96 hours	LC50	75 mg/l
Epichlorhydrin - trimethylolpropane	30499-70-8	Green algae	Experimental	72 hours	EC50	9 mg/l

copolymer						
Epichlorhydrin - trimethylolpropane copolymer	30499-70-8	Water flea	Experimental	48 hours	EC50	3.7 mg/l
Epichlorhydrin - trimethylolpropane copolymer	30499-70-8	Green algae	Experimental	72 hours	NOEC	2.5 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
1,2-Ethanediamine, phosphate	14852-17-6	Green algae	Experimental	72 hours	ErC50	>400 mg/l
1,2-Ethanediamine, phosphate	14852-17-6	Water flea	Experimental	48 hours	EC50	12.5 mg/l
1,2-Ethanediamine, phosphate	14852-17-6	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
1,2-Ethanediamine, phosphate	14852-17-6	Water flea	Experimental	21 days	EC10	0.25 mg/l
Silane, trimethoxyoctyl-, hydrolysis products with silica	92797-60-9	Algae or other aquatic plants	Experimental	72 hours	EC50	>=10,000 mg/l
Silane, trimethoxyoctyl-, hydrolysis products with silica	92797-60-9	Water flea	Experimental	24 hours	EL50	>10,000 mg/l
Silane, trimethoxyoctyl-, hydrolysis products with silica	92797-60-9	Zebra Fish	Experimental	96 hours	LC50	>10,000 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3- epoxypropoxy)prop	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l

yl]trimethoxysilane						
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Epichlorhydrin - trimethylolpropane copolymer	30499-70-8	Experimental Biodegradation	28 days	BOD	8 %BOD/ThOD	OECD 301F - Manometric respirometry
Oxide glass chemicals	65997-17-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
1,2-Ethanediamine, phosphate	14852-17-6	Experimental Biodegradation	28 days	BOD	74 %BOD/ThOD	OECD 301D - Closed bottle test
Silane, trimethoxyoctyl-, hydrolysis products with silica	92797-60-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)prop	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test

yl]trimethoxysilane						
[3-(2,3-	2530-83-8	Experimental		Hydrolytic half-life	6.5 hours (t 1/2)	OECD 111 Hydrolysis func
epoxypropoxy)prop		Hydrolysis		(pH 7)		of pH
yl]trimethoxysilane						
Titanium dioxide	13463-67-7	Data not availbl-	N/A	N/A	N/A	N/A
		insufficient				
toluene	108-88-3	Experimental	20 days	BOD	80 %BOD/ThOD	APHA Std Meth
		Biodegradation				Water/Wastewater
toluene	108-88-3	Experimental		Photolytic half-life	5.2 days (t 1/2)	
		Photolysis		(in air)		

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Epichlorhydrin - trimethylolpropane copolymer	30499-70-8	Experimental Bioconcentration		Log Kow	≤3.4	
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
1,2-Ethanediamine, phosphate	14852-17-6	Experimental Bioconcentration		Log Kow	1.865	OECD 117 log Kow HPLC method
Silane, trimethoxyoctyl-, hydrolysis products with silica	92797-60-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Experimental Bioconcentration		Log Kow	0.5	Episuite <sup>™</sup>
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)pheny l]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite <sup>TM</sup>
1,2-Ethanediamine, phosphate	14852-17-6	Experimental Mobility in Soil	Koc	28.2 l/kg	OECD 121 Estim. of Koc by HPLC
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Modeled Mobility in Soil	Koc	10 l/kg	Episuite <sup>TM</sup>
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

# 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

# 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

# **SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name  14.3 Transport hazard	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(BISPHENOL A DIGLYCIDYL ETHER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(BISPHENOL A DIGLYCIDYL ETHER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(BISPHENOL A DIGLYCIDYL ETHER)
class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation	Not applicable.	Not applicable.	NONE

# 3M<sup>™</sup> Scotch-Weld<sup>™</sup> Epoxy Adhesive EC-3542 B/A FR Part B

Code		
Code		

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Carcinogenicity

Ingredient	CAS Nbr	Classification	Regulation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible humar care.	
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

# Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	CAS Nbr	
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	
toluene	108-88-3	

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of

Restriction

### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements	
E2 Hazardous to the Aquatic	200	500	
environment			

\_\_\_\_\_

Seveso named dangerous substances, Annex 1, Part 2 None

#### Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

# **SECTION 16: Other information**

#### List of relevant H statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H351i	Suspected of causing cancer by inhalation.
H360F	May damage fertility.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# **Revision information:**

GB Section 02: CLP Ingredient table information was modified.

GB Section 15: Carcinogenicity information information was modified.

Section 1: E-mail address information was modified.

Label: CLP Precautionary - Prevention information was modified.

Section 3: Composition/Information of ingredients table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: Occupational exposure limit table information was modified.

OEL Reg Agency Desc information was modified.

Section 08: Personal Protection - Apron Statement information was added.

Section 8: Personal Protection - Skin/body information information was modified.

Section 8: Skin protection - protective clothing information information was deleted.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Particle Characteristics N/A information was added.

Section 9: Property description for optional properties information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 15: Seveso Substance Text information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our

# 3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Adhesive EC-3542 B/A FR Part B

knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

# 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.