

Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 16-5983-8
 Version Number:
 7.00

 Issue Date:
 09/10/2025
 Supersedes Date:
 29/07/2021

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M[™] Polystyrene Foam Insulation Spray Adhesive 78

Product Identification Numbers

62-4951-4950-2 62-4951-4955-1 62-4951-4970-0 62-4951-4975-9

1.2. Recommended use and restrictions on use

Recommended use

aerosol adhesive, aerosol insulation adhesive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301

Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1. Gas Under Pressure: Liquefied gas. Skin Corrosion/Irritation: Category 2. Serious Eye Damage/Irritation: Category 2. Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 2.

Chronic Aquatic Toxicity: Category 4.

2.2. Label elements

Signal word

Danger

Symbols

Flame |Gas cylinder |Exclamation mark |Health Hazard |

Pictograms



Hazard Statements:

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

H371 May cause damage to organs: cardiovascular system.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P281 Use personal protective equipment as required.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical attention.

Storage:

P403 Store in a well-ventilated place.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

Disposal:

P501 Dispose of contents and container in accordance with applicable local, regional,

national, and international regulations.

2.3. Other hazards

Aspiration classification does not apply as this product is sold in sealed, self-pressurized containers with nozzles designed to prevent formation of a stream during usage., Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal., May cause drowsiness or dizziness., May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Cyclohexane	110-82-7	10 - 30
Dimethyl ether	115-10-6	10 - 30
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-	31393-98-3	10 - < 25
TRIMETHYL-,POLYMER WITH 6,6-		
DIMETHYL-2-		
METHYLENEBICYCLO[3.1.1]HEPTANE		
Nonvolatile components	Trade Secret	5 - 25
2-Methylpentane	107-83-5	5 - 13
Hydrotreated light naphtha (petroleum)	64742-49-0	5 - 13
Acetone	67-64-1	1 - 5
1,1-Difluoroethane	75-37-6	1 - < 5
Petroleum naphtha	64742-48-9	1 - < 5
Pentane	109-66-0	< 1.2
Toluene	108-88-3	< 1
Hexane	110-54-3	< 0.12

Any remaining components do not contribute to the hazards of this material.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance Condition Aldehvdes **During Combustion** Hvdrocarbons **During Combustion** Formaldehyde **During Combustion During Combustion** Methane **During Combustion** Carbon monoxide **During Combustion** Carbon dioxide Hydrogen Fluoride **During Combustion** Ketones **During Combustion** Toxic Vapor, Gas, Particulate **During Combustion**

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
HEXANE (ISOMERS OTHER	107-83-5	ACGIH	TWA:200 ppm	A3: Confirmed animal
THAN N-HEXANE)				carcin.
HEXANE (ISOMERS OTHER	107-83-5	Malaysia OELs	TWA(8 hours):1760	
THAN N-HEXANE)			mg/m3(500 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcin, Ototoxicant
Toluene	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m3(50	SKIN
			ppm)	
Pentane, all isomers	109-66-0	ACGIH	TWA:1000 ppm	
Pentane, all isomers	109-66-0	Malaysia OELs	TWA(8 hours):1770	
			mg/m3(600 ppm)	
Hexane	110-54-3	ACGIH	TWA:50 ppm	Danger of cutaneous
				absorption
Hexane	110-54-3	Malaysia OELs	TWA(8 hours):176 mg/m3(50	SKIN
			ppm)	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	Malaysia OELs	TWA(8 hours):1030	
			mg/m3(300 ppm)	
Naphtha	64742-49-0	Malaysia OELs	TWA(8 hours):1590	
			mg/m3(400 ppm)	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human
				carcin
Acetone	67-64-1	Malaysia OELs	TWA(8 hours):1187	
			mg/m3(500 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer's Recommended Guidelines

Malaysia OELs: Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

Half facepiece or full facepiece supplied-air respirator

Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Specific Physical Form:	Aerosol	
Color	Colorless	
Odor	Fruity Odor, Mild Solvent	
Odor threshold	No Data Available	
рН	No Data Available	
Melting point/Freezing point	No Data Available	
Boiling point/Initial boiling point/Boiling range	[Details:Compressed gas]Not Applicable	
Flash Point	-45.6 °C [Test Method: Tagliabue Closed Cup]	
Evaporation rate	1.9 [Ref Std:ETHER=1]	
Flammability	Flammable Aerosol: Category 1.	
Flammable Limits(LEL)	No Data Available	
Flammable Limits(UEL)	No Data Available	
Vapor Pressure	[Details: Compressed gas]Not Applicable	
Relative Vapor Density	>=2.57 [<i>Ref Std</i> :AIR=1]	
Density	0.761 g/ml	
Relative Density	0.761 [<i>Ref Std</i> :WATER=1]	
Water solubility	Nil	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	No Data Available	
Autoignition temperature	No Data Available	
Decomposition temperature	No Data Available	
Kinematic Viscosity	Not Applicable	
Volatile Organic Compounds	<=493 g/l [Test Method:calculated SCAQMD rule 443.1]	
	[Details:Material VOC]	
Volatile Organic Compounds	<=64.8 % [Test Method:calculated per CARB title 2]	
Percent volatile	No Data Available	
VOC Less H2O & Exempt Solvents	No Data Available	

Particle Characteristics	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the

cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation- Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6-DIMETHYL-2- METHYLENEBICYCLO[3.1.1]HEPTANE	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6-DIMETHYL-2- METHYLENEBICYCLO[3.1.1]HEPTANE	Ingestion	Rat	LD50 > 2,000 mg/kg
2-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Methylpentane	Inhalation- Vapor		LC50 estimated to be > 50 mg/l
2-Methylpentane	Ingestion		LD50 estimated to be > 5,000 mg/kg
Dimethyl ether	Inhalation- Gas (4 hours)	Rat	LC50 164,000 ppm
Hydrotreated light naphtha (petroleum)	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated light naphtha (petroleum)	Inhalation- Vapor (4 hours)	Rat	LC50 > 14.7 mg/l
Hydrotreated light naphtha (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Nonvolatile components	Dermal	Not available	LD50 > 2,000 mg/kg
Nonvolatile components	Ingestion	Not available	LD50 > 2,000 mg/kg
Petroleum naphtha	Dermal	similar compoun ds	LD50 > 2,200 mg/kg
Petroleum naphtha	Ingestion	similar	LD50 > 15,000 mg/kg

		aamnaun	
		compoun ds	
1170 4	T 1 1 4		LC50 > 427,000
1,1-Difluoroethane	Inhalation-	Rat	LC50 > 437,000 ppm
	Gas (4		
	hours)		
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-	Rat	LC50 76 mg/l
	Vapor (4		
	hours)		
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Pentane	Dermal	Rabbit	LD50 3,000 mg/kg
Pentane	Inhalation-	Rat	LC50 > 18 mg/l
	Vapor (4		
	hours)		
Pentane	Ingestion	Rat	LD50 > 2,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		
	hours)		
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-	Rat	LC50 170 mg/l
	Vapor (4		
	hours)		
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Cyclohexane	Rabbit	Mild irritant
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6- DIMETHYL-2-METHYLENEBICYCLO[3.1.1]HEPTANE	In vitro data	No significant irritation
2-Methylpentane	Professio nal judgemen t	Mild irritant
Hydrotreated light naphtha (petroleum)	Rabbit	Irritant
Nonvolatile components	Professio nal judgemen t	No significant irritation
Petroleum naphtha	similar compoun ds	Mild irritant
Acetone	Mouse	Minimal irritation
Pentane	Rabbit	Minimal irritation
Toluene	Rabbit	Irritant
Hexane	Human and animal	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Cyclohexane	Rabbit	Mild irritant
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6- DIMETHYL-2-METHYLENEBICYCLO[3.1.1]HEPTANE	In vitro data	No significant irritation
2-Methylpentane	Professio nal judgemen t	Moderate irritant
Hydrotreated light naphtha (petroleum)	Rabbit	Mild irritant
Nonvolatile components	Professio nal	No significant irritation

	judgemen	
Petroleum naphtha	similar	No significant irritation
	compoun	
	ds	
Acetone	Rabbit	Severe irritant
Pentane	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
Hexane	Rabbit	Mild irritant

Sensitization:

Skin Sensitization

Name	Species	Value
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6- DIMETHYL-2-METHYLENEBICYCLO[3.1.1]HEPTANE	Multiple animal species	Not classified
Hydrotreated light naphtha (petroleum)	Guinea pig	Not classified
Nonvolatile components		Not classified
Petroleum naphtha	similar compoun ds	Not classified
Pentane	Guinea pig	Not classified
Toluene	Guinea pig	Not classified
Hexane	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6- DIMETHYL-2-METHYLENEBICYCLO[3.1.1]HEPTANE	In Vitro	Not mutagenic
Dimethyl ether	In Vitro	Not mutagenic
Dimethyl ether	In vivo	Not mutagenic
Hydrotreated light naphtha (petroleum)	In Vitro	Not mutagenic
Petroleum naphtha	In Vitro	Not mutagenic
1,1-Difluoroethane	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1-Difluoroethane	In vivo	Some positive data exist, but the data are not sufficient for classification
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Pentane	In vivo	Not mutagenic
Pentane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Hexane	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Dimethyl ether	Inhalation	Rat	Not carcinogenic

Dogg 10 of 2

Hydrotreated light naphtha (petroleum)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
1,1-Difluoroethane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Acetone	Not Specified	Multiple animal species	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration	
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation	
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation	
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation	
Dimethyl ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis	
1,1-Difluoroethane	Inhalation	Not classified for development	Rat	NOAEL 50,000 ppm	during organogenesis	
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks	
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis	
Pentane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis	
Pentane	Inhalation	Not classified for development	Rat	NOAEL 30 mg/l	during organogenesis	
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure	
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation	
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation	
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse	
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis	
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation	
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days	
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days	

Target Organ(s)

Specific Target Organ Toxicity - single exposure

specific ranger organiz	i onicio	mgre emposure				
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure

						Duration
Cyclohexane	Inhalation	central nervous system depression	3		NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
2-Methylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
2-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	
2-Methylpentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Dimethyl ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Hydrotreated light naphtha (petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated light naphtha (petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated light naphtha (petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Petroleum naphtha	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
1,1-Difluoroethane	Inhalation	cardiac sensitization	Causes damage to organs	Human and animal	NOAEL Not available	poisoning and/or abuse
1,1-Difluoroethane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL 100,000 ppm	
1,1-Difluoroethane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Pentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
Pentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available

Page: 12 of 20

Pentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	not available
Pentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	not available
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
BICYCLO[3.1.1]HEPT-2- ENE,2,6,6- TRIMETHYL-,POLYME R WITH 6,6-DIMETHYL- 2- METHYLENEBICYCLO[3.1.1]HEPTANE	Ingestion	heart gastrointestinal tract hematopoietic system liver nervous system eyes kidney and/or bladder	Not classified	Rat	NOAEL 331 mg/kg/day	90 days
2-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
2-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
2-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg	28 days
Dimethyl ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
1,1-Difluoroethane	Inhalation	hematopoietic system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks

Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Pentane	Inhalation	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Pentane	Inhalation	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 20 mg/l	13 weeks
Pentane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or	Not classified	Multiple	NOAEL	13 weeks

Page: 14 of 20

				species	mg/kg/day	
Toluene	Ingestion	hematopoietic	Not classified	Mouse	NOAEL 600	14 days
		system			mg/kg/day	
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105	28 days
					mg/kg/day	
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105	4 weeks
					mg/kg/day	
Hexane	Inhalation	peripheral nervous	Causes damage to organs through	Human	NOAEL Not	occupational
		system	prolonged or repeated exposure		available	exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the	Mouse	LOAEL 1.76	13 weeks
			data are not sufficient for		mg/l	
			classification			
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not	6 months
					available	
Hexane	Inhalation	kidney and/or	Not classified	Rat	LOAEL 1.76	6 months
		bladder			mg/l	
Hexane	Inhalation	hematopoietic	Not classified	Mouse	NOAEL 35.2	13 weeks
		system			mg/l	
Hexane	Inhalation	auditory system	Not classified	Human	NOAEL Not	occupational
		immune system			available	exposure
		eyes				
Hexane	Inhalation	heart skin	Not classified	Rat	NOAEL 1.76	6 months
		endocrine system			mg/l	
Hexane	Ingestion	peripheral nervous	Some positive data exist, but the	Rat	NOAEL	90 days
		system	data are not sufficient for		1,140	
			classification		mg/kg/day	
Hexane	Ingestion	endocrine system	Not classified	Rat	NOAEL Not	13 weeks
		hematopoietic			available	
		system liver				
		immune system				
		kidney and/or				
		bladder				

Aspiration Hazard

Name	Value
Cyclohexane	Aspiration hazard
2-Methylpentane	Aspiration hazard
Hydrotreated light naphtha (petroleum)	Aspiration hazard
Petroleum naphtha	Aspiration hazard
Pentane	Aspiration hazard
Toluene	Aspiration hazard
Hexane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 4: May cause long lasting harmful effects to aquatic organisms

No product test data available

Material	Cas #	Organism	Туре	Exposure	Test Endpoint	Test Result
Cyclohexane	110-82-7	Fathead Minnow	Experimental	96 hours	LC50	4.53 mg/l
Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
Cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
Dimethyl ether	115-10-6	Bacteria	Experimental	N/A	EC10	>1,600 mg/l
Dimethyl ether	115-10-6	Guppy	Experimental	96 hours	LC50	>4,100 mg/l
Dimethyl ether	115-10-6	Water flea	Experimental	48 hours	EC50	>4,400 mg/l
BICYCLO[3.1.1]H EPT-2-ENE,2,6,6- TRIMETHYL-,PO LYMER WITH 6,6-DIMETHYL-2- METHYLENEBIC		Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
YCLO[3.1.1]HEPT ANE BICYCLO[3.1.1]H EPT-2-ENE,2,6,6- TRIMETHYL-,PO LYMER WITH	31393-98-3	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
6,6-DIMETHYL-2- METHYLENEBIC YCLO[3.1.1]HEPT ANE						
BICYCLO[3.1.1]H EPT-2-ENE,2,6,6- TRIMETHYL-,PO LYMER WITH 6,6-DIMETHYL-2- METHYLENEBIC YCLO[3.1.1]HEPT ANE	31393-98-3	Water flea	Endpoint not reached	21 days	EL10	>100 mg/l
Nonvolatile	Trade Secret	N/A	Data not available	N/A	N/A	N/A
components			or insufficient for classification			
2-Methylpentane	107-83-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrotreated light naphtha (petroleum)	64742-49-0	Fathead Minnow	Estimated	96 hours	LL50	8.2 mg/l
Hydrotreated light naphtha (petroleum)	64742-49-0	Green algae	Estimated	72 hours	EL50	3.1 mg/l
Hydrotreated light naphtha (petroleum)	64742-49-0	Water flea	Estimated	48 hours	EL50	4.5 mg/l
Hydrotreated light naphtha (petroleum)	64742-49-0	Green algae	Estimated	72 hours	NOEL	0.5 mg/l
Hydrotreated light naphtha (petroleum)	64742-49-0	Water flea	Estimated	21 days	NOEL	2.6 mg/l
1,1-Difluoroethane	75-37-6	Bacteria	Analogous Compound	6 hours	EC50	>472.57 mg/l
1,1-Difluoroethane	75-37-6	Rainbow Trout	Analogous Compound	96 hours	LC50	291.31 mg/l
1,1-Difluoroethane	75-37-6	Water flea	Analogous Compound	48 hours	EC50	634.41 mg/l
Acetone	67-64-1	Algae or other aquatic plants	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Invertebrate	Experimental	24 hours	LC50	2,100 mg/l
Acetone	67-64-1	Rainbow Trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100

Petroleum naphtha	64742-48-9	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Petroleum naphtha	64742-48-9	Rainbow Trout	Experimental	96 hours	LL50	>1,000 mg/l
Petroleum naphtha	64742-48-9	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Petroleum naphtha	64742-48-9	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
Pentane	109-66-0	Green algae	Experimental	72 hours	EC50	10.7 mg/l
Pentane	109-66-0	Rainbow Trout	Experimental	96 hours	LC50	4.26 mg/l
Pentane	109-66-0	Water flea	Experimental	48 hours	EC50	2.7 mg/l
Pentane	109-66-0	Green algae	Experimental	72 hours	NOEC	2.04 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of
						bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Hexane	110-54-3	Fathead Minnow	Experimental	96 hours	LC50	2.5 mg/l
Hexane	110-54-3	Water flea	Experimental	48 hours	LC50	3.9 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	Biological Oxygen Demand	77 %BOD/ThOD	OECD 301F - Manometric Respiro
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.3 days (t 1/2)	
Dimethyl ether	115-10-6	Experimental Biodegradation	28 days	Biological Oxygen Demand	5 %BOD/ThOD	OECD 301D - Closed Bottle Test
Dimethyl ether	115-10-6	Experimental Photolysis		Photolytic half-life (in air)	12.4 days (t 1/2)	
BICYCLO[3.1.1]H EPT-2-ENE,2,6,6- TRIMETHYL-,PO LYMER WITH 6,6-DIMETHYL-2- METHYLENEBIC YCLO[3.1.1]HEPT ANE	31393-98-3	Experimental Biodegradation	28 days	Biological Oxygen Demand	4 %BOD/ThOD	OECD 301D - Closed Bottle Test
Nonvolatile components	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
2-Methylpentane	107-83-5	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Hydrotreated light naphtha (petroleum)	64742-49-0	Estimated Biodegradation	28 days	Biological Oxygen Demand	77 %BOD/ThOD	OECD 301F - Manometric Respiro
1,1-Difluoroethane	75-37-6	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	3 %BOD/ThOD	OECD 301D - Closed Bottle Test
1,1-Difluoroethane	75-37-6	Modeled Photolysis		Photolytic half-life (in air)	916 days (t 1/2)	Episuite TM
Acetone	67-64-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	78 %BOD/ThOD	OECD 301D - Closed Bottle Test
Acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Petroleum naphtha	64742-48-9	Experimental	28 days	Biological Oxygen	31 %BOD/ThOD	OECD 301F - Manometric

		Biodegradation		Demand		Respiro
Pentane	109-66-0	Experimental	28 days	Biological Oxygen	87 %BOD/ThOD	OECD 301F - Manometric
		Biodegradation		Demand		Respiro
Pentane	109-66-0	Experimental Photolysis		Photolytic half-life (in air)	8.07 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Hexane	110-54-3	Experimental Bioconcentration	28 days	Biological Oxygen Demand	100 %BOD/ThOD	OECD 301C - MITI (I)
Hexane	110-54-3	Experimental Photolysis		Photolytic half-life (in air)	5.4 days (t 1/2)	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Cyclohexane	110-82-7	Experimental BCF - Fish	56 days	Bioaccumulation Factor	129	OECD305-Bioconcentration
Cyclohexane	110-82-7	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	3.44	
Dimethyl ether	115-10-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
BICYCLO[3.1.1]H EPT-2-ENE,2,6,6- TRIMETHYL-,PO LYMER WITH 6,6-DIMETHYL-2- METHYLENEBIC YCLO[3.1.1]HEPT ANE	31393-98-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	7.41	
Nonvolatile components	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Methylpentane	107-83-5	Estimated Bioconcentration		Bioaccumulation Factor	150	
Hydrotreated light naphtha (petroleum)	64742-49-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,1-Difluoroethane	75-37-6	Modeled Bioconcentration		Log of Octanol/H2O part. coeff	1.13	Episuite TM
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulation Factor	0.65	
Acetone	67-64-1	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-0.24	
Petroleum naphtha	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Pentane	109-66-0	Estimated Bioconcentration		Bioaccumulation Factor	26	
Toluene	108-88-3		72 hours	Bioaccumulation Factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.73	
Hexane	110-54-3	Modeled Bioconcentration		Bioaccumulation Factor	50	Catalogic TM

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: None assigned. Hazard Class/Division: 2.1 Subsidiary Risk: None assigned. Packing Group: None assigned.

Limited Quantity: Yes

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: None assigned. Hazard Class/Division: 2.1 Subsidiary Risk: None assigned. Packing Group: None assigned. Limited Quantity: None assigned. Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The

components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my