



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	41-7613-7	Version Number:	1.00
Issue Date:	05/30/2025	Supersedes Date:	Initial Issue

This Safety Data Sheet has been prepared in accordance with the DENR Administrative Order No. 2015-09 Rules and Procedures for the Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) in Preparation of Safety Data Sheet (SDS) and Labelling Requirements of Toxic Chemical Substances.

SECTION 1: Identification

1.1. Product identifier

3M™ Glass Pre-Treatment, 39903

Product Identification Numbers

60-4551-1113-2

1.2. Recommended use and restrictions on use

Recommended use

Automotive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS:	3M Philippines, Inc., 18th Floor, Bonifacio Stopover Corporate Center, 31st Street corner, 2nd Avenue, Bonifacio Global City, Taguig City, 1635 Philippines
Telephone:	+632 827 11680
E Mail:	mcvillalva@mmm.com
Website:	www.3m.com/ph

1.4. Emergency telephone number

+632 827 11680

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark |

Pictograms



Hazard statements

H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

P501	Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.
------	---

2.3. Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Isopropyl Alcohol	67-63-0	80 - 95
Water	7732-18-5	5 - 10
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcin
Isopropyl Alcohol	67-63-0	Philippines OELs	TWA(8 hours):980 mg/m3(400 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Philippines OELs : Philippines. Threshold Limit Values for Airborne Contaminants

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Colorless
Odor	Mild Alcohol
Odor threshold	<i>No Data Available</i>
pH	5 - 6
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	82.2 °C
Flash Point	11.7 °C [<i>Test Method: Closed Cup</i>]
Evaporation rate	1.2
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	2 %
Flammable Limits(UEL)	12.5 %
Vapor Pressure	5,732.8 Pa [<i>@ 25 °C</i>]
Relative Vapor Density	2.07 [<i>Ref Std: AIR=1</i>]
Density	0.8 g/ml
Relative Density	0.8 [<i>@ 15.6 °C</i>]
Water solubility	100 %
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	3.8 mm ² /sec
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H ₂ O & Exempt Solvents	732 g/l

Particle Characteristics	<i>Not Applicable</i>
--------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Carbon monoxide

Carbon dioxide

Condition

Not Specified

Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May cause additional health effects (see below).

Skin Contact:

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-	Rat	LC50 72.6 mg/l

	Vapor (4 hours)		
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
3-(trimethoxysilyl)propyl glycidyl ether	Dermal	Rabbit	LD50 4,000 mg/kg
3-(trimethoxysilyl)propyl glycidyl ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	Rat	LD50 7,010 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isopropyl Alcohol	Multiple animal species	No significant irritation
3-(trimethoxysilyl)propyl glycidyl ether	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Isopropyl Alcohol	Rabbit	Severe irritant
3-(trimethoxysilyl)propyl glycidyl ether	Rabbit	Corrosive

Sensitization:

Skin Sensitization

Name	Species	Value
Isopropyl Alcohol	Guinea pig	Not classified
3-(trimethoxysilyl)propyl glycidyl ether	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
3-(trimethoxysilyl)propyl glycidyl ether	In Vitro	Some positive data exist, but the data are not sufficient for classification
3-(trimethoxysilyl)propyl glycidyl ether	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
3-(trimethoxysilyl)propyl glycidyl ether	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation

Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not

expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Isopropyl Alcohol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Invertebrate	Experimental	24 hours	LC50	>10,000 mg/l
Isopropyl Alcohol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Biodegradation	14 days	Biological Oxygen Demand	86 %BOD/ThOD	OECD 301C - MITI (I)
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.05	
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	Experimental Bioconcentration		Log of Octanol/H2O part.	0.5	Episuite™

opyl glycidyl ether				coeff		
---------------------	--	--	--	-------	--	--

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN1219

Proper Shipping Name:ISOPROPANOL SOLUTION

Technical Name:None assigned.

Hazard Class/Division:3

Subsidiary Risk:None assigned.

Packing Group:II

Limited Quantity:Yes

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN1219

Proper Shipping Name:ISOPROPANOL SOLUTION

Technical Name:None assigned.

Hazard Class/Division:3

Subsidiary Risk:None assigned.

Packing Group:II

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Philippines SDSs are available at www.3m.com/ph