

# **Safety Data Sheet**

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 09-0182-7
 Version number:
 29.00

 Revision date:
 27/03/2025
 Supersedes date:
 24/03/2025

Transportation version number:

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

# IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

3M<sup>™</sup> Scotch-Weld<sup>™</sup> Epoxy Structural Adhesive DP-760 Off-White

**Product Identification Numbers** 

FS-9100-4045-0 UU-0101-3339-3 UU-0101-3340-1

7000006834 7100200505 7100200506

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Identified uses

Structural adhesive.

#### 1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.

**Telephone:** +353 1 280 3555

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

09-0180-1, 09-0181-9

# TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

# KIT LABEL

# 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

#### **CLASSIFICATION:**

Acute Toxicity, Category 4 - Acute Tox. 4; H302 Acute Toxicity, Category 4 - Acute Tox. 4; H312 Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Germ Cell Mutagenicity, Category 2 - Muta. 2; H341

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

# 2.2. Label elements CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### **Symbols**

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

#### **Pictograms**



#### Contains:

p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline; Amines, polyethylenepoly-, triethylenetetramine fraction; bis-[4-(2,3-epoxipropoxi)phenyl]propane; Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane.

### **HAZARD STATEMENTS:**

H302 + H312
 Harmful if swallowed or in contact with skin.
 H314
 Causes severe skin burns and eye damage.
 H317
 May cause an allergic skin reaction.
 H341
 Suspected of causing genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure: gastrointestinal tract.

H411 Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P260A Do not breathe vapours.

P273 Avoid release to the environment.

Dogge 2 of

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White

P280D Wear protective gloves, protective clothing, and eye/face protection.

**Response:** 

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

# For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

#### <=125 ml Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

### <=125 ml Precautionary statements

**Prevention:** 

P260A Do not breathe vapours.

P280D Wear protective gloves, protective clothing, and eye/face protection.

**Response:** 

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

# SUPPLEMENTAL INFORMATION:

#### **Supplemental Hazard Statements:**

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

#### **Revision information:**

Section 02: CLP Physical and Health Hazard Statements information was modified.

Label: CLP Classification information was modified.

Label: CLP Target Organ Hazard Statement information was added.



# Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 09-0180-1
 Version number:
 26.02

 Revision date:
 24/03/2025
 Supersedes date:
 06/12/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Structural Adhesive DP-760 Off-White: Part A

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Structural adhesive.

# 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.

**Telephone:** +353 1 280 3555

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

# **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

#### **CLASSIFICATION:**

Acute Toxicity, Category 4 - Acute Tox. 4; H302

Acute Toxicity, Category 4 - Acute Tox. 4; H312

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

\_\_\_\_\_\_

For full text of H phrases, see Section 16.

#### 2.2. Label elements

### CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### **Symbols**

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

#### **Pictograms**



#### **Ingredients:**

Ingredient CAS Nbr EC No. % by Wt

Amines, polyethylenepoly-, triethylenetetramine 90640-67-8 292-588-2 40 - 45

fraction

#### **HAZARD STATEMENTS:**

H302 + H312 Harmful if swallowed or in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

# PRECAUTIONARY STATEMENTS

**Prevention:** 

P260F Do not breathe fumes.

P273 Avoid release to the environment.

P280D Wear protective gloves, protective clothing, and eye/face protection.

**Response:** 

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

# For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

#### <=125 ml Hazard statements

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

#### <=125 ml Precautionary statements

**Prevention:** 

P260F Do not breathe fumes.

P280D Wear protective gloves, protective clothing, and eye/face protection.

**Response:** 

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

#### SUPPLEMENTAL INFORMATION:

# **Supplemental Hazard Statements:**

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

50% of the mixture consists of components of unknown acute oral toxicity. 50% of the mixture consists of components of unknown acute dermal toxicity.

Contains 52% of components with unknown hazards to the aquatic environment.

#### 2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

# 3.2. Mixtures

Ingredient	Identifier(s)	0/0	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Amine terminated adduct	None	40 - 50	Substance not classified as hazardous
Amines, polyethylenepoly-, triethylenetetramine fraction	(CAS-No.) 90640-67-8 (EC-No.) 292-588-2	40 - 45	Aquatic Chronic 3, H412 Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317
Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	5 - 10	Substance with a national occupational exposure limit
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01- 2119489379-17	1 - 3	Carc. 2, H351 (inhalation)
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	1 - 3	Substance not classified as hazardous
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	(EC-No.) ELINCS 484- 050-2 (REACH-No.) 01- 0000020228-74	< 1.5	Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White: Part A

Octadecanoic acid, 12-hydroxy-, reaction	(CAS-No.) 198028-14-7	< 1.5	Substance not classified as hazardous
products with decanoic acid and	(EC-No.) 907-495-0		
ethylenediamine			

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Harmful in contact with skin. Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Harmful if swallowed.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Amine compounds.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Oxides of nitrogen.	During combustion.

### 5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

# 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

Titanium dioxide

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

13463-67-7 Ireland OELs

TWA(Total inhalable dust)(8 hours):10 mg/m3;TWA(as respirable dust)(8 hours):4

mg/m3

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White: Part A

Mineral wool, with the exception 65997-17-3 Ireland OELs TWA(8 hours):5 mg/m3(2

of those specified elsewhere in fiber/cc)

this Annex

Oxide glass chemicals 65997-17-3 Manufacturer TWA(as non-fibrous, determined respirable)(8 hours):3

mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10

mg/m3

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**Recommended monitoring procedures:**Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

# 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.5	=>8 hours
Fluoroelastomer	0.4	=>8 hours
Neoprene.	0.5	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then

in this product is used in a mainer that presents a higher potential for exposure (e.g. spraying, high sprash potential etc.), then

use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Neoprene apron.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties				
Physical state	Solid.			
Specific Physical Form:	Paste			
Colour	Off-White			
Odor	Light Amine			
Odour threshold	No data available.			
Melting point/freezing point	Not applicable.			
Boiling point/boiling range	Not applicable.			
Flammability	Not applicable.			
Flammable Limits(LEL)	No data available.			
Flammable Limits(UEL)	No data available.			
Flash point	>=100 °C [Test Method:Closed Cup]			
Autoignition temperature	Not applicable.			
Decomposition temperature	No data available.			
pH	substance/mixture is non-soluble (in water)			
Kinematic Viscosity	No data available.			
Water solubility	No data available.			
Solubility- non-water	No data available.			
Partition coefficient: n-octanol/water	No data available.			
Vapour pressure	Not applicable.			
Density	0.79 - 0.85 g/ml			
Relative density	0.79 - 0.85 [ <i>Ref Std</i> :WATER=1]			
Relative Vapour Density	Not applicable.			
Particle Characteristics	Not applicable.			

# 9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

Evaporation rate

Molecular weight

Percent volatile

No data available.
No data available.
No data available.
1 % weight

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

#### 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Heat.

#### 10.5 Incompatible materials

Strong bases.

Water

#### 10.6 Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

#### Eve contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion

Harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

#### Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >1,000 - =2,000
		1	mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000
			mg/kg
Amines, polyethylenepoly-, triethylenetetramine fraction	Dermal	Rabbit	LD50 1,465 mg/kg
Amines, polyethylenepoly-, triethylenetetramine fraction	Ingestion	Rat	LD50 1,591 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine	Dermal	Rat	LD50 > 2,000 mg/kg
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.1 mg/l
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine	Ingestion	Rat	LD50 > 2,000 mg/kg
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	Dermal	Rat	LD50 > 2,000
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.3
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	Ingestion	Rat	LD50 > 2,000

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
Amines, polyethylenepoly-, triethylenetetramine fraction	Rabbit	Corrosive
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and	Rabbit	No significant irritation
ethylenediamine		
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide,	Rabbit	No significant irritation
12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-		

alkandiylbis[12-hydroxyoctadecanamide]		
--	--	--

**Serious Eye Damage/Irritation** 

Name	Species	Value
Amines, polyethylenepoly-, triethylenetetramine fraction	Rabbit	Corrosive
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and	Rabbit	No significant irritation
ethylenediamine		
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide,	Rabbit	Mild irritant
12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-		
alkandiylbis[12-hydroxyoctadecanamide]		

# **Skin Sensitisation**

Name	Species	Value
Amines, polyethylenepoly-, triethylenetetramine fraction	Guinea pig	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
Titanium dioxide	Human and animal	Not classified
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine	Mouse	Not classified
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	Mouse	Not classified

# **Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Amines, polyethylenepoly-, triethylenetetramine fraction	In vivo	Not mutagenic
Amines, polyethylenepoly-, triethylenetetramine fraction	In Vitro	Some positive data exist, but the data are not sufficient for classification
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Octadecanoic acid, 12-hydroxy-, reaction products with decanoic acid and ethylenediamine	In Vitro	Not mutagenic
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Amines, polyethylenepoly-, triethylenetetramine fraction	Dermal	Mouse	Not carcinogenic
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White: Part A

Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Amines, polyethylenepoly-, triethylenetetramine fraction	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	during organogenesis
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]octadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]octadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Amines, polyethylenepoly-, triethylenetetramine fraction	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

# **Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

\_\_\_\_\_

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

#### 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Туре	Exposure	Test endpoint	Test result
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Fathead minnow	Experimental	96 hours	LC50	330 mg/l
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Green algae	Experimental	72 hours	ErC50	20 mg/l
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Water flea	Experimental	48 hours	EC50	31.1 mg/l
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Green algae	Experimental	72 hours	ErC10	1.34 mg/l
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Water flea	Experimental	21 days	EC10	1.9 mg/l
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Bacteria	Experimental	2 hours	EC50	15.7 mg/l
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Redworm	Experimental	56 days	EC10	31.1 mg/kg (Dry Weight)
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Soil microbes	Experimental	28 days	EC50	>100 mg/kg (Dry Weight)
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Octadecanoic acid, 12- hydroxy-, reaction products with decanoic acid and ethylenediamine	198028-14-7	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Octadecanoic acid, 12- hydroxy-, reaction products with decanoic acid and ethylenediamine	198028-14-7	Green algae	Experimental	72 hours	ErC50	43.2 mg/l
Octadecanoic acid, 12- hydroxy-, reaction products with decanoic acid and ethylenediamine	198028-14-7	Rainbow trout	Experimental	96 hours	LC50	>=100 mg/l
Octadecanoic acid, 12- hydroxy-, reaction products with decanoic acid and ethylenediamine	198028-14-7	Water flea	Experimental	48 hours	EC50	94.9 mg/l
Octadecanoic acid, 12- hydroxy-, reaction products with decanoic acid and ethylenediamine	198028-14-7	Green algae	Experimental	72 hours	NOEC	20.7 mg/l
Octadecanoic acid, 12- hydroxy-, reaction products with decanoic acid and ethylenediamine	198028-14-7	Water flea	Experimental	21 days	NOEL	>=20 mg/l
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]o ctadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]o ctadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamid e]	484-050-2	Water flea	Endpoint not reached	48 hours	EC50	>100 mg/l
Reaction mass of 12- hydroxy-N-[2-[(1- oxodecyl)amino]alkyl]o ctadecanamide, 12- hydroxy-N-[2-[(1- oxooctyl)amino]alkyl]o ctadecanamide and N,N'-1,2- alkandiylbis[12- hydroxyoctadecanamid e]	484-050-2	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Reaction mass of 12- hydroxy-N-[2-[(1- oxodecyl)amino]alkyl]o ctadecanamide, 12- hydroxy-N-[2-[(1- oxooctyl)amino]alkyl]o ctadecanamide and	484-050-2	Common Carp	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l

N,N'-1,2- alkandiylbis[12- hydroxyoctadecanamid e]						
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]o ctadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]o ctadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	484-050-2	Green algae	Experimental	72 hours	EC50	0.025 mg/l
Reaction mass of 12-hydroxy-N-[2-[(1-oxodecyl)amino]alkyl]o ctadecanamide, 12-hydroxy-N-[2-[(1-oxooctyl)amino]alkyl]o ctadecanamide and N,N'-1,2-alkandiylbis[12-hydroxyoctadecanamide]	484-050-2	Water flea	Endpoint not reached	21 days	NOEC	>100 mg/l
Reaction mass of 12- hydroxy-N-[2-[(1- oxodecyl)amino]alkyl]o ctadecanamide, 12- hydroxy-N-[2-[(1- oxooctyl)amino]alkyl]o ctadecanamide and N,N'-1,2- alkandiylbis[12- hydroxyoctadecanamid e]	484-050-2	Green algae	Experimental	72 hours	NOEC	0.007 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Experimental Aquatic Inherent Biodegrad.	84 days	Dissolv. Organic Carbon Deplet	20 %removal of DOC	OECD 302A - Modified SCAS Test
Oxide glass chemicals	65997-17-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Octadecanoic acid, 12- hydroxy-, reaction products with decanoic acid and ethylenediamine	198028-14-7	Experimental Biodegradation	28 days	BOD	14 %BOD/ThO D	OECD 301D - Closed bottle test
Reaction mass of 12- hydroxy-N-[2-[(1- oxodecyl)amino]alkyl]octad ecanamide, 12-hydroxy-N- [2-[(1- oxooctyl)amino]alkyl]octad ecanamide and N,N'-1,2- alkandiylbis[12- hydroxyoctadecanamide]	484-050-2	Experimental Biodegradation	28 days	CO2 evolution	7 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Experimental Bioconcentration		Log Kow	<-2.0	
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
Octadecanoic acid, 12- hydroxy-, reaction products with decanoic acid and ethylenediamine	198028-14-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Reaction mass of 12- hydroxy-N-[2-[(1- oxodecyl)amino]alkyl]octa decanamide, 12-hydroxy- N-[2-[(1- oxooctyl)amino]alkyl]octad ecanamide and N,N'-1,2- alkandiylbis[12- hydroxyoctadecanamide]	484-050-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	Experimental Mobility in Soil	Koc	1600-5000 l/kg	
Reaction mass of 12- hydroxy-N-[2-[(1- oxodecyl)amino]alkyl]octa decanamide, 12-hydroxy- N-[2-[(1- oxooctyl)amino]alkyl]octad ecanamide and N,N'-1,2- alkandiylbis[12- hydroxyoctadecanamide]	484-050-2	Experimental Mobility in Soil	Koc	>430000 l/kg	OECD 121 Estim. of Koc by HPLC

# 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

# 12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

#### 12.7. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of

handling halogenated materials. If no other disposal options are available, waste product—that has been completely cured or polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

# EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

# **SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3259	UN3259	UN3259
14.2 UN proper shipping name	N.O.S.(FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH	AMINES, SOLID, CORROSIVE, N.O.S.(FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH TRIETHYLENETETRAMINE )	AMINES, SOLID, CORROSIVE, N.O.S.(FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH TRIETHYLENETETRAMIN E; POLYAMIDE WAX)
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	II	II	II
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White: Part A

ADR Classification Code	C8	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	18 - ALKALIS

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Carcinogenicity

<u>Ingredient</u>	CAS Nbr	<u>Classification</u>	<b>Regulation</b>
Titanium dioxide	13463-67-7	Grp. 2B: Possible human	International Agency
		carc.	for Research on Cancer

# Global inventory status

Contact 3M for more information.

# DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements		
E2 Hazardous to the Aquatic	200	500		
environment				

Seveso named dangerous substances, Annex 1, Part 2 None

# Regulation (EU) No 649/2012

No chemicals listed

# 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

# **SECTION 16: Other information**

#### List of relevant H statements

H302	Harmful if swallowed.
H302 + H312	Harmful if swallowed or in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H351i	Suspected of causing cancer by inhalation.

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White: Part A

H400 Very toxic to aquatic life.
----------------------------------

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

#### **Revision information:**

Section 1: E-mail address information was modified.

CLP: Ingredient table information was modified.

Section 3: Composition/Information of ingredients table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 14 Proper Shipping Name information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



# Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 09-0181-9
 Version number:
 26.00

 Revision date:
 27/03/2025
 Supersedes date:
 08/01/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotch-Weld<sup>TM</sup> Epoxy Structural Adhesive DP-760 Off-White: Part B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Structural adhesive.

# 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.

**Telephone:** +353 1 280 3555

**E Mail:** ner-productstewardship@mmm.com

Website: www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

# **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

### **CLASSIFICATION:**

Acute Toxicity, Category 4 - Acute Tox. 4; H302

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Germ Cell Mutagenicity, Category 2 - Muta. 2; H341

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

WARNING.

#### **Symbols**

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

#### **Pictograms**







#### **Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	5026-74-4	225-716-2	30 - 60
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	< 25
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-		701-263-0	5 - 15
[methylenebis(4,1- phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-	_		
(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxira			

#### **HAZARD STATEMENTS:**

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure: gastrointestinal tract.

H411 Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P273 Avoid release to the environment.

P280E Wear protective gloves.

**Response:** 

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White: Part B

<=125 ml Hazard statements

H317 May cause an allergic skin reaction. H341 Suspected of causing genetic defects.

#### <=125 ml Precautionary statements

**Prevention:** 

P280E Wear protective gloves.

**Response:** 

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

#### SUPPLEMENTAL INFORMATION:

**Supplemental Hazard Statements:** 

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Contains 11% of components with unknown hazards to the aquatic environment.

# 2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

Not applicable

# 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	(CAS-No.) 5026-74-4 (EC-No.) 225-716-2	30 - 60	Aquatic Chronic 2, H411 Acute Tox. 4, H302 Skin Sens. 1A, H317 Muta. 2, H341 STOT RE 2, H373
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01- 2119456619-26	< 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxira ne	(EC-No.) 701-263-0	5 - 15	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411
Acrylic copolymer	Trade Secret	< 8	Substance not classified as hazardous
Vinyl-Acrylic copolymer	Trade Secret	< 8	Substance not classified as hazardous
Silica, vitreous	(CAS-No.) 60676-86-0 (EC-No.) 262-373-8	3 - 8	Substance with a national occupational exposure limit

Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	1 - 5	Substance not classified as hazardous
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01- 2119489379-17	1 - 3	Carc. 2, H351 (inhalation)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2 (REACH-No.) 01- 2119513212-58		Eye Dam. 1, H318 Aquatic Chronic 3, H412

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

# **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxi)phenyl]propane		$(C \ge 5\%)$ Skin Irrit. 2, H315
		$(C \ge 5\%)$ Eye Irrit. 2, H319
	(REACH-No.) 01-	
	2119456619-26	

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Harmful if swallowed. Target organ effects. See Section 11 for additional details.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

Substance

Carbon monoxide Carbon dioxide.

Irritant vapours or gases.

#### Condition

During combustion.

During combustion.

During combustion.

#### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

#### 6.2. Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and

personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

# Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Titanium dioxide 13463-67-7 Ireland OELs TWA(Total inhalable dust)(8 hours):10 mg/m3;TWA(as

respirable dust)(8 hours):4

mg/m3

Silica, vitreous 60676-86-0 Ireland OELs TWA(as respirable dust)(8

hours):0.08 mg/m3

Ireland OELs : Ireland. OELs TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### **Derived no effect level (DNEL)**

Ingredient	Degradation	Population	Human exposure	DNEL
	Product		pattern	
bis-[4-(2,3-		Worker	Dermal, Long-term	8.3 mg/kg bw/d
epoxipropoxi)phenyl]prop			exposure (8 hours),	
ane			Systemic effects	
bis-[4-(2,3-		Worker	Dermal, Short-term	8.3 mg/kg bw/d
epoxipropoxi)phenyl]prop			exposure, Systemic	
ane			effects	
bis-[4-(2,3-		Worker	Inhalation, Long-term	12.3 mg/m <sup>3</sup>
epoxipropoxi)phenyl]prop			exposure (8 hours),	
ane			Systemic effects	
bis-[4-(2,3-		Worker	Inhalation, Short-term	12.3 mg/m <sup>3</sup>
epoxipropoxi)phenyl]prop			exposure, Systemic	
ane			effects	

# Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne		Freshwater	0.003 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne		Freshwater sediments	0.5 mg/kg d.w.
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne		Intermittent releases to water	0.013 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne		Marine water	0.0003 mg/l

bis-[4-(2,3- epoxipropoxi)phenyl]propa	Marine water sediments	0.5 mg/kg d.w.
ne		
bis-[4-(2,3-	Sewage Treatment Plant	10 mg/l
epoxipropoxi)phenyl]propa		
ne		

**Recommended monitoring procedures:**Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

#### 8.2. Exposure controls

In addition, refer to the annex for more information.

# 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

# Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

Half facepiece or full facepiece supplied-air respirator

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White: Part B

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter type A

# 8.2.3. Environmental exposure controls

Refer to Annex

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

information on basic physical and encinical properties					
Physical state	Solid.				
Specific Physical Form:	Paste				
Colour	Off-White				
Odor	Light Epoxy				
Odour threshold	No data available.				
Melting point/freezing point	No data available.				
Boiling point/boiling range	Not applicable.				
Flammability	Not applicable.				
Flammable Limits(LEL)	Not applicable.				
Flammable Limits(UEL)	Not applicable.				
Flash point	>=100 °C [Test Method:Closed Cup]				
Autoignition temperature	Not applicable.				
Decomposition temperature	No data available.				
pH	substance/mixture is non-soluble (in water)				
Kinematic Viscosity	826,772 mm <sup>2</sup> /sec				
Water solubility	Negligible				
Solubility- non-water	No data available.				
Partition coefficient: n-octanol/water	No data available.				
Vapour pressure	Not applicable.				
Density	>=1.23 g/cm3				
Relative density	1.23 - 1.29 [ <i>Ref Std</i> :WATER=1]				
Relative Vapour Density	Not applicable.				
Particle Characteristics	Not applicable.				

#### 9.2. Other information

# 9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNot applicable.Molecular weightNo data available.Percent volatile1 % weight

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

# 10.2 Chemical stability

# 3M™ Scotch-Weld™ Epoxy Structural Adhesive DP-760 Off-White: Part B

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Heat.

# 10.5 Incompatible materials

Strong acids.

# 10.6 Hazardous decomposition products

Substance

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

# Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

# Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

#### Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

# **Acute Toxicity**

Overall product		Species	Value
Overan product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	Dermal	Rat	LD50 > 4,000 mg/kg
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	Ingestion	Rat	LD50 1,037 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane	Dermal	Rat	LD50 > 2,000 mg/kg
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane	Ingestion	Rat	LD50 > 5,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg

ATE = acute toxicity estimate

# **Skin Corrosion/Irritation**

Name		Value
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	Rabbit	No significant irritation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane)	Rabbit	Irritant
and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-		
(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane		
Silica, vitreous	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant

**Serious Eye Damage/Irritation** 

Name	Species	Value
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	Rabbit	Mild irritant
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane)	Rabbit	No significant irritation
and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-		
(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane		
Silica, vitreous	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation

Titanium dioxide		No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive

# **Skin Sensitisation**

Name	Species	Value
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	Mouse	Sensitising
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Sensitising
	and	
	animal	
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane)	Multiple	Sensitising
and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-	animal	
(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane	species	
Silica, vitreous	Human	Not classified
	and	
	animal	
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
	and	
	animal	
Titanium dioxide	Human	Not classified
	and	
	animal	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea	Not classified
	pig	

**Respiratory Sensitisation** 

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route	Value
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	In Vitro	Some positive data exist, but the data are not sufficient for classification
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	In vivo	Mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane	In vivo	Not mutagenic
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Caremogenicity			
Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple	Not carcinogenic

		animal species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	Ingestion	Not classified for male reproduction	Rat	NOAEL 25 mg/kg/day	2 generation
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during gestation
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	Ingestion	Toxic to female reproduction	Rat	NOAEL 50 mg/kg/day	28 days
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]b is(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylene)]b is(oxirane) and 2-([2-[4- (oxiran-2- ylmethoxy)benzyl]phenoxy [methyl)oxirane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

# Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	Ingestion	gastrointestinal tract	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 15 mg/kg/day	90 days
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	Ingestion	endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   kidney and/or bladder   nervous system	Not classified	Rat	NOAEL 450 mg/kg/day	28 days
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	Ingestion	eyes	Not classified	Rat	NOAEL 15 mg/kg/day	90 days
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]b is(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylene)]b is(oxirane) and 2-([2-[4- (oxiran-2- ylmethoxy)benzyl]phenox y]methyl)oxirane	Ingestion	heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Silica, vitreous	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3- epoxypropoxy)propyl]trim ethoxysilane	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard**For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

#### 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	5026-74-4	Water flea	Analogous Compound	48 hours	EC50	18 mg/l
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	5026-74-4	Bacteria	Experimental	16 hours	EC50	>=10 mg/l
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	5026-74-4	Common Carp	Experimental	96 hours	LC50	4.2 mg/l
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	5026-74-4	Green algae	Experimental	96 hours	ErC50	13 mg/l
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	5026-74-4	Green algae	Experimental	96 hours	NOEC	4.2 mg/l
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	5026-74-4	Water flea	Experimental	21 days	NOEC	0.42 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylen e)]bis(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylen e)]bis(oxirane) and 2- ([2-[4-(oxiran-2-	701-263-0	Green algae	Experimental	72 hours	EbC50	1.8 mg/l

Dagge 14 of 2

1 4 1 1 1 1				1	1	1
ylmethoxy)benzyl]phen oxy]methyl)oxirane						
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylen e)]bis(oxirane) and 2,2'-	701-263-0	Rainbow trout	Experimental	96 hours	LC50	2 mg/l
[methylenebis(4,1- phenyleneoxymethylen e)]bis(oxirane) and 2-						
([2-[4-(oxiran-2- ylmethoxy)benzyl]phen oxy]methyl)oxirane						
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylen e)]bis(oxirane) and 2,2'- [methylenebis(4,1-	701-263-0	Water flea	Experimental	48 hours	EC50	1.6 mg/l
phenyleneoxymethylen e)]bis(oxirane) and 2- ([2-[4-(oxiran-2- ylmethoxy)benzyl]phen						
oxy]methyl)oxirane Reaction mass of 2,2'-	701-263-0	Water flea	Analogous	21 days	NOEC	0.3 mg/l
[methylenebis(2,1-phenyleneoxymethylen e)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylen e)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phen oxy]methyl)oxirane	701-203-0	water frea	Compound	21 days	NOEC	0.3 mg/1
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylen e)]bis(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylen e)]bis(oxirane) and 2- ([2-[4-(oxiran-2- ylmethoxy)benzyl]phen oxy]methyl)oxirane	701-263-0	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
[3-(2,3- epoxypropoxy)propyl]tr imethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3- epoxypropoxy)propyl]tr imethoxysilane	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3- epoxypropoxy)propyl]tr imethoxysilane	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3- epoxypropoxy)propyl]tr	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l

imethoxysilane						
[3-(2,3-	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
epoxypropoxy)propyl]tr imethoxysilane						
[3-(2,3- epoxypropoxy)propyl]tr imethoxysilane		Activated sludge	Experimental	3 hours	EC50	>100 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	5026-74-4	Experimental Biodegradation	29 days	CO2 evolution	≤10 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
p-(2,3-epoxypropoxy)-N,N-bis(2,3-epoxypropyl)aniline	5026-74-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	4.1 days (t 1/2)	OECD 111 Hydrolysis func of pH
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	1/2)	OECD 111 Hydrolysis func of pH
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]bi s(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylene)]bi s(oxirane) and 2-([2-[4- (oxiran-2- ylmethoxy)benzyl]phenoxy] methyl)oxirane		Experimental Biodegradation	28 days	CO2 evolution	16 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]bi s(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylene)]bi s(oxirane) and 2-([2-[4- (oxiran-2- ylmethoxy)benzyl]phenoxy] methyl)oxirane	701-263-0	Analogous Compound Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Silica, vitreous	60676-86-0	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)propyl]trimet hoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3- epoxypropoxy)propyl]trimet hoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	5026-74-4	Modeled Bioconcentration		Log Kow	0.87	Episuite <sup>TM</sup>
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method

Page: 16 of 22

Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]b is(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylene)]b is(oxirane) and 2-([2-[4- (oxiran-2- ylmethoxy)benzyl]phenoxy ]methyl)oxirane	701-263-0	Experimental Bioconcentration		Log Kow	3.6	OECD 117 log Kow HPLC method
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
[3-(2,3- epoxypropoxy)propyl]trime thoxysilane	2530-83-8	Experimental Bioconcentration		Log Kow	0.5	Episuite™

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
p-(2,3-epoxypropoxy)- N,N-bis(2,3- epoxypropyl)aniline	5026-74-4	Experimental Mobility in Soil	Koc	84 l/kg	OECD 121 Estim. of Koc by HPLC
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite <sup>TM</sup>
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]b is(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylene)]b is(oxirane) and 2-([2-[4- (oxiran-2- ylmethoxy)benzyl]phenoxy ]methyl)oxirane	701-263-0	Experimental Mobility in Soil	Koc	4,460 l/kg	OECD 121 Estim. of Koc by HPLC
[3-(2,3- epoxypropoxy)propyl]trime thoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite <sup>TM</sup>

# 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

# 12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

#### 12.7. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative,

incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

#### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

# **SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	SUBSTANCE, SOLID, N.O.S.(TRIGYLCIDYL-P-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(TRIGYLCIDYL-P-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(TRIGYLCIDYL-P-
14.3 Transport hazard class(es)	AMINOPHENOL) 9	AMINOPHENOL) 9	AMINOPHENOL) 9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user		Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
ADR Classification Code	M7	Not applicable.	Not applicable.

3M <sup>TM</sup> Scotch-Weld <sup>TM</sup> Epox	v Structural	Adhesive DP-760	Off-White: Part B

IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	CAS Nbr	<u>Classification</u>	Regulation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency
			for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human	International Agency
		carc.	for Research on Cancer

# Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingredient CAS Nbr bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

# Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic	200	500
environment		

Seveso named dangerous substances, Annex 1, Part 2 None

#### Regulation (EU) No 649/2012

No chemicals listed

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

# **SECTION 16: Other information**

#### List of relevant H statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H351i	Suspected of causing cancer by inhalation.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: gastrointestinal tract.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Revision information:**

Section 1: E-mail address information was modified.

CLP: Ingredient table information was modified.

Label: CLP Classification information was modified.

Label: CLP Percent Unknown information was deleted.

Label: CLP Percent Unknown information was modified.

Label: CLP Target Organ Hazard Statement information was added.

Section 3: Composition/Information of ingredients table information was modified.

Section 04: First Aid - Symptoms and Effects (CLP) information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: Eye/face protection information information was modified.

Section 8: Respiratory protection - recommended respirators information information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Health Effects - Ingestion information information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

# **Annex**

1. Title		
Substance identification	bis-[4-(2,3-epoxipropoxi)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;	
	CAG Not 1075-54-5,	
Exposure Scenario Name	Formulation	
Lifecycle Stage	Formulation or re-packing	
Contributing activities	PROC 09 -Transfer of substance or mixture into small containers (dedicated	
	filling line, including weighing)	
	ERC 02 -Formulation into mixture	
Processes, tasks and activities covered	Batch manufacture of a chemical substance or formulation (including	
	polymerisation reactions).	
2. Operational conditions and risk management measures		

Operating Conditions	Physical state:Liquid.	
	General operating conditions:	
	Duration of use: 8 hours/day;	
	Emission days per year: <= 225 days per year;	
Risk management measures	Under the operational conditions described above the following risk management	
	measures apply:	
	General risk management measures:	
	Human health:	
	Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for	
	specific glove material.;	
	Environmental:	
	Waste Water treatment - Incineration;	
Waste management measures	Do not apply industrial sludge to natural soils;	
waste management measures	Prevent leaks and prevent soil / water pollution caused by leaks;	
	revent teaks and prevent son? water pondition eadsed by leaks,	
3. Prediction of exposure		
Prediction of exposure	sure Human and environmental exposures are not expected to exceed the DNELs and	
_	PNECs when the identified risk management measures are adopted.	

1. Title		
Substance identification	bis-[4-(2,3-epoxipropoxi)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;	
Exposure Scenario Name	Industrial Use of Adhesives	
Lifecycle Stage	Use at industrial sites	
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non- dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article	
Processes, tasks and activities covered	applicator gun. Application with a wipe. Transfers without dedicated controls, including loading, filling, dumping, bagging.	
2. Operational conditions and risk mana	0	
Operating Conditions	Physical state:Liquid. General operating conditions: Duration of use: 8 hours/day; Emission days per year: 220 days/year; Frequency of exposure at workplace [for one worker]: 5 days/week;	
Risk management measures	Under the operational conditions described above the following risk management measures apply:  General risk management measures:  Human health:  Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.;  Environmental:  None needed;	
Waste management measures	Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater;	
3. Prediction of exposure		
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.	

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com