

Safety Data Sheet

Copyright,2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	26-5022-4	Version number:	6.01
Issue Date:	2020/10/28	Supercedes Date:	2020/03/09

SECTION 1: Identification

1.1. Product identifier

5798A-MT QSIII

Product Identification Numbers 78-8126-0326-0 80-6112-3231-7

1.2. Recommended use and restrictions on use

Recommended use

Electrical

1.3. Supplier's details

Company:	3M Canada Company	
Division:	Electrical Markets Division	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1

Telephone:	(800) 364-3577
E Mail:	

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

06-4861-8, 40-0153-3, 26-2852-7

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright,2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	40-0153-3	Version number:	1.02
Issue Date:	2022/09/21	Supercedes Date:	2021/02/10

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification	
----------------------------------	--

1.1. Product identifier

3M Sheath Wrap Roll

Product Identification Numbers	Product	Identification	Numbers
--------------------------------	---------	----------------	---------

CE-1006-9128-2	CE-1006-9129-0	UU-0102-5729-1	UU-0102-5730-9	UU-0102-5913-1
UU-0102-5914-9	UU-0102-5915-6	UU-0102-5936-2	UU-0102-5937-0	UU-0102-5938-8
UU-0102-6051-9	UU-0102-6052-7	UU-0112-2563-6		

1.2. Recommended use and restrictions on use

Intended Use Industrial use

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company	
Division:	Electronics & Energy Business Spons	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1
Telephone:	(800) 364-3577	
Website:	www.3M.ca	

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Respiratory Sensitizer: Category 1. Skin Sensitizer: Category 1. Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements Signal word Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure: respiratory system

Precautionary statements

Prevention:

Do not breathe dust/fume/gas/mist/vapours/spray. In case of inadequate ventilation wear respiratory protection. Wear protective gloves. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Oxide glass chemicals	65997-17-3	40 - 70	Glass, oxide, chemicals
Polymer	Trade Secret	30 - 60	Not Applicable
Iron Oxide (FE3O4)	1317-61-9	1 - 5	Iron oxide (Fe3O4)
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	1 - 5 Trade Secret *	Benzene, 1,1'-methylenebis[4-isocyanato-
Diphenylmethane-2,4'-	5873-54-1	0.5 - 1.5 Trade Secret *	Benzene, 1-isocyanato-2-[(4-
diisocyanate			isocyanatophenyl)methyl]-
CHROMIUM (CR+6)	18540-29-9	0.001 - 0.02	No Data Available

Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

No need for first aid is anticipated.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide Hydrogen Cyanide Oxides of Nitrogen

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

Condition

During Combustion

During Combustion

During Combustion

During Combustion

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon

as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-Methylenebis(phenyl	101-68-8	ACGIH	TWA:0.005 ppm	
isocyanate)				
CHROMIUM (HEXAVALENT COMPOUNDS)	18540-29-9	ACGIH	TWA(as Cr(IV), inhalable fraction):0.0002 mg/m3;STEL(as Cr(IV), inhalable fraction):0.0005 mg/m3	
CHROMIUM (VI), WATER SOLUBLE COMPOUNDS	18540-29-9	ACGIH	TWA(as Cr(IV), inhalable fraction):0.0002 mg/m3;TWA(as Cr):0.05 mg/m3;STEL(as Cr(IV), inhalable fraction):0.0005 mg/m3	Dermal/Respiratory Sensitizer
Chromium(6+), insoluble compounds	18540-29-9	ACGIH	TWA(as Cr):0.01 mg/m3	
Water-soluble inorganic Cr(6+) compounds	18540-29-9	ACGIH	TWA(as Cr):0.05 mg/m3	
Oxide glass chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection

equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

intormation on basic physical and chemical property	
Physical state	Solid
Specific Physical Form:	Resin Sat.Glass Tape
Colour	Black
Odour	Slight Odour
Odour threshold	Not Applicable
рН	No Data Available
Melting point/Freezing point	Not Applicable
Boiling point	Not Applicable
Flash Point	174.4 °C [Test Method:Closed Cup]
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapour Pressure	No Data Available
Vapour Density and/or Relative Vapour Density	No Data Available
Density	No Data Available
Relative density	Not Applicable
Water solubility	Nil
Solubility- non-water	Nil [Details:water sulubility]
Partition coefficient: n-octanol/ water	No Data Available

Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	Not Applicable
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid Sparks and/or flames

10.5. Incompatible materials

Alcohols Amines Strong bases Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u> None known **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Chromium Hexavalent Compounds	18540-29-9	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Chromium[VI] compounds	18540-29-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Hexavalent chromium compounds	18540-29-9	Cancer hazard	OSHA Carcinogens
Glass Wool Fibers (Inhalable), Certain	65997-17-3	Anticipated human carcinogen	National Toxicology Program Carcinogens

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

	Value	Species	Route	Name
ted ATE >5,000 mg/kg	No data available; calculated ATE >5,000 m		Dermal	Overall product
uted ATE >2,000 - =5,000	No data available; calculated ATE >2,000 -		Ingestion	Overall product
	mg/kg			
,000 mg/kg	LD50 estimated to be > 5,000 mg/kg		Dermal	Oxide glass chemicals
00 - 5,000 mg/kg	LD50 estimated to be 2,000 - 5,000 mg/kg		Ingestion	Oxide glass chemicals
,000 mg/kg	LD50 estimated to be > 5,000 mg/kg		Dermal	Polymer
00 - 5,000 mg/kg	LD50 estimated to be 2,000 - 5,000 mg/kg		Ingestion	Polymer
	LD50 > 5,000 mg/kg	Rabbit	Dermal	P,P'-Methylenebis(phenyl isocyanate)
	LC50 0.368 mg/l	Rat	Inhalation-	P,P'-Methylenebis(phenyl isocyanate)
			Dust/Mist	
			(4 hours)	
	LD50 31,600 mg/kg	Rat	Ingestion	P,P'-Methylenebis(phenyl isocyanate)
	LD50 3,100 mg/kg	Not	Dermal	Iron Oxide (FE3O4)
		available		
	LD50 3,700 mg/kg	Not	Ingestion	Iron Oxide (FE3O4)
		available	-	
	LD50 > 5,000 mg/kg	Rabbit	Dermal	Diphenylmethane-2,4'-diisocyanate
	LC50 0.368 mg/l	Rat	Inhalation-	Diphenylmethane-2,4'-diisocyanate
			Dust/Mist	
			(4 hours)	
	LD50 31,600 mg/kg	Rat	Ingestion	Diphenylmethane-2,4'-diisocyanate
) - 1,000 mg/kg	LD50 estimated to be 200 - 1,000 mg/kg		Dermal	CHROMIUM (CR+6)
0.05 mg/l	LC50 estimated to be 0 - 0.05 mg/l		Inhalation-	CHROMIUM (CR+6)
-			Dust/Mist	• •
50 mg/kg	LD50 estimated to be 5 - 50 mg/kg		Ingestion	CHROMIUM (CR+6)
0.05 mg/	LD50 estimated to be 200 - 1,000 LC50 estimated to be 0 - 0.05 mg/	Rat	Ingestion Dermal Inhalation- Dust/Mist	CHROMIUM (CR+6) CHROMIUM (CR+6)

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Oxide glass chemicals	Professio nal judgeme nt	No significant irritation
P,P'-Methylenebis(phenyl isocyanate)	official classifica tion	Irritant
Iron Oxide (FE3O4)	Rabbit	No significant irritation
Diphenylmethane-2,4'-diisocyanate	official classifica tion	Irritant
CHROMIUM (CR+6)	Human	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgeme	
	nt	
P,P'-Methylenebis(phenyl isocyanate)	official	Severe irritant
	classifica	
	tion	
Iron Oxide (FE3O4)	Rabbit	No significant irritation
Diphenylmethane-2,4'-diisocyanate	official	Severe irritant
	classifica	
	tion	
CHROMIUM (CR+6)	similar	Corrosive
	health	
	hazards	

Skin Sensitization

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	official classifica	Sensitizing
	tion	
Iron Oxide (FE3O4)	Human	Not classified
Diphenylmethane-2,4'-diisocyanate	official	Sensitizing
	classifica	
	tion	
CHROMIUM (CR+6)	Human	Sensitizing
	and	
	animal	

Respiratory Sensitization

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	Human	Sensitizing
Diphenylmethane-2,4'-diisocyanate	Human	Sensitizing
CHROMIUM (CR+6)	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
P,P'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Iron Oxide (FE3O4)	In Vitro	Not mutagenic
Diphenylmethane-2,4'-diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
CHROMIUM (CR+6)	In Vitro	Some positive data exist, but the data are not

3M Sheath Wrap Roll

		sufficient for classification
CHROMIUM (CR+6)	In vivo	Mutagenic

Carcinogenicity

Name	Route	Species	Value
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Iron Oxide (FE3O4)	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Diphenylmethane-2,4'-diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
CHROMIUM (CR+6)	Not Specified	Human	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s
Diphenylmethane-2,4'-diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s
CHROMIUM (CR+6)	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.0002 mg/l	3 generation
CHROMIUM (CR+6)	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.0002 mg/l	3 generation
CHROMIUM (CR+6)	Inhalation	Not classified for development	Rat	NOAEL 0.0002 mg/l	3 generation
CHROMIUM (CR+6)	Ingestion	Toxic to female reproduction	Mouse	LOAEL 6 mg/kg/day	12 weeks
CHROMIUM (CR+6)	Ingestion	Toxic to male reproduction	Mouse	LOAEL 6 mg/kg/day	12 weeks
CHROMIUM (CR+6)	Ingestion	Toxic to development	Mouse	LOAEL 57 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
Diphenylmethane-2,4'- diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
CHROMIUM (CR+6)	Dermal	kidney and/or bladder	Not classified	Human	NOAEL Not available	
CHROMIUM (CR+6)	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
CHROMIUM (CR+6)	Ingestion	kidney and/or bladder	Causes damage to organs	Human	NOAEL Not available	
CHROMIUM (CR+6)	Ingestion	hematoppoitic system liver	Not classified	Human	NOAEL Not available	
CHROMIUM (CR+6)	Ingestion	nervous system	Not classified	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Iron Oxide (FE3O4)	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Diphenylmethane-2,4'- diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
CHROMIUM (CR+6)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
CHROMIUM (CR+6)	Inhalation	immune system	Not classified	Rat	NOAEL Not available	90 days
CHROMIUM (CR+6)	Inhalation	heart endocrine system hematopoietic system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 0.02 mg/l	2 years
CHROMIUM (CR+6)	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 100 mg/kg/day	28 days
CHROMIUM (CR+6)	Ingestion	nervous system	Not classified	Rat	LOAEL 98 mg/kg/day	28 days
CHROMIUM (CR+6)	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
CHROMIUM (CR+6)	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL Not available	1 generation

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	40-0153-3	Version number:	1.02
Issue Date:	2022/09/21	Supercedes Date:	2021/02/10

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	26-2852-7	Version number:	8.00
Issue Date:	2025/04/29	Supercedes Date:	2022/06/24

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M[™] Cable Preparation Kit CC-2 (Can)

1.2. Recommended use and restrictions on use

Intended Use

Electrical, SOLVENT SOAKED PADS FOR CLEANING CABLE

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company	
Division:	Electrical Markets Division	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1
Telephone:	(800) 364-3577	
Website:	www.3M.ca	

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 4. Skin Corrosion/Irritation: Category 2. Skin Sensitizer: Category 1B.

2.2. Label elements Signal word Warning

Symbols Exclamation mark |

Pictograms



Hazard Statements Combustible Liquid Causes skin irritation. May cause an allergic skin reaction.

Precautionary statements

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
HYDROTREATED HEAVY	64742-48-9	50 - 70	Naphtha, petroleum, hydrotreated heavy
NAPHTHA (PETROLEUM)			
Cotton Pads	None	25 - 40	Not Applicable
D-LIMONENE	5989-27-5	5 - 20	Cyclohexene, 1-methyl-4-(1-
			methylethenyl)-, (R)-

Cotton Pads is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
D-LIMONENE	5989-27-5	AIHA	TWA:165.5 mg/m3(30 ppm)	
	(1 T 1 (¹ 1 1	· · · ·		

ACGIH : American Conference of Governmental Industrial Hygienists AIHA : American Industrial Hygiene Association CMRG : Chemical Manufacturer's Recommended Guidelines TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Nitrile Rubber Polyvinyl Alcohol (PVA) Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

pperues		
Solid (Lint-free cloths soaked with liquid)		
Cloth pads soaked in liquid in can or bag		
White		
Moderate Citrus		
No Data Available		
7		
No Data Available		
193.3 °С - 248.9 °С		
62.2 °C [Test Method:Closed Cup]		
No Data Available		
Flammable Liquid: Category 4.		
No Data Available		
No Data Available		
< 133.3 Pa [@ 25 °C]		
> 1 [<i>Ref Std</i> :AIR=1]		
0.76 g/ml		
0.76 [<i>Ref Std</i> :WATER=1]		
Nil		
No Data Available		
Image: No Data Available 2 mm2/sec		
Approximately 740 %		
No Data Available		
760 g/l		
No Data Available		

Particle Characteristics

Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u> Carbon monoxide Carbon dioxide Condition Not Specified Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent regulatory authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-		No data available; calculated ATE >50 mg/l
	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Dermal	similar	LD50 > 2,200 mg/kg
		compoun	
		ds	
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Ingestion	similar	LD50 > 15,000 mg/kg
		compoun	
		ds	
D-LIMONENE	Inhalation-	Mouse	LC50 > 3.14 mg/l
	Vapor (4		
	hours)		
D-LIMONENE	Dermal	Rabbit	LD50 > 5,000 mg/kg
D-LIMONENE	Ingestion	Rat	LD50 4,400 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar compoun ds	Mild irritant
D-LIMONENE	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar compoun ds	No significant irritation
D-LIMONENE	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	similar	Not classified
	compoun	
	ds	
D-LIMONENE	Mouse	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In Vitro	Not mutagenic
D-LIMONENE	In Vitro	Not mutagenic
D-LIMONENE	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
D-LIMONENE	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
D-LIMONENE	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	premating & during gestation
D-LIMONENE	Ingestion	Not classified for development	Multiple animal species	NOAEL 591 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
HYDROTREATED	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
HEAVY NAPHTHA			data are not sufficient for	health	available	
(PETROLEUM)			classification	hazards		
D-LIMONENE	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
			data are not sufficient for	health	available	
			classification	hazards		
D-LIMONENE	Ingestion	nervous system	Not classified		NOAEL Not	
					available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
D-LIMONENE	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 75 mg/kg/day	103 weeks
D-LIMONENE	Ingestion	liver	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
D-LIMONENE	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	103 weeks

Aspiration Hazard

Name	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Aspiration hazard
D-LIMONENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The

components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard ClassificationHealth: 2Flammability: 2Physical Hazard: 0Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	26-2852-7	Version number:	8.00
Issue Date:	2025/04/29	Supercedes Date:	2022/06/24

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	06-4861-8	Version number:	11.06
Issue Date:	2025/04/30	Supercedes Date:	2021/06/08

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION	1: Identification
SECTOR	1. Iuchuncanon

1.1. Product identifier

3MTM P55/R Lubricant, Red

1.2. Recommended use and restrictions on use

Intended Use Electrical

Specific Use ELECTRICAL LUBRICATING GREASE

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company	
Division:	Electrical Markets Division	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1
Telephone:	(800) 364-3577	
Website:	www.3M.ca	

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

2.2. Label elements Signal word Not applicable.

Symbols Not applicable

Pictograms

Not applicable

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
1,1,2,3,3,3-HEXAFLUORO-1-	69991-67-9	95 - 98	1-Propene, 1,1,2,3,3,3-hexafluoro-,
PROPENE, OXIDIZED,			oxidized, polymd.
POLYMD.			
Synthetic Amorphous Silica,	112945-52-5	<= 5	Fumed amorphous silica, crystalline-free
Fumed, Crystalline Free			
C.I. PIGMENT RED 170	2786-76-7	<= 0.05	No Data Available

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbonyl Fluoride Carbon monoxide Condition During Combustion During Combustion

Carbon dioxide	During Combustion
Hydrogen Fluoride	During Combustion
Oxides of Nitrogen	During Combustion

5.4. Special protection actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Avoid release to the environment. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid			
Specific Physical Form:	Paste			
Colour	Red			
Odour	Odourless			
Odour threshold	Not Applicable			
рН	Not Applicable			
Melting point/Freezing point	Not Applicable			
Boiling point	270 °C [Details: MITS data (per supplier info)]			
Flash Point	Flash point > 93 °C (200 °F)			
Evaporation rate	No Data Available			
Flammability	Not Applicable			
Flammable Limits(LEL)	Not Applicable			
Flammable Limits(UEL)	Not Applicable			
Vapour Pressure	<=1.3 Pa			
Relative Vapour Density	No Data Available			
Density	No Data Available			
Relative density	Approximately 1.99 [<i>Ref Std</i> :WATER=1]			
Water solubility	Nil			
Solubility- non-water	Not Applicable			
Partition coefficient: n-octanol/ water	No Data Available			
Autoignition temperature	Not Applicable			
Decomposition temperature	Not Applicable			
Kinematic Viscosity	No Data Available			
Volatile Organic Compounds	No Data Available			
Percent volatile	0 %			
VOC Less H2O & Exempt Solvents	No Data Available			
Average particle size	No Data Available			
Bulk density	No Data Available			
Molecular weight	No Data Available			
Softening point	No Data Available			
ticle Characteristics	Not Applicable			

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Strong acids Strong bases Reactive metals

No Data Available

10.6. Hazardous decomposition products

Substance None known. Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent regulatory authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation: No known health effects.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

No known health effects.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
1,1,2,3,3,3-HEXAFLUORO-1-PROPENE, OXIDIZED, POLYMD.	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
1,1,2,3,3,3-HEXAFLUORO-1-PROPENE, OXIDIZED, POLYMD.	Ingestion	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Human	Not classified
	and	
	animal	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	line Free Not Mouse Some positive data exist, but the data ar		Some positive data exist, but the data are not
	Specified		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation

Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard ClassificationHealth: 0Flammability: 1Physical Hazard: 0Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	06-4861-8	Version number:	11.06
Issue Date:	2025/04/30	Supercedes Date:	2021/06/08

Reason for Reissue

Conversion to GHS format SDS.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca