Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	33-4674-9	**Version number:**	3.00
Issue Date:	2025/12/16	**Supersedes Date:**	2020/10/26

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier
3M™ Paint Protection Film Installation Gel, 38590, 38591

Product Identification Numbers
60-4550-8388-5 60-4550-8389-3

1.2. Recommended use and restrictions on use

Intended Use
Automotive

Specific Use
Installation aide for professionally installed paint protection film.

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Automotive Aftermarket
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Not classified according to the Canadian Hazardous Products Regulation.

2.2. Label elements
Signal word
Not applicable.

Symbols
Not applicable

Pictograms
Not applicable

2.3. Other hazards
None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Water	7732-18-5	60 - 100	Water
Isopropyl Alcohol	67-63-0	1 - 5	2-Propanol
5-chloro-2-methyl-4-isothiazoline-3-one	26172-55-4	< 0.01	3(2H)-Isothiazolone, 5-chloro-2-methyl-
2-Methyl-4-isothiazoline-3-one	2682-20-4	< 0.001	3(2H)-Isothiazolone, 2-methyl-

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
If exposed, wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Unsuitable extinguishing media
None Determined

5.3. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition

Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.4. Special protection actions for fire-fighters
Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial or professional use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities
No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection
None required.

Skin/hand protection
No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Colourless
Odour	Slight Alcohol
Odour threshold	*No Data Available*
pH	6.8
Melting point/Freezing point	*No Data Available*
Boiling point	100 ºC
Flash Point	No flash point [*Test Method:*Closed Cup]
Evaporation rate	*No Data Available*
Flammability	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapour Pressure	*No Data Available*
Relative Vapour Density	*No Data Available*
Density	0.829 g/ml
Relative density	0.829 [*Ref Std:*WATER=1]
Water solubility	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	6,634 mm2/sec
Volatile Organic Compounds	2 % weight [*Test Method:*calculated per CARB title 2]
Volatile Organic Compounds	<=45 g/l [*Test Method:*calculated SCAQMD rule 443.1]
Percent volatile	99.9 % weight

VOC Less H2O & Exempt Solvents	<=250 g/l [*Test Method:*calculated SCAQMD rule 443.1]
Molecular weight	*Not Applicable*

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
None known.

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	**Condition**
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
5-chloro-2-methyl-4-isothiazoline-3-one	Dermal	Rabbit	LD50 87 mg/kg
5-chloro-2-methyl-4-isothiazoline-3-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.171 mg/l
5-chloro-2-methyl-4-isothiazoline-3-one	Ingestion	Rat	LD50 40 mg/kg
2-Methyl-4-isothiazoline-3-one	Dermal	Rabbit	LD50 87 mg/kg
2-Methyl-4-isothiazoline-3-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.171 mg/l
2-Methyl-4-isothiazoline-3-one	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isopropyl Alcohol	Multiple animal species	No significant irritation
5-chloro-2-methyl-4-isothiazoline-3-one	Rabbit	Corrosive
2-Methyl-4-isothiazoline-3-one	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Isopropyl Alcohol	Rabbit	Severe irritant
5-chloro-2-methyl-4-isothiazoline-3-one	Rabbit	Corrosive
2-Methyl-4-isothiazoline-3-one	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Isopropyl Alcohol	Guinea pig	Not classified
5-chloro-2-methyl-4-isothiazoline-3-one	Human and animal	Sensitizing
2-Methyl-4-isothiazoline-3-one	Human and animal	Sensitizing

Photosensitization

Name	Species	Value
5-chloro-2-methyl-4-isothiazoline-3-one	Human and animal	Not sensitizing
2-Methyl-4-isothiazoline-3-one	Human and animal	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
5-chloro-2-methyl-4-isothiazoline-3-one	In vivo	Not mutagenic
5-chloro-2-methyl-4-isothiazoline-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Methyl-4-isothiazoline-3-one	In vivo	Not mutagenic
2-Methyl-4-isothiazoline-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
5-chloro-2-methyl-4-isothiazoline-3-one	Dermal	Mouse	Not carcinogenic
5-chloro-2-methyl-4-isothiazoline-3-one	Ingestion	Rat	Not carcinogenic
2-Methyl-4-isothiazoline-3-one	Dermal	Mouse	Not carcinogenic
2-Methyl-4-isothiazoline-3-one	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
5-chloro-2-methyl-4-isothiazoline-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
5-chloro-2-methyl-4-isothiazoline-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
5-chloro-2-methyl-4-isothiazoline-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours

Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
5-chloro-2-methyl-4-isothiazoline-3-one	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
2-Methyl-4-isothiazoline-3-one	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.
Health: 2 **Flammability:** 0 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	33-4674-9	**Version number:**	3.00
Issue Date:	2025/12/16	**Supersedes Date:**	2020/10/26

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca