

Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 26-0144-1
 Version number:
 6.04

 Revision date:
 07/04/2025
 Supersedes date:
 14/02/2019

Transportation version number:

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M Scotchcast[™] Electrical Resin 235 (A & B)

Product Identification Numbers

80-6116-2518-9

7100151599

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Electrical

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

24-9198-3, 24-9173-6

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms





Contains:

reaction product: bisphenol-A-(epichlorhydrin); Dodecenylsuccinic anhydride

HAZARD STATEMENTS:

H315 Causes skin irritation. H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours. P280E Wear protective gloves.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

GB Kit Information: CLP Percent Unknown information was added. GB Label: CLP Ingredients - kit components information was added.

Label: CLP Percent Unknown - Kit information was deleted.
Label: CLP Ingredients - kit components information was deleted.

Section 1: E-mail address information was modified.

Section 02: CLP Physical and Health Hazard Statements information was modified.

Label: CLP Classification information was modified.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 24-9173-6 Version number: 9.00 **Revision date:** 28/10/2025 Supersedes date: 27/10/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M ScotchcastTM Electrical Resin 235 Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Electrical

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms





Ingredient CAS Nbr EC No. % by Wt

reaction product: bisphenol-A-(epichlorhydrin) 25068-38-6 500-033-5 80 - 100

HAZARD STATEMENTS:

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273 Avoid release to the environment.

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation
			(EC) No. 1272/2008 [CLP], as
			amended for GB

reaction product: bisphenol-A- (epichlorhydrin)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5	l .	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
			Aquatic Chronic 2, H411
C.I. PIGMENT YELLOW 14	(CAS-No.) 5468-75-7 (EC-No.) 226-789-3	< 5	Substance not classified as hazardous
3-Hydroxy-4-[(2-methyl-5-nitrophenyl)azo]-N-phenylnaphthalene-2-carboxamide	(CAS-No.) 6448-95-9 (EC-No.) 229-245-3	< 5	Substance not classified as hazardous

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
1 1	1	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionAldehydes.During combustion.Carbon monoxideDuring combustion.Carbon dioxide.During combustion.Hydrogen ChlorideDuring combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Information on basic physical and chemical properties					
Physical state	Liquid.				
Specific Physical Form:	Resin				
Colour	Red				
Odor	Epoxy				
Odour threshold	No data available.				
Melting point/freezing point	No data available.				
Boiling point/boiling range	260 °C [Test Method: Tested per ASTM protocol]				
Flammability	Not applicable.				
Flammable Limits(LEL)	No data available.				
Flammable Limits(UEL)	No data available.				
Flash point	248.9 °C [Test Method:Pensky-Martens Closed Cup]				
Autoignition temperature	No data available.				
Decomposition temperature	No data available.				
рН					
Kinematic Viscosity	10,776 mm ² /sec				
Water solubility	Negligible				
Solubility- non-water	No data available.				
Partition coefficient: n-octanol/water	No data available.				
Vapour pressure	< 186,158.4 Pa [@ 55 °C] [Test Method: Tested per ASTM				
	protocol] [Ref Std: AIR=1]				
Density	No data available.				
Relative density	1.16 [Test Method:Tested per ASTM protocol] [Ref				
	Std:WATER=1]				
Relative Vapour Density	Nil				
Particle Characteristics	Not applicable.				
	·				

9.2. Other information

9.2.2 Other safety characteristics

Average particle sizeNo data available.Bulk densityNo data available.EU Volatile Organic CompoundsNo data available.Evaporation rateNo data available.Molecular weightNo data available.Percent volatileNo data available.Softening pointNo data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

No data available.

None known.

10.6 Hazardous decomposition products

Substance

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

3M ScotchcastTM Electrical Resin 235 Part A

reaction product: bisphenol-A-(epichlorhydrin)	Dermal	Rat	LD50 > 1,600 mg/kg
reaction product: bisphenol-A-(epichlorhydrin)	Ingestion	Rat	LD50 > 1,000 mg/kg
C.I. PIGMENT YELLOW 14	Dermal	Rat	LD50 > 1,710 mg/kg
C.I. PIGMENT YELLOW 14	Inhalation-	Rat	LC50 > 4.25 mg/l
	Dust/Mist		
	(4 hours)		
C.I. PIGMENT YELLOW 14	Ingestion	Rat	LD50 2,228 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Rabbit	Mild irritant
C.I. PIGMENT YELLOW 14	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Rabbit	Moderate irritant
C.I. PIGMENT YELLOW 14	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Human and animal	Sensitising
C.I. PIGMENT YELLOW 14	Multiple animal species	Not classified

Respiratory Sensitisation

Name	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
reaction product: bisphenol-A-(epichlorhydrin)	In vivo	Not mutagenic
reaction product: bisphenol-A-(epichlorhydrin)	In Vitro	Some positive data exist, but the data are not sufficient for classification
C.I. PIGMENT YELLOW 14	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
reaction product: bisphenol-A-(epichlorhydrin)	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
C.I. PIGMENT YELLOW 14	Ingestion	Multiple	Not carcinogenic
		animal	
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
reaction product: bisphenol-A- (epichlorhydrin)	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
reaction product: bisphenol-A-	Ingestion	Not classified for male reproduction	Rat	NOAEL 750	2 generation

(epichlorhydrin)				mg/kg/day	
reaction product: bisphenol-A-	Dermal	Not classified for development	Rabbit	NOAEL 300	during
(epichlorhydrin)				mg/kg/day	organogenesis
reaction product: bisphenol-A- (epichlorhydrin)	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
C.I. PIGMENT YELLOW 14	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
C.I. PIGMENT YELLOW 14	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
C.I. PIGMENT YELLOW 14	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data is currently available or the data is not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
reaction product: bisphenol-A- (epichlorhydrin)	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
reaction product: bisphenol-A- (epichlorhydrin)	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
reaction product: bisphenol-A- (epichlorhydrin)	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
C.I. PIGMENT YELLOW 14	Inhalation	respiratory system	Not classified	Rat	NOAEL 157 mg/m³	21 days
C.I. PIGMENT YELLOW 14	Inhalation	heart endocrine system blood liver immune system nervous system eyes kidney and/or bladder	Not classified	Rat	NOAEL 410 mg/m³	21 days
C.I. PIGMENT YELLOW 14	Ingestion	heart endocrine system gastrointestinal tract hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
reaction product:	25068-38-6	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bisphenol-A-						
(epichlorhydrin)						
reaction product:	25068-38-6	Water flea	Estimated	48 hours	LC50	1.8 mg/l
bisphenol-A-						
(epichlorhydrin)						
reaction product:	25068-38-6	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
bisphenol-A- (epichlorhydrin)						
reaction product:	25068-38-6	Green algae	Experimental	72 hours	EC50	>11 mg/l
bisphenol-A-	23008-38-0	Green algae	Experimental	72 Hours	ECSO	711 Hig/1
(epichlorhydrin)						
reaction product:	25068-38-6	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bisphenol-A-	23000 30 0	Green argue	Experimental	72 110415	I TOLE	1.2
(epichlorhydrin)						
reaction product:	25068-38-6	Water flea	Experimental	21 days	NOEC	0.3 mg/l
bisphenol-A-			1			
(epichlorhydrin)						
3-Hydroxy-4-[(2-	6448-95-9	Activated sludge	Estimated	3 hours	NOEC	>1,000 mg/l
methyl-5-						
nitrophenyl)azo]-						
N- phenylnaphthalene-						
2-carboxamide						
3-Hydroxy-4-[(2-	6448-95-9	Golden Orfe	Estimated	96 hours	LC50	>100 mg/l
methyl-5-	0110 35 3	Golden Olic	Estimated	yo nours	Lesv	100 mg/1
nitrophenyl)azo]-						
N-						
phenylnaphthalene-						
2-carboxamide						
3-Hydroxy-4-[(2-	6448-95-9	Green algae	Estimated	72 hours	EC50	>100 mg/l
methyl-5-						
nitrophenyl)azo]- N-						
phenylnaphthalene-						
2-carboxamide						
3-Hydroxy-4-[(2-	6448-95-9	Water flea	Estimated	48 hours	EC50	>100 mg/l
methyl-5-						
nitrophenyl)azo]-						
N-						
phenylnaphthalene- 2-carboxamide						
3-Hydroxy-4-[(2-	6448-95-9	Green algae	Estimated	72 hours	NOEC	100 mg/l
3-Hydroxy-4-[(2- methyl-5-	0440-73-7	Green algae	Estimated	/2 nours	INOEC	100 mg/i
nitrophenyl)azo]-						
N-						
phenylnaphthalene-						
2-carboxamide						
3-Hydroxy-4-[(2-	6448-95-9	Water flea	Estimated	21 days	NOEC	100 mg/l
methyl-5-						
nitrophenyl)azo]-						
N-	<u> </u>				1	

phenylnaphthalene- 2-carboxamide						
C.I. PIGMENT YELLOW 14	5468-75-7	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
C.I. PIGMENT YELLOW 14	5468-75-7	Green algae	Analogous Compound	72 hours	EC50	>100 mg/l
C.I. PIGMENT YELLOW 14	5468-75-7	Water flea	Analogous Compound	48 hours	EC50	>100 mg/l
C.I. PIGMENT YELLOW 14	5468-75-7	Zebra Fish	Analogous Compound	96 hours	LC50	>100 mg/l
C.I. PIGMENT YELLOW 14	5468-75-7	Green algae	Analogous Compound	72 hours	NOEC	100 mg/l
C.I. PIGMENT YELLOW 14	5468-75-7	Water flea	Analogous Compound	21 days	NOEC	100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
reaction product: bisphenol-A- (epichlorhydrin)	25068-38-6	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
reaction product: bisphenol-A- (epichlorhydrin)	25068-38-6	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
3-Hydroxy-4-[(2-methyl-5-nitrophenyl)azo]-N-phenylnaphthalene-2-carboxamide	6448-95-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
C.I. PIGMENT YELLOW 14	5468-75-7	Analogous Compound Biodegradation	28 days	BOD	16 %BOD/ThOD	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
reaction product: bisphenol-A- (epichlorhydrin)	25068-38-6	Experimental Bioconcentration		Log Kow	3.242	
3-Hydroxy-4-[(2-methyl-5- nitrophenyl)azo]- N- phenylnaphthalene- 2-carboxamide	6448-95-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
C.I. PIGMENT YELLOW 14	5468-75-7	Analogous Compound BCF - Fish	28 days	Bioaccumulation factor	≤6.2	OECD305-Bioconcentration

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
3-Hydroxy-4-[(2-	6448-95-9	Estimated Mobility	Koc	91,000 l/kg	ACD/Labs ChemSketch™
methyl-5-		in Soil			
nitrophenyl)azo]-N-					
phenylnaphthalene-					
2-carboxamide					

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.

Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements	
E2 Hazardous to the Aquatic	200	500	
environment			

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Revision information:

GB Section 02: CLP Ingredient table information was modified.

GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was added.

GB Section 04: Information on toxicological effects information was modified.

Label: CLP Precautionary - Disposal information was deleted.

Label: CLP Precautionary - Response information was modified.

3M ScotchcastTM Electrical Resin 235 Part A

- Section 02: Label Elements: GB Percent Unknown information was deleted.
- Section 08: Personal Protection Apron Statement information was added.
- Section 09: Flammability information information was added.
- Section 09: Particle Characteristics N/A information was added.
- Section 1: E-mail address information was modified.
- Section 11: Health Effects Inhalation information information was modified.
- Section 13: Standard Phrase Category Waste GHS information was modified.
- Section 15: Seveso Hazard Category Text information was added.
- Section 15: Seveso Substance Text information was deleted.
- Section 3: Composition/Information of ingredients table information was modified.
- Section 5: Hazardous combustion products table information was modified.
- Section 6: Accidental release personal information information was modified.
- Section 8: Appropriate Engineering controls information information was modified.
- Section 8: Eye/face protection information information was modified.
- Section 8: Personal Protection Respiratory Information information was added.
- Section 8: Personal Protection Skin/body information information was deleted.
- Section 8: Respiratory protection recommended respirators guide information was added.
- Section 8: Respiratory protection recommended respirators information information was added.
- Section 8: Respiratory protection information information was deleted.
- Section 8: Skin protection protective clothing information information was deleted.
- Section 9: Flammability (solid, gas) information information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 24-9198-3 **Version number:** 8.00

Revision date: 28/10/2025 **Supersedes date:** 27/10/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3MTM ScotchcastTM Electrical Resin 235 Part B

Product Identification Numbers

80-6116-2520-5

7100151626

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Electrical

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

3MTM ScotchcastTM Electrical Resin 235 Part B

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS08 (Health Hazard) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
Dodecenylsuccinic anhydride	25377-73-5	246-917-1	30 - 60
maleic anhydride	108-31-6	203-571-6	< 0.09

HAZARD STATEMENTS:

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours. P280E Wear protective gloves.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

Contains 44% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB			
Dodecenylsuccinic anhydride	(CAS-No.) 25377-73-5 (EC-No.) 246-917-1	30 - 60	Acute Tox. 4, H332 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1A, H317 Aquatic Chronic 3, H412			
Glycol Copolymer	Trade Secret	40 - 50	Substance not classified as hazardous			
maleic anhydride	(CAS-No.) 108-31-6 (EC-No.) 203-571-6	< 0.09	EUH071 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372			

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
1	(CAS-No.) 108-31-6 (EC-No.) 203-571-6	(C >= 0.001%) Skin Sens. 1A, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Carbon monoxide

Carbon dioxide.

Irritant vapours or gases.

Condition

During combustion. During combustion.

During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

IngredientCAS Nbr
maleic anhydrideAgency
108-31-6Limit type
UK HSEAdditional comments
TWA: 1 mg/m³; STEL: 3
mg/m³

UK HSE: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.			
Colour	Black			
Odor	Maleic Anhydride			
Odour threshold	No data available.			
Melting point/freezing point	No data available.			
Boiling point/boiling range	>= 93.9 °C [Test Method: Tested per ASTM protocol]			
Flammability	Not applicable.			
Flammable Limits(LEL)	No data available.			
Flammable Limits(UEL)	No data available.			
Flash point	>= 93.9 °C [Test Method:Closed Cup]			
Autoignition temperature	No data available.			
Decomposition temperature	No data available.			
рН	substance/mixture is non-soluble (in water)			
Kinematic Viscosity	1,373 mm ² /sec			
Water solubility	Negligible			
Solubility- non-water	No data available.			
Partition coefficient: n-octanol/water	No data available.			
Vapour pressure	<= 186,158.4 Pa [@ 55 °C]			
Density	1.02 g/ml			
Relative density	1.02 [Ref Std:WATER=1]			
Relative Vapour Density	Not applicable.			
Particle Characteristics	Not applicable.			

9.2. Other information

9.2.2 Other safety characteristics

Average particle size

Bulk density

No data available.

EU Volatile Organic Compounds

Evaporation rate

Molecular weight

Percent volatile

Softening point

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong oxidising agents.

Strong bases.

No data available.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Dodecenylsuccinic anhydride	Dermal	Rabbit	LD50 > 6,200 mg/kg
Dodecenylsuccinic anhydride	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.2 mg/l
Dodecenylsuccinic anhydride	Ingestion	Rat	LD50 2,900 mg/kg
Glycol Copolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Glycol Copolymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
maleic anhydride	Dermal	Rabbit	LD50 2,620 mg/kg
maleic anhydride	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Dodecenylsuccinic anhydride	Rabbit	Mild irritant
maleic anhydride	Human and animal	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Dodecenylsuccinic anhydride	Rabbit	Severe irritant
maleic anhydride	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Dodecenylsuccinic anhydride	similar	Sensitising
	compoun	
	ds	
maleic anhydride	Multiple	Sensitising
	animal	
	species	

Respiratory Sensitisation

Name	Species	Value

Dodecenylsuccinic anhydride	similar	Sensitising
	compoun	
	ds	
maleic anhydride	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Dodecenylsuccinic anhydride	In Vitro	Not mutagenic
maleic anhydride	In vivo	Not mutagenic
maleic anhydride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
maleic anhydride	Ingestion	Not classified for female reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
maleic anhydride	Ingestion	Not classified for male reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
maleic anhydride	Ingestion	Not classified for development	Rat	NOAEL 140 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dodecenylsuccinic anhydride	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
maleic anhydride	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dodecenylsuccinic anhydride	Ingestion	heart endocrine system hematopoietic system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 300 mg/kg/day	14 days
maleic anhydride	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
maleic anhydride	Inhalation	endocrine system hematopoietic system nervous system kidney and/or bladder heart liver eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
maleic anhydride	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
maleic anhydride	Ingestion	liver	Some positive data exist, but the data are not sufficient for	Rat	LOAEL 250 mg/kg/day	183 days

			classification			
maleic anhydride	Ingestion	heart nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
maleic anhydride	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
maleic anhydride	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
maleic anhydride	Ingestion	skin endocrine system immune system eyes respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Dodecenylsuccinic anhydride	25377-73-5	Medaka	Experimental	96 hours	LC50	3.8 mg/l
Dodecenylsuccinic anhydride	25377-73-5	Water flea	Experimental	48 hours	EC50	13 mg/l
Dodecenylsuccinic anhydride	25377-73-5	Green algae	Experimental	72 hours	NOEC	0.76 mg/l
Dodecenylsuccinic anhydride	25377-73-5	Water flea	Experimental	21 days	NOEC	0.31 mg/l
Glycol Copolymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
maleic anhydride	108-31-6	Bacteria	Experimental	18 hours	EC10	44.6 mg/l
maleic anhydride	108-31-6	Rainbow trout	Experimental	96 hours	LC50	75 mg/l
maleic anhydride	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC50	74.4 mg/l
maleic anhydride	108-31-6	Water flea	Hydrolysis Product	48 hours	EC50	93.8 mg/l
maleic anhydride	108-31-6	Water flea	Experimental	21 days	NOEC	10 mg/l
maleic anhydride	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC10	11.8 mg/l

12.2. Persistence and degradability

Material (CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Dodecenylsuccinic 2	25377-73-5		28 days		87 %CO2	Catalogic TM

anhydride		Biodegradation			evolution/THCO2 evolution	
Dodecenylsuccinic anhydride	25377-73-5	Modeled Hydrolysis		Hydrolytic half-life (pH 7)	25 days (t 1/2)	Catalogic [™]
Glycol Copolymer	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
maleic anhydride	108-31-6	Hydrolysis product Biodegradation	25 days		>90 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
maleic anhydride	108-31-6	Experimental Hydrolysis		Hydrolytic half-life	0.37 minutes (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Dodecenylsuccinic	25377-73-5	Modeled		Bioaccumulation	6.2	Catalogic [™]
anhydride		Bioconcentration		factor		
Glycol Copolymer	Trade Secret	Estimated		Bioaccumulation	3.0	
		Bioconcentration		factor		
maleic anhydride	108-31-6	Experimental		Log Kow	-2.61	OECD 107 log Kow shke
		Bioconcentration				flsk mtd

12.4. Mobility in soil

No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

EUH071	Corrosive to the respiratory tract.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

GB Section 02: CLP Ingredient table information was modified.

GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was added.

GB Section 04: Information on toxicological effects information was modified.

Label: CLP Precautionary - Disposal information was deleted.

Label: CLP Precautionary - Response information was modified.

Section 08: Personal Protection - Apron Statement information was added.

Section 11: Acute Toxicity table information was modified.

Section 11: Health Effects - Eye information information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 3: Composition/Information of ingredients table information was modified.

Section 4: First aid for eye contact information information was modified.

Section 6: Accidental release personal information information was modified.

Section 8: Eye/face protection information information was modified.

Section 8: Personal Protection - Skin/body information information was deleted.

Section 8: Respiratory protection - recommended respirators information information was modified.

Section 8: Skin protection - protective clothing information information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.