



Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	41-7494-2	Version number:	2.00
Revision date:	17/09/2024	Supersedes date:	25/08/2021
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™ Scotch-Weld™ Flexible Acrylic Adhesive DP8610NS, Black, Kit

Product Identification Numbers

62-2869-1445-2 62-2869-3630-7

7100232802 7100233359

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Product

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com

Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

41-7445-4, 41-7463-7

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) | GHS07 (Exclamation mark) |

Pictograms



Contains:

2-hydroxyethyl methacrylate; mequinol; benzyltributylammonium chloride; CYCLOHEXYL METHACRYLATE; methyl methacrylate; Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-; Tert-butyl 3,5,5-trimethylperoxyhexanoate.

HAZARD STATEMENTS:

H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280B Wear protective gloves and eye/face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements**Prevention:**

P280B	Wear protective gloves and eye/face protection.
-------	---

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Kit: Component document group number(s) information was modified.
Label: CLP Ingredients - kit components information was modified.
Section 1: Product use information information was modified.
Section 2: <125ml Hazard - Environmental information was added.
Section 2: <125ml Hazard - Health information was modified.
Section 2: <125ml Precautionary - Prevention information was modified.
Section 2: <125ml Precautionary - Response information was modified.
Section 02: CLP Physical and Health Hazard Statements information was modified.
Label: CLP Classification information was modified.
Label: CLP Environmental Hazard Statements information was modified.
Label: CLP Precautionary - Prevention information was modified.
Label: CLP Precautionary - Response information was modified.
Label: Graphic information was modified.
Label: Signal Word information was modified.



Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	41-7445-4	Version number:	2.00
Revision date:	17/12/2024	Supersedes date:	25/08/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Flexible Acrylic Adhesive DP8610NS, Black, Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Product

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.
Telephone: +353 1 280 3555
E Mail: tox.uk@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |

Pictograms**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	236-050-7	0.1 - 10

HAZARD STATEMENTS:

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**<=125 ml Hazard statements**

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements**Prevention:**

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

21% of the mixture consists of components of unknown acute oral toxicity.

Contains 55% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Oxydipropyl dibenzoate	(CAS-No.) 27138-31-4 (EC-No.) 248-258-5	45 - 65	Aquatic Chronic 3, H412
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	(CAS-No.) 25101-28-4	10 - 30	Substance not classified as hazardous
Catalyst.	Trade Secret	1 - 20	Substance not classified as hazardous
BENZOATE ESTERS	None	< 12	Substance not classified as hazardous
Other esters	Trade Secret	< 10	Substance not classified as hazardous
Tert-butyl 3,5,5-trimethylperoxyhexanoate	(CAS-No.) 13122-18-4 (EC-No.) 236-050-7	0.1 - 10	Org. Perox. CD, H242 Skin Sens. 1B, H317 Aquatic Acute 1, H400,M=1 Aquatic Chronic 3, H412

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayedThe most important symptoms and effects based on the CLP classification include:
Allergic skin reaction (redness, swelling, blistering, and itching).**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Grey
Odor	Mild Hydrocarbon
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	>=65.6 °C
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	> 93.3 °C [Test Method: Closed Cup]

Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	18,520 mm ² /sec
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	1.08 g/ml
Relative density	1.08 [Ref Std: WATER=1]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Molecular weight	<i>Not applicable.</i>
Percent volatile	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.
Sparks and/or flames.

10.5 Incompatible materials

Amines.
Strong acids.
Strong bases.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition,

statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Oxydipropyl dibenzoate	Dermal	Rat	LD50 > 2,000 mg/kg
Oxydipropyl dibenzoate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Oxydipropyl dibenzoate	Ingestion	Rat	LD50 3,295 mg/kg
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	Dermal		LD50 estimated to be > 5,000 mg/kg
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Catalyst.	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Catalyst.	Ingestion	Rat	LD50 > 2,000 mg/kg
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Dermal	Rat	LD50 > 2,000 mg/kg
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.8 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Ingestion	Rat	LD50 12,905 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Oxydipropyl dibenzoate	Rabbit	No significant irritation
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Oxydipropyl dibenzoate	Rabbit	No significant irritation
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Oxydipropyl dibenzoate	Guinea pig	Not classified
Catalyst.	Mouse	Not classified
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Oxydipropyl dibenzoate	In Vitro	Not mutagenic
Catalyst.	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Oxydipropyl dibenzoate	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Oxydipropyl dibenzoate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Oxydipropyl dibenzoate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Catalyst.	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxydipropyl dibenzoate	Ingestion	hematopoietic system liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Oxydipropyl dibenzoate	27138-31-4	Fathead minnow	Experimental	96 hours	LC50	3.7 mg/l
Oxydipropyl dibenzoate	27138-31-4	Green algae	Experimental	72 hours	EL50	4.9 mg/l
Oxydipropyl dibenzoate	27138-31-4	Water flea	Experimental	48 hours	EL50	19.31 mg/l
Oxydipropyl dibenzoate	27138-31-4	Green algae	Experimental	72 hours	EC10	0.89 mg/l
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Catalyst.	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Green algae	Experimental	72 hours	ErC50	0.51 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Rainbow trout	Experimental	96 hours	LC50	7.03 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Green algae	Experimental	72 hours	NOEC	0.125 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Water flea	Experimental	21 days	NOEC	0.22 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Activated sludge	Experimental	3 hours	EC50	327.02 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Oxydipropyl dibenzoate	27138-31-4	Experimental Biodegradation	28 days	CO2 evolution	85 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Catalyst.	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	29.1 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2

Catalyst.	Trade Secret	Estimated Photolysis		Photolytic half-life (in air)	1.48 days (t 1/2)	
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Experimental Biodegradation	28 days	BOD	72 %BOD/ThOD	OECD 301D - Closed bottle test
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Experimental Aquatic Inherent Biodegrad.	56 days	BOD	58 %BOD/ThOD	OECD 302A - Modified SCAS Test
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	51 hours (t 1/2)	OECD 111 Hydrolysis func of pH

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Oxydipropyl dibenzoate	27138-31-4	Modeled Bioconcentration		Bioaccumulation factor	8	Catalogic™
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Catalyst.	Trade Secret	Experimental Bioconcentration		Log Kow	2.57	
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Modeled Bioconcentration		Bioaccumulation factor	380	Catalogic™
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Experimental Bioconcentration		Log Kow	5.16	OECD 117 log Kow HPLC method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Catalyst.	Trade Secret	Estimated Mobility in Soil	Koc	<270 l/kg	ACD/Labs ChemSketch™
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Modeled Mobility in Soil	Koc	3,550 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are

complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H242	Heating may cause a fire.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 1: Product use information information was modified.

Section 2: <125ml Hazard - Environmental information was added.

Label: CLP Classification information was modified.

Label: CLP Environmental Hazard Statements information was modified.

Label: CLP Percent Unknown information was added.

Label: CLP Percent Unknown information was modified.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.

Label: Graphic information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 4: First aid for eye contact information information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: glove data value information was modified.

Section 8: Personal Protection - Skin/body information information was added.

Section 8: Personal Protection - Skin/hand information information was modified.

Section 8: Skin protection - protective clothing information information was added.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Odor information was modified.

Section 09: Particle Characteristics N/A information was added.

Section 9: Vapour density value information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Target Organs - Repeated Table information was added.

Section 11: Target Organs - Repeated Table information was deleted.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 14 Multiplier – Main Heading information was deleted.

Section 14 Multiplier – Regulation Data information was deleted.

Section 14 Transport Category – Main Heading information was deleted.

Section 14 Transport Category – Regulation Data information was deleted.

Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was modified.

Section 14 Tunnel Code – Main Heading information was deleted.

Section 14 Tunnel Code – Regulation Data information was deleted.

Section 14 UN Number information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Section 2: No PBT/vPvB information available warning information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	41-7463-7	Version number:	2.00
Revision date:	25/06/2025	Supersedes date:	25/08/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Flexible Acrylic Adhesive DP8610NS, Black, Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Product

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone:	+353 1 280 3555
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) | GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
2-hydroxyethyl methacrylate	868-77-9	212-782-2	5 - 20
CYCLOHEXYL METHACRYLATE	101-43-9	202-943-5	1 - 15
mequinol	150-76-5	205-769-8	< 0.5
methyl methacrylate	80-62-6	201-297-1	< 0.5
benzyltributylammonium chloride	23616-79-7	245-787-3	<= 3
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	95175-93-2		< 3

HAZARD STATEMENTS:

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P280B	Wear protective gloves and eye/face protection.
-------	---

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P280B	Wear protective gloves and eye/face protection.
-------	---

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
--------------------	--

P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

10% of the mixture consists of components of unknown acute oral toxicity.

Contains 17% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Propenoic acid, 2-methyl-, 2-(2-butoxyethoxy)ethyl ester	(CAS-No.) 7328-22-5 (EC-No.) 230-813-8	10 - 30	Substance not classified as hazardous
Kaolin	(CAS-No.) 1332-58-7 (EC-No.) 310-194-1	9 - 30	Substance with a national occupational exposure limit
2-hydroxyethyl methacrylate	(CAS-No.) 868-77-9 (EC-No.) 212-782-2	5 - 20	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Nota D,D
CYCLOHEXYL METHACRYLATE	(CAS-No.) 101-43-9 (EC-No.) 202-943-5	1 - 15	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Sens. 1, H317
Acrylonitrile - butadiene polymer	(CAS-No.) 9003-18-3	1 - 15	Substance not classified as hazardous
Polymeric Methacrylate	Trade Secret	0.1 - 11	Substance not classified as hazardous
Acrylic Copolymer (NJTS Reg. No. 04499600-7448)	Trade Secret	0.6 - 10	Substance not classified as hazardous
methyl methacrylate	(CAS-No.) 80-62-6 (EC-No.) 201-297-1	< 0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 Nota D,D
mequinol	(CAS-No.) 150-76-5 (EC-No.) 205-769-8	< 0.5	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	0.1 - 5	Substance not classified as hazardous
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	(CAS-No.) 95175-93-2	< 3	Skin Irrit. 2, H315 Eye Dam. 1, H318

benzyltributylammonium chloride	(CAS-No.) 23616-79-7 (EC-No.) 245-787-3	<= 3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT SE 3, H335
naphthenic acids, copper salts	(CAS-No.) 1338-02-9 (EC-No.) 215-657-0	<= 0.2	Flam. Liq. 3, H226 Acute Tox. 4, H302 Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=1
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	< 1	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Condition

During combustion.

Carbon dioxide.
Hydrogen Chloride
Hydrogen Fluoride
Oxides of nitrogen.

During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid inhalation of thermal decomposition products. For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Kaolin	1332-58-7	Ireland OELs	TWA(as respirable dust)(8 hours):2 mg/m ³	
Carbon black	1333-86-4	Ireland OELs	TWA(inhalable fraction)(8 hours):3 mg/m ³	
mequinol	150-76-5	Ireland OELs	TWA(8 hours):5 mg/m ³	
methyl methacrylate	80-62-6	Ireland OELs	TWA(8 hours):50 ppm;TWA(8 hours):50 ppm;STEL(15 minutes):100 ppm;STEL(15 minutes):100 ppm	Respiratory/Dermal Sensitizer

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
----------	----------------	-------------------

Polymer laminate

No data available

No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Black
Odor	Mild Acrylate
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	No data available.
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	> 93.3 °C [Test Method:Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	54,000 mm²/sec
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	1.11 g/ml
Relative density	1.11 [Ref Std:WATER=1]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate

No data available.

Molecular weight

Not applicable.

Percent volatile

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
CYCLOHEXYL METHACRYLATE	Dermal	Rat	LD50 > 2,000 mg/kg
CYCLOHEXYL METHACRYLATE	Ingestion	Rat	LD50 12,900 mg/kg
CYCLOHEXYL METHACRYLATE	Inhalation-Vapour	similar compound	LC50 estimated to be 20 - 50 mg/l
Acrylonitrile - butadiene polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile - butadiene polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
benzyltributylammonium chloride	Ingestion	Not available	LD50 500 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
naphthenic acids, copper salts	Dermal	similar compound	LD50 > 2,000 mg/kg
naphthenic acids, copper salts	Ingestion	similar compound	LD50 > 300, < 2,000 mg/kg
methyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
methyl methacrylate	Inhalation-Vapour (4 hours)	Rat	LC50 29.8 mg/l
methyl methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
mequinol	Dermal	Rat	LD50 > 2,000 mg/kg
mequinol	Ingestion	Rat	LD50 1,630 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2-hydroxyethyl methacrylate	Rabbit	Minimal irritation
Kaolin	Professional judgement	No significant irritation
CYCLOHEXYL METHACRYLATE	Rabbit	Minimal irritation
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Not available	Irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
benzyltributylammonium chloride	Guinea pig	Corrosive
Carbon black	Rabbit	No significant irritation
naphthenic acids, copper salts	Rabbit	No significant irritation
methyl methacrylate	Rabbit	Irritant
mequinol	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant
Kaolin	Professional judgement	No significant irritation
CYCLOHEXYL METHACRYLATE	In vitro data	Severe irritant
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Not available	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
benzyltributylammonium chloride	similar health hazards	Corrosive
Carbon black	Rabbit	No significant irritation
naphthenic acids, copper salts	In vitro data	No significant irritation
methyl methacrylate	Rabbit	Mild irritant
mequinol	Rabbit	Severe irritant

Skin Sensitisation

Name	Species	Value
2-hydroxyethyl methacrylate	Human and animal	Sensitising
CYCLOHEXYL METHACRYLATE	Mouse	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
naphthenic acids, copper salts	Guinea pig	Not classified
methyl methacrylate	Human and animal	Sensitising

mequinol	Guinea pig	Sensitising
----------	------------	-------------

Respiratory Sensitisation

Name	Species	Value
methyl methacrylate	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
CYCLOHEXYL METHACRYLATE	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
methyl methacrylate	In vivo	Not mutagenic
methyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
mequinol	In vivo	Not mutagenic
mequinol	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
methyl methacrylate	Ingestion	Rat	Not carcinogenic
methyl methacrylate	Inhalation	Human and animal	Not carcinogenic
mequinol	Dermal	Multiple animal species	Not carcinogenic
mequinol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
CYCLOHEXYL METHACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000	premating into lactation

				mg/kg/day	
CYCLOHEXYL METHACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	15 weeks
CYCLOHEXYL METHACRYLATE	Ingestion	Not classified for development	Rabbit	NOAEL 500 mg/kg/day	during gestation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
methyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
methyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
methyl methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 450 mg/kg/day	during gestation
methyl methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
mequinol	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
mequinol	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	28 days
mequinol	Ingestion	Not classified for development	Rat	NOAEL 200 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
CYCLOHEXYL METHACRYLATE	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Poly[oxy(methyl-1,2-ethanediyl)], a.-(2-methyl-1-oxo-2-propenyl)-w.-(phosphonoxy)-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
benzyltributylammonium chloride	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
methyl methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
mequinol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
CYCLOHEXYL METHACRYLATE	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder nervous system eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	15 weeks
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational

					available	exposure
methyl methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
methyl methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
methyl methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Ingestion	kidney and/or bladder heart skin endocrine system gastrointestinal tract hematopoietic system liver muscles nervous system respiratory system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
mequinol	Ingestion	gastrointestinal tract	Not classified	Rat	LOAEL 300 mg/kg/day	28 days
mequinol	Ingestion	liver immune system	Not classified	Rat	NOAEL 300 mg/kg/day	28 days
mequinol	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 300 mg/kg/day	28 days
mequinol	Ingestion	heart endocrine system hematopoietic system nervous system respiratory system	Not classified	Rat	NOAEL 300 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
2-Propenoic acid, 2-methyl-, 2-(2-butoxyethoxy)ethyl ester	7328-22-5	Green algae	Experimental	72 hours	EC50	95 mg/l
2-Propenoic acid, 2-methyl-, 2-(2-	7328-22-5	Rainbow trout	Experimental	96 hours	LC50	22.36 mg/l

3M™ Scotch-Weld™ Flexible Acrylic Adhesive DP8610NS, Black, Part B

butoxyethoxy)ethyl ester						
2-Propenoic acid, 2-methyl-, 2-(2-butoxyethoxy)ethyl ester	7328-22-5	Water flea	Experimental	48 hours	EC50	94.7 mg/l
2-Propenoic acid, 2-methyl-, 2-(2-butoxyethoxy)ethyl ester	7328-22-5	Water flea	Estimated	21 days	EC10	7.51 mg/l
2-Propenoic acid, 2-methyl-, 2-(2-butoxyethoxy)ethyl ester	7328-22-5	Green algae	Experimental	72 hours	EC10	34 mg/l
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
2-hydroxyethyl methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
Acrylonitrile - butadiene polymer	9003-18-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
CYCLOHEXYL METHACRYLATE	101-43-9	Activated sludge	Experimental	30 minutes	EC50	900 mg/l
CYCLOHEXYL METHACRYLATE	101-43-9	Green algae	Experimental	72 hours	EC50	12.5 mg/l
CYCLOHEXYL METHACRYLATE	101-43-9	Water flea	Experimental	48 hours	EC50	33.9 mg/l
CYCLOHEXYL METHACRYLATE	101-43-9	Zebra Fish	Experimental	96 hours	LC50	590 mg/l
CYCLOHEXYL METHACRYLATE	101-43-9	Zebra Fish	Estimated	35 days	NOEC	9.4 mg/l
CYCLOHEXYL METHACRYLATE	101-43-9	Green algae	Experimental	72 hours	EC10	5.49 mg/l
mequinol	150-76-5	Ciliated protozoa	Experimental	40 hours	IC50	171.4 mg/l
mequinol	150-76-5	Green algae	Experimental	72 hours	ErC50	54.7 mg/l
mequinol	150-76-5	Rainbow trout	Experimental	96 hours	LC50	28.5 mg/l
mequinol	150-76-5	Water flea	Experimental	48 hours	EC50	2.2 mg/l
mequinol	150-76-5	Green algae	Experimental	72 hours	NOEC	2.96 mg/l
mequinol	150-76-5	Water flea	Experimental	21 days	NOEC	0.68 mg/l
methyl methacrylate	80-62-6	Green algae	Experimental	72 hours	EC50	>110 mg/l
methyl methacrylate	80-62-6	Rainbow trout	Experimental	96 hours	LC50	>79 mg/l
methyl methacrylate	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
methyl methacrylate	80-62-6	Green algae	Experimental	72 hours	NOEC	110 mg/l

3M™ Scotch-Weld™ Flexible Acrylic Adhesive DP8610NS, Black, Part B

methyl methacrylate	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
methyl methacrylate	80-62-6	Activated sludge	Experimental	30 minutes	EC20	150 mg/l
methyl methacrylate	80-62-6	Soil microbes	Experimental	28 days	NOEC	>1,000 mg/kg (Dry Weight)
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
benzyltributylammonium chloride	23616-79-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	95175-93-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
naphthenic acids, copper salts	1338-02-9	Green algae	Estimated	72 hours	ErC50	0.629 mg/l
naphthenic acids, copper salts	1338-02-9	Water flea	Estimated	48 hours	EC50	0.0756 mg/l
naphthenic acids, copper salts	1338-02-9	Zebra Fish	Estimated	96 hours	LC50	0.07 mg/l
naphthenic acids, copper salts	1338-02-9	Fathead minnow	Estimated	32 days	EC10	0.0354 mg/l
naphthenic acids, copper salts	1338-02-9	Green algae	Estimated	N/A	NOEC	0.132 mg/l
naphthenic acids, copper salts	1338-02-9	Sediment Worm	Estimated	28 days	NOEC	110 mg/kg (Dry Weight)
naphthenic acids, copper salts	1338-02-9	Water flea	Estimated	7 days	NOEC	0.02 mg/l
naphthenic acids, copper salts	1338-02-9	Activated sludge	Estimated	N/A	EC50	42 mg/l
naphthenic acids, copper salts	1338-02-9	Barley	Estimated	4 days	NOEC	96 mg/kg (Dry Weight)
naphthenic acids, copper salts	1338-02-9	Redworm	Estimated	56 days	NOEC	60 mg/kg (Dry Weight)
naphthenic acids, copper salts	1338-02-9	Soil microbes	Estimated	4 days	NOEC	72 mg/kg (Dry Weight)
naphthenic acids, copper salts	1338-02-9	Springtail	Estimated	28 days	NOEC	167 mg/kg (Dry Weight)
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-Propenoic acid, 2-methyl-, 2-(2-butoxyethoxy)ethyl ester	7328-22-5	Experimental Biodegradation	28 days	CO2 evolution	91 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Kaolin	1332-58-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/CO D	OECD 301D - Closed bottle test
2-hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
Acrylonitrile - butadiene polymer	9003-18-3	Data not availbl-insufficient	N/A	N/A	N/A	N/A
CYCLOHEXYL	101-43-9	Experimental	28 days	CO2 evolution	70-80 %CO2	OECD 310 CO2 Headspace

METHACRYLATE		Biodegradation			evolution/THC O2 evolution	
Polymeric Methacrylate	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
mequinol	150-76-5	Experimental Biodegradation - Anaerobic	28 days	Percent degraded	>90 %degraded	
mequinol	150-76-5	Experimental Biodegradation	28 days	BOD	86 %BOD/ThO D	OECD 301C - MITI test (I)
methyl methacrylate	80-62-6	Experimental Biodegradation	14 days	BOD	94 %BOD/ThO D	OECD 301C - MITI test (I)
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
benzyltributylammonium chloride	23616-79-7	Estimated Biodegradation	28 days	BOD	3.9 %BOD/Th OD	OECD 301C - MITI test (I)
Poly[oxy(methyl-1,2- ethanediyl)], .a.-(2-methyl- 1-oxo-2-propenyl)-.w.- (phosphonoxy)-	95175-93-2	Data not availbl- insufficient	N/A	N/A	N/A	N/A
naphthenic acids, copper salts	1338-02-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
2-Propenoic acid, 2- methyl-, 2-(2- butoxyethoxy)ethyl ester	7328-22-5	Experimental Bioconcentration		Log Kow	3.1	
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flsk mtd
Acrylonitrile - butadiene polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
CYCLOHEXYL METHACRYLATE	101-43-9	Experimental Bioconcentration		Log Kow	3.9	
Polymeric Methacrylate	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
mequinol	150-76-5	Experimental Bioconcentration		Log Kow	1.58	
methyl methacrylate	80-62-6	Experimental Bioconcentration		Log Kow	1.38	OECD 107 log Kow shke flsk mtd
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
benzyltributylammonium chloride	23616-79-7	Estimated Bioconcentration		Bioaccumulation factor	31.7	
Poly[oxy(methyl-1,2- ethanediyl)], .a.-(2-methyl- 1-oxo-2-propenyl)-.w.- (phosphonoxy)-	95175-93-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
naphthenic acids, copper salts	1338-02-9	Analogous Compound BCF - Fish	42 days	Bioaccumulation factor	≤27	OECD305-Bioconcentration
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
2-Propenoic acid, 2-methyl-, 2-(2-butoxyethoxy)ethyl ester	7328-22-5	Estimated Mobility in Soil	Koc	80 l/kg	Episuite™
2-hydroxyethyl methacrylate	868-77-9	Experimental Mobility in Soil	Koc	42.7 l/kg	
CYCLOHEXYL METHACRYLATE	101-43-9	Estimated Mobility in Soil	Koc	190 l/kg	Episuite™
mequinol	150-76-5	Experimental Mobility in Soil	Koc	55.7 l/kg	
methyl methacrylate	80-62-6	Experimental Mobility in Soil	Koc	8.7-72 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

080411* Adhesive and sealant sludges containing organic solvents or other dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.

14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

Carbon black

methyl methacrylate

CAS Nbr

1333-86-4

80-62-6

Classification

Grp. 2B: Possible human carc.

Gr. 3: Not classifiable

Regulation

International Agency for Research on Cancer

International Agency for Research on Cancer

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 1: Address information was modified.

Section 1: E-mail address information was modified.

Section 1: Product use information information was modified.

Section 2: <125ml Hazard - Health information was modified.

Section 2: <125ml Precautionary - Prevention information was modified.

Section 2: <125ml Precautionary - Response information was modified.

CLP: Ingredient table information was modified.

Section 02: CLP Physical and Health Hazard Statements information was modified.

Label: CLP Classification information was modified.

Label: CLP Percent Unknown information was modified.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.

Label: Graphic information was modified.

Label: Signal Word information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 04: First Aid - Symptoms and Effects (CLP) information was modified.

Section 4: First aid for eye contact information information was modified.

Section 5: Fire - Special hazards information information was modified.

Section 5: Hazardous combustion products table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 7: Precautions safe handling information information was modified.

Section 8: Appropriate Engineering controls information information was modified.

Section 8: Eye/face protection information information was modified.

Section 8: Occupational exposure limit table information was modified.

OEL Reg Agency Desc information was modified.
Section 8: Personal Protection - Respiratory Information information was modified.
Section 8: Respiratory protection - recommended respirators information information was modified.
Section 9: Flammability (solid, gas) information information was deleted.
Section 09: Flammability information information was added.
Section 09: Odor information was modified.
Section 09: Particle Characteristics N/A information was added.
Section 9: Vapour density value information was modified.
Section 10: Hazardous Decomposition Products information information was added.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Health Effects - Eye information information was modified.
Section 11: Health Effects - Inhalation information information was modified.
Section 11: Health Effects - Skin information information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was added.
Section 11: Target Organs - Repeated Table information was deleted.
Section 11: Target Organs - Single Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Mobility in soil information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Bioaccumulative potential information information was modified.
Section 14 Multiplier – Main Heading information was deleted.
Section 14 Multiplier – Regulation Data information was deleted.
Section 14 Transport Category – Main Heading information was deleted.
Section 14 Transport Category – Regulation Data information was deleted.
Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was modified.
Section 14 Tunnel Code – Main Heading information was deleted.
Section 14 Tunnel Code – Regulation Data information was deleted.
Section 14 UN Number information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material.
information was modified.
Section 2: No PBT/vPvB information available warning information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com