



Safety Data Sheet

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 27-4388-8
Issue Date: 29/04/2025

Version number: 5.01
Supersedes date: 11/04/2025

This Safety Data Sheet has been prepared in accordance with the South African National Standard SANS 10234:2008.

SECTION 1: Identification

1.1. Product identifier

3M Perfect-It III 50383 and 51302 Ultrafina SE

Product Identification Numbers

GC-8010-3470-0

1.2. Recommended use and restrictions on use

Recommended use

Automotive., For use with a rotary polishing machine for the removal of swirls and holograms to achieve a high gloss finish.

1.3. Supplier's details

Address: 3M South Africa (Pty) Ltd, Private Bag X926, Rivonia 2128
Telephone: 011 806 2000
E Mail: Not available.
Website: www.3m.co.za

1.4. Emergency telephone number

011 806 2000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 3.

Acute Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word

Warning

Symbols

Not applicable

Pictograms

Not applicable

HAZARD STATEMENTS:

H316 Causes mild skin irritation.

H402 Harmful to aquatic life.

PRECAUTIONARY STATEMENTS**General:**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Response:

P332 + P313 If skin irritation occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Aspiration classification does not apply due to the viscosity of the product.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Water	7732-18-5	40 - 70
Dodecamethylcyclhexasiloxane	540-97-6	7 - 15
Distillates (petroleum), hydrotreated light	64742-47-8	7 - 15
Aluminium oxide	1344-28-1	< 7
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	< 5
NOT CLASSIFIED OILS	Trade Secret	< 1.5
Glycerol	56-81-5	< 1.5
Undecan-1-ol, ethoxylated	34398-01-1	< 0.3

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin
Aluminum, insoluble compounds	1344-28-1	South Africa RELs	TWA(as Al, respirable fraction)(8 hours):2 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	South Africa RELs	TWA(respirable fraction)(8 hours):5 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	South Africa RELs	TWA(8 hours):10 mg/m ³	
JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m ³	A3: Confirmed animal carcin., SKIN
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m ³	A3: Confirmed animal carcin., SKIN
MINERAL OILS, HIGHLY-REFINED OILS	64742-47-8	ACGIH	TWA(inhalable fraction):5 mg/m ³	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

South Africa CLs : South Africa. Control Limits. Regulations for Hazardous Chemical Substances, Table 1

South Africa RELs : South Africa. Recommended Exposure Limits (RELs) Regulations for Hazardous Chemical Substances, Table 2

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Thixotropic liquid.
Colour	Light Blue
Odor	Solvent
Odour threshold	<i>No data available.</i>
pH	7,5 - 8,5 Units not available or not applicable. [Details:@ 25° C
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	>= 110 °C [Test Method:Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative Vapor Density	<i>No data available.</i>
Density	0,959 - 0,984 g/cm3 [@ 25 °C]
Relative density	0,911 - 1,007 [Ref Std:WATER=1]
Water solubility	Appreciable
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
Kinematic Viscosity	10 427 - 13 555 mm²/sec
Volatile organic compounds (VOC)	18,51 %
Percent volatile	57,2 %
VOC less H2O & exempt solvents	<i>No data available.</i>

Particle Characteristics	<i>Not applicable.</i>
---------------------------------	------------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

High shear and high temperature conditions

Sparks and/or flames.

Temperatures above the boiling point.

10.5 Incompatible materials

Alkali and alkaline earth metals.

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system:

Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5 000 mg/kg
Dodecamethylcyclohexasiloxane	Dermal	Rat	LD50 > 2 000 mg/kg
Dodecamethylcyclohexasiloxane	Ingestion	Rat	LD50 > 2 000 mg/kg
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 15 000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	similar compounds	LD50 > 5 000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5 000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2,3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5 000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Rabbit	LD50 > 5 000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Ingestion	Rat	LD50 > 5 000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 4 mg/l
Glycerol	Dermal	Rabbit	LD50 estimated to be > 5 000 mg/kg
Glycerol	Ingestion	Rat	LD50 > 5 000 mg/kg
Undecan-1-ol, ethoxylated	Dermal	Rabbit	LD50 > 2 000 mg/kg
Undecan-1-ol, ethoxylated	Ingestion	Rat	LD50 > 700 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	similar compounds	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Solvent dewaxed heavy paraffinic distillate (petroleum)	Rabbit	No significant irritation
Glycerol	Rabbit	No significant irritation
Undecan-1-ol, ethoxylated	similar health hazards	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	similar compounds	No significant irritation
Aluminium oxide	Rabbit	No significant irritation
Solvent dewaxed heavy paraffinic distillate (petroleum)	Rabbit	No significant irritation
Glycerol	Rabbit	No significant irritation
Undecan-1-ol, ethoxylated	Professional judgement	Corrosive

Sensitization:**Skin Sensitisation**

Name	Species	Value
------	---------	-------

Dodecamethylcyclotrisiloxane	Guinea pig	Not classified
Distillates (petroleum), hydrotreated light	similar compounds	Not classified
Solvent dewaxed heavy paraffinic distillate (petroleum)	Guinea pig	Not classified
Glycerol	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Dodecamethylcyclotrisiloxane	In Vitro	Not mutagenic
Dodecamethylcyclotrisiloxane	In vivo	Not mutagenic
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
Aluminium oxide	In Vitro	Not mutagenic
Solvent dewaxed heavy paraffinic distillate (petroleum)	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminium oxide	Inhalation	Rat	Not carcinogenic
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Mouse	Not carcinogenic
Glycerol	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Dodecamethylcyclotrisiloxane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1 000 mg/kg/day	2 generation
Dodecamethylcyclotrisiloxane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1 000 mg/kg/day	2 generation
Dodecamethylcyclotrisiloxane	Ingestion	Not classified for development	Multiple animal species	NOAEL 1 000 mg/kg/day	during gestation
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Not classified for development	Rat	NOAEL 1 000 mg/kg/day	during gestation
Glycerol	Ingestion	Not classified for female reproduction	Rat	NOAEL 2 000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for male reproduction	Rat	NOAEL 2 000 mg/kg/day	2 generation
Glycerol	Ingestion	Not classified for development	Rat	NOAEL 2 000 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dodecamethylcyclotrisiloxane	Inhalation	respiratory irritation	Some positive data exist, but the	Rat	NOAEL not	

oxane			data are not sufficient for classification		available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Undecan-1-ol, ethoxylated	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dodecamethylcyclohexasil oxane	Inhalation	liver	Not classified	Rat	NOAEL 0,546 mg/l	90 days
Dodecamethylcyclohexasil oxane	Inhalation	respiratory system	Not classified	Rat	NOAEL 0,018 mg/l	90 days
Dodecamethylcyclohexasil oxane	Inhalation	hematopoietic system eyes	Not classified	Rat	NOAEL 0,546 mg/l	90 days
Dodecamethylcyclohexasil oxane	Ingestion	endocrine system liver hematopoietic system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1 000 mg/kg/day	28 days
Distillates (petroleum), hydrotreated light	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (petroleum), hydrotreated light	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1,5 mg/l	13 weeks
Distillates (petroleum), hydrotreated light	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (petroleum), hydrotreated light	Ingestion	liver	Not classified	Rat	NOAEL 1 000 mg/kg/day	13 weeks
Distillates (petroleum), hydrotreated light	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
Distillates (petroleum), hydrotreated light	Ingestion	hematopoietic system eyes	Not classified	Rat	NOAEL 1 000 mg/kg/day	13 weeks
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	skin liver hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 2 000 mg/kg/day	13 weeks
Glycerol	Inhalation	respiratory system heart liver kidney and/or bladder	Not classified	Rat	NOAEL 3,91 mg/l	14 days
Glycerol	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10 000 mg/kg/day	2 years

Aspiration Hazard

Name	Value
Distillates (petroleum), hydrotreated light	Aspiration hazard
Solvent dewaxed heavy paraffinic distillate (petroleum)	Not an aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Dodecamethylcycl ohexasiloxane	540-97-6	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Green algae	Experimental	72 hours	EC50	>100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Fathead minnow	Experimental	49 days	NOEC	100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Green algae	Experimental	72 hours	NOEC	100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Water flea	Experimental	21 days	NOEC	100 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green algae	Experimental	72 hours	EL50	>1 000 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Rainbow trout	Experimental	96 hours	LL50	>1 000 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Experimental	48 hours	EL50	>1 000 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green algae	Experimental	72 hours	NOEL	1 000 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Green algae	Analogous Compound	96 hours	EC50	>100 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Water flea	Analogous Compound	48 hours	EC50	>100 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Water flea	Experimental	21 days	NOEC	100 mg/l
Glycerol	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54 000 mg/l
Glycerol	56-81-5	Water flea	Experimental	48 hours	LC50	1 955 mg/l
Glycerol	56-81-5	Bacteria	Experimental	16 hours	NOEC	10 000 mg/l
Undecan-1-ol,	34398-01-1	Green algae	Analogous	72 hours	ErC50	0,43 mg/l

ethoxylated			Compound			
Undecan-1-ol, ethoxylated	34398-01-1	Green algae	Analogous Compound	72 hours	NOEC	0,09 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Dodecamethylcycl ohexasiloxane	540-97-6	Experimental Biodegradation	28 days	CO2 evolution	4.47 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
Distillates (petroleum), hydrotreated light	64742-47-8	Estimated Biodegradation	28 days	BOD	69 %BOD/ThOD	OECD 301F - Manometric respirometry
Aluminium oxide	1344-28-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Experimental Biodegradation	28 days	CO2 evolution	23 %CO2 evolution/THCO2 evolution	similar to OECD 301B
Glycerol	56-81-5	Experimental Biodegradation	14 days	BOD	63 %BOD/ThOD	OECD 301C - MITI test (I)
Undecan-1-ol, ethoxylated	34398-01-1	Modeled Biodegradation	28 days	CO2 evolution	95 %CO2 evolution/THCO2 evolution	Catalogic™

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Dodecamethylcycl ohexasiloxane	540-97-6	Experimental BCF - Fish	49 days	Bioaccumulation factor	1160	OECD305-Bioconcentration
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol	56-81-5	Experimental Bioconcentration		Log Kow	-1.75	similar to OECD 107
Undecan-1-ol, ethoxylated	34398-01-1	Modeled Bioconcentration		Bioaccumulation factor	50	Catalogic™

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product must only be disposed of by an authorized/permitted waste disposal contractor or incinerated in an industrial or commercial facility in the presence of a combustible material.

SECTION 14: Transport Information

Compliance is required to South African Transport Information Road Traffic Act & Regulations and Railroad regulations, IATA Standards for airfreight and Maritime standards for ocean freight.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

Revision information:

Section 2: Ingredient table information was modified.

Section 6: Accidental release personal information information was modified.

Section 8: Occupational exposure limit table information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M South Africa SDSs are available at www.3m.co.za