Safety Data Sheet

Copyright,2025, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	28-0070-4	**Version Number:**	2.00
Issue Date:	11/09/2025	**Supersedes Date:**	09/08/2020

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier
3M™ Rocker Panel Coating, PN 08889

Product Identification Numbers
60-4551-0252-9

1.2. Recommended use and restrictions on use

Recommended use
Automotive

For Industrial or Professional use only

1.3. Supplier's details
ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number
+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Flammable Aerosol: Category 2.
Gas Under Pressure: Liquefied gas.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 2.
Carcinogenicity: Category 1A.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (single exposure): Category 2.
Specific Target Organ Toxicity (repeated exposure): Category 1.
Aspiration Hazard: Category 1.

Chronic Aquatic Toxicity: Category 3.

2.2. Label elements
Signal word
Danger

Symbols
Flame |Gas cylinder |Exclamation mark |Health Hazard |

Pictograms



Hazard Statements:

H223	Flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H304	May be fatal if swallowed and enters airways.
H371	May cause damage to organs: cardiovascular system.
H372	Causes damage to organs through prolonged or repeated exposure: nervous system | respiratory system | sensory organs.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements
General:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention:

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P281	Use personal protective equipment as required.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice.

Storage:

P405	Store locked up.	
P410 + P403	Protect from sunlight.	Store in a well-ventilated place.
P410 + P412	Protect from sunlight.	Do not expose to temperatures exceeding 122°F (50°C).

Disposal:

P501	Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

May cause drowsiness or dizziness., May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Toluene	108-88-3	30 - 40
Kaolin	1332-58-7	15 - 25
Dimethyl Ether	115-10-6	10 - 20
Hexane	110-54-3	3 - 10
Coumarone-Indene Resins	63393-89-5	5 - 10
Hydrogenated Styrene-Butadiene Polymer	66070-58-4	5 - 10
Propane	74-98-6	3 - 7
Propyl Propionate	106-36-5	3 - 7
Hexane, branched and linear	92112-69-1	1 - 5
3-Methylpentane	96-14-0	< 5
Methylcyclopentane	96-37-7	< 2
Quartz Silica	14808-60-7	0.1 - 1
Titanium Dioxide	13463-67-7	0.1 - 1
Benzene	71-43-2	< 0.05

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required
Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

5.3. Special protective actions for fire-fighters
Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

6.2. Environmental precautions
For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m3(50 ppm)	SKIN
Hexane	110-54-3	ACGIH	TWA:50 ppm	Danger of cutaneous absorption
Hexane	110-54-3	Malaysia OELs	TWA(8 hours):176 mg/m3(50 ppm)	SKIN
Kaolin	1332-58-7	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
Kaolin	1332-58-7	Malaysia OELs	TWA (proposed)(respirable fraction)(8 hours):2 mg/m3	
DUST, INERT OR NUISANCE	13463-67-7	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m3;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	Malaysia OELs	TWA(8 hours):10 mg/m3	
Quartz Silica	14808-60-7	Malaysia OELs	TWA(respirable fraction)(8 hours):0.1 mg/m3	
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Benzene	71-43-2	ACGIH	TWA:0.02 ppm	A1: Confirmed human carcin., Danger of cutaneous absorption
Benzene	71-43-2	Malaysia OELs	TWA(8 hours):1.6 mg/m3(0.5 ppm)	
Propane	74-98-6	ACGIH	Limit value not established:	simple asphyxiant
Propane	74-98-6	Malaysia OELs	TWA(8 hours):2500 ppm	
HEXANE (ISOMERS OTHER THAN N-HEXANE)	92112-69-1	ACGIH	TWA:200 ppm	A3: Confirmed animal carcin.
HEXANE (ISOMERS OTHER THAN N-HEXANE)	92112-69-1	Malaysia OELs	TWA(8 hours):1760 mg/m3(500 ppm)	
HEXANE (ISOMERS OTHER THAN N-HEXANE)	96-14-0	ACGIH	TWA:200 ppm	A3: Confirmed animal carcin.
HEXANE (ISOMERS OTHER THAN N-HEXANE)	96-14-0	Malaysia OELs	TWA(8 hours):1760 mg/m3(500 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists
CMRG : Chemical Manufacturer's Recommended Guidelines
Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Full Face Shield
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Fluoroelastomer, Polyethylene, Polyvinyl Alcohol (PVA)

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.
An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Color	Colorless
Odor	Mild Solvent
Odor threshold	*No Data Available*
pH	*No Data Available*
Melting point/Freezing point	*No Data Available*

Boiling point/Initial boiling point/Boiling range	110 ºC
Flash Point	4 ºC [*Test Method:*Pensky-Martens Closed Cup]
Evaporation rate	*No Data Available*
Flammability	Flammable Aerosol: Category 2.
Flammable Limits(LEL)	1.2 %
Flammable Limits(UEL)	7.1 %
Vapor Pressure	*No Data Available*
Relative Vapor Density	*No Data Available*
Density	1.125 g/ml
Relative Density	1.125
Water solubility	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*No Data Available*
Volatile Organic Compounds	59.6 % weight [*Test Method:*calculated per CARB title 2]
Volatile Organic Compounds	671 g/l [*Test Method:*calculated SCAQMD rule 443.1]
Percent volatile	59.6 % weight
VOC Less H2O & Exempt Solvents	5.61 lb/gal [*Test Method:*calculated SCAQMD rule 443.1]

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:
Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:
Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause target organ effects:
Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Prolonged or repeated exposure by ingestion may cause:
Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:
Contains a chemical or chemicals which can cause cancer.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Dimethyl Ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-Vapor (4 hours)	Rat	LC50 170 mg/l
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
Coumarone-Indene Resins	Dermal		LD50 estimated to be > 5,000 mg/kg
Coumarone-Indene Resins	Ingestion	Rat	LD50 > 16,000 mg/kg
Hydrogenated Styrene-Butadiene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Hydrogenated Styrene-Butadiene Polymer	Ingestion		LD50 estimated to be > 5,000 mg/kg
Propyl Propionate	Dermal		estimated to be > 5,000 mg/kg
Propyl Propionate	Inhalation-Dust/Mist		estimated to be > 12.5 mg/l
Propyl Propionate	Inhalation-Vapor		estimated to be 10 - 20 mg/l
Propyl Propionate	Ingestion		estimated to be > 5,000 mg/kg
3-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
3-Methylpentane	Inhalation-Vapor		LC50 estimated to be > 50 mg/l
3-Methylpentane	Ingestion		LD50 estimated to be > 5,000 mg/kg
Methylcyclopentane	Inhalation-Vapor (4 hours)	Rat	LC50 > 25.3 mg/l
Methylcyclopentane	Ingestion	Rat	LD50 > 5,000 mg/kg
Methylcyclopentane	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Benzene	Dermal	Multiple	LD50 > 8,260 mg/kg

		animal species	
Benzene	Inhalation-Vapor (4 hours)	Rat	LC50 43.8 mg/l
Benzene	Ingestion	Rat	LD50 5,970 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Toluene	Rabbit	Irritant
Kaolin	Professional judgement	No significant irritation
Propane	Rabbit	Minimal irritation
Hexane	Human and animal	Mild irritant
3-Methylpentane	Professional judgement	Mild irritant
Methylcyclopentane	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Quartz Silica	Professional judgement	No significant irritation
Benzene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Toluene	Rabbit	Moderate irritant
Kaolin	Professional judgement	No significant irritation
Propane	Rabbit	Mild irritant
Hexane	Rabbit	Mild irritant
3-Methylpentane	Professional judgement	Moderate irritant
Methylcyclopentane	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation
Benzene	Rabbit	Severe irritant

Sensitization:

Skin Sensitization

Name	Species	Value
Toluene	Guinea pig	Not classified
Hexane	Human	Not classified
Methylcyclopentane	similar compounds	Not classified
Titanium Dioxide	Human and animal	Not classified

Benzene	Multiple animal species	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic
Propane	In Vitro	Not mutagenic
Hexane	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic
Methylcyclopentane	In vivo	Not mutagenic
Methylcyclopentane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification
Benzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Benzene	In vivo	Mutagenic

Carcinogenicity

Name	Route	Species	Value
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Dimethyl Ether	Inhalation	Rat	Not carcinogenic
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Quartz Silica	Inhalation	Human and animal	Carcinogenic
Benzene	Dermal	Mouse	Carcinogenic
Benzene	Ingestion	Multiple animal species	Carcinogenic
Benzene	Inhalation	Human	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not	occupational

				available	exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Dimethyl Ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
Benzene	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.96 mg/l	premating into lactation
Benzene	Inhalation	Not classified for development	Rat	NOAEL 0.032 mg/l	during organogenesis
Benzene	Ingestion	Toxic to male reproduction	Rat	LOAEL 50 mg/kg/day	90 days

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
3-Methylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
3-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
3-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not	

					available	
3-Methylpentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Methylcyclopentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Methylcyclopentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Benzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not Available	
Benzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not Available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Toluene	Inhalation	auditory system | nervous system | eyes | olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart | liver | kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system | vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver | kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Dimethyl Ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl Ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for	Mouse	LOAEL 1.76 mg/l	13 weeks

			classification			
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
Hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
Hexane	Inhalation	auditory system | immune system | eyes	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	heart | skin | endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Ingestion	endocrine system | hematopoietic system | liver | immune system | kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
3-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
3-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
3-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg/day	28 days
Methylcyclopentane	Inhalation	liver | kidney and/or bladder | heart | skin | endocrine system | gastrointestinal tract | bone, teeth, nails, and/or hair | hematopoietic system | immune system | muscles | nervous system | eyes | respiratory system | vascular system	Not classified	Rat	NOAEL 20.2 mg/l	13 weeks
Methylcyclopentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL 800 mg/kg/day	8 weeks
Methylcyclopentane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	4 weeks
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Benzene	Inhalation	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	Human and animal	NOAEL Not Available	
Benzene	Inhalation	heart | endocrine system | gastrointestinal tract | bone, teeth, nails, and/or hair | liver | immune system | muscles | nervous system | eyes | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 0.96 mg/l	90 days
Benzene	Ingestion	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 25 mg/kg/day	90 days

Benzene	Ingestion	heart | endocrine system | gastrointestinal tract | bone, teeth, nails, and/or hair | liver | immune system | nervous system | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	90 days

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard
Hexane	Aspiration hazard
3-Methylpentane	Aspiration hazard
Methylcyclopentane	Aspiration hazard
Benzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:
GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:
GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Dimethyl Ether	115-10-6	Bacteria	Experimental	N/A	EC10	>1,600 mg/l
Dimethyl Ether	115-10-6	Guppy	Experimental	96 hours	LC50	>4,100 mg/l
Dimethyl Ether	115-10-6	Water flea	Experimental	48 hours	EC50	>4,400 mg/l
Coumarone-Indene	63393-89-5	N/A	Data not available	N/A	N/A	N/A

Resins			or insufficient for classification			
Hexane	110-54-3	Fathead Minnow	Experimental	96 hours	LC50	2.5 mg/l
Hexane	110-54-3	Water flea	Experimental	48 hours	LC50	3.9 mg/l
Hydrogenated Styrene-Butadiene Polymer	66070-58-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Propane	74-98-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Propyl Propionate	106-36-5	Green algae	Experimental	96 hours	ErC50	>1,004 mg/l
Propyl Propionate	106-36-5	Rainbow Trout	Experimental	96 hours	LC50	10.8 mg/l
Propyl Propionate	106-36-5	Water flea	Experimental	48 hours	EC50	37.8 mg/l
Propyl Propionate	106-36-5	Green algae	Experimental	96 hours	NOEC	245 mg/l
3-Methylpentane	96-14-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hexane, branched and linear	92112-69-1	N/A	Data not available or insufficient for classification	N/A	N/A	n/a
Methylcyclopentane	96-37-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Quartz Silica	14808-60-7	Green algae	Estimated	72 hours	EC50	440 mg/l
Quartz Silica	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l
Quartz Silica	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l
Quartz Silica	14808-60-7	Green algae	Estimated	72 hours	NOEC	60 mg/l
Titanium Dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium Dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium Dioxide	13463-67-7	Fathead Minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium Dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium Dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Benzene	71-43-2	Green algae	Experimental	72 hours	EC50	100 mg/l
Benzene	71-43-2	Rainbow Trout	Experimental	96 hours	LC50	5.3 mg/l
Benzene	71-43-2	Water flea	Experimental	48 hours	EC50	10 mg/l
Benzene	71-43-2	Fathead Minnow	Experimental	32 days	NOEC	0.8 mg/l
Benzene	71-43-2	Green algae	Experimental	72 hours	EC10	34 mg/l
Benzene	71-43-2	Water flea	Experimental	7 days	NOEC	3 mg/l
Benzene	71-43-2	Bacteria	Experimental	24 hours	IC50	13 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Toluene	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Kaolin	1332-58-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Dimethyl Ether	115-10-6	Experimental Biodegradation	28 days	Biological Oxygen Demand	5 %BOD/ThOD	OECD 301D - Closed Bottle Test
Dimethyl Ether	115-10-6	Experimental Photolysis		Photolytic half-life (in air)	12.4 days (t 1/2)	
Coumarone-Indene Resins	63393-89-5	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Hexane	110-54-3	Experimental Bioconcentration	28 days	Biological Oxygen Demand	100 %BOD/ThOD	OECD 301C - MITI (I)
Hexane	110-54-3	Experimental Photolysis		Photolytic half-life (in air)	5.4 days (t 1/2)	
Hydrogenated Styrene-Butadiene Polymer	66070-58-4	Data not availbl-insufficient	N/A	N/A	N/A	N/A

Propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	
Propyl Propionate	106-36-5	Experimental Biodegradation	28 days	Biological Oxygen Demand	64 %BOD/ThOD	OECD 301D - Closed Bottle Test
Propyl Propionate	106-36-5	Experimental Photolysis		Photolytic half-life (in air)	7.5 days (t 1/2)	Episuite™
Propyl Propionate	106-36-5	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	204 days (t 1/2)	OECD 111 Hydrolysis func of pH
3-Methylpentane	96-14-0	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	93 %BOD/ThOD	OECD 301C - MITI (I)
3-Methylpentane	96-14-0	Experimental Photolysis		Photolytic half-life (in air)	6.1 days (t 1/2)	
Hexane, branched and linear	92112-69-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Methylcyclopentane	96-37-7	Experimental Biodegradation	28 days	Biological Oxygen Demand	2 %BOD/ThOD	OECD 301C - MITI (I)
Methylcyclopentane	96-37-7	Estimated Photolysis		Photolytic half-life (in air)	5.33 days (t 1/2)	
Quartz Silica	14808-60-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Titanium Dioxide	13463-67-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Benzene	71-43-2	Experimental Biodegradation	28 days	Biological Oxygen Demand	96 %BOD/ThOD	OECD 301F - Manometric Respiro
Benzene	71-43-2	Experimental Photolysis		Photolytic half-life (in air)	26 days (t 1/2)	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation Factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.73	
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl Ether	115-10-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Coumarone-Indene Resins	63393-89-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hexane	110-54-3	Modeled Bioconcentration		Bioaccumulation Factor	50	Catalogic™
Hydrogenated Styrene-Butadiene Polymer	66070-58-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propane	74-98-6	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.36	
Propyl Propionate	106-36-5	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	1.71	
3-Methylpentane	96-14-0	Modeled Bioconcentration		Bioaccumulation Factor	81	Catalogic™
3-Methylpentane	96-14-0	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	3.6	
Hexane, branched and linear	92112-69-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Methylcyclopentane	96-37-7	Experimental Bioconcentration		Log of Octanol/H2O part.	3.37	

				coeff		
Quartz Silica	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium Dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation Factor	9.6	
Benzene	71-43-2	Experimental BCF - Other		Bioaccumulation Factor	<10	similar to OECD 305
Benzene	71-43-2	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.13	

12.4. Mobility in soil
Please contact manufacturer for more details

12.5 Other adverse effects
No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN1950
Proper Shipping Name:AEROSOLS, FLAMMABLE
Technical Name: None assigned.
Hazard Class/Division:2.1
Subsidiary Risk: None assigned.
Packing Group: None assigned.
Limited Quantity: Yes
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Air Transport (IATA)

UN Number:UN1950
Proper Shipping Name:AEROSOLS, FLAMMABLE
Technical Name: None assigned.
Hazard Class/Division:2.1
Subsidiary Risk: None assigned.
Packing Group: None assigned.
Limited Quantity: None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying

with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status
Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my