

Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 34-4961-8 **Version Number:** 5.00

Issue Date: 12/11/2025 **Supersedes Date:** 23/07/2024

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M[™] Finesse-it[™] Polish - Final Finish [105]

Product Identification Numbers

60-4402-4233-1 60-4402-4234-9 60-4402-4235-6 60-4402-4236-4 60-4402-4237-2

60-4402-4547-4 60-4402-4548-2

1.2. Recommended use and restrictions on use

Recommended use

Abrasive Product, Polish. For industrial/occupational use only. Not for consumer sale or use.

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301

Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Not classified as hazardous according to Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

2.2. Label elements

Signal word

Not applicable

Symbols

3MTM Finesse-itTM Polish - Final Finish [105]

Not applicable

Pictograms

Not applicable

2.3. Other hazards

Aspiration hazard classification does not apply due to the kinematic viscosity of the product.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	45 - 60
Aluminum Oxide Mineral (non-fibrous)	1344-28-1	10 - 20
Glycerin	56-81-5	5 - 15
Hydrotreated Heavy Naptha (Petroleum)	64742-48-9	10 - 15
Distillates (Petroleum), Acid Treated, Light	64742-14-9	5 - 10
Mineral Oil	8042-47-5	1 - 5
Morpholine	110-91-8	0.1 - 1
Propylene Glycol	57-55-6	< 0.1
Carbon Black	1333-86-4	< 0.1

Any remaining components do not contribute to the hazards of this material.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep from freezing. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Morpholine	110-91-8	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcin,Danger of
				cutaneous absorption
Morpholine	110-91-8	Malaysia OELs	TWA(8 hours):71 mg/m3(20	SKIN
			ppm)	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3	A3: Confirmed animal

			mg/m3	carcin.
Carbon Black	1333-86-4	Malaysia OELs	TWA(8 hours):3.5 mg/m3	
Particulates not Otherwise	1333-86-4	Malaysia OELs	TWA (proposed)(respirable	
Classified (PNOC), Inhalable			particles)(8 hours):3	
particulate			mg/m3;TWA	
			(proposed)(Inhalable	
			particulate)(8 hours):10 mg/m3	
Aluminum metal and insoluble	1344-28-1	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
compounds, respirable fraction			mg/m3	carcin
Aluminum Oxide Mineral (non-	1344-28-1	Malaysia OELs	TWA (proposed)(8 hours):10	
fibrous)			mg/m3	
Glycerin	56-81-5	Malaysia OELs	TWA(as mist)(8 hours):10	
			mg/m3	
Particulates not Otherwise	56-81-5	Malaysia OELs	TWA (proposed)(respirable	
Classified (PNOC), Inhalable			particles)(8 hours):3	
particulate			mg/m3;TWA	
			(proposed)(Inhalable	
			particulate)(8 hours):10 mg/m3	
Mineral oil, excluding metal	8042-47-5	ACGIH	TWA(inhalable fraction):5	A4: Not class. as human
working fluids, pure, highly and			mg/m3	carcin
severely refined, inhalable				
fraction				
Oil mist, mineral	8042-47-5	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer's Recommended Guidelines

Malaysia OELs: Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on dasic physical and chemical properties			
Physical state	Liquid		
Color	Gray		
Odor	Slight Solvent		
Odor threshold	No Data Available		
рН	8.3 - 8.7		
Melting point/Freezing point	No Data Available		
Boiling point/Initial boiling point/Boiling range	Approximately 100 °C		
Flash Point	Flash point > 93 °C (200 °F)		
Evaporation rate	1 [Ref Std:ETHER=1]		
Flammability	Not Applicable		
Flammable Limits(LEL)	Not Applicable		
Flammable Limits(UEL)	Not Applicable		
Vapor Pressure	No Data Available		
Relative Vapor Density	1 [Ref Std:AIR=1]		
Density	1 - 1.1 kg/l		
Relative Density	1.014 - 1.062 [<i>Ref Std</i> :WATER=1]		
Water solubility	Negligible		
Solubility- non-water	No Data Available		
Partition coefficient: n-octanol/ water	No Data Available		
Autoignition temperature	Not Applicable		
Decomposition temperature	No Data Available		
Kinematic Viscosity	14,451 mm2/sec		
Volatile Organic Compounds	20.5 % weight [Details: Calculated]		
Percent volatile	75.6 % weight [Details: Calculated including water]		
VOC Less H2O & Exempt Solvents	500.7 g/l [Details: Calculated]		
Molecular weight	No Data Available		
L	I		

Particle Characteristics	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

SubstanceConditionCarbon monoxideNot SpecifiedCarbon dioxideNot Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide Mineral (non-fibrous)	Inhalation- Dust/Mist	Rat	LC50 > 2.3 mg/l
	(4 hours)		

3MTM Finesse-itTM Polish - Final Finish [105]

Aluminum Oxide Mineral (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Heavy Naptha (Petroleum)	Dermal	similar	LD50 > 5,000 mg/kg
		compoun	
		ds	
Hydrotreated Heavy Naptha (Petroleum)	Ingestion	similar	LD50 > 5,000 mg/kg
		compoun	
		ds	
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (Petroleum), Acid Treated, Light	Ingestion	Rat	LD50 > 15,000 mg/kg
Distillates (Petroleum), Acid Treated, Light	Dermal	similar	LD50 > 5,000 mg/kg
		compoun	
		ds	
Mineral Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg
Morpholine	Dermal	Rabbit	LD50 500 mg/kg
Morpholine	Inhalation-	Rat	LC50 estimated to be 10 - 20 mg/l
	Vapor		
Morpholine	Ingestion	Rat	LD50 1,680 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Propylene Glycol	Dermal	Rabbit	LD50 20,800 mg/kg
Propylene Glycol	Ingestion	Rat	LD50 22,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Hydrotreated Heavy Naptha (Petroleum)	similar compoun ds	Mild irritant
Glycerin	Rabbit	No significant irritation
Distillates (Petroleum), Acid Treated, Light	similar compoun ds	Mild irritant
Mineral Oil	Rabbit	No significant irritation
Morpholine	Rabbit	Corrosive
Carbon Black	Rabbit	No significant irritation
Propylene Glycol	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Rabbit	No significant irritation
Hydrotreated Heavy Naptha (Petroleum)	similar	No significant irritation
	compoun	
	ds	
Glycerin	Rabbit	No significant irritation
Distillates (Petroleum), Acid Treated, Light	similar	No significant irritation
	compoun	
	ds	
Mineral Oil	Rabbit	Mild irritant
Morpholine	Rabbit	Corrosive
Carbon Black	Rabbit	No significant irritation
Propylene Glycol	Rabbit	No significant irritation

Sensitization:

Skin Sensitization

Skiii Selisiuzauoli				
Name	Species	Value		
	*			
		27 1 10 1		
Hydrotreated Heavy Naptha (Petroleum)	similar	Not classified		
	compoun			

3MTM Finesse-itTM Polish - Final Finish [105]

	ds	
Glycerin	Guinea	Not classified
	pig	
Distillates (Petroleum), Acid Treated, Light	similar	Not classified
	compoun	
	ds	
Mineral Oil	Guinea	Not classified
	pig	
Morpholine	Guinea	Not classified
	pig	
Propylene Glycol	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Aluminum Oxide Mineral (non-fibrous)	In Vitro	Not mutagenic
Hydrotreated Heavy Naptha (Petroleum)	In Vitro	Not mutagenic
Distillates (Petroleum), Acid Treated, Light	In Vitro	Not mutagenic
Mineral Oil	In Vitro	Not mutagenic
Morpholine	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Morpholine	In vivo	Some positive data exist, but the data are not
		sufficient for classification
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not
		sufficient for classification
Propylene Glycol	In Vitro	Not mutagenic
Propylene Glycol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide Mineral (non-fibrous)	Inhalation	Rat	Not carcinogenic
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Mineral Oil	Dermal	Mouse	Not carcinogenic
Mineral Oil	Inhalation	Multiple animal	Not carcinogenic
		species	
Morpholine	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Morpholine	Inhalation	Rat	Not carcinogenic
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic
Propylene Glycol	Dermal	Mouse	Not carcinogenic
Propylene Glycol	Ingestion	Multiple	Not carcinogenic
		animal	
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation

Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Mineral Oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Morpholine	Ingestion	Not classified for development		NA	
Morpholine	Ingestion	Toxic to male reproduction	similar compoun ds	NOAEL 60 mg/kg/day	2 generation
Propylene Glycol	Ingestion	Not classified for female reproduction	Mouse	NOAEL 10,100 mg/kg/day	2 generation
Propylene Glycol	Ingestion	Not classified for male reproduction	Mouse	NOAEL 10,100 mg/kg/day	2 generation
Propylene Glycol	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,230 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydrotreated Heavy Naptha (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Distillates (Petroleum), Acid Treated, Light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Morpholine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Propylene Glycol	Ingestion	central nervous system depression	Not classified	Human and animal	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide Mineral (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Glycerin	Inhalation	respiratory system	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Inhalation	heart	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Inhalation	liver	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Glycerin	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years

Glycerin	Ingestion	liver	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Glycerin	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Distillates (Petroleum), Acid Treated, Light	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Distillates (Petroleum), Acid Treated, Light	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Mineral Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
Mineral Oil	Ingestion	liver	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Mineral Oil	Ingestion	immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Morpholine	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Guinea pig	LOAEL 900 mg/kg/day	13 days
Morpholine	Dermal	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	LOAEL 900 mg/kg/day	13 days
Morpholine	Dermal	hematopoietic system	Not classified	Guinea pig	NOAEL 900 mg/kg/day	13 days
Morpholine	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Morpholine	Inhalation	pulmonary fibrosis	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.09 mg/l	13 weeks
Morpholine	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 64 mg/l	5 days
Morpholine	Inhalation	liver	Not classified	Rat	LOAEL 64 mg/l	5 days
Morpholine	Inhalation	heart	Not classified	Rat	NOAEL 0.9 mg/l	13 weeks
Morpholine	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.9 mg/l	13 weeks
Morpholine	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 0.53 mg/l	104 weeks
Morpholine	Inhalation	nervous system	Not classified	Rat	NOAEL 0.53 mg/l	104 weeks
Morpholine	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 160 mg/kg/day	30 days
Morpholine	Ingestion	hematopoietic	Not classified	Rat	NOAEL 800	30 days

		system			mg/kg/day	
Morpholine	Ingestion	endocrine system	Not classified	Rat	NOAEL 323	4 weeks
		-			mg/kg/day	
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not	occupational
					available	exposure
Propylene Glycol	Ingestion	hematopoietic	Not classified	Multiple	NOAEL	117 days
		system		animal	1,370	-
				species	mg/kg/day	
Propylene Glycol	Ingestion	kidney and/or	Not classified	Dog	NOAEL	104 weeks
		bladder			5,000	
					mg/kg/day	

Aspiration Hazard

Name	Value
Hydrotreated Heavy Naptha (Petroleum)	Aspiration hazard
Distillates (Petroleum), Acid Treated, Light	Aspiration hazard
Mineral Oil	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Aluminum Oxide Mineral (non- fibrous)	1344-28-1	N/A	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide Mineral (non- fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide Mineral (non- fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide Mineral (non- fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Glycerin	56-81-5	Rainbow Trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerin	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
Glycerin	56-81-5	Bacteria	Experimental	16 hours	NOEC	10,000 mg/l
Hydrotreated Heavy Naptha (Petroleum)	64742-48-9	Green algae	Analogous Compound	72 hours	EL50	>1,000 mg/l
Hydrotreated Heavy Naptha (Petroleum)	64742-48-9	Rainbow Trout	Analogous Compound	96 hours	LL50	>1,000 mg/l

Hydrotreated	64742-48-9	Water flea	Analogous	48 hours	EL50	>1,000 mg/l
Heavy Naptha	04742-46-9	Water fiea	Compound	46 1100115	ELSO	-1,000 Hig/1
(Petroleum)			Сотроина			
Hydrotreated	64742-48-9	Fathead Minnow	Analogous	32 days	NOEL	>100 mg/l
Heavy Naptha	017.2 10 7	T durioud Tillinio II	Compound	5 2 day 5	1,022	100 mg/1
(Petroleum)			1			
Hydrotreated	64742-48-9	Green algae	Analogous	72 hours	NOEL	1,000 mg/l
Heavy Naptha			Compound			
(Petroleum)						
Hydrotreated	64742-48-9	Water flea	Experimental	21 days	NOEL	>1 mg/l
Heavy Naptha						
(Petroleum)						
Distillates	64742-14-9	Green algae	Estimated	72 hours	EL50	>1,000 mg/l
(Petroleum), Acid						
Treated, Light	64742 14 0	D : 1	To discontinuation	061	11.50	. 1 000 //
Distillates	64742-14-9	Rainbow Trout	Estimated	96 hours	LL50	>1,000 mg/l
(Petroleum), Acid Treated, Light						
Distillates	64742-14-9	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
(Petroleum), Acid	04/42-14-9	water fiea	Estimateu	46 110015	ELSO	71,000 Hig/1
Treated, Light						
Distillates	64742-14-9	Green algae	Estimated	72 hours	NOEL	>1,000 mg/l
(Petroleum), Acid	01712117	Green uigue	Estimated	72 hours	TOLL	1,000 mg/1
Treated, Light						
Mineral Oil	8042-47-5	Water flea	Analogous	48 hours	EL50	>100 mg/l
			Compound			
Mineral Oil	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
Mineral Oil	8042-47-5	Green algae	Analogous	72 hours	NOEL	100 mg/l
			Compound			
Mineral Oil	8042-47-5	Water flea	Analogous	21 days	NOEL	>100 mg/l
		1	Compound			
Morpholine	110-91-8	Activated sludge	Experimental	30 minutes	EC20	>1,000 mg/l
Morpholine	110-91-8	Fish	Experimental	96 hours	LC50	100 mg/l
Morpholine	110-91-8	Green algae	Experimental	96 hours	ErC50	28 mg/l
Morpholine	110-91-8	Rainbow Trout	Experimental	96 hours	LC50	180 mg/l
Morpholine	110-91-8	Water flea	Experimental	48 hours	EC50	45 mg/l
Morpholine	110-91-8	Green algae	Experimental	96 hours	NOEC	10 mg/l
Morpholine	110-91-8	Water flea	Experimental	21 days	NOEC	5 mg/l
Carbon Black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt	>100 mg/l
Carbon Black	1222 06 4	Zebra Fish	Г	061	of water sol	> 100 //
Carbon Black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon Black	1333-86-4	Croon algon	Exmanimantal	72 hours	No tox obs at lmt	100 mg/l
Carbon Black	1333-80-4	Green algae	Experimental	72 Hours	of water sol	100 mg/1
Carbon Black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l
Propylene Glycol	57-55-6	Amphipod	Experimental	10 days	LC50	6,983 mg/kg (Dry Weight)
Propylene Glycol	57-55-6	Green algae	Experimental	96 hours	EC50	19,000 mg/l
Propylene Glycol	57-55-6	Mysid Shrimp	Experimental	96 hours	LC50	18,800 mg/l
Propylene Glycol	57-55-6	Rainbow Trout	Experimental	96 hours	LC50	40,613 mg/l
Propylene Glycol	57-55-6	Water flea	Experimental	48 hours	EC50	18,340 mg/l
Propylene Glycol	57-55-6	Green algae	Experimental	96 hours	NOEC	15,000 mg/l
Propylene Glycol	57-55-6	Water flea	Experimental	7 days	NOEC	13,020 mg/l
Propylene Glycol	57-55-6	Bacteria	Experimental	18 hours	NOEC	>20,000 mg/l
1 ropyrene Grycol	121-22-0	расила	Lexperimental	10 110015	INOEC	1~20,000 HIg/I

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Aluminum Oxide Mineral (non- fibrous)	1344-28-1	Data not availblinsufficient	N/A	N/A	N/A	N/A
Glycerin	56-81-5	Experimental Biodegradation	14 days	Biological Oxygen Demand	63 %BOD/ThOD	OECD 301C - MITI (I)

Hydrotreated Heavy Naptha (Petroleum)	64742-48-9	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	31.3 %BOD/ThOD	OECD 301F - Manometric Respiro
Distillates (Petroleum), Acid Treated, Light	64742-14-9	Estimated Biodegradation	28 days	Biological Oxygen Demand	69 %BOD/ThOD	OECD 301F - Manometric Respiro
Mineral Oil	8042-47-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Morpholine	110-91-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	93 %removal of DOC	OECD 301E - Modif. OECD Screen
Morpholine	110-91-8	Experimental Biodegradation	31 days	Dissolv. Organic Carbon Deplet	98 %removal of DOC	OECD 302B Zahn- Wellens/EVPA
Carbon Black	1333-86-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Propylene Glycol	57-55-6	Experimental Biodegradation	28 days	Biological Oxygen Demand	90 %BOD/ThOD	OECD 301C - MITI (I)
Propylene Glycol	57-55-6	Experimental Biodegradation	64 days	Dissolv. Organic Carbon Deplet	95.8 %removal of DOC	OECD 306(Misc)-Biodegrad. Seaw

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Aluminum Oxide Mineral (non- fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerin	56-81-5	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-1.75	similar to OECD 107
Hydrotreated Heavy Naptha (Petroleum)	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (Petroleum), Acid Treated, Light	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mineral Oil	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Morpholine	110-91-8	Experimental BCF - Fish	42 days	Bioaccumulation Factor	<2.8	OECD305-Bioconcentration
Morpholine	110-91-8	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-2.55	OECD 107 log Kow shke flsk mtd
Carbon Black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propylene Glycol	57-55-6	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-1.07	EC A.8 Partition Coefficient

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number: None assigned.

Proper Shipping Name: None assigned.

Technical Name: None assigned.

Hazard Class/Division: None assigned.

Subsidiary Risk:None assigned. **Packing Group:**None assigned.

Limited Quantity: None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number: None assigned.

Proper Shipping Name: None assigned.

Technical Name: None assigned.

Hazard Class/Division: None assigned.

Subsidiary Risk: None assigned.

Packing Group: None assigned.

Limited Quantity: None assigned. Marine Pollutant: None assigned.

Marine I onutant. None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my