Safety Data Sheet

Copyright,2024, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	43-6983-1	**Version Number:**	2.00
Issue Date:	13/11/2024	**Supercedes Date:**	02/09/2022

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier
3M™ Perfect-It Ultrafine Machine Polish PN06068

Product Identification Numbers
XP-0038-3289-4

1.2. Recommended use and restrictions on use

Recommended use
Abrasive Product

For Industrial or Professional use only

1.3. Supplier's details
ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number
+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Skin Sensitizer: Category 1.
Chronic Aquatic Toxicity: Category 3.

2.2. Label elements
Signal word
Warning

Symbols
Exclamation mark |

Pictograms

Hazard Statements:

H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P280E	Wear protective gloves.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Aspiration classification does not apply due to the viscosity of the product.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	40 - 70
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	10 - 30
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	< 20
Aluminum Oxide	1344-28-1	3 - 7
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	1 - 5
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	64742-56-9	< 2
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	< 2
2-Methyl-4-isothiazoline-3-one	2682-20-4	< 0.1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) May form combustible dust during processing. Dust clouds of this material in sufficient concentration in combination with an ignition source may be explosive. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions. Routine housekeeping should be instituted to ensure that combustible dusts do not accumulate on surfaces. Combustible dust may form by action of this product on another material (substrate). Dust generated from the substrate during use of this product may be explosive if in sufficient concentration with an ignition source. Dust deposits should not be allowed to accumulate on surfaces because of the potential for secondary explosions.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m3	
Aluminum Oxide	1344-28-1	Malaysia OELs	TWA (proposed)(8 hours):10 mg/m3	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
OIL MIST, MINERAL	64742-55-8	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m3	
OIL MIST, MINERAL	64742-56-9	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m3	
MINERAL OILS, HIGHLY-REFINED OILS	64742-56-9	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
OIL MIST, MINERAL	64742-65-0	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
CMRG : Chemical Manufacturer's Recommended Guidelines
Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide local exhaust at process emission sources to control exposure near the source and to prevent the escape of dust into the work area. It is recommended that all dust control equipment (such as local exhaust ventilation), process equipment, and material transport systems involved in handling of this product be evaluated for the need for explosion-protection safeguards. Recognized safeguards include explosion relief vents, explosion suppression systems, and oxygen deficient process environments. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Evaluate the need for electrically classified equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection
None required.

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Emulsion
Color	Blue
Odor	Slight Petroleum
Odor threshold	*No Data Available*
pH	7.5 - 8.5
Melting point/Freezing point	*No Data Available*
Boiling point/Initial boiling point/Boiling range	>=100 ºC
Flash Point	>=110 ºC [*Test Method:*Closed Cup]
Evaporation rate	*No Data Available*

Flammability	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*
Relative Vapor Density	*No Data Available*
Density	0.911 - 1.007 g/ml
Relative Density	0.911 - 1.007 [*Ref Std:*WATER=1]
Water solubility	*No Data Available*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*No Data Available*
Volatile Organic Compounds	*No Data Available*
Percent volatile	*No Data Available*
VOC Less H2O & Exempt Solvents	*No Data Available*
Molecular weight	*No Data Available*

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat
Sparks and/or flames

10.5. Incompatible materials
Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	**Condition**
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
DODECAMETHYLCYCLOHEXASILOXANE	Dermal	Rat	LD50 > 2,000 mg/kg
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	Rat	LD50 > 2,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	similar compounds	LD50 > 2,000 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Solvent dewaxed heavy paraffinic distillate (petroleum)	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 4 mg/l
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Dermal	Rabbit	LD50 > 5,000 mg/kg
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES	Inhalation-	Rat	LC50 > 4 mg/l

(PETROLEUM)	Dust/Mist (4 hours)		
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated light paraffinic distillates (petroleum)	Dermal	similar compounds	LD50 > 2,000 mg/kg
Hydrotreated light paraffinic distillates (petroleum)	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 5.53 mg/l
Hydrotreated light paraffinic distillates (petroleum)	Ingestion	similar compounds	LD50 > 5,000 mg/kg
2-Methyl-4-isothiazoline-3-one	Dermal	Rat	LD50 242 mg/kg
2-Methyl-4-isothiazoline-3-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.11 mg/l
2-Methyl-4-isothiazoline-3-one	Ingestion	Rat	LD50 120 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
DODECAMETHYLCYCLOHEXASILOXANE	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Aluminum Oxide	Rabbit	No significant irritation
Solvent dewaxed heavy paraffinic distillate (petroleum)	Rabbit	No significant irritation
Hydrotreated light paraffinic distillates (petroleum)	similar compounds	No significant irritation
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Rabbit	Minimal irritation
2-Methyl-4-isothiazoline-3-one	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
DODECAMETHYLCYCLOHEXASILOXANE	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Aluminum Oxide	Rabbit	No significant irritation
Solvent dewaxed heavy paraffinic distillate (petroleum)	Rabbit	No significant irritation
Hydrotreated light paraffinic distillates (petroleum)	similar compounds	No significant irritation
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Rabbit	No significant irritation
2-Methyl-4-isothiazoline-3-one	Rabbit	Corrosive

Sensitization:

Skin Sensitization

Name	Species	Value
DODECAMETHYLCYCLOHEXASILOXANE	Guinea pig	Not classified
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea pig	Not classified
Solvent dewaxed heavy paraffinic distillate (petroleum)	Guinea pig	Not classified
Hydrotreated light paraffinic distillates (petroleum)	similar compounds	Not classified
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Guinea pig	Not classified
2-Methyl-4-isothiazoline-3-one	Human and	Sensitizing

	animal	

Photosensitization

Name	Species	Value
2-Methyl-4-isothiazoline-3-one	Human and animal	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
DODECAMETHYLCYCLOHEXASILOXANE	In Vitro	Not mutagenic
DODECAMETHYLCYCLOHEXASILOXANE	In vivo	Not mutagenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
Aluminum Oxide	In Vitro	Not mutagenic
Solvent dewaxed heavy paraffinic distillate (petroleum)	In Vitro	Not mutagenic
Hydrotreated light paraffinic distillates (petroleum)	In Vitro	Not mutagenic
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	In vivo	Not mutagenic
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Methyl-4-isothiazoline-3-one	In vivo	Not mutagenic
2-Methyl-4-isothiazoline-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Mouse	Not carcinogenic
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
2-Methyl-4-isothiazoline-3-one	Dermal	Mouse	Not carcinogenic
2-Methyl-4-isothiazoline-3-one	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,000 mg/kg/day	during gestation
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
2-Methyl-4-isothiazoline-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DODECAMETHYLCYCLOHEXASILOXANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Notavailable	
2-Methyl-4-isothiazoline-3-one	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DODECAMETHYLCYCLOHEXASILOXANE	Inhalation	liver	Not classified	Rat	NOAEL 0.546 mg/l	90 days
DODECAMETHYLCYCLOHEXASILOXANE	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.018 mg/l	90 days
DODECAMETHYLCYCLOHEXASILOXANE	Inhalation	hematopoietic system | eyes	Not classified	Rat	NOAEL 0.546 mg/l	90 days
DODECAMETHYLCYCLOHEXASILOXANE	Ingestion	endocrine system | liver | hematopoietic system | nervous system | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Aluminum Oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Solvent dewaxed heavy paraffinic distillate (petroleum)	Dermal	skin | liver | hematopoietic system | kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	13 weeks
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Dermal	hematopoietic system | liver | kidney and/or bladder	Not classified	Rabbit	NOAEL 5,000 mg/kg/day	3 weeks

Aspiration Hazard

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
Solvent dewaxed heavy paraffinic distillate (petroleum)	Not an aspiration hazard
Hydrotreated light paraffinic distillates (petroleum)	Aspiration hazard
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:
GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:
GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Green algae	Experimental	72 hours	EC50	>100 mg/l
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Fathead Minnow	Experimental	49 days	NOEC	100 mg/l
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Green algae	Experimental	72 hours	NOEC	100 mg/l
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Water flea	Experimental	21 days	NOEC	100 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Green algae	Estimated	72 hours	EC50	1 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Rainbow Trout	Estimated	96 hours	LL50	2 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Water flea	Estimated	48 hours	EL50	1.4 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Green algae	Estimated	72 hours	NOEL	1 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Water flea	Estimated	21 days	NOEL	0.48 mg/l
Aluminum Oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Green algae	Analogous Compound	96 hours	EC50	>100 mg/l
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Water flea	Analogous Compound	48 hours	EC50	>100 mg/l
Solvent dewaxed	64742-65-0	Rainbow Trout	Experimental	96 hours	LC50	>100 mg/l

heavy paraffinic distillate (petroleum)						
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Water flea	Experimental	21 days	NOEC	100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Fathead Minnow	Estimated	96 hours	LL50	>100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Water flea	Estimated	48 hours	EL50	>100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Green algae	Estimated	72 hours	NOEL	100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Water flea	Estimated	21 days	NOEC	10 mg/l
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	64742-56-9	Fathead Minnow	Estimated	96 hours	LL50	>100 mg/l
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	64742-56-9	Green algae	Estimated	72 hours	EL50	>100 mg/l
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	64742-56-9	Water flea	Estimated	48 hours	EL50	>100 mg/l
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	64742-56-9	Green algae	Estimated	72 hours	NOEL	100 mg/l
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	64742-56-9	Water flea	Estimated	21 days	NOEL	100 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Diatom	Experimental	72 hours	ErC50	0.099 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Green algae	Experimental	96 hours	ErC50	0.23 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Mysid Shrimp	Experimental	96 hours	LC50	1.81 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Sheepshead Minnow	Experimental	96 hours	LC50	25.1 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Water flea	Experimental	48 hours	LC50	0.934 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Blackworm	Experimental	28 days	NOEC	25 mg/kg (Dry Weight)
2-Methyl-4-isothiazoline-3-one	2682-20-4	Diatom	Experimental	72 hours	ErC10	0.04 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Fathead Minnow	Experimental	33 days	NOEC	2.1 mg/l
2-Methyl-4-isothiazoline-3-one	2682-20-4	Green algae	Experimental	96 hours	NOEC	0.12 mg/l
2-Methyl-4-	2682-20-4	Water flea	Experimental	21 days	NOEC	0.044 mg/l

isothiazoline-3-one						
2-Methyl-4-isothiazoline-3-one	2682-20-4	Activated sludge	Experimental	3 hours	EC50	41 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Experimental Biodegradation	28 days	Carbon dioxide evolution	4.47 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Aluminum Oxide	1344-28-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Experimental Biodegradation	28 days	Carbon dioxide evolution	23 %CO2 evolution/THCO2 evolution	similar to OECD 301B
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Estimated Biodegradation	28 days	Carbon dioxide evolution	22 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	64742-56-9	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	31 %BOD/ThOD	OECD 301F - Manometric Respiro
2-Methyl-4-isothiazoline-3-one	2682-20-4	Experimental Biodegradation	29 days	Carbon dioxide evolution	50 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
2-Methyl-4-isothiazoline-3-one	2682-20-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	Experimental BCF - Fish	49 days	Bioaccumulation Factor	1160	OECD305-Bioconcentration
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminum Oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent dewaxed heavy paraffinic distillate (petroleum)	64742-65-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATES (PETROLEUM)	64742-56-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Methyl-4-	2682-20-4	Analogous	56 days	Bioaccumulation	5.75	

isothiazoline-3-one		Compound BCF - Fish		Factor		
2-Methyl-4-isothiazoline-3-one	2682-20-4	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-0.486	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil
Please contact manufacturer for more details

12.5 Other adverse effects
No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number: None assigned.
Proper Shipping Name: None assigned.
Technical Name: None assigned.
Hazard Class/Division: None assigned.
Subsidiary Risk: None assigned.
Packing Group: None assigned.
Limited Quantity: None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Air Transport (IATA)

UN Number: None assigned.
Proper Shipping Name: None assigned.
Technical Name: None assigned.
Hazard Class/Division: None assigned.
Subsidiary Risk: None assigned.
Packing Group: None assigned.
Limited Quantity: None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to

transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status
Contact 3M for more information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my