

Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 44-4760-3
 Version number:
 2.00

 Issue Date:
 2025/09/25
 Supersedes Date:
 2024/06/06

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Bondo® Fiberglass Resin Liquid Hardener, 20126, 912, 912M, 912C, 912ES, 401, 401C, 402, 402C, 402T, 402Z, 404, 404C, 404Z, 420, 420C, 420E, 420K, 420T, 422, 422C, 411, 609, 912, 912M, 912C, 912ES, 7653081

Product Identification Numbers

60-4550-6615-3

1.2. Recommended use and restrictions on use

Intended Use

Automotive

Specific Use

Curing Agent

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company

Division: Construction and Home Improvement Markets

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

The following product identification number(s) are sold in the consumer market place: 60-4550-6615-3

2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 4. Skin Corrosion/Irritation: Category 1C.

Serious Eye Damage/Irritation: Category 1.

Reproductive Toxicity: Category 2.

Health Hazards Not Otherwise Classified - Category 1

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Harmful if swallowed. Causes severe skin burns and eye damage. Suspected of damaging fertility or the unborn child. May cause chemical gastrointestinal burns.

Precautionary statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Obtain, read and follow all safety instructions before use. Do not breathe vapours, dust, or spray. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, protective clothing, eye protection, and face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards

None known.

3% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Methyl Ethyl Ketone Peroxide | 1338-23-4 | 15 - 40 Trade Secret * | 2-Butanone, peroxide |
|---------------------------------|-----------|------------------------|--------------------------------------------|
| 2,2,4-Trimethyl-1,3-pentanediol | 6846-50-0 | 10 - 30 Trade Secret * | Propanoic acid, 2-methyl-, 2,2-dimethyl-1- |
| diisobutyrate | | | (1-methylethyl)-1,3-propanediyl ester |
| Hydrogen Peroxide | 7722-84-1 | 1 - 5 Trade Secret * | Hydrogen peroxide (H2O2) |
| Methyl Ethyl Ketone | 78-93-3 | 1 - 5 | 2-Butanone |

^{*}The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Unsuitable extinguishing media

None Determined

5.3. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionIrritant Vapours or GasesDuring Combustion

5.4. Special protection actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Page: 3 of 11

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Store at temperatures not exceeding 77°F (25°C). Keep cool. Keep only in original container. Store away from acids. Store away from oxidizing agents. Store away from other materials. Keep/store away from clothing and other combustible materials. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|------------------------------|------------|--------|--------------|--------------------------------|
| Methyl Ethyl Ketone Peroxide | 1338-23-4 | ACGIH | CEIL:0.2 ppm | |
| Hydrogen Peroxide | 7722-84-1 | ACGIH | TWA:1 ppm | |
| Methyl Ethyl Ketone | 78-93-3 | ACGIH | | Danger of cutaneous absorption |

Dagas A of 1

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Butyl Rubber

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| mor mation on basic physical and chemical properties | | |
|------------------------------------------------------|-------------------|--|
| Physical state | Liquid | |
| Colour | Colourless | |
| Odour | Slight Odour | |
| Odour threshold | No Data Available | |
| pH | No Data Available | |
| Melting point/Freezing point | No Data Available | |

| Boiling point | 117.8 °C | |
|-----------------------------------------|---------------------------------------------------------|--|
| Flash Point | > 93.3 °C [Test Method:Closed Cup] [Details:No flash to | |
| | boiling point.] | |
| Evaporation rate | No Data Available | |
| Flammability | Organic Peroxide: Type D. | |
| | | |
| Flammable Limits(LEL) | No Data Available | |
| Flammable Limits(UEL) | No Data Available | |
| Vapour Pressure | No Data Available | |
| Relative Vapour Density | > 1 Units not available or not applicable | |
| Density | 1.1 g/ml | |
| Relative density | 1.1 [Ref Std:WATER=1] | |
| Water solubility | Negligible | |
| Solubility- non-water | No Data Available | |
| Partition coefficient: n-octanol/ water | No Data Available | |
| Autoignition temperature | No Data Available | |
| Decomposition temperature | No Data Available | |
| Kinematic Viscosity | No Data Available | |
| Volatile Organic Compounds | 39 g/l [Test Method:calculated SCAQMD rule 443.1] | |
| Volatile Organic Compounds | 3.5 % weight [Test Method: Tested per ASTM protocol] | |
| Percent volatile | 45 % weight | |
| VOC Less H2O & Exempt Solvents | 39 g/l [Test Method:calculated SCAQMD rule 443.1] | |

| Particle Characteristics | Not Applicable |
|--------------------------|----------------|
|--------------------------|----------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Light

Sparks and/or flames

Temperatures above the boiling point

10.5. Incompatible materials

Strong oxidizing agents Alkali and alkaline earth metals Strong acids

10.6. Hazardous decomposition products

Condition Substance

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. May cause additional health effects (see below).

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Dermal Effects: Signs/symptoms may include changes in skin pigmentation and/or colouration.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-----------------------------------------------|---------------------------------------|--------------------------|-------------------------------------------------------|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation- Vapor(4 hr) | | No data available; calculated ATE >20 - =50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >300 - =2,000 mg/kg |
| Methyl Ethyl Ketone Peroxide | Dermal | Rabbit | LD50 4,000 mg/kg |
| Methyl Ethyl Ketone Peroxide | Inhalation- Vapor (4 hours) | Rat | LC50 15.4 mg/l |
| Methyl Ethyl Ketone Peroxide | Ingestion | Rat | LD50 484 mg/kg |
| Methyl Ethyl Ketone Peroxide | Inhalation- Dust/Mist (4 hours) | similar compoun ds | LC50 1.5 mg/l |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate | Dermal | Guinea pig | LD50 > 18,800 mg/kg |

Page: 7 of 11

| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 8 mg/l |
|-----------------------------------------------|---------------------------------------|--------|--------------------|
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate | Ingestion | Rat | LD50 > 3,200 mg/kg |
| Methyl Ethyl Ketone | Dermal | Rabbit | LD50 > 8,050 mg/kg |
| Methyl Ethyl Ketone | Inhalation- Vapor (4 hours) | Rat | LC50 34.5 mg/l |
| Methyl Ethyl Ketone | Ingestion | Rat | LD50 2,737 mg/kg |
| Hydrogen Peroxide | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Hydrogen Peroxide | Inhalation- Dust/Mist (4 hours) | Rat | LC50 2 mg/l |
| Hydrogen Peroxide | Ingestion | Rat | LD50 1,193 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|------------------------------|---------|--------------------|
| | | |
| Methyl Ethyl Ketone Peroxide | Rabbit | Corrosive |
| Methyl Ethyl Ketone | Rabbit | Minimal irritation |
| Hydrogen Peroxide | Rabbit | Corrosive |

Serious Eye Damage/Irritation

| Name | Species | Value |
|------------------------------|---------|-----------------|
| Methyl Ethyl Ketone Peroxide | Human | Corrosive |
| Methyl Ethyl Ketone | Rabbit | Severe irritant |
| Hydrogen Peroxide | Rabbit | Corrosive |

Skin Sensitization

| Name | Species | Value |
|------------------------------|---------|----------------|
| Methyl Ethyl Ketone Peroxide | Human | Not classified |
| Hydrogen Peroxide | Guinea | Not classified |
| | niσ | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|------------------------------|----------|------------------------------------------------------------------------------|
| Methyl Ethyl Ketone Peroxide | In vivo | Not mutagenic |
| Methyl Ethyl Ketone Peroxide | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Methyl Ethyl Ketone | In Vitro | Not mutagenic |
| Hydrogen Peroxide | In vivo | Not mutagenic |
| Hydrogen Peroxide | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|------------------------------|------------------|-------------------------------|------------------------------------------------------------------------------|
| Methyl Ethyl Ketone Peroxide | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Methyl Ethyl Ketone | Inhalation | Human | Not carcinogenic |
| Hydrogen Peroxide | Dermal | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Hydrogen Peroxide | Ingestion | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

D 0 c 1

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|-----------------------------------------------|------------|----------------------------------------|-------------------------------|------------------------|----------------------|
| Methyl Ethyl Ketone Peroxide | Ingestion | Not classified for female reproduction | Rat | NOAEL 180 mg/kg/day | 2 generation |
| Methyl Ethyl Ketone Peroxide | Ingestion | Not classified for male reproduction | Rat | NOAEL 180 mg/kg/day | 2 generation |
| Methyl Ethyl Ketone Peroxide | Ingestion | Not classified for development | Multiple animal species | NOAEL 200 mg/kg/day | during gestation |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate | Ingestion | Toxic to development | Rabbit | NOAEL 300 mg/kg/day | during gestation |
| Methyl Ethyl Ketone | Inhalation | Not classified for development | Rat | LOAEL 8.8 mg/l | during gestation |
| Hydrogen Peroxide | Ingestion | Not classified for female reproduction | Rat | LOAEL 5 mg/kg/day | 6 months |
| Hydrogen Peroxide | Ingestion | Not classified for male reproduction | Rat | LOAEL 5 mg/kg/day | 6 months |
| Hydrogen Peroxide | Ingestion | Not classified for development | Rat | LOAEL 5 mg/kg/day | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------------------------|------------|--------------------------------------|------------------------------------------------------------------------------|-----------------------------------|------------------------|---------------------------|
| Methyl Ethyl Ketone Peroxide | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| Methyl Ethyl Ketone | Inhalation | central nervous system depression | May cause drowsiness or dizziness | official classifica tion | NOAEL Not available | |
| Methyl Ethyl Ketone | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Methyl Ethyl Ketone | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professio nal judgeme nt | NOAEL Not available | |
| Methyl Ethyl Ketone | Ingestion | liver | Not classified | Rat | NOAEL Not available | not applicable |
| Methyl Ethyl Ketone | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 1,080 mg/kg | not applicable |
| Hydrogen Peroxide | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | |
| Hydrogen Peroxide | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Human | LOAEL Not available | poisoning and/or abuse |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------|------------------------|----------------------|
| Methyl Ethyl Ketone Peroxide | Ingestion | hematopoietic system nervous system eyes | Not classified | Rat | NOAEL 150 mg/kg/day | 90 days |
| Methyl Ethyl Ketone | Dermal | nervous system | Not classified | Guinea pig | NOAEL Not available | 31 weeks |
| Methyl Ethyl Ketone | Inhalation | liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune | Not classified | Rat | NOAEL 14.7 mg/l | 90 days |

Page: 9 of 11

| | | system muscles | | | | |
|---------------------|-----------|-----------------------|----------------|-------|------------|----------|
| Methyl Ethyl Ketone | Ingestion | liver | Not classified | Rat | NOAEL Not | 7 days |
| | | | | | available | |
| Methyl Ethyl Ketone | Ingestion | nervous system | Not classified | Rat | NOAEL 173 | 90 days |
| | | | | | mg/kg/day | - |
| Hydrogen Peroxide | Ingestion | hematopoietic | Not classified | Rat | NOEL 0.005 | 6 months |
| | | system | | | mg/kg/day | |
| Hydrogen Peroxide | Ingestion | liver kidney and/or | Not classified | Mouse | NOAEL Not | 35 weeks |
| | _ | bladder | | | available | |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

n.... 10 . c . 11

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: Oxidizer

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| Document group: | 44-4760-3 | Version number: | 2.00 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2025/09/25 | Supersedes Date: | 2024/06/06 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

n.... 11 .c. 11