Safety Data Sheet

Copyright,2025, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	23-3337-5	**Version Number:**	7.00
Issue Date:	08/29/25	**Supersedes Date:**	12/15/22

SECTION 1: Identification

1.1. Product identifier
3M™ UV-Curable Adhesive LC-3200

Product Identification Numbers
JS-5000-0006-7
7000008167

1.2. Recommended use and restrictions on use

Recommended use
Adhesive

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	3M Japan Electronics Materials Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification
Serious Eye Damage/Irritation: Category 2B.
Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1A.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements
Signal word
Danger

Symbols
Exclamation mark | Health Hazard |

Pictograms



Hazard Statements
Causes eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure:
skin |

Precautionary Statements

Prevention:
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
IF exposed or concerned: Get medical advice/attention.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

70% of the mixture consists of ingredients of unknown acute oral toxicity.
70% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Acrylate Oligomer	Trade Secret*	45 - 70
HDODA	13048-33-4	25 - 55 Trade Secret *
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	119313-12-1	1 - 10 Trade Secret *
2-HYDROXYETHYL ACRYLATE	818-61-1	< 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities
Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
HDODA	13048-33-4	AIHA	TWA:1 mg/m3(0.11 ppm)	Dermal Sensitizer

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates, including oily mists

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	Light Yellow
Specific Physical Form:	Viscous
Odor	Acrylate
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*Not Applicable*
Boiling Point	>=151 ºC
Flash Point	151 ºC [*Test Method:*Closed Cup]
Evaporation rate	*Not Applicable*
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*
Vapor Density	*Not Applicable*
Density	1.03 g/ml
Specific Gravity	1.03 [*Ref Std:*WATER=1]
Solubility In Water	<=0.1 %
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Viscosity	1,000 - 10,000 centipoise
Molecular weight	*No Data Available*
Percent volatile	0 %

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
None known.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
May be harmful in contact with skin.
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:
Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:
Dermal Effects: Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Reproductive/Developmental Toxicity:
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HDODA	Dermal	Rabbit	LD50 3,636 mg/kg
HDODA	Ingestion	Rat	LD50 > 5,000 mg/kg
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Dermal	Rat	LD50 > 2,000 mg/kg
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Rat	LD50 > 5,000 mg/kg
2-HYDROXYETHYL ACRYLATE	Inhalation-Dust/Mist	Professional judgement	LC50 estimated to be 5 - 12.5 mg/l
2-HYDROXYETHYL ACRYLATE	Dermal	Rat	LD50 550-1000 mg/kg
2-HYDROXYETHYL ACRYLATE	Ingestion	Rat	LD50 548 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
HDODA	Rabbit	Irritant
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Rabbit	No significant irritation
2-HYDROXYETHYL ACRYLATE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
HDODA	Rabbit	Moderate irritant
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Rabbit	No significant irritation
2-HYDROXYETHYL ACRYLATE	similar health hazards	Corrosive

Skin Sensitization

Name	Species	Value
Acrylate Oligomer	Professional judgement	Some positive data exist, but the data are not sufficient for classification
HDODA	Guinea pig	Sensitizing
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Guinea pig	Not classified
2-HYDROXYETHYL ACRYLATE	Human and	Sensitizing

	animal	

Respiratory Sensitization
For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
HDODA	In Vitro	Some positive data exist, but the data are not sufficient for classification
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	In Vitro	Not mutagenic
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	In vivo	Not mutagenic
2-HYDROXYETHYL ACRYLATE	In vivo	Not mutagenic
2-HYDROXYETHYL ACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
HDODA	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
HDODA	Not Specified	Not classified for development	Rat	NOAEL 750 mg/kg/day	during organogenesis
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Toxic to development	Rat	NOAEL 30 mg/kg/day	1 generation
2-HYDROXYETHYL ACRYLATE	Dermal	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	7 weeks
2-HYDROXYETHYL ACRYLATE	Dermal	Not classified for male reproduction	Rat	NOAEL 10 mg/kg	7 weeks
2-HYDROXYETHYL ACRYLATE	Dermal	Not classified for development	Rat	NOAEL 10 mg/kg/day	7 weeks

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HDODA	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-HYDROXYETHYL ACRYLATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HDODA	Dermal	skin	May cause damage to organs	Mouse	LOAEL 70	80 weeks

			though prolonged or repeated exposure		mg/kg/day	
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	endocrine system | hematopoietic system | liver | kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	28 days
2-HYDROXYETHYL ACRYLATE	Dermal	hematopoietic system | immune system | heart | endocrine system | gastrointestinal tract | bone, teeth, nails, and/or hair | bone marrow | liver | muscles | nervous system | eyes | kidney and/or bladder | respiratory system | vascular system	Not classified	Rat	NOAEL 10 mg/kg/day	13 weeks

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable

Health Hazards
Reproductive toxicity
Respiratory or Skin Sensitization
Serious eye damage or eye irritation
Skin Corrosion or Irritation
Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	23-3337-5	**Version Number:**	7.00
Issue Date:	08/29/25	**Supersedes Date:**	12/15/22

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to

determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com