



Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	26-0472-6	Version number:	9.00
Revision date:	17/04/2025	Supersedes date:	16/04/2025
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™ Scotchcast™ Reenterable Electrical Insulating Resin 2123 Kit (A & B)

Product Identification Numbers

80-0002-1521-2	80-6112-6441-9	80-6112-6442-7	UU-0109-0262-3	UU-0109-0329-0
UU-0109-0330-8	UU-0109-1471-9			
7000031696	7000006197	7100179833	7100220930	7100220970
7100220994	7100220923			

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Electrical

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: ner-productstewardship@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

25-0707-7, 25-0695-4

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Reproductive Toxicity, Category 2 - Repr. 2; H361d

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Contains:

Distillates (petroleum), hydrotreated heavy naphthenic; 1,3-Butadiene, homopolymer, hydroxy-terminated; N-Methyldidecylamine

HAZARD STATEMENTS:

H317	May cause an allergic skin reaction.
H361d	Suspected of damaging the unborn child.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273	Avoid release to the environment.
P280K	Wear protective gloves and respiratory protection.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Nota L applied.

Revision information:

GB Label: CLP Ingredients - kit components information was added.

Kit: Component document group number(s) information was modified.

Label: CLP Classification information was modified.

Label: CLP Precautionary - Prevention information was modified.

Label: Graphic information was modified.

Section 02: CLP Physical and Health Hazard Statements information was modified.

Section 1: E-mail address information was modified.



Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	25-0695-4	Version number:	9.01
Revision date:	20/08/2025	Supersedes date:	05/08/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotchcast™ Reenterable Electrical Insulating Resin 2123, Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Electrical

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain**SIGNAL WORD**

WARNING.

Symbols

GHS07 (Exclamation mark) |

Pictograms**HAZARD STATEMENTS:**

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P280E Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

28% of the mixture consists of components of unknown acute oral toxicity.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Soybean oil	(CAS-No.) 8001-22-7 (EC-No.) 232-274-4	60 - 75	Substance with a national occupational exposure limit
Butadiene-maleic anhydride copolymer	(CAS-No.) 25655-35-0	15 - 30	Substance not classified as hazardous
Soybean oil, epoxidised	(CAS-No.) 8013-07-8 (EC-No.) 232-391-0	1 - 10	Substance not classified as hazardous
2,6-Di-tert-butyl-p-cresol	(CAS-No.) 128-37-0	< 1	Aquatic Chronic 1, H410,M=1

	(EC-No.) 204-881-4		Aquatic Acute 1, H400,M=1
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 0.3	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412
maleic anhydride	(CAS-No.) 108-31-6 (EC-No.) 203-571-6	< 0.3	EUH071 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
maleic anhydride	(CAS-No.) 108-31-6 (EC-No.) 203-571-6	(C >= 0.001%) Skin Sens. 1A, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:
Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
maleic anhydride	108-31-6	UK HSE	TWA: 1 mg/m ³ ; STEL: 3 mg/m ³	Respiratory Sensitizer
toluene	108-88-3	UK HSE	TWA: 191 mg/m ³ (50 ppm); STEL: 384 mg/m ³ (100 ppm)	SKIN
2,6-Di-tert-butyl-p-cresol	128-37-0	UK HSE	TWA:10 mg/m ³	
DUST, INERT OR NUISANCE	8001-22-7	UK HSE	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	

UK HSE : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	>.3	=>8 hours
Neoprene.	>.3	=>8 hours
Nitrile rubber.	>.3	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing.

Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Resin
Colour	Brown, Transparent Yellow
Odor	Mild Hydrocarbon
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	246.1 °C
Flammability	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	>= 148.9 °C [Test Method:Closed Cup]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<= 186,158.4 Pa [@ 55 °C]
Density	0.89 g/ml
Relative density	0.89 [Ref Std:WATER=1]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

Average particle size	No data available.
Bulk density	No data available.
EU Volatile Organic Compounds	No data available.
Evaporation rate	No data available.
Molecular weight	No data available.
Percent volatile	No data available.
Softening point	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong acids.

Strong bases.

Reducing agents.

Strong oxidising agents.

No data available.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo

induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Soybean oil	Dermal		LD50 estimated to be > 5,000 mg/kg
Soybean oil	Ingestion		LD50 estimated to be > 5,000 mg/kg
Soybean oil, epoxidised	Dermal	Rabbit	LD50 > 20,000 mg/kg
Soybean oil, epoxidised	Ingestion	Rat	LD50 > 5,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg
maleic anhydride	Dermal	Rabbit	LD50 2,620 mg/kg
maleic anhydride	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Soybean oil	Professional judgement	Minimal irritation
Soybean oil, epoxidised	Rabbit	No significant irritation
2,6-Di-tert-butyl-p-cresol	Human and animal	Minimal irritation
toluene	Rabbit	Irritant
maleic anhydride	Human and animal	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Soybean oil	Professional judgement	Mild irritant

Soybean oil, epoxidised	Rabbit	No significant irritation
2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant
toluene	Rabbit	Moderate irritant
maleic anhydride	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Soybean oil, epoxidised	Guinea pig	Not classified
2,6-Di-tert-butyl-p-cresol	Human	Not classified
toluene	Guinea pig	Not classified
maleic anhydride	Multiple animal species	Sensitising

Respiratory Sensitisation

Name	Species	Value
maleic anhydride	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Soybean oil, epoxidised	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
maleic anhydride	In vivo	Not mutagenic
maleic anhydride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Soybean oil, epoxidised	Ingestion	Rat	Not carcinogenic
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Soybean oil, epoxidised	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
Soybean oil, epoxidised	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
Soybean oil, epoxidised	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	1 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500	2 generation

3M™ Scotchcast™ Reenterable Electrical Insulating Resin 2123, Part A

				mg/kg/day	
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
maleic anhydride	Ingestion	Not classified for female reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
maleic anhydride	Ingestion	Not classified for male reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
maleic anhydride	Ingestion	Not classified for development	Rat	NOAEL 140 mg/kg/day	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
maleic anhydride	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Soybean oil, epoxidised	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 1,250 mg/kg/day	2 years
2,6-Di-tert-butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-Di-tert-butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks

3M™ Scotchcast™ Reenterable Electrical Insulating Resin 2123, Part A

toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
maleic anhydride	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
maleic anhydride	Inhalation	endocrine system hematopoietic system nervous system kidney and/or bladder heart liver eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
maleic anhydride	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
maleic anhydride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
maleic anhydride	Ingestion	heart nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
maleic anhydride	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
maleic anhydride	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
maleic anhydride	Ingestion	skin endocrine system immune system eyes respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

Aspiration Hazard

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications

in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Soybean oil	8001-22-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Butadiene-maleic anhydride copolymer	25655-35-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Soybean oil, epoxidised	8013-07-8	Green algae	Endpoint not reached	72 hours	EbC50	>100 mg/l
Soybean oil, epoxidised	8013-07-8	Water flea	Experimental	24 hours	No tox obs at lmt of water sol	>100 mg/l
Soybean oil, epoxidised	8013-07-8	Green algae	Endpoint not reached	72 hours	NOEC	>100 mg/l
Soybean oil, epoxidised	8013-07-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Soybean oil, epoxidised	8013-07-8	Rape	Experimental	21 days	EC50	909 mg/kg (Dry Weight)
Soybean oil, epoxidised	8013-07-8	Redworm	Experimental	56 days	NOEC	1,000 mg/kg (Dry Weight)
Soybean oil, epoxidised	8013-07-8	Soil microbes	Experimental	28 days	EC50	402 mg/kg (Dry Weight)
2,6-Di-tert-butyl-p-cresol	128-37-0	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC10	0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l
maleic anhydride	108-31-6	Bacteria	Experimental	18 hours	EC10	44.6 mg/l
maleic anhydride	108-31-6	Rainbow trout	Experimental	96 hours	LC50	75 mg/l
maleic anhydride	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC50	74.4 mg/l
maleic anhydride	108-31-6	Water flea	Hydrolysis Product	48 hours	EC50	93.8 mg/l
maleic anhydride	108-31-6	Water flea	Experimental	21 days	NOEC	10 mg/l
maleic anhydride	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC10	11.8 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l

3M™ Scotchcast™ Reenterable Electrical Insulating Resin 2123, Part A

toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Soybean oil	8001-22-7	Experimental Biodegradation	28 days	CO2 evolution	76 %CO2 evolution/THCO2 evolution	
Butadiene-maleic anhydride copolymer	25655-35-0	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Soybean oil, epoxidised	8013-07-8	Experimental Biodegradation	28 days	CO2 evolution	92 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Soybean oil, epoxidised	8013-07-8	Analogous Compound Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH
2,6-Di-tert-butyl-p-cresol	128-37-0	Data not availbl-insufficient	N/A	N/A	N/A	N/A
maleic anhydride	108-31-6	Hydrolysis product Biodegradation	25 days	CO2 evolution	>90 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
maleic anhydride	108-31-6	Experimental Hydrolysis		Hydrolytic half-life	0.37 minutes (t 1/2)	
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Soybean oil	8001-22-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Butadiene-maleic anhydride copolymer	25655-35-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Soybean oil, epoxidised	8013-07-8	Experimental Bioconcentration		Log Kow	>6.2	OECD 117 log Kow HPLC method
2,6-Di-tert-butyl-p-cresol	128-37-0	Experimental BCF - Fish	56 days	Bioaccumulation factor	1277	OECD305-Bioconcentration
maleic anhydride	108-31-6	Experimental Bioconcentration		Log Kow	-2.61	OECD 107 log Kow shke flsk mtd
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Soybean oil, epoxidised	8013-07-8	Modeled Mobility in Soil	Koc	10,000,000,000 l/kg	Episuite™
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for	Please refer to the other sections of the SDS for further	Please refer to the other sections of the SDS for further information.

	further information.	information.	
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
2,6-Di-tert-butyl-p-cresol	128-37-0	Gr. 3: Not classifiable	International Agency for Research on Cancer
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
toluene	108-88-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and

Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information**List of relevant H statements**

EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 8: Personal Protection - Skin/body information information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



Safety Data Sheet

Copyright, 2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	25-0707-7	Version number:	14.00
Revision date:	14/04/2026	Supersedes date:	13/04/2026

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotchcast™ Reenterable Electrical Insulating Resin 2123, Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Electrical

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

A similar mixture has been tested for eye damage/irritation and the test results do not meet the criteria for classification.

A similar mixture has been tested for skin corrosion/irritation and the test results do not meet the criteria for classification.

Aspiration hazard classification does not apply due to the kinematic viscosity of the product.

CLASSIFICATION:

Reproductive Toxicity, Category 2 - Repr. 2; H361d

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	65 - 80
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5		15 - 30
N-Methyldidecylamine	7396-58-9	230-990-1	3 - 7

HAZARD STATEMENTS:

- H361d Suspected of damaging the unborn child.
- H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

- P273 Avoid release to the environment.
- P280E Wear protective gloves.

Response:

- P391 Collect spillage.

Nota L applied.

2.3. Other hazards

None known.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as
------------	---------------	---	---

			amended for GB
Distillates (petroleum), hydrotreated heavy naphthenic	(CAS-No.) 64742-52-5 (EC-No.) 265-155-0	65 - 80	Nota L Asp. Tox. 1, H304
1,3-Butadiene, homopolymer, hydroxy-terminated	(CAS-No.) 69102-90-5	15 - 30	Substance not classified as hazardous
N-Methyldidecylamine	(CAS-No.) 7396-58-9 (EC-No.) 230-990-1	3 - 7	Aquatic Acute 1, H400,M=100 Aquatic Chronic 1, H410,M=10 Acute Tox. 4, H302 Skin Irrit. 2, H315 Repr. 2, H361d

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons.
Carbon monoxide
Carbon dioxide.

Condition

During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls**8.2.1. Engineering controls**

Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type A

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Resin
Colour	Amber
Odor	Mild Epoxy
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	>= 260 °C
Flammability	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>

Flash point	>= 232.2 °C [Test Method: Closed Cup]
Autoignition temperature	>= 260 °C
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	665 mm ² /sec
Water solubility	<= 1 % [@ 77 °F]
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	<= 1 mm Hg [@ 131 °F]
Density	0.94 g/ml
Relative density	0.94 [Ref Std: WATER=1]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

Average particle size	No data available.
Bulk density	No data available.
EU Volatile Organic Compounds	No data available.
Evaporation rate	No data available.
Molecular weight	No data available.
Percent volatile	No data available.
Softening point	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong acids.
Strong bases.
Strong oxidising agents.
Reducing agents.

No data available.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic	Dermal	Rabbit	LD50 > 2,000 mg/kg
Distillates (petroleum), hydrotreated heavy naphthenic	Ingestion	Rat	LD50 > 5,000 mg/kg
1,3-Butadiene, homopolymer, hydroxy-terminated	Dermal		LD50 estimated to be > 5,000 mg/kg
1,3-Butadiene, homopolymer, hydroxy-terminated	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
N-Methyldidecylamine	Dermal	Rabbit	LD50 > 5,000 mg/kg
N-Methyldidecylamine	Ingestion	Rat	LD50 990 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Distillates (petroleum), hydrotreated heavy naphthenic	Rabbit	Minimal irritation
N-Methyldidecylamine	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Distillates (petroleum), hydrotreated heavy naphthenic	Rabbit	Mild irritant
N-Methyldidecylamine	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Distillates (petroleum), hydrotreated heavy naphthenic	Guinea pig	Not classified
N-Methyldidecylamine	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
N-Methyldidecylamine	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Distillates (petroleum), hydrotreated heavy naphthenic	Ingestion	Rat	Not carcinogenic
Distillates (petroleum), hydrotreated heavy naphthenic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
N-Methyldidecylamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 50 mg/kg/day	29 days
N-Methyldidecylamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 30 mg/kg/day	prematuring into lactation
N-Methyldidecylamine	Ingestion	Toxic to development	Rat	NOAEL 30 mg/kg/day	prematuring into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated heavy naphthenic	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
N-Methyldidecylamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
N-Methyldidecylamine	Ingestion	gastrointestinal tract respiratory system	Not classified	Rat	NOAEL 30 mg/kg/day	29 days
N-Methyldidecylamine	Ingestion	heart endocrine system hematopoietic system liver immune system	Not classified	Rat	NOAEL 50 mg/kg/day	29 days

		nervous system kidney and/or bladder				
--	--	--	--	--	--	--

Aspiration Hazard

Name	Value
Distillates (petroleum), hydrotreated heavy naphthenic	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Water flea	Analogous Compound	48 hours	No tox obs at lmt of water sol	>100 mg/l
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Fathead minnow	Endpoint not reached	96 hours	LL50	>100 mg/l
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Green algae	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Water flea	Analogous Compound	21 days	NOEL	10 mg/l
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Bacteria	Analogous Compound	10 minutes	NOEL	>1.93 mg/l
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
N-Methyldidecylamine	7396-58-9	Activated sludge	Experimental	3 hours	EC50	948 mg/l
N-Methyldidecylamine	7396-58-9	Green algae	Experimental	72 hours	ErC50	0.004 mg/l
N-Methyldidecylamine	7396-58-9	Rainbow trout	Experimental	96 hours	LC50	0.41 mg/l
N-Methyldidecylamine	7396-58-9	Water flea	Experimental	48 hours	EC50	0.024 mg/l
N-Methyldidecylamine	7396-58-9	Green algae	Experimental	72 hours	NOEC	0.002 mg/l

e						
---	--	--	--	--	--	--

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Analogous Compound Biodegradation	28 days	BOD	31 %BOD/ThOD	OECD 301F - Manometric respirometry
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	Data not available/insufficient	N/A	N/A	N/A	N/A
N-Methyldidecylamine	7396-58-9	Experimental Biodegradation	28 days	CO2 evolution	74 %CO2 evolution/THCO2 evolution (does not pass 10-day window)	OECD 301B - Modified Sturm or CO2

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Analogous Compound Bioconcentration		Log Kow	>6.0	
1,3-Butadiene, homopolymer, hydroxy-terminated	69102-90-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
N-Methyldidecylamine	7396-58-9	Modeled Bioconcentration		Bioaccumulation factor	405	Episuite™
N-Methyldidecylamine	7396-58-9	Modeled Bioconcentration		Log Kow	8.8	Episuite™

12.4. Mobility in soil

No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of

3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(METHYLDIDECYL AMINE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(METHYLDIDECYL AMINE)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(METHYLDIDECYL AMINE)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable.	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E1 Hazardous to the Aquatic environment	100	200

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information**List of relevant H statements**

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

List of Relevant Notas

Nota L	The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ('Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method' Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
--------	---

Revision information:

EU Section 09: pH information information was modified.

EU Section 14 - Table Data information was added.
EU Section 14 - Table Headers information was added.
GBSDS Section 14 Transport in bulk - Main Heading information was deleted.
GBSDS Section 14 UN Number information was deleted.
Label: Graphic information was modified.
Section 11: Aspiration Hazard Table information was added.
Section 11: Aspiration Hazard text information was deleted.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Bioaccumulative potential information information was modified.
Section 14 Classification Code – Main Heading information was deleted.
Section 14 Classification Code – Regulation Data information was deleted.
Section 14 Control Temperature – Main Heading information was deleted.
Section 14 Control Temperature – Regulation Data information was deleted.
Section 14 Emergency Temperature – Main Heading information was deleted.
Section 14 Emergency Temperature – Regulation Data information was deleted.
Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.
Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.
Section 14 Other Dangerous Goods – Main Heading information was deleted.
Section 14 Other Dangerous Goods – Regulation Data information was deleted.
Section 14 Packing Group – Main Heading information was deleted.
Section 14 Packing Group – Regulation Data information was deleted.
Section 14 Proper Shipping Name information was deleted.
Section 14 Regulations – Main Headings information was deleted.
Section 14 Segregation – Regulation Data information was deleted.
Section 14 Segregation Code – Main Heading information was deleted.
Section 14 Special Precautions – Main Heading information was deleted.
Section 14 Special Precautions – Regulation Data information was deleted.
Section 14 Transport in bulk – Regulation Data information was deleted.
Section 14 UN Number Column data information was deleted.
Section 16: Two-column table displaying the unique list of Notas for all components of the given material. information was added.
Section 3: Composition/ Information of ingredients table information was modified.
Section 8: Respiratory protection - recommended respirators information information was modified.
Section 9: Vapour pressure value information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.