



Safety Data Sheet

Copyright,2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	11-1278-8	Version number:	10.00
Revision date:	11/02/2026	Supersedes date:	03/12/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld(tm) Clear Primer 9348

Product Identification Numbers

UU-0082-7733-5

7100132671

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesive primer

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone: +353 1 280 3555
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
 Carcinogenicity, Category 2 - Carc. 2; H351
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
acetone	67-64-1	200-662-2	30 - 50
butanone	78-93-3	201-159-0	30 - 40
tetrahydrofuran	109-99-9	203-726-8	1 - 5

HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261A	Avoid breathing vapours.
P280K	Wear protective gloves and respiratory protection.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066

Repeated exposure may cause skin dryness or cracking.

13% of the mixture consists of components of unknown acute oral toxicity.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2	30 - 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
butanone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (REACH-No.) 01-2119457290-43	30 - 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Acrylic polymer	Trade Secret	10 - 15	Substance not classified as hazardous
tetrahydrofuran	(CAS-No.) 109-99-9 (EC-No.) 203-726-8	1 - 5	Flam. Liq. 2, H225 EUH019 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335 Acute Tox. 4, H302 STOT SE 3, H336
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	< 3	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412
Resin acids and rosin acids, esters with glycerol	(CAS-No.) 8050-31-5 (EC-No.) 232-482-5	0.5 - 1.5	Substance not classified as hazardous
methyl acetate	(CAS-No.) 79-20-9 (EC-No.) 201-185-2	< 1.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
4-methylpentan-2-one	(CAS-No.) 108-10-1 (EC-No.) 203-550-1	< 1	Flam. Liq. 2, H225 Acute Tox. 4, H332(LC50 = 11 mg/l ATE values per Annex VI) Eye Irrit. 2, H319 Carc. 2, H351

			STOT SE 3, H336 EUH066
cyclohexane	(CAS-No.) 110-82-7 (EC-No.) 203-806-2	< 1	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
tetrahydrofuran	(CAS-No.) 109-99-9 (EC-No.) 203-726-8	(C >= 25%) Eye Irrit. 2, H319 (C >= 25%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Dermal defatting (localized redness, itching, drying and cracking of skin). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Hydrocarbons.
Carbon monoxide
Carbon dioxide.
Hydrogen cyanide.
Ketones.
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in

eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
4-methylpentan-2-one	108-10-1	Ireland OELs	TWA(8 hours):83 mg/m3(20 ppm);TWA(8 hours):20 ppm(83 mg/m3);STEL(15 minutes):208 mg/m3(50 ppm);STEL(15 minutes):50 ppm(208 mg/m3)	SKIN
toluene	108-88-3	Ireland OELs	TWA(8 hours):192 mg/m3(50 ppm);TWA(8 hours):50 ppm(192 mg/m3);STEL(15 minutes):384 mg/m3(100 ppm);STEL(15 minutes):100 ppm(384 mg/m3)	SKIN
tetrahydrofuran	109-99-9	Ireland OELs	TWA(8 hours):150 mg/m3(50 ppm);TWA(8 hours):50 ppm(150 mg/m3);STEL(15 minutes):300 mg/m3(100 ppm);STEL(15 minutes):100 ppm(300 mg/m3)	SKIN
cyclohexane	110-82-7	Ireland OELs	TWA(8 hours):700 mg/m3(200 ppm);TWA(8 hours):200 ppm(700 mg/m3)	
acetone	67-64-1	Ireland OELs	TWA(8 hours):1210 mg/m3(500 ppm);TWA(8 hours):500 ppm(1210 mg/m3)	
butanone	78-93-3	Ireland OELs	TWA(8 hours):600 mg/m3(200 ppm);TWA(8 hours):200 ppm(600 mg/m3);STEL(15 minutes):900 mg/m3(300 ppm);STEL(15 minutes):300 ppm(900 mg/m3)	SKIN
methyl acetate	79-20-9	Ireland OELs	TWA(8 hours):610 mg/m3(200 ppm);STEL(15 minutes):760	

mg/m³(250 ppm)

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Safety glasses with side shields.
- Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 16321

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	>0.30	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

- Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates
- Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Colour	Transparent Colorless
Odor	Ketones.
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	>=56 °C [<i>Details: Acetone boiling point</i>]
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	>=-18 °C [<i>Test Method: Closed Cup</i>]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	68.5 mm ² /sec [<i>@ 20 °C</i>]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	<i>No data available.</i>
Relative density	0.73 - 0.93 [<i>Ref Std: WATER=1</i>]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information**9.2.2 Other safety characteristics**

EU Volatile Organic Compounds

No data available.

Evaporation rate

No data available.

Percent volatile

approximately 88

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Ocular effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
acetone	Ingestion	Rat	LD50 5,800 mg/kg
butanone	Dermal	Rabbit	LD50 > 8,050 mg/kg
butanone	Inhalation-Vapour (4 hours)	Rat	LC50 34.5 mg/l
butanone	Ingestion	Rat	LD50 2,737 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg
tetrahydrofuran	Dermal	Rat	LD50 > 2,000 mg/kg
tetrahydrofuran	Inhalation-Vapour (4 hours)	Rat	LC50 54 mg/l
tetrahydrofuran	Ingestion	Rat	LD50 1,650 mg/kg
methyl acetate	Dermal	Rat	LD50 > 2,000 mg/kg
methyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 > 49 mg/l
methyl acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Resin acids and rosin acids, esters with glycerol	Dermal	Rabbit	LD50 > 5,000 mg/kg
Resin acids and rosin acids, esters with glycerol	Ingestion	Rat	LD50 > 2,000 mg/kg
4-methylpentan-2-one	Dermal	Rabbit	LD50 > 16,000 mg/kg
4-methylpentan-2-one	Inhalation-Vapour (4 hours)	Rat	LC50 11 mg/l
4-methylpentan-2-one	Ingestion	Rat	LD50 3,038 mg/kg
cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
cyclohexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 32.9 mg/l
cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
acetone	Mouse	Minimal irritation
butanone	Rabbit	Minimal irritation
toluene	Rabbit	Irritant
tetrahydrofuran	Rabbit	Minimal irritation
methyl acetate	Rabbit	No significant irritation
Resin acids and rosin acids, esters with glycerol	Rabbit	Minimal irritation
4-methylpentan-2-one	Rabbit	Mild irritant
cyclohexane	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
acetone	Rabbit	Severe irritant
butanone	Rabbit	Severe irritant
toluene	Rabbit	Moderate irritant
tetrahydrofuran	Rabbit	Corrosive
methyl acetate	Rabbit	Moderate irritant
Resin acids and rosin acids, esters with glycerol	Rabbit	Mild irritant
4-methylpentan-2-one	Rabbit	Mild irritant
cyclohexane	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
toluene	Guinea pig	Not classified
tetrahydrofuran	Human and animal	Not classified
methyl acetate	Human	Not classified
Resin acids and rosin acids, esters with glycerol	Guinea pig	Not classified
4-methylpentan-2-one	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
acetone	In vivo	Not mutagenic
acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
butanone	In Vitro	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
tetrahydrofuran	In Vitro	Not mutagenic
tetrahydrofuran	In vivo	Not mutagenic
methyl acetate	In Vitro	Not mutagenic
methyl acetate	In vivo	Not mutagenic
Resin acids and rosin acids, esters with glycerol	In Vitro	Not mutagenic
4-methylpentan-2-one	In Vitro	Not mutagenic
cyclohexane	In Vitro	Not mutagenic
cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
acetone	Not specified.	Multiple animal species	Not carcinogenic
butanone	Inhalation	Human	Not carcinogenic
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
tetrahydrofuran	Inhalation	Multiple	Carcinogenic.

		animal species	
4-methylpentan-2-one	Inhalation	Multiple animal species	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
butanone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
tetrahydrofuran	Ingestion	Not classified for female reproduction	Rat	NOAEL 782 mg/kg/day	2 generation
tetrahydrofuran	Ingestion	Not classified for male reproduction	Rat	NOAEL 782 mg/kg/day	2 generation
tetrahydrofuran	Ingestion	Not classified for development	Rat	NOAEL 305 mg/kg/day	2 generation
tetrahydrofuran	Inhalation	Not classified for development	Mouse	NOAEL 1.8 mg/l	during gestation
4-methylpentan-2-one	Inhalation	Not classified for female reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
4-methylpentan-2-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-methylpentan-2-one	Inhalation	Not classified for male reproduction	Multiple animal species	NOAEL 8.2 mg/l	2 generation
4-methylpentan-2-one	Inhalation	Not classified for development	Mouse	NOAEL 12.3 mg/l	during organogenesis
cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
acetone	Inhalation	liver	Not classified	Guinea	NOAEL Not	

				pig	available	
acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
butanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
butanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
butanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
butanone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
tetrahydrofuran	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
tetrahydrofuran	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
tetrahydrofuran	Inhalation	respiratory system	Not classified	Rabbit	NOAEL 2.9 mg/l	4 hours
tetrahydrofuran	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL 180 mg/kg	not applicable
methyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
methyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
methyl acetate	Inhalation	blindness	Not classified		NOAEL Not available	
methyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
4-methylpentan-2-one	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 0.1 mg/l	2 hours
4-methylpentan-2-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
4-methylpentan-2-one	Inhalation	vascular system	Not classified	Dog	NOAEL Not available	not available
4-methylpentan-2-one	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 900 mg/kg	not applicable
cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

3M Scotch-Weld(tm) Clear Primer 9348

acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
butanone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
butanone	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
butanone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the	Rat	NOAEL 625	13 weeks

			data are not sufficient for classification		mg/kg/day	
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
tetrahydrofuran	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.6 mg/l	12 weeks
tetrahydrofuran	Inhalation	respiratory system	Not classified	Rat	NOAEL 2.9 mg/l	12 weeks
tetrahydrofuran	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.6 mg/l	105 weeks
tetrahydrofuran	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	2 weeks
methyl acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
methyl acetate	Inhalation	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Resin acids and rosin acids, esters with glycerol	Ingestion	liver heart skin endocrine system bone, teeth, nails, and/or hair blood bone marrow hematopoietic system immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 5,000 mg/kg/day	90 days
4-methylpentan-2-one	Inhalation	liver	Not classified	Rat	NOAEL 0.41 mg/l	13 weeks
4-methylpentan-2-one	Inhalation	heart	Not classified	Multiple animal species	NOAEL 0.8 mg/l	2 weeks
4-methylpentan-2-one	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 0.4 mg/l	90 days
4-methylpentan-2-one	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 4.1 mg/l	14 weeks
4-methylpentan-2-one	Inhalation	endocrine system hematopoietic system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	90 days
4-methylpentan-2-one	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	13 weeks
4-methylpentan-2-one	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-methylpentan-2-one	Ingestion	heart immune	Not classified	Rat	NOAEL	120 days

3M Scotch-Weld(tm) Clear Primer 9348

		system muscles nervous system respiratory system			1,040 mg/kg/day	
cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks

Aspiration Hazard

Name	Value
toluene	Aspiration hazard
4-methylpentan-2-one	Some positive data exist, but the data are not sufficient for classification
cyclohexane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
acetone	67-64-1	Algae or other aquatic plants	Experimental	96 hours	EC50	11,493 mg/l
acetone	67-64-1	Invertebrate	Experimental	24 hours	LC50	2,100 mg/l
acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
butanone	78-93-3	Fathead minnow	Experimental	96 hours	LC50	2,993 mg/l
butanone	78-93-3	Green algae	Experimental	96 hours	ErC50	2,029 mg/l
butanone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
butanone	78-93-3	Green algae	Experimental	96 hours	ErC10	1,289 mg/l
butanone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l

3M Scotch-Weld(tm) Clear Primer 9348

butanone	78-93-3	Bacteria	Experimental	16 hours	LOEC	1,150 mg/l
Acrylic polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
tetrahydrofuran	109-99-9	Activated sludge	Experimental	3 hours	IC50	460 mg/l
tetrahydrofuran	109-99-9	Fathead minnow	Experimental	96 hours	LC50	2,160 mg/l
tetrahydrofuran	109-99-9	Water flea	Experimental	48 hours	LC50	3,485 mg/l
tetrahydrofuran	109-99-9	Fathead minnow	Experimental	33 days	NOEC	216 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Resin acids and rosin acids, esters with glycerol	8050-31-5	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Rainbow trout	Estimated	96 hours	No tox obs at lmt of water sol	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Resin acids and rosin acids, esters with glycerol	8050-31-5	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
methyl acetate	79-20-9	Green algae	Experimental	72 hours	ErC50	>120 mg/l
methyl acetate	79-20-9	Water flea	Experimental	48 hours	EC50	1,026.7 mg/l
methyl acetate	79-20-9	Zebra Fish	Experimental	96 hours	LC50	250 mg/l
methyl acetate	79-20-9	Green algae	Experimental	72 hours	NOEC	120 mg/l
methyl acetate	79-20-9	Bacteria	Experimental	16 hours	EC50	6,000 mg/l
cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l

3M Scotch-Weld(tm) Clear Primer 9348

cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
4-methylpentan-2-one	108-10-1	Green algae	Experimental	96 hours	EC50	400 mg/l
4-methylpentan-2-one	108-10-1	Water flea	Experimental	48 hours	EC50	>200 mg/l
4-methylpentan-2-one	108-10-1	Zebra Fish	Experimental	96 hours	LC50	>179 mg/l
4-methylpentan-2-one	108-10-1	Fathead minnow	Experimental	32 days	NOEC	56.2 mg/l
4-methylpentan-2-one	108-10-1	Water flea	Experimental	21 days	NOEC	78 mg/l
4-methylpentan-2-one	108-10-1	Activated sludge	Experimental	30 minutes	EC50	>1,000

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 %BOD/ThOD	OECD 301D - Closed bottle test
acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
butanone	78-93-3	Experimental Biodegradation	28 days	BOD	98 %BOD/ThOD	OECD 301D - Closed bottle test
Acrylic polymer	Trade Secret	Data not available/insufficient	N/A	N/A	N/A	N/A
tetrahydrofuran	109-99-9	Experimental Biodegradation	28 days	BOD	39 %BOD/ThOD	
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Resin acids and rosin acids, esters with glycerol	8050-31-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
methyl acetate	79-20-9	Experimental Biodegradation	28 days	BOD	70 %BOD/ThOD	OECD 301D - Closed bottle test
methyl acetate	79-20-9	Experimental Aquatic Inherent Biodegrad.	6 days	Dissolv. Organic Carbon Deplet	>95 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
methyl acetate	79-20-9	Experimental Photolysis		Photolytic half-life (in air)	94 days (t 1/2)	
methyl acetate	79-20-9	Experimental Hydrolysis		Hydrolytic half-life	44 days (t 1/2)	
cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 %BOD/ThOD	OECD 301F - Manometric respirometry
cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.3 days (t 1/2)	
4-methylpentan-2-one	108-10-1	Experimental Biodegradation	28 days	BOD	83 %BOD/ThOD	OECD 301F - Manometric respirometry
4-methylpentan-2-one	108-10-1	Experimental Photolysis		Photolytic half-life (in air)	2.3 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	
acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	
butanone	78-93-3	Experimental Bioconcentration		Log Kow	0.3	OECD 117 log Kow HPLC method
Acrylic polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

tetrahydrofuran	109-99-9	Experimental Bioconcentration		Log Kow	0.45	
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	
Resin acids and rosin acids, esters with glycerol	8050-31-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
methyl acetate	79-20-9	Experimental Bioconcentration		Log Kow	0.18	
cyclohexane	110-82-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	129	OECD305-Bioconcentration
cyclohexane	110-82-7	Experimental Bioconcentration		Log Kow	3.44	
4-methylpentan-2-one	108-10-1	Experimental Bioconcentration		Log Kow	1.9	OECD 117 log Kow HPLC method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
acetone	67-64-1	Modeled Mobility in Soil	Koc	9.7 l/kg	Episuite™
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	
Resin acids and rosin acids, esters with glycerol	8050-31-5	Estimated Mobility in Soil	Koc	>1000 l/kg	Episuite™
methyl acetate	79-20-9	Experimental Mobility in Soil	Koc	1.5 l/kg	OECD 121 Estim. of Koc by HPLC
cyclohexane	110-82-7	Modeled Mobility in Soil	Koc	970 l/kg	Episuite™
4-methylpentan-2-one	108-10-1	Modeled Mobility in Soil	Koc	150 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN1993	UN1993	UN1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.(METHYL ETHYL KETONE)	FLAMMABLE LIQUID, N.O.S.(METHYL ETHYL KETONE)	FLAMMABLE LIQUID, N.O.S.(METHYL ETHYL KETONE)
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	II	II	II
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	F1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity****Ingredient****CAS Nbr****Classification****Regulation**

4-methylpentan-2-one	108-10-1	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
4-methylpentan-2-one	108-10-1	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
tetrahydrofuran	109-99-9	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
tetrahydrofuran	109-99-9	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
cyclohexane	110-82-7
toluene	108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Regulation (EU) 2019/1148 (marketing and use of explosive precursors)

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see your local legislation.

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 1: Address information was modified.

Section 1: E-mail address information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 09: Color information was modified.

Section 9: Specific physical form information information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com