# Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document Group:** | 39-1672-3 | **Version Number:** | 6.02 |
| **Issue Date:** | 07/23/26 | **Supersedes Date:** | 05/15/26 |

## SECTION 1: Identification

**1.1. Product identifier**
3M™ UV Inkjet Ink 1513 Black

**Product Identification Numbers**
42-0033-0147-2, 70-0012-1454-6, 75-0302-8355-2
4100030195, 7100173384, 7100332144

**1.2. Recommended use and restrictions on use**

**Recommended use**
Ink

**1.3. Supplier's details**

| | |
|---|---|
| **MANUFACTURER:** | 3M |
| **DIVISION:** | Commercial Branding and Transportation Division |
| **ADDRESS:** | 3M Center, St. Paul, MN 55144-1000, USA |
| **Telephone:** | 1-888-3M HELPS (1-888-364-3577) |

**1.4. Emergency telephone number**
1-800-364-3577 or (651) 737-6501 (24 hours)

## SECTION 2: Hazard identification

**2.1. Hazard classification**
Acute Toxicity (inhalation): Category 4.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 1.
Skin Sensitizer: Category 1.
Carcinogenicity: Category 1B.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (repeated exposure): Category 1.

**2.2. Label elements**
**Signal word**
Danger

**Symbols**
Corrosion |Exclamation mark |Health Hazard |

**Pictograms**



**Hazard Statements**

Harmful if inhaled.
Causes skin irritation.
Causes serious eye damage.
May cause an allergic skin reaction.
May cause cancer.
May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure: respiratory system.
May cause damage to organs through prolonged or repeated exposure: gastrointestinal tract | immune system | kidney/urinary tract.

**Precautionary statements**

**Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe vapors.
Wash exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves, eye protection, face protection, and if needed, respiratory protection (see SDS Section 8).

**Response:**
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Immediately call a POISON CENTER or doctor.
Get medical attention if you feel unwell.
If skin irritation or rash occurs: Get medical attention.
Take off contaminated clothing and wash it before reuse.

**Storage:**
Store locked up.

**Disposal:**
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

**2.3. Hazards not otherwise classified**
May cause chemical gastrointestinal burns.

8% of the mixture consists of ingredients of unknown acute oral toxicity.
18% of the mixture consists of ingredients of unknown acute dermal toxicity.
98% of the mixture consists of ingredients of unknown acute inhalation toxicity.

## SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|---|---|
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | 66492-51-1 | 7 - 30 Trade Secret * |
| PHENOXY ETHYL ACRYLATE | 48145-04-6 | 10 - 30 Trade Secret * |
| Acrylate Polymer | Trade Secret*<br>3M Unique ID: 657077 | 10 - 30 Trade Secret * |
| VINYLCAPROLACTAM | 2235-00-9 | 7 - 13 Trade Secret * |
| TETRAHYDROFURFURYL ACRYLATE | 2399-48-6 | 5 - 10 Trade Secret * |
| Proprietary Polymer | Trade Secret*<br>3M Unique ID: 101736 | < 6.4 |
| TS Polymer | Trade Secret* | 1 - 5 |
| Amine Compound | Trade Secret*<br>3M Unique ID: 531083 | 1 - 5 Trade Secret * |
| Siloxanes and Silicones, di-Me, hydroxy-terminated, ethers with polyethylene-polypropylene glycol mono-Me ether | 155490-71-4 | 1 - 5 |
| BENZOPHENONE | 119-61-9 | 1 - 5 Trade Secret * |
| Carbon Black | 1333-86-4 | 1 - 5 Trade Secret * |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | 75980-60-8 | 1 - 5 Trade Secret * |
| 2-Phenoxyethanol | 122-99-6 | 0.1 - 1.5 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**
Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**
Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**
Rinse mouth. Do not induce vomiting. Get immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

**4.3. Indication of any immediate medical attention and special treatment required**
Not applicable.

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**
Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

| Substance | Condition |
|---|---|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |

**5.3. Special protective actions for fire-fighters**
Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

**6.2. Environmental precautions**
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**
Store away from oxidizing agents.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Occupational exposure limits**
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|---|---|---|---|
| BENZOPHENONE | 119-61-9 | AIHA | TWA:0.5 mg/m3 | |
| Carbon Black | 1333-86-4 | ACGIH | TWA(inhalable fraction):3 mg/m3 | A3: Confirmed animal carcin. |
| Carbon Black | 1333-86-4 | OSHA | TWA:3.5 mg/m3 | |
| VINYLCAPROLACTAM | 2235-00-9 | Manufacturer determined | TWA(8 hours):0.1 ppm(0.57 mg/m3) | |
| TETRAHYDROFURFURYL ACRYLATE | 2399-48-6 | Manufacturer determined | TWA:0.1 ppm(0.64 mg/m3);STEL:0.3 ppm(1.91 mg/m3) | Dermal Sensitizer |

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

### 8.2. Exposure controls

**8.2.1. Engineering controls**
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Full Face Shield
Indirect Vented Goggles

**Skin/hand protection**
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| **Physical state** | Liquid |
| **Specific Physical Form:** | Liquid |
| **Color** | Black |
| **Odor** | Acrylate |
| **Odor threshold** | *No Data Available* |
| **pH** | *Not Applicable* |
| **Melting point** | *Not Applicable* |
| **Boiling Point** | > 200 ºF |
| **Flash Point** | > 200 ºF [*Test Method:*Closed Cup] |
| **Evaporation rate** | *No Data Available* |
| **Flammability** | Not Applicable |
| **Flammable Limits(LEL)** | *No Data Available* |
| **Flammable Limits(UEL)** | *No Data Available* |
| **Vapor Pressure** | < 10 mmHg [@ 20 ºC] |
| **Relative Vapor Density** | > 1 [*Ref Std:*AIR=1] |
| **Density** | 1.04 g/ml |
| **Relative Density** | 1.04 [*Ref Std:*WATER=1] |
| **Solubility in Water** | Negligible |
| **Solubility- non-water** | *No Data Available* |
| **Partition coefficient: n-octanol/ water** | *No Data Available* |
| **Autoignition temperature** | *No Data Available* |
| **Decomposition temperature** | *No Data Available* |
| **Kinematic Viscosity** | *No Data Available* |
| **Percent volatile** | *No Data Available* |
| **Particle Characteristics** | *Not Applicable* |

## SECTION 10: Stability and reactivity

**10.1. Reactivity**
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**
Stable.

**10.3. Possibility of hazardous reactions**
Hazardous polymerization may occur. (Upon depletion of inhibitor or exposure to heat)

**10.4. Conditions to avoid**
Light

**10.5. Incompatible materials**

Strong oxidizing agents

**10.6. Hazardous decomposition products**

| Substance | Condition |
|---|---|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

**The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.**

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**
Harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin Contact:**
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

**Eye Contact:**
Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion:**
May be harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen. May cause additional health effects (see below).

**Additional Health Effects:**

**Prolonged or repeated exposure may cause target organ effects:**
Immunological Effects: Signs/symptoms may include alterations in the number of circulating immune cells, allergic skin and /or respiratory reaction, and changes in immune function. Gastrointestinal Effects: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure. Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

**Reproductive/Developmental Toxicity:**
Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|---|---|---|---|
| Benzophenone | 119-61-9 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Carbon black | 1333-86-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

**Toxicological Data**
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Dust/Mist(4 hr) | | No data available; calculated ATE >1 - =5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >2,000 - =5,000 mg/kg |
| PHENOXY ETHYL ACRYLATE | Dermal | Rat | LD50 > 2,000 mg/kg |
| PHENOXY ETHYL ACRYLATE | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Acrylate Polymer | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Acrylate Polymer | Ingestion | Rat | LD50 4,350 mg/kg |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Dermal | Rat | LD50 > 2,000 mg/kg |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | Rat | LD50 > 2,000 mg/kg |
| VINYLCAPROLACTAM | Dermal | Rabbit | LD50 1,700 mg/kg |
| VINYLCAPROLACTAM | Ingestion | Rat | LD50 1,049 mg/kg |
| TETRAHYDROFURFURYL ACRYLATE | Ingestion | Rat | LD50 882 mg/kg |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | Dermal | Professional judgement | LD50 estimated to be > 5,000 mg/kg |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | Ingestion | Rat | LD50 > 5,000 mg/kg |
| BENZOPHENONE | Dermal | Rabbit | LD50 3,535 mg/kg |
| BENZOPHENONE | Ingestion | Rat | LD50 1,900 mg/kg |
| Carbon Black | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Carbon Black | Ingestion | Rat | LD50 > 8,000 mg/kg |
| Amine Compound | Dermal | Rat | LD50 > 2,000 mg/kg |
| Amine Compound | Ingestion | Rat | LD50 >500, <2,000 mg/kg |
| Amine Compound | Inhalation-Dust/Mist (4 hours) | similar compounds | LC50 2.8 mg/l |
| TS Polymer | Ingestion | similar compounds | LD50 > 5,000 mg/kg |
| TS Polymer | Dermal | similar health hazards | LD50 estimated to be > 5,000 mg/kg |
| 2-Phenoxyethanol | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| 2-Phenoxyethanol | Inhalation-Dust/Mist | Rat | LC50 > 1.5 mg/l |
| 2-Phenoxyethanol | Ingestion | Rat | LD50 1,394 mg/kg |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name | Species | Value |
|---|---|---|
| Overall product | Professional judgement | Irritant |
| PHENOXY ETHYL ACRYLATE | Rabbit | No significant irritation |
| Acrylate Polymer | Rabbit | Minimal irritation |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Rabbit | Irritant |

| | | |
|---|---|---|
| VINYLCAPROLACTAM | Rabbit | Minimal irritation |
| TETRAHYDROFURFURYL ACRYLATE | Rabbit | Corrosive |
| Proprietary Polymer | similar compounds | Irritant |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | Rabbit | No significant irritation |
| BENZOPHENONE | Rabbit | No significant irritation |
| Carbon Black | Rabbit | No significant irritation |
| Amine Compound | Rabbit | No significant irritation |
| TS Polymer | similar compounds | No significant irritation |
| 2-Phenoxyethanol | Rabbit | No significant irritation |

**Serious Eye Damage/Irritation**

| Name | Species | Value |
|---|---|---|
| PHENOXY ETHYL ACRYLATE | Rabbit | No significant irritation |
| Acrylate Polymer | Rabbit | Mild irritant |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Rabbit | No significant irritation |
| VINYLCAPROLACTAM | Rabbit | Severe irritant |
| TETRAHYDROFURFURYL ACRYLATE | Rabbit | Corrosive |
| Proprietary Polymer | similar compounds | Severe irritant |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | Rabbit | No significant irritation |
| BENZOPHENONE | Rabbit | Mild irritant |
| Carbon Black | Rabbit | No significant irritation |
| Amine Compound | Rabbit | Severe irritant |
| TS Polymer | similar compounds | No significant irritation |
| 2-Phenoxyethanol | Rabbit | Corrosive |

**Skin Sensitization**

| Name | Species | Value |
|---|---|---|
| PHENOXY ETHYL ACRYLATE | Guinea pig | Sensitizing |
| Acrylate Polymer | Human and animal | Sensitizing |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Mouse | Sensitizing |
| VINYLCAPROLACTAM | Mouse | Sensitizing |
| TETRAHYDROFURFURYL ACRYLATE | Professional judgement | Sensitizing |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | Mouse | Sensitizing |
| BENZOPHENONE | Guinea pig | Not classified |
| Amine Compound | Guinea pig | Not classified |
| 2-Phenoxyethanol | Guinea pig | Not classified |

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

| Name | Route | Value |
|---|---|---|
| Acrylate Polymer | In Vitro | Not mutagenic |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | In Vitro | Not mutagenic |

| | | |
|---|---|---|
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | In vivo | Not mutagenic |
| VINYLCAPROLACTAM | In Vitro | Not mutagenic |
| TETRAHYDROFURFURYL ACRYLATE | In Vitro | Not mutagenic |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | In Vitro | Not mutagenic |
| BENZOPHENONE | In Vitro | Not mutagenic |
| BENZOPHENONE | In vivo | Not mutagenic |
| Carbon Black | In Vitro | Not mutagenic |
| Carbon Black | In vivo | Some positive data exist, but the data are not sufficient for classification |
| Amine Compound | In Vitro | Not mutagenic |
| 2-Phenoxyethanol | In Vitro | Not mutagenic |
| 2-Phenoxyethanol | In vivo | Not mutagenic |

## Carcinogenicity

| Name | Route | Species | Value |
|---|---|---|---|
| BENZOPHENONE | Dermal | Multiple animal species | Not carcinogenic |
| BENZOPHENONE | Ingestion | Multiple animal species | Carcinogenic |
| Carbon Black | Dermal | Mouse | Not carcinogenic |
| Carbon Black | Ingestion | Mouse | Not carcinogenic |
| Carbon Black | Inhalation | Rat | Carcinogenic |
| 2-Phenoxyethanol | Ingestion | Multiple animal species | Not carcinogenic |

## Reproductive Toxicity

## Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|
| PHENOXY ETHYL ACRYLATE | Ingestion | Not classified for male reproduction | Rat | NOAEL 800 mg/kg/day | 43 days |
| PHENOXY ETHYL ACRYLATE | Ingestion | Toxic to female reproduction | Rat | NOAEL 300 mg/kg/day | premating into lactation |
| PHENOXY ETHYL ACRYLATE | Ingestion | Toxic to development | Rat | NOAEL 300 mg/kg/day | premating into lactation |
| Acrylate Polymer | Ingestion | Not classified for male reproduction | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | Not classified for female reproduction | Rat | NOAEL 100 mg/kg/day | premating into lactation |
| Acrylate Polymer | Ingestion | Not classified for development | Rat | NOAEL 100 mg/kg/day | premating into lactation |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | Not classified for female reproduction | Rat | NOAEL 250 mg/kg/day | premating into lactation |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | Not classified for male reproduction | Rat | NOAEL 250 mg/kg/day | 31 days |
| TETRAHYDROFURFURYL ACRYLATE | Ingestion | Toxic to female reproduction | Rat | NOAEL 50 mg/kg/day | premating into lactation |
| TETRAHYDROFURFURYL ACRYLATE | Dermal | Toxic to male reproduction | Rat | NOAEL 100 mg/kg/day | 90 days |
| TETRAHYDROFURFURYL ACRYLATE | Ingestion | Toxic to male reproduction | Rat | NOAEL 35 mg/kg/day | 90 days |
| TETRAHYDROFURFURYL ACRYLATE | Inhalation | Toxic to male reproduction | Rat | NOAEL 0.6 mg/l | 90 days |
| TETRAHYDROFURFURYL ACRYLATE | Ingestion | Toxic to development | Rat | NOAEL 50 mg/kg/day | premating into lactation |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | Ingestion | Toxic to development | Rat | NOAEL 150 mg/kg/day | during gestation |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | Ingestion | Toxic to female reproduction | Rat | NOAEL 200 mg/kg/day | premating into lactation |
| 2,4,6-Trimethylbenzoyldiphenylphosphine oxide | Ingestion | Toxic to male reproduction | Rat | NOAEL 60 mg/kg/day | 85 days |

| | | | | | |
|---|---|---|---|---|---|
| BENZOPHENONE | Ingestion | Not classified for female reproduction | Rat | NOAEL 100 mg/kg/day | 2 generation |
| BENZOPHENONE | Ingestion | Not classified for male reproduction | Rat | NOAEL 80 mg/kg/day | 2 generation |
| BENZOPHENONE | Ingestion | Not classified for development | Rabbit | NOAEL 25 mg/kg/day | during gestation |
| 2-Phenoxyethanol | Ingestion | Not classified for female reproduction | Mouse | NOAEL 3,700 mg/kg/day | 2 generation |
| 2-Phenoxyethanol | Ingestion | Not classified for male reproduction | Mouse | NOAEL 3,700 mg/kg/day | 2 generation |
| 2-Phenoxyethanol | Dermal | Not classified for development | Rabbit | NOAEL 600 mg/kg/day | during organogenesis |
| 2-Phenoxyethanol | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | during gestation |

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|---|
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not Available | |
| VINYLCAPROLACTAM | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL Not available | |
| TETRAHYDROFURFURYL ACRYLATE | Inhalation | respiratory irritation | May cause respiratory irritation | Human and animal | NOAEL Not available | |
| Proprietary Polymer | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| Amine Compound | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| 2-Phenoxyethanol | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available | |

### Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|---|---|---|---|---|---|
| Acrylate Polymer | Ingestion | gastrointestinal tract | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | immune system | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | heart | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | endocrine system | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | liver | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | nervous system | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| Acrylate Polymer | Ingestion | respiratory system | Not classified | Rat | NOAEL 500 mg/kg/day | 31 days |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | gastrointestinal tract | Not classified | Rat | NOAEL 250 mg/kg/day | 31 days |
| 2-Propenoic acid, (5-ethyl- | Ingestion | heart | Not classified | Rat | NOAEL 250 | 31 days |

| | | | | | | |
|---|---|---|---|---|---|---|
| 1,3-dioxan-5-yl)methyl ester | | | | | mg/kg/day | |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | endocrine system | Not classified | Rat | NOAEL 250 mg/kg/day | 31 days |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 250 mg/kg/day | 31 days |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | liver | Not classified | Rat | NOAEL 250 mg/kg/day | 31 days |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | immune system | Not classified | Rat | NOAEL 250 mg/kg/day | 31 days |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | nervous system | Not classified | Rat | NOAEL 250 mg/kg/day | 31 days |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 250 mg/kg/day | 31 days |
| 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester | Ingestion | respiratory system | Not classified | Rat | NOAEL 250 mg/kg/day | 31 days |
| VINYLCAPROLACTAM | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | NOAEL 0.001 mg/l | 28 days |
| VINYLCAPROLACTAM | Inhalation | blood | Not classified | Rat | NOAEL 0.18 mg/l | 90 days |
| VINYLCAPROLACTAM | Inhalation | liver | Not classified | Rat | NOAEL 0.18 mg/l | 90 days |
| VINYLCAPROLACTAM | Inhalation | kidney and/or bladder | Not classified | Rat | NOAEL 0.18 mg/l | 90 days |
| VINYLCAPROLACTAM | Inhalation | eyes | Not classified | Rat | NOAEL 0.18 mg/l | 90 days |
| VINYLCAPROLACTAM | Ingestion | liver | Not classified | Rat | NOAEL 260 mg/kg/day | 3 months |
| 2,4,6-Trimethylbenzoyldiphenyl phosphine oxide | Ingestion | skin | Not classified | Rat | NOAEL 1,000 mg/kg/day | 90 days |
| 2,4,6-Trimethylbenzoyldiphenyl phosphine oxide | Ingestion | blood | Not classified | Rat | NOAEL 1,000 mg/kg/day | 90 days |
| 2,4,6-Trimethylbenzoyldiphenyl phosphine oxide | Ingestion | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 90 days |
| 2,4,6-Trimethylbenzoyldiphenyl phosphine oxide | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 90 days |
| 2,4,6-Trimethylbenzoyldiphenyl phosphine oxide | Ingestion | nervous system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 90 days |
| BENZOPHENONE | Ingestion | kidney and/or bladder | May cause damage to organs though prolonged or repeated exposure | Rat | LOAEL 75 mg/kg/day | 14 weeks |
| BENZOPHENONE | Ingestion | heart | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |
| BENZOPHENONE | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |
| BENZOPHENONE | Ingestion | liver | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |
| BENZOPHENONE | Ingestion | immune system | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |
| BENZOPHENONE | Ingestion | endocrine system | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |
| BENZOPHENONE | Ingestion | bone, teeth, nails, and/or hair | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |
| BENZOPHENONE | Ingestion | nervous system | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |

| | | | | | | |
|---|---|---|---|---|---|---|
| BENZOPHENONE | Ingestion | eyes | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |
| BENZOPHENONE | Ingestion | respiratory system | Not classified | Rat | NOAEL 850 mg/kg/day | 14 weeks |
| Carbon Black | Inhalation | pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Amine Compound | Ingestion | gastrointestinal tract | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 15 mg/kg/day | 28 days |
| Amine Compound | Ingestion | immune system | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 15 mg/kg/day | 28 days |
| 2-Phenoxyethanol | Dermal | skin | Not classified | Rabbit | NOAEL 500 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Dermal | hematopoietic system | Not classified | Rabbit | NOAEL 500 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Dermal | liver | Not classified | Rabbit | NOAEL 500 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Dermal | eyes | Not classified | Rabbit | NOAEL 500 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Ingestion | heart | Not classified | Rat | NOAEL 1,514 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Ingestion | endocrine system | Not classified | Rat | NOAEL 1,514 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 1,514 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Ingestion | liver | Not classified | Rat | NOAEL 1,514 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Ingestion | immune system | Not classified | Rat | NOAEL 1,514 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Ingestion | nervous system | Not classified | Rat | NOAEL 1,514 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 1,514 mg/kg/day | 13 weeks |
| 2-Phenoxyethanol | Ingestion | respiratory system | Not classified | Rat | NOAEL 1,514 mg/kg/day | 13 weeks |

**Aspiration Hazard**
For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

# SECTION 12: Ecological information

## Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

## Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# SECTION 13: Disposal considerations

**13.1. Disposal methods**
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

# SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# SECTION 15: Regulatory information

## 15.1. US Federal Regulations
Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

| **Physical Hazards** |
|---|
| Not Applicable. |

| **Health Hazards** |
|---|
| Acute toxicity |
| Carcinogenicity |
| Hazard Not Otherwise Classified (HNOC) |
| Reproductive toxicity |
| Respiratory or Skin Sensitization |
| Serious eye damage or eye irritation |
| Skin Corrosion or Irritation |
| Specific target organ toxicity (single or repeated exposure) |

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

| Ingredient | C.A.S. No | % by Wt |
|---|---|---|
| 2-Phenoxyethanol | 122-99-6 | Trade Secret 0.1 - 1.5 |

## 15.2. State Regulations
Contact 3M for more information.

## 15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

**NFPA Hazard Classification**
**Health:** 3 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|---|---|---|---|
| **Document Group:** | 39-1672-3 | **Version Number:** | 6.02 |
| **Issue Date:** | 07/23/26 | **Supersedes Date:** | 05/15/26 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at www.3M.com**