

Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	10-2507-1	Version Number:	84.01
Issue Date:	01/02/25	Supercedes Date:	11/26/24

SECTION 1: Identification

1.1. Product identifier

3MTM Scotch-WeldTM Structural Adhesive Film AF 163-2

Product Identification Numbers

rroduct Identification Numbers
62-0080-5305-0, 62-0080-5306-8, 62-0187-0120-1, 62-0187-0155-7, 62-0187-0455-1, 62-0187-0835-4, 62-0187-1005-3, 62-0187-0120-1, 62-0187-0120-1, 62-0187-0455-1, 62-0187-0455-1, 62-0187-0120-1, 62-0187-0120-1, 62-0187-0455-1, 62-0187-0455-1, 62-0187-0120-1, 62-0187-0120-1, 62-0187-0455-1, 62-0187-0455-1, 62-0187-0120-1, 62-0187-0120-1, 62-0187-0455-1, 62-0187-0455-1, 62-0187-0120-1, 62-0187-0120-1, 62-0187-0455-1, 62-0187-0455-1, 62-0187-0187-0455-1, 62-0187-0455-1, 62-0187-0187-0455-1, 62-0187-0455-1, 62-0187-0187-0455-1, 62-0187-0455-1, 62-0187-0187-0455-1, 62-0187-0455-1, 62-0187-0187-0455-1, 62-0187-0455-1, 62-0187-0187-0455-1, 62-0187-0455-1, 62-0187-0187-0455-1, 62-0187-045-1, 62-045-1, 62-045-1, 62-045-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 62-045-1, 6
0187-1105-1, 62-0187-1500-3, 62-0187-1600-1, 62-0187-1685-2, 62-0187-1701-7, 62-0187-1736-3, 62-0187-1750-4, 62-
0187-2125-8, 62-0187-2405-4, 62-0187-2505-1, 62-0187-2507-7, 62-0187-2850-1, 62-0187-2920-2, 62-0187-3905-2, 62-
0187-4205-6, 62-0187-4505-9, 62-0187-4506-7, 62-0187-4805-3, 62-0187-5308-7, 62-0187-5309-5, 62-0187-5310-3, 62-
0187-5345-9, 62-0187-5349-1, 62-0187-6005-8, 62-0189-5305-9, 62-0189-5306-7, 62-0197-0135-8, 62-0197-0305-7, 62-
0197-2205-7, 62-0197-2895-5, 62-0197-3907-7, 62-0197-5305-2, 62-0197-5309-4, 62-2623-4805-5, 62-2623-4825-3, 62-
2623-6009-2, 62-3042-5306-5, 62-3042-6003-7, 62-3042-6009-4, 62-3064-0305-6, 62-3064-0805-5, 62-3064-3905-0, 62-
3064-4506-5, 62-3064-4805-1, 62-3064-5305-1, 62-3064-5306-9, 62-3064-5309-3, 62-3077-6005-8, 62-3087-3905-1, 62-
3087-4356-6, 62-3087-4505-8, 62-3087-5305-2, 62-3087-5309-4, 62-3087-6009-9, 62-3137-5305-5, 62-3137-5306-3, 62-
3146-0155-0, 62-3146-0355-6, 62-3146-1205-2, 62-3146-5306-4, 62-3146-5307-2, 62-3146-5309-8, 62-3147-5306-2, 62-
3147-5309-6, 62-3162-0305-8, 62-3162-0555-8, 62-3162-5306-1, 62-3162-5309-5, 62-3189-2205-1, 62-3189-4505-2, 62-
3189-5301-5, 62-3189-5302-3, 62-3189-5309-8, 62-3189-6005-1, 62-3189-6255-2, 62-3190-0305-9, 62-3190-1005-4, 62-
3190-1205-0, 62-3190-1755-4, 62-3190-2405-5, 62-3190-2805-6, 62-3190-3155-5, 62-3190-3906-1, 62-3190-4505-0, 62-
3190-5302-1, 62-3190-5303-9, 62-3190-5309-6, 62-3192-0455-8, 62-3192-3905-9, 62-3192-5300-1, 62-3192-5305-0, 62-
3192-5309-2, 87-2500-0336-2, 87-2500-0390-9, 87-2500-0391-7, 87-2500-0393-3, 87-3300-0007-3, 87-3300-0008-1, 87-
3300-0013-1, 87-3300-0014-9, 87-3300-0015-6, 87-3300-0019-8, 87-3300-0020-6, 87-3300-0021-4, 87-3300-0028-9, 87-
3300-0029-7, 87-3300-0042-0, 87-3300-0043-8, 87-3300-0113-9, 87-3300-0501-5, 87-3300-0502-3, 87-3300-0503-1, 87-
3300-0504-9, 87-3300-0505-6, 87-3300-0506-4, 87-3300-0507-2, 87-3300-0508-0, 87-3300-0526-2, 87-3300-0527-0, 87-
3300-0530-4, 87-3300-0531-2, 87-3300-0532-0, 87-3300-0533-8, 87-3300-0543-7, 87-3300-0544-5, 87-3300-0545-2, 87-
3300-0546-0, 87-3300-0547-8, 87-3300-0548-6, 87-3300-0549-4, 87-3300-0550-2, 87-3300-0551-0, 87-3300-0552-8, 87-
3300-0562-7, 87-3300-0563-5, 87-3300-0564-3, 87-3300-0565-0, 87-3300-0566-8, 87-3300-0567-6, 87-3300-0572-6, 87-
3300-0573-4, 87-3300-0574-2, 87-3300-0575-9, 87-3300-0576-7, 87-3300-0577-5, 87-3300-0579-1, 87-3300-0580-9, 87-
3300-0581-7, 87-3300-0582-5, 87-3300-0583-3, 87-3300-0584-1, 87-3300-0614-6, 87-3300-0615-3
7010292696, 7010365902, 7010330017, 7000046318, 7010309710, 7010365904, 7000000789, 7000000790, 7010301015,
7010365906, 7000046319, 7010309711, 7010365908, 7010330020, 7010295291, 7000121192, 7000046320, 7000046370,
7100005489, 7000046406, 7000046409, 7010295305, 7100079639, 7100058843, 7000046410, 7000046415, 7000046416,
7000046417, 7000121248, 7000000837, 7100007551, 7100094932, 7010301046, 7000046424, 7000000840, 7100112021,
7000046425, 7000046426, 7000046429, 7000046430, 7100070565, 7000046431, 7100139407, 7100054781, 7000046433,
7010329695, 7010291341, 7010366117, 7010274880, 7000046434, 7000046435, 7000046436, 7010365907, 7100183189,
7010399426, 7010297842, 7000058939, 7010321077, 7010352084, 7010399453, 7010399456, 7010399454, 7010321076,
7010352086, 7100067099, 7100067098, 7100067113, 7100067114, 7100067112, 7100067111, 7100067110, 7100066704,
7100067289, 7100067300, 7100067303, 7100067304, 7100067281, 7100067333, 7100067335, 7100067336, 7100067337,
7100067338, 7100067339, 7100067405, 7100067406, 7100067407, 7100067280, 7100067408, 7100067133, 7100067422,
7100067131, 7100067132, 7100067130, 7100067423, 7100067552, 7100067428, 7100067554, 7100067553, 7100067559,
7100067556, 7100067557, 7100067598, 7100067653, 7100067654, 7100067205, 7100067137, 7100067504, 7100067427,

7010411505

1.2. Recommended use and restrictions on use

Recommended use

Structural Film Adhesive., Structural Adhesive Film for Bonding Applications

1.3. Supplier's details	
MANUFACTURER:	3M
DIVISION:	Automotive and Aerospace Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

60% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
EPOXY RESIN REACTION PRODUCT	None	45 - 65
Bisphenol A Diglycidyl Ether	1675-54-3	10 - 20 Trade Secret *
Epoxy Resin C	25068-38-6	5 - 20 Trade Secret *
Dicyandiamide	461-58-5	< 5
1,1'-(4-METHYL-M-PHENYLENE)BIS(3,3-	17526-94-2	< 1.5
DIMETHYLUREA)		
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL	2530-83-8	< 1
ETHER		
Adipic Dihydrazide	1071-93-8	< 1 Trade Secret *
PHENOL, 2,2',6-TRIBROMO-4,4'-	6386-73-8	< 1
ISOPROPYLIDENEDI-		
Dye	Trade Secret*	< 0.2

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

	SECTION 4: First aid measures
ľ	

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

Skin Contact:

If exposed, wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Hydrogen Cyanide	During Combustion
Hydrogen Fluoride	During Combustion
Ammonia	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with

applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of vapors created during cure cycle. Do not breathe thermal decomposition products. Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial/occupational use only. Not for consumer sale or use. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

No protective gloves required.

Respiratory protection

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

1 0	
Appearance	
Physical state	Solid
Color	Red
Specific Physical Form:	Film
Ödor	Odorless
Odor threshold	No Data Available
рН	Not Applicable

Melting point	No Data Available
Boiling Point	Not Applicable
Flash Point	No flash point
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapor Pressure	Not Applicable
Vapor Density	Not Applicable
Density	1.27 g/ml
Specific Gravity	1.27 [<i>Ref Std</i> :WATER=1]
Solubility in Water	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	Not Applicable
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Viscosity	Not Applicable
Molecular weight	No Data Available
Percent volatile	Negligible

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat

10.5. Incompatible materials Amines

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No known health effects.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Bisphenol A Diglycidyl Ether	Dermal	Rat	LD50 > 1,600 mg/kg
Bisphenol A Diglycidyl Ether	Ingestion	Rat	LD50 > 1,000 mg/kg
Epoxy Resin C	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin C	Ingestion	Rat	LD50 > 1,000 mg/kg
Dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg
1,1'-(4-METHYL-M-PHENYLENE)BIS(3,3- DIMETHYLUREA)	Dermal	Rat	LD50 > 2,000 mg/kg
1,1'-(4-METHYL-M-PHENYLENE)BIS(3,3- DIMETHYLUREA)	Ingestion	Rat	LD50 > 2,000 mg/kg
Adipic Dihydrazide	Ingestion	Mouse	LD50 > 5,000 mg/kg
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Dermal	Rabbit	LD50 4,000 mg/kg
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Rat	LD50 7,010 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Multiple	No significant irritation
	animal	
	species	
Bisphenol A Diglycidyl Ether	Rabbit	Mild irritant
Epoxy Resin C	Rabbit	Mild irritant
Dicyandiamide	Human	Minimal irritation
	and	
	animal	
1,1'-(4-METHYL-M-PHENYLENE)BIS(3,3-DIMETHYLUREA)	Rabbit	No significant irritation
Adipic Dihydrazide	Rabbit	No significant irritation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value

Bisphenol A Diglycidyl Ether	Rabbit	Moderate irritant
Epoxy Resin C	Rabbit	Moderate irritant
Dicyandiamide	Professio	Mild irritant
	nal	
	judgeme	
	nt	
1,1'-(4-METHYL-M-PHENYLENE)BIS(3,3-DIMETHYLUREA)	Rabbit	No significant irritation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Overall product	Guinea	Not classified
	pig	
Bisphenol A Diglycidyl Ether	Human	Sensitizing
	and	
	animal	
Epoxy Resin C	Human	Sensitizing
	and	
	animal	
Dicyandiamide	Guinea	Not classified
	pig	
Adipic Dihydrazide	Guinea	Sensitizing
	pig	
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Guinea	Not classified
	pig	

Respiratory Sensitization

Name	Species	Value
Bisphenol A Diglycidyl Ether	Human	Not classified
Epoxy Resin C	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Bisphenol A Diglycidyl Ether	In vivo	Not mutagenic
Bisphenol A Diglycidyl Ether	In Vitro	Some positive data exist, but the data are not sufficient for classification
Epoxy Resin C	In vivo	Not mutagenic
Epoxy Resin C	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	In Vitro	Not mutagenic
Adipic Dihydrazide	In vivo	Not mutagenic
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	In Vitro	Some positive data exist, but the data are not sufficient for classification
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Bisphenol A Diglycidyl Ether	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Epoxy Resin C	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Dicyandiamide	Ingestion	Rat	Not carcinogenic
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Bisphenol A Diglycidyl Ether	Ingestion	Not classified for female reproduction	Rat	NOAEL 750	2 generation

				mg/kg/day	
Bisphenol A Diglycidyl Ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesi s
Bisphenol A Diglycidyl Ether	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin C	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin C	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin C	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesi s
Epoxy Resin C	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Dicyandiamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dicyandiamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
Dicyandiamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesi

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Bisphenol A Diglycidyl Ether	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Bisphenol A Diglycidyl Ether	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Bisphenol A Diglycidyl Ether	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Epoxy Resin C	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin C	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin C	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

		bladder				
Dicyandiamide	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks
3- (TRIMETHOXYSILYL)P ROPYL GLYCIDYL ETHER	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Not applicable

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

meanin: 5 Flammability: 1 Instability: 0 Special Hazarus: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride. During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

Document Group:	10-2507-1	Version Number:	84.01
Issue Date:	01/02/25	Supercedes Date:	11/26/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com