Safety Data Sheet

Copyright,2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	41-5319-3	**Version number:**	3.01
Issue Date:	2026/08/21	**Supersedes Date:**	2025/06/26

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier
3M™ Ceramic Boost Spray, 39905

1.2. Recommended use and restrictions on use

Intended Use
Automotive

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Automotive Aftermarket
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Flammable Liquid: Category 2.

2.2. Label elements
Signal word
Danger

Symbols
Flame |

Pictograms



Hazard Statements
Highly flammable liquid and vapour.

Precautionary statements
General:
Keep out of reach of children.

Prevention:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves, eye protection, and face protection.

Response:
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:
Store in a well-ventilated place. Keep cool.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards
None known.

10% of the mixture consists of ingredients of unknown acute oral toxicity.
10% of the mixture consists of ingredients of unknown acute dermal toxicity.
10% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Hexamethyldisiloxane	107-46-0	80 - 100	Disiloxane, hexamethyl-
Siloxane Polymer	Trade Secret	5 - 10	Not Applicable
Silane, Trimethoxy(2-Methylpropyl)-	18395-30-7	1 - 5 Trade Secret *	No Data Available

Siloxane Polymer is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Unsuitable extinguishing media
None Determined

5.3. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.4. Special protection actions for fire-fighters
Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities
Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Nitrile Rubber

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Colourless
Odour	Slight Minty
Odour threshold	*No Data Available*
pH	*No Data Available*
Melting point/Freezing point	*No Data Available*
Boiling point	100 ºC
Flash Point	-11 ºC [*Test Method:*Closed Cup]
Evaporation rate	3.8 [*Ref Std:*BUOAC=1]
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	1.25 % volume
Flammable Limits(UEL)	18.6 % volume
Vapour Pressure	32.25 mmHg [@ 20 ºC] [*Ref Std:*AIR=1]
Relative Vapour Density	5.5 [*Ref Std:*AIR=1]
Density	0.79 g/cm3 [*Ref Std:*WATER=1]
Relative density	0.79 [*Ref Std:*WATER=1]
Water solubility	Negligible
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	340 ºC
Decomposition temperature	*No Data Available*
Kinematic Viscosity	0.65 mm2/sec
Volatile Organic Compounds	2.99 % weight
Percent volatile	*No Data Available*
VOC Less H2O & Exempt Solvents	*No Data Available*
Average particle size	*No Data Available*
Bulk density	*No Data Available*
Molecular weight	*No Data Available*
Softening point	*No Data Available*

* The values noted with an asterisk (*) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at a facility, including further changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct

characterization testing based on the use factors at the specific facility.

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
Not determined

No Data Available

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:
Sprayed material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hexamethyldisiloxane	Dermal	Rabbit	LD50 12,160 mg/kg
Hexamethyldisiloxane	Inhalation-Vapor (4 hours)	Rat	LC50 106 mg/l
Hexamethyldisiloxane	Ingestion	Rat	LD50 > 12,200 mg/kg
Silane, Trimethoxy(2-Methylpropyl)-	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Silane, Trimethoxy(2-Methylpropyl)-	Inhalation-Vapor (4 hours)	Rat	LC50 > 11 mg/l
Silane, Trimethoxy(2-Methylpropyl)-	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hexamethyldisiloxane	Rabbit	No significant irritation
Silane, Trimethoxy(2-Methylpropyl)-	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Hexamethyldisiloxane	Rabbit	Mild irritant
Silane, Trimethoxy(2-Methylpropyl)-	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Hexamethyldisiloxane	Human	Not classified
Silane, Trimethoxy(2-Methylpropyl)-	Guinea pig	Not classified

Respiratory Sensitization
For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hexamethyldisiloxane	In Vitro	Not mutagenic
Hexamethyldisiloxane	In vivo	Not mutagenic
Silane, Trimethoxy(2-Methylpropyl)-	In Vitro	Not mutagenic
Silane, Trimethoxy(2-Methylpropyl)-	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hexamethyldisiloxane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hexamethyldisiloxane	Inhalation	Not classified for female reproduction	Rabbit	NOAEL 33 mg/l	2 generation
Hexamethyldisiloxane	Inhalation	Not classified for male reproduction	Rabbit	NOAEL 33 mg/l	2 generation
Hexamethyldisiloxane	Inhalation	Not classified for development	Multiple animal species	NOAEL 19.9 mg/l	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Silane, Trimethoxy(2-Methylpropyl)-	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL not available	
Silane, Trimethoxy(2-Methylpropyl)-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Silane, Trimethoxy(2-Methylpropyl)-	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hexamethyldisiloxane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Hexamethyldisiloxane	Dermal	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Hexamethyldisiloxane	Dermal	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Hexamethyldisiloxane	Dermal	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Hexamethyldisiloxane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Hexamethyldisiloxane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 1.3 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	heart	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	endocrine system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	liver	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	immune system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	nervous system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	eyes	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	respiratory system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 640 mg/kg/day	4 weeks
Hexamethyldisiloxane	Ingestion	liver	Not classified	Rat	NOAEL 640	4 weeks

					mg/kg/day	
Hexamethyldisiloxane	Ingestion	immune system	Not classified	Rat	NOAEL 640 mg/kg/day	4 weeks
Hexamethyldisiloxane	Ingestion	nervous system	Not classified	Rat	NOAEL 640 mg/kg/day	4 weeks
Hexamethyldisiloxane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 640 mg/kg/day	4 weeks

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.
Health: 1 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	41-5319-3	**Version number:**	3.01
Issue Date:	2026/08/21	**Supersedes Date:**	2025/06/26

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca