

Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 28-7775-1
 Version number:
 10.01

 Revision date:
 23/06/2025
 Supersedes date:
 19/01/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Sealant 740 UV, White, Gray and Black

Product Identification Numbers

UU-0031-1795-7 UU-0031-1811-2 UU-0031-1815-3 UU-0031-1816-1 UU-0031-1817-9

UU-0031-1818-7 UU-0031-1819-5

7100078074 7100075873 7100077122 7100075868 7100077298

7100077297 7100077103

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2

Telephone: +353 1 280 3555

E Mail: ner-productstewardship@mmm.com

Website: www.3M.com

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

CLASSIFICATION:

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

HAZARD STATEMENTS:

H412 Harmful to aquatic life with long lasting effects.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

EUH208 Contains Dioctyltinbis(acetylacetonate). | N-(3-

(Trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium Carbonate	(CAS-No.) 471-34-1 (EC-No.) 207-439-9 (REACH-No.) 01- 2119486795-18	50 - 70	Substance not classified as hazardous
Polyether	Trade Secret	10 - 20	Substance not classified as hazardous
Diisodecyl Phthalate	(CAS-No.) 68515-49-1 (EC-No.) 271-091-4 (REACH-No.) 01- 2119422347-43	5 - 10	Substance not classified as hazardous
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01- 2119489379-17	< 10	Carc. 2, H351 (inhalation)
Dioctyltinbis(acetylacetonate)	(CAS-No.) 54068-28-9 (EC-No.) ELINCS 483- 270-6 (REACH-No.) 01- 0000020199-67	0.1 - 0.5	Skin Sens. 1B, H317 Repr. 2, H361d STOT RE 1, H372 Aquatic Chronic 2, H411
copper flakes (coated with aliphatic acid)	(CAS-No.) 7440-50-8 (EC-No.) 231-159-6	< 0.005	Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=1
Hydrocarbons, C12-C15, n-alkanes,	(EC-No.) 920-107-4	< 5	Asp. Tox. 1, H304

isoalkanes < 2% aromatics	(REACH-No.) 01-		EUH066
	2119453414-43		
Phenol alkyl sulphonate	Trade Secret	< 5	Substance not classified as hazardous
Carbon black	(CAS-No.) 1333-86-4	< 3	Substance with a national occupational
	(EC-No.) 215-609-9		exposure limit
	(REACH-No.) 01-		
	2119384822-32		
N-(3-	(CAS-No.) 1760-24-3	< 1	Acute Tox. 4, H332
(Trimethoxysilyl)propyl)ethylenediamine	(EC-No.) 217-164-6		Acute Tox. 4, H302
	(REACH-No.) 01-		Eye Dam. 1, H318
	2119970215-39		Skin Sens. 1, H317
			STOT RE 2, H373
Hindered Amine	(CAS-No.) 63843-89-0	< 0.1	Aquatic Chronic 1, H410,M=10
	(EC-No.) 264-513-3		Acute Tox. 4, H302
	(REACH-No.) 01-		STOT RE 1, H372
	2119978231-37		

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide. Irritant vapours or gases. Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Carbon black	1333-86-4	Ireland OELs	TWA(inhalable fraction)(8	
			hours):3 mg/m3	
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8	
			hours):10 mg/m3;TWA(as	
			respirable dust)(8 hours):4	
			mg/m3	~
TIN, ORGANIC COMPOUNDS	54068-28-9	Ireland OELs	TWA(8 hours):0.1	as Sn
			mg/m3;STEL(15 minutes):0.2	
0.1 / .1 .1	5440.50.0	T 1 10FF	mg/m3	G 1
copper flakes (coated with	7440-50-8	Ireland OELs	TWA(as fume)(8 hours):0.2	as Cu dust
aliphatic acid)			mg/m3;TWA(as dust or mist)(8	
			hours):1 mg/m3;TWA(as Cu,	
			fume)(8 hours):0.2	
			mg/m3;TWA(as Cu dust or	
			mist)(8 hours):1 mg/m3	
Ireland OFI c : Ireland OFI c				

Ireland OELs : Ireland. OELs TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile rubber.

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.		
Specific Physical Form:	Paste		
Colour	Multicolor		
Odor	Slight Polyether		
Odour threshold	No data available.		
Melting point/freezing point	No data available.		
Boiling point/boiling range	> 120 °C		
Flammability	Not applicable.		
Flammable Limits(LEL)	Not applicable.		
Flammable Limits(UEL)	Not applicable.		
Flash point	No flash point		
Autoignition temperature	> 200 °C		
Decomposition temperature	No data available.		
рН	substance/mixture is non-soluble (in water)		
Kinematic Viscosity	No data available.		
Water solubility	Negligible		
Solubility- non-water	No data available.		
Partition coefficient: n-octanol/water	No data available.		
Vapour pressure	Not applicable.		
Density	1.65 g/cm3		
Relative density	No data available.		
Relative Vapour Density	Not applicable.		
Particle Characteristics	Not applicable.		

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNo data available.Molecular weightNo data available.

Solids content 99 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Alcohols.

Water

Amines.

10.6 Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Polyether	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyether	Ingestion	Rat	LD50 5,000 mg/kg
Diisodecyl Phthalate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Diisodecyl Phthalate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 12.5 mg/l
Diisodecyl Phthalate	Ingestion	Rat	LD50 > 9,700 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	Dermal	similar compoun ds	LD50 > 3,160 mg/kg
Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	Ingestion	similar compoun ds	LD50 > 15,000 mg/kg
Phenol alkyl sulphonate	Dermal	Rat	LD50 > 1,000 mg/kg
Phenol alkyl sulphonate	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Inhalation- Dust/Mist (4 hours)	Rat	LC50 >1.49, <2.44 mg/l
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Ingestion	Rat	LD50 1,897 mg/kg
Dioctyltinbis(acetylacetonate)	Dermal	Rat	LD50 > 2,000 mg/kg
Dioctyltinbis(acetylacetonate)	Ingestion	Rat	LD50 > 2,000 mg/kg
Hindered Amine	Dermal	Rat	LD50 > 3,170 mg/kg
Hindered Amine	Ingestion	Rat	LD50 1,490 mg/kg
copper flakes (coated with aliphatic acid)	Dermal	Rat	LD50 > 2,000 mg/kg
copper flakes (coated with aliphatic acid)	Inhalation-	Rat	LC50 > 5.11 mg/l

Page: 8 of 18

3MTM Sealant 740 UV, White, Gray and Black

	Dust/Mist (4 hours)		
copper flakes (coated with aliphatic acid)	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Minimal irritation
Titanium dioxide	Rabbit	No significant irritation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	similar	Mild irritant
	compoun	
	ds	
Carbon black	Rabbit	No significant irritation
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Rabbit	Mild irritant
Dioctyltinbis(acetylacetonate)	Rabbit	No significant irritation
Hindered Amine	Rabbit	No significant irritation
copper flakes (coated with aliphatic acid)	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Mild irritant
Titanium dioxide	Rabbit	No significant irritation
Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	similar	No significant irritation
	compoun	
	ds	
Carbon black	Rabbit	No significant irritation
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Rabbit	Corrosive
Dioctyltinbis(acetylacetonate)	Rabbit	Mild irritant
Hindered Amine	Rabbit	Mild irritant
copper flakes (coated with aliphatic acid)	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Diisodecyl Phthalate	Guinea	Not classified
	pig	
Titanium dioxide	Human	Not classified
	and	
	animal	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	similar	Not classified
	compoun	
	ds	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	Multiple	Sensitising
	animal	
	species	
Dioctyltinbis(acetylacetonate)	Mouse	Sensitising
Hindered Amine	Guinea	Not classified
	pig	

Photosensitisation

Name	Species	Value
Hindered Amine	Guinea	Not sensitising
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Diisodecyl Phthalate	In Vitro	Not mutagenic
Diisodecyl Phthalate	In vivo	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not
		sufficient for classification
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	In Vitro	Not mutagenic
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	In vivo	Not mutagenic
Dioctyltinbis(acetylacetonate)	In Vitro	Not mutagenic
Hindered Amine	In vivo	Not mutagenic
Hindered Amine	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Titanium dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Diisodecyl Phthalate	Ingestion	Not classified for female reproduction	Rat	NOAEL 927 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Not classified for male reproduction	Rat	NOAEL 929 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Toxic to development	Rat	NOAEL 38 mg/kg/day	2 generation
N-(3- (Trimethoxysilyl)propyl)ethylenediamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	premating into lactation
N-(3- (Trimethoxysilyl)propyl)ethylenediamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	28 days
N-(3- (Trimethoxysilyl)propyl)ethylenediamine	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	during gestation
Dioctyltinbis(acetylacetonate)	Ingestion	Toxic to development	similar compoun ds	NOAEL not available	2 generation
Hindered Amine	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	premating into lactation
Hindered Amine	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	36 days
Hindered Amine	Ingestion	Not classified for development	Rat	NOAEL 10 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration

Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL	90 minutes
					0.812 mg/l	
Hydrocarbons, C12-C15,	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
n-alkanes, isoalkanes < 2%			data are not sufficient for	health	available	
aromatics			classification	hazards		
N-(3-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
(Trimethoxysilyl)propyl)et			data are not sufficient for	health	available	
hylenediamine			classification	hazards		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Diisodecyl Phthalate	Inhalation	respiratory system hematopoietic system liver	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Diisodecyl Phthalate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.5 mg/l	2 generation
Diisodecyl Phthalate	Ingestion	endocrine system	Not classified	Rat	NOAEL 686 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	liver kidney and/or bladder heart	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 320 mg/kg/day	90 days
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	Dermal	skin endocrine system hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 1,545 mg/kg/day	11 days
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.015 mg/l	90 days
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	Inhalation	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 0.044 mg/l	90 days
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	Ingestion	hematopoietic system nervous system	Not classified	Rat	NOAEL 500 mg/kg/day	28 days
Dioctyltinbis(acetylaceton ate)	Ingestion	immune system	Causes damage to organs through prolonged or repeated exposure	similar compoun ds	NOAEL not available	
Hindered Amine	Ingestion	gastrointestinal tract hematopoietic system liver immune system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 2 mg/kg/day	36 days

Aspiration Hazard

_				
	Name	Value		
ſ	Hydrocarbons, C12-C15, n-alkanes, isoalkanes < 2% aromatics	Aspiration hazard		

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Calcium Carbonate	471-34-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Calcium Carbonate	471-34-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Calcium Carbonate	471-34-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Calcium Carbonate	471-34-1	Green algae	Experimental	72 hours	EC10	100 mg/l
Polyether	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Diisodecyl Phthalate	68515-49-1	Activated sludge	Experimental	30 minutes	EC50	>83.3 mg/l
Diisodecyl Phthalate	68515-49-1	Green algae	Experimental	96 hours	EC50	>100 mg/l
Diisodecyl Phthalate	68515-49-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Diisodecyl Phthalate	68515-49-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Diisodecyl Phthalate	68515-49-1	Green algae	Experimental	96 hours	NOEC	100 mg/l
Diisodecyl Phthalate	68515-49-1	Water flea	Experimental	21 days	NOEC	100 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Green algae	Analogous Compound	72 hours	ErC50	0.1049 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Water flea	Analogous Compound	48 hours	EC50	0.0126 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Zebra Fish	Analogous Compound	96 hours	LC50	0.0117 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Fathead minnow	Analogous Compound	32 days	EC10	0.0059 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Green algae	Analogous Compound	N/A	NOEC	0.022 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Water flea	Analogous Compound	7 days	NOEC	0.004 mg/l
copper flakes (coated with aliphatic acid)	7440-50-8	Activated sludge	Analogous Compound	N/A	EC50	7 mg/l
Dioctyltinbis(acetylacet onate)	54068-28-9	Fathead minnow	Estimated	96 hours	LC50	282 mg/l
Dioctyltinbis(acetylacet onate)	54068-28-9	Green algae	Estimated	72 hours	ErC50	226 mg/l

D 10 0

Dioctyltinbis(acetylacet onate)	54068-28-9	Water flea	Estimated	48 hours	EC50	70.2 mg/l
Dioctyltinbis(acetylacet onate)	54068-28-9	Fathead minnow	Estimated	34 days	NOEC	27 mg/l
Dioctyltinbis(acetylacet onate)	54068-28-9	Green algae	Estimated	72 hours	NOEC	8.7 mg/l
Dioctyltinbis(acetylacet onate)	54068-28-9	Water flea	Estimated	21 days	NOEC	0.62 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes < 2% aromatics	920-107-4	Green algae	Estimated	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes < 2% aromatics	920-107-4	Rainbow trout	Estimated	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes < 2% aromatics	920-107-4	Water flea	Estimated	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C12- C15, n-alkanes, isoalkanes < 2% aromatics	920-107-4	Green algae	Estimated	72 hours	NOEL	1,000 mg/l
Phenol alkyl sulphonate	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l
N-(3- (Trimethoxysilyl)propy l)ethylenediamine	1760-24-3	Bacteria	Experimental	16 hours	EC50	67 mg/l
N-(3- (Trimethoxysilyl)propy l)ethylenediamine	1760-24-3	Fathead minnow	Experimental	96 hours	LC50	168 mg/l
N-(3- (Trimethoxysilyl)propy l)ethylenediamine	1760-24-3	Green algae	Experimental	72 hours	ErC50	8.8 mg/l
N-(3- (Trimethoxysilyl)propy l)ethylenediamine	1760-24-3	Water flea	Experimental	48 hours	EC50	81 mg/l
N-(3- (Trimethoxysilyl)propy l)ethylenediamine	1760-24-3	Green algae	Experimental	72 hours	NOEC	3.1 mg/l
Hindered Amine	63843-89-0	Activated sludge	Experimental	3 hours	IC20	>100 mg/l
Hindered Amine	63843-89-0	Water flea	Experimental	21 days	NOEC	0.002 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Calcium Carbonate	471-34-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Polyether	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Diisodecyl Phthalate	68515-49-1	Experimental Biodegradation	28 days	BOD	74 %BOD/ThO D	OECD 301F - Manometric respirometry
Titanium dioxide	13463-67-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
copper flakes (coated with	7440-50-8	Data not availbl-	N/A	N/A	N/A	N/A

aliphatic acid)		insufficient				
Dioctyltinbis(acetylacetonat	54068-28-9	Experimental	28 days	BOD	9 %BOD/ThO	OECD 301F - Manometric
e)		Biodegradation			D	respirometry
Dioctyltinbis(acetylacetonat	54068-28-9	Experimental		Hydrolytic half-life	<10 minutes (t	OECD 111 Hydrolysis func
e)		Hydrolysis		(pH 7)	1/2)	of pH
Hydrocarbons, C12-C15, n-	920-107-4	Estimated	28 days	BOD	67.6 %BOD/Th	OECD 301F - Manometric
alkanes, isoalkanes < 2%		Biodegradation	_		OD	respirometry
aromatics						
Phenol alkyl sulphonate	Trade Secret	Data not availbl-	N/A	N/A	N/A	N/A
		insufficient				
Carbon black	1333-86-4	Data not availbl-	N/A	N/A	N/A	N/A
		insufficient				
N-(3-	1760-24-3	Experimental	28 days	Dissolv. Organic	39 %removal	EC C.4.A. DOC Die-Away
(Trimethoxysilyl)propyl)eth		Biodegradation	_	Carbon Deplet	of DOC	Test
ylenediamine				_		
N-(3-	1760-24-3	Experimental		Hydrolytic half-life	1.5 minutes (t	
(Trimethoxysilyl)propyl)eth		Hydrolysis		(pH 7)	1/2)	
ylenediamine		* *		,	ĺ	
Hindered Amine	63843-89-0	Experimental	28 days	CO2 evolution	2 %CO2	OECD 301B - Modified
		Biodegradation			evolution/THC	sturm or CO2
					O2 evolution	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Calcium Carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyether	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diisodecyl Phthalate	68515-49-1	Estimated BCF - Fish	56 days	Bioaccumulation factor	<14.4	OECD305-Bioconcentration
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
copper flakes (coated with aliphatic acid)	7440-50-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dioctyltinbis(acetylacetona te)	54068-28-9	Analogous Compound BCF - Fish	30 days	Bioaccumulation factor	<100	OECD305-Bioconcentration
Dioctyltinbis(acetylacetona te)	54068-28-9	Hydrolysis product Bioconcentration		Log Kow	0.68	EC A.8 Partition Coefficient
Hydrocarbons, C12-C15, n- alkanes, isoalkanes < 2% aromatics	920-107-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Phenol alkyl sulphonate	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
N-(3- (Trimethoxysilyl)propyl)et hylenediamine	1760-24-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hindered Amine	63843-89-0	Experimental BCF - Fish	60 days	Bioaccumulation factor	≤437.1	OECD305-Bioconcentration

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Dioctyltinbis(acetylacetona te)		Analogous Compound Mobility in Soil	Koc	290,000 l/kg	
Dioctyltinbis(acetylacetona	54068-28-9	Analogous	Koc	33 l/kg	ACD/Labs ChemSketch TM

te)		Compound Mobility in Soil			
Hindered Amine	63843-89-0	Modeled Mobility	Koc	≥420 l/kg	ACD/Labs ChemSketch™
		in Soil			

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.

14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	Regulation
Carbon black	1333-86-4	Grp. 2B: Possible human	International Agency
		carc.	for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human	International Agency
		carc.	for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

IngredientCAS NbrDiisodecyl Phthalate68515-49-1

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact manufacturer for more information

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

Chemical	Identifier(s)	Annex I
Dioctyltinbis(acetylacetonate)	54068-28-9	Part 1

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H351i	Suspected of causing cancer by inhalation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section	1.	Addrage	information	was modified
Section	1.	Address	iniormation	was modified

- Section 1: E-mail address information was modified.
- Section 1: Product name information was modified.
- Section 1: Product use information information was modified.
- Section 3: Composition/Information of ingredients table information was modified.
- Section 6: Accidental release personal information information was modified.
- Section 7: Conditions safe storage information was modified.
- Section 8: Occupational exposure limit table information was modified.
- Section 9: Flammability (solid, gas) information information was deleted.
- Section 09: Flammability information information was added.
- Section 09: Particle Characteristics N/A information was added.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Carcinogenicity Table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Health Effects Inhalation information information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.

3MTM Sealant 740 UV, White, Gray and Black

- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Single Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Mobility in soil information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.
- Section 15: Seveso Substance Text information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com