



Safety Data Sheet

Copyright, 2025, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Safety Data Sheet has been prepared in accordance with the SS586 Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods.

Document group:	16-5850-9	Version number:	4.00
Issue Date:	01/12/2025	Supersedes date:	29/08/2024

SECTION 1: Identification

1.1. Product identifier

3M™ Marine Adhesive Sealant Fast Cure 5200, White; PN 06520 , 05220, 06534, 06535

1.2. Recommended use and restrictions on use

Recommended use

Adhesive Sealant, Sealant.

1.3. Supplier's details

Address: 3M Technologies (S) Pte Ltd, 10 Ang Mo Kio Street 65, Singapore 569059
Telephone: +65 6450 8888
Website: www.3m.com.sg

1.4. Emergency telephone number

+65 6591 6601 (8.15am - 5.00pm, Monday - Friday)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 2.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

SIGNAL WORD

DANGER!

Symbols

Health Hazard | Environment |

Pictograms

**HAZARD STATEMENTS**

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280K	Wear protective gloves and if needed, respiratory protection (see SDS Section 8).

Response:

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical attention.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor.
P391	Collect spillage.

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.
------	---

2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. Although titanium dioxide is classified as a carcinogen, exposures associated with this health effect are not expected during normal, intended use of this product.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Wt
Urethane Polymer	51447-37-1	40 - 70
Titanium dioxide	13463-67-7	10 - 30
4,4'-methylenediphenyl diisocyanate	101-68-8	1 - < 5
Synthetic Amorphous Silica	112945-52-5	1 - 5
Zinc oxide	1314-13-2	< 2.5
Alkyl Isocyanate Silane	85702-90-5	< 2
Aluminium hydroxide	21645-51-2	< 2
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	<= 2

Fumed silica	7631-86-9	1 - 2
Heptane	142-82-5	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Isocyanates
Carbon monoxide.
Carbon dioxide.
Hydrogen cyanide.
Oxides of nitrogen.
Oxides of sulphur.
Toxic vapour, gas, particulate.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers

an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
4,4'-methylenediphenyl diisocyanate	101-68-8	Singapore PELs	TWA(8 hours):0.051 mg/m3(0.005 ppm)	
Zinc oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m3;STEL(respirable fraction):10 mg/m3	
Zinc oxide	1314-13-2	Singapore PELs	TWA(as fume)(8 hours):5 mg/m3;TWA(as dust)(8 hours):10 mg/m3;STEL(as fume)(15 minutes):10 mg/m3	
Titanium dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable	A3: Confirmed animal carcin.

			finescale particles):2.5 mg/m3	
Titanium dioxide	13463-67-7	Singapore PELs	TWA(8 hours):10 mg/m3	
Heptane	142-82-5	Singapore PELs	TWA(8 hours):1640 mg/m3(400 ppm);STEL(15 minutes):2050 mg/m3(500 ppm)	
Heptane, straight and branched isomers	142-82-5	ACGIH	TWA:200 ppm;STEL:400 ppm	Ototoxicant
Aluminum metal and insoluble compounds, respirable fraction	21645-51-2	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Nuisance particulates	21645-51-2	Singapore PELs	TWA(as particulate)(8 hours):10 mg/m3	
Nuisance particulates	7631-86-9	Singapore PELs	TWA(as particulate)(8 hours):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

Singapore PELs : Singapore. Workplace Safety and Health (Permissible Exposure Levels of Toxic Substances) Order

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Color	White
Odor	Slight Urethane
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>Not applicable.</i>
Flash point	No flash point
Evaporation rate	<i>No data available.</i>
Flammability	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>No data available.</i>
Relative Vapor Density	<i>No data available.</i>
Density	1.3 g/ml
Relative density	1.3 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Kinematic Viscosity	230,769 mm ² /sec
Volatile organic compounds (VOC)	38 g/l [Test Method: tested per EPA method 24] [Details: EU VOC content]
Percent volatile	2.83 % weight
VOC less H₂O & exempt solvents	38 g/l [Test Method: tested per EPA method 24]
Molecular weight	<i>No data available.</i>

Particle Characteristics	<i>Not applicable.</i>
---------------------------------	------------------------

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Amines.

Alcohols.

Water

10.6 Hazardous decomposition products**Substance**

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-		No data available; calculated ATE >50 mg/l

	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Urethane Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Urethane Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Synthetic Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
2-(2-Ethoxyethoxy)ethyl acetate	Dermal	Rabbit	LD50 15,000 mg/kg
2-(2-Ethoxyethoxy)ethyl acetate	Ingestion	Rat	LD50 11,000 mg/kg
Fumed silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fumed silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fumed silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Aluminium hydroxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium hydroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium hydroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Alkyl Isocyanate Silane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Alkyl Isocyanate Silane	Ingestion	Rat	LD50 > 5,000 mg/kg
Heptane	Dermal	similar compound	LD50 > 2,000 mg/kg
Heptane	Inhalation-Vapor (4 hours)	similar compound	LC50 > 33.5 mg/l
Heptane	Ingestion	similar compound	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Titanium dioxide	Rabbit	No significant irritation
Synthetic Amorphous Silica	Rabbit	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classification	Irritant
Zinc oxide	Human and animal	No significant irritation
2-(2-Ethoxyethoxy)ethyl acetate	Human and animal	Minimal irritation
Fumed silica	Rabbit	No significant irritation
Aluminium hydroxide	Rabbit	No significant irritation

Alkyl Isocyanate Silane	Rabbit	Minimal irritation
Heptane	Professional judgement	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Titanium dioxide	Rabbit	No significant irritation
Synthetic Amorphous Silica	Rabbit	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classification	Severe irritant
Zinc oxide	Rabbit	Mild irritant
2-(2-Ethoxyethoxy)ethyl acetate	Rabbit	Severe irritant
Fumed silica	Rabbit	No significant irritation
Aluminium hydroxide	Rabbit	No significant irritation
Alkyl Isocyanate Silane	Rabbit	No significant irritation
Heptane	similar compounds	Mild irritant

Sensitization:

Skin Sensitisation

Name	Species	Value
Titanium dioxide	Human and animal	Not classified
Synthetic Amorphous Silica	Human and animal	Not classified
4,4'-methylenediphenyl diisocyanate	Mouse	Sensitising
Zinc oxide	Guinea pig	Not classified
2-(2-Ethoxyethoxy)ethyl acetate	Human and animal	Not classified
Fumed silica	Human and animal	Not classified
Aluminium hydroxide	Guinea pig	Not classified
Alkyl Isocyanate Silane	Guinea pig	Sensitising
Heptane	similar compounds	Not classified

Respiratory Sensitisation

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	Human	Sensitising
Alkyl Isocyanate Silane	official classification	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Titanium dioxide	In Vitro	Not mutagenic

Titanium dioxide	In vivo	Not mutagenic
Synthetic Amorphous Silica	In Vitro	Not mutagenic
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
2-(2-Ethoxyethoxy)ethyl acetate	In Vitro	Not mutagenic
Fumed silica	In Vitro	Not mutagenic
Alkyl Isocyanate Silane	In Vitro	Not mutagenic
Alkyl Isocyanate Silane	In vivo	Not mutagenic
Heptane	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Synthetic Amorphous Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Fumed silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium hydroxide	Not specified.	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Synthetic Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
4,4'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
Fumed silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fumed silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fumed silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Aluminium hydroxide	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

2-(2-Ethoxyethoxy)ethyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	not applicable
2-(2-Ethoxyethoxy)ethyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not applicable
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic Amorphous Silica	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic Amorphous Silica	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc oxide	Ingestion	endocrine system	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Zinc oxide	Ingestion	hematopoietic system	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Zinc oxide	Ingestion	kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
2-(2-Ethoxyethoxy)ethyl acetate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.48 mg/l	2 weeks
2-(2-Ethoxyethoxy)ethyl acetate	Inhalation	liver	Not classified	Rat	NOAEL 0.48 mg/l	2 weeks
2-(2-Ethoxyethoxy)ethyl acetate	Inhalation	immune system	Not classified	Rat	NOAEL 0.48 mg/l	2 weeks
2-(2-Ethoxyethoxy)ethyl acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.48 mg/l	2 weeks
Fumed silica	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Fumed silica	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Alkyl Isocyanate Silane	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Alkyl Isocyanate Silane	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Alkyl Isocyanate Silane	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Alkyl Isocyanate Silane	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Alkyl Isocyanate Silane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Heptane	Inhalation	nervous system	Not classified	Rat	NOAEL 6.15 mg/l	30 weeks
Heptane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 12.5 mg/l	16 weeks

Heptane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
Heptane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks

Aspiration Hazard

Name	Value
Heptane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Urethane Polymer	51447-37-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	21 days	NOEC	10 mg/l
Synthetic Amorphous Silica	112945-52-5	Green algae	Analogous Compound	72 hours	ErC50	>173.1 mg/l
Synthetic Amorphous Silica	112945-52-5	Sediment organism	Analogous Compound	96 hours	EC50	8,500 mg/kg (Dry Weight)

Synthetic Amorphous Silica	112945-52-5	Water flea	Analogous Compound	24 hours	EL50	>10,000 mg/l
Synthetic Amorphous Silica	112945-52-5	Zebra Fish	Analogous Compound	96 hours	LL50	>10,000 mg/l
Synthetic Amorphous Silica	112945-52-5	Green algae	Analogous Compound	72 hours	NOEC	173.1 mg/l
Synthetic Amorphous Silica	112945-52-5	Water flea	Analogous Compound	21 days	NOEC	68 mg/l
Synthetic Amorphous Silica	112945-52-5	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Zinc oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
Zinc oxide	1314-13-2	Green algae	Estimated	72 hours	EC50	0.052 mg/l
Zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
Zinc oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
Zinc oxide	1314-13-2	Green algae	Estimated	72 hours	NOEC	0.006 mg/l
Zinc oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l
Alkyl Isocyanate Silane	85702-90-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Aluminium hydroxide	21645-51-2	Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	Fathead minnow	Experimental	96 hours	LC50	110 mg/l
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
Fumed silica	7631-86-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Heptane	142-82-5	Water flea	Experimental	48 hours	EC50	1.5 mg/l
Heptane	142-82-5	Water flea	Estimated	21 days	NOEC	0.17 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Urethane Polymer	51447-37-1	Data not available-insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available-insufficient	N/A	N/A	N/A	N/A
4,4'-methylenediphenyl diisocyanate	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	
Synthetic Amorphous Silica	112945-52-5	Data not available-insufficient	N/A	N/A	N/A	N/A
Zinc oxide	1314-13-2	Data not available-insufficient	N/A	N/A	N/A	N/A

Alkyl Isocyanate Silane	85702-90-5	Data not available-insufficient	N/A	N/A	N/A	N/A
Aluminium hydroxide	21645-51-2	Data not available-insufficient	N/A	N/A	N/A	N/A
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	Experimental Biodegradation	28 days	BOD	100 %BOD/ThOD	OECD 301C - MITI test (I)
Fumed silica	7631-86-9	Data not available-insufficient	N/A	N/A	N/A	N/A
Heptane	142-82-5	Experimental Biodegradation	28 days	BOD	101 %BOD/ThOD	OECD 301C - MITI test (I)
Heptane	142-82-5	Experimental Photolysis		Photolytic half-life (in air)	4.24 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Urethane Polymer	51447-37-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
4,4'-methylenebis(phenyl diisocyanate)	101-68-8	Experimental BCF - Fish	28 days	Bioaccumulation factor	200	OECD305-Bioconcentration
Synthetic Amorphous Silica	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Zinc oxide	1314-13-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	≤217	OECD305-Bioconcentration
Alkyl Isocyanate Silane	85702-90-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium hydroxide	21645-51-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-(2-Ethoxyethoxy)ethyl acetate	112-15-2	Experimental Bioconcentration		Log Kow	0.74	
Fumed silica	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Heptane	142-82-5	Estimated Bioconcentration		Bioaccumulation factor	105	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered,

stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

International Regulations

UN No.: None assigned

UN Proper shipping name: None assigned

Transportation Class (IMO): None assigned

Transportation Class (IATA): None assigned

Other Dangerous Goods Descriptions (IMO): Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

Other Dangerous Goods Descriptions (IATA): Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

Packing Group: None assigned

Marine pollutant: None assigned

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

This product may contain component(s) that are regulated by the following:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: this product is subject to SDS, labelling, PEL and other requirements in the Act/Regulations.

Fire Safety (Petroleum and Flammable Materials) Regulations: This product is subject to the requirements in the Regulations

Environmental Protection and Management (Hazardous Substances) Regulations: This product is subject to the requirements in the Regulations

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Singapore SDSs are available at www.3m.com.sg