



Safety Data Sheet

Copyright,2026, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	10-2818-2	Version Number:	25.01
Issue Date:	02/24/26	Supersedes Date:	12/12/24

SECTION 1: Identification

1.1. Product identifier

3M™ TroubleShooter™ Baseboard Stripper

Product Identification Numbers

ID Number	UPC	ID Number	UPC
61-5000-6131-4	00-48011-14001-8		

7100134190

1.2. Recommended use and restrictions on use

Recommended use

Baseboard Stripper, Heavy duty aerosol cleaner removes soil, grease and finish buildup. Upside down spray feature for hard-to-reach places. Use on baseboards, floor edges, corners, stairways and ceramic tile. Contains no ozone depleting chemicals.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Commercial Branding and Transportation Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Aerosol Category 3

Skin Corrosion/Irritation: Category 1B.

Serious Eye Damage/Irritation: Category 1.

Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Health Hazard |

Pictograms



Hazard Statements

Pressurized container: may burst if heated.

Causes severe skin burns and eye damage.

Causes damage to organs: cardiovascular system.

Precautionary statements

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not pierce or burn, even after use.

Do not breathe vapor or spray.

Wash exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves, protective clothing, eye protection, and face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Immediately call a POISON CENTER or doctor.

Wash contaminated clothing before reuse.

Storage:

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	60 - 80
Butoxyethanol	111-76-2	10 - 30 Trade Secret *
PETROLEUM GASES, LIQUIFIED, SWEETENED	68476-86-8	5 - 10 Trade Secret *
Ethanolamine	141-43-5	1 - 5 Trade Secret *

C12-C15 Alcohols Ethoxylated	68131-39-5	< 1
Magnesium Aluminum Silicate	12199-37-0	< 1
Xanthan Gum	11138-66-2	< 1
Fragrance Compound	Trade Secret*	< 1

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide

Condition

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with

good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralize spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralizing agent until reaction stops. Let cool before collecting. Or use a commercially available caustic (alkaline or basic) spill clean-up kit. Follow kit directions exactly. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Butoxyethanol	111-76-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
Butoxyethanol	111-76-2	OSHA	TWA:240 mg/m ³ (50 ppm)	SKIN
Ethanolamine	141-43-5	ACGIH	TWA:3 ppm;STEL:6 ppm	
Ethanolamine	141-43-5	OSHA	TWA:6 mg/m ³ (3 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield
 Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Polymer laminate

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors
 Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Color	Off-White
Odor	Strong Petroleum
Odor threshold	No Data Available
pH	11 - 12.1
Melting point/Freezing point	Not Applicable

Boiling point/Initial boiling point/Boiling range	> 100 °C
Flash Point	<i>No Data Available</i>
Evaporation rate	<i>No Data Available</i>
Flammability	Non-flammable Aerosol: Category 3.
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>
Relative Vapor Density	<i>No Data Available</i>
Density	0.967 g/ml - 1.027 g/ml
Relative Density	0.967 - 1.027 [Ref Std: WATER=1]
Water solubility	Complete
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	80.2 mm ² /sec
Volatile Organic Compounds	15 - 20 % weight [Test Method:calculated per CARB title 2]
Percent volatile	60 - 90 % weight
VOC Less H₂O & Exempt Solvents	615 - 645 g/l [Test Method:calculated per CARB title 2]
Molecular weight	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
---------------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

Strong acids

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be

reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Additional Health Effects:

Single exposure may cause target organ effects:

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Butoxyethanol	Dermal	Guinea pig	LD50 > 2,000 mg/kg
Butoxyethanol	Inhalation-Vapor (4 hours)	Guinea pig	LC50 > 2.6 mg/l
Butoxyethanol	Ingestion	Guinea pig	LD50 1,200 mg/kg
PETROLEUM GASES, LIQUIFIED, SWEETENED	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
Ethanolamine	Inhalation-Vapor	official classification	LC50 estimated to be 10 - 20 mg/l
Ethanolamine	Dermal	Rabbit	LD50 2,504 mg/kg

Ethanolamine	Ingestion	Rat	LD50 1,089 mg/kg
C12-C15 Alcohols Ethoxylated	Ingestion	similar compounds	LD50 > 2,000 mg/kg
C12-C15 Alcohols Ethoxylated	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Xanthan Gum	Dermal		LD50 estimated to be > 5,000 mg/kg
Xanthan Gum	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.25 mg/l
Xanthan Gum	Ingestion	Rat	LD50 > 45,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro data	Corrosive
Butoxyethanol	Rabbit	Irritant
PETROLEUM GASES, LIQUIFIED, SWEETENED	Professional judgement	No significant irritation
Ethanolamine	Rabbit	Corrosive
C12-C15 Alcohols Ethoxylated	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Professional judgement	Severe irritant
Butoxyethanol	Rabbit	Severe irritant
PETROLEUM GASES, LIQUIFIED, SWEETENED	Professional judgement	No significant irritation
Ethanolamine	Rabbit	Corrosive
C12-C15 Alcohols Ethoxylated	similar compounds	No significant irritation

Skin Sensitization

Name	Species	Value
Butoxyethanol	Guinea pig	Not classified
Ethanolamine	Guinea pig	Not classified
C12-C15 Alcohols Ethoxylated	similar compounds	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
PETROLEUM GASES, LIQUIFIED, SWEETENED	In Vitro	Not mutagenic

Ethanolamine	In Vitro	Not mutagenic
Ethanolamine	In vivo	Not mutagenic
C12-C15 Alcohols Ethoxylated	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
Butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
Butoxyethanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
Ethanolamine	Dermal	Not classified for development	Rat	NOAEL 225 mg/kg/day	during organogenesis
Ethanolamine	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	during organogenesis
C12-C15 Alcohols Ethoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
C12-C15 Alcohols Ethoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
C12-C15 Alcohols Ethoxylated	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	prematuring into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
Butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
Butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Butoxyethanol	Inhalation	central nervous system depression	Not classified	Professional judgement	NOAEL Not available	
Butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
Butoxyethanol	Ingestion	central nervous system depression	Not classified	Professional judgement	NOAEL Not available	

Butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
PETROLEUM GASES, LIQUIFIED, SWEETENED	Inhalation	cardiac sensitization	Causes damage to organs	similar compounds	NOAEL Not available	
PETROLEUM GASES, LIQUIFIED, SWEETENED	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
PETROLEUM GASES, LIQUIFIED, SWEETENED	Inhalation	respiratory irritation	Not classified		NOAEL Not available	
Ethanolamine	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
C12-C15 Alcohols Ethoxylated	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not Available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available
Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
Butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
Butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
Butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
Butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
Butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
PETROLEUM GASES, LIQUIFIED, SWEETENED	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL Not available	
Ethanolamine	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	liver	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.0102 mg/l	28 days
Ethanolamine	Inhalation	heart	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	immune system	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	nervous system	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	eyes	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Ingestion	hematopoietic system	Not classified	Rat	NOAEL Not available	
Ethanolamine	Ingestion	liver	Not classified	Rat	NOAEL Not available	

					available	
Ethanolamine	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL Not available	
Ethanolamine	Ingestion	respiratory system	Not classified	Rat	NOAEL Not available	
C12-C15 Alcohols Ethoxylated	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
C12-C15 Alcohols Ethoxylated	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
C12-C15 Alcohols Ethoxylated	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
C12-C15 Alcohols Ethoxylated	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
C12-C15 Alcohols Ethoxylated	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
C12-C15 Alcohols Ethoxylated	Ingestion	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
C12-C15 Alcohols Ethoxylated	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

A 3M Product Environmental Data Sheet (PED) is available.

Chemical fate information

A 3M Product Environmental Data Sheet (PED) is available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not Applicable.

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Butoxyethanol	111-76-2	Trade Secret 10 - 30

15.2. State Regulations

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

This product complies with the New Zealand Hazardous Substances and New Organisms Act (1996).

15.4. International Regulations

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	10-2818-2	Version Number:	25.01
Issue Date:	02/24/26	Supersedes Date:	12/12/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com