



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 28-8279-3
Issue Date: 02/21/25

Version Number: 3.03
Supersedes Date: 02/19/25

SECTION 1: Identification

1.1. Product identifier

3M™ Marine Adhesive Sealant Fast Cure 4000 UV, White

Product Identification Numbers

62-5563-1632-1, 62-5563-5232-6, 62-5563-5235-9
7000121531, 7000046623, 7000121533

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Industrial Adhesives and Tapes Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms

**Hazard Statements**

May cause an allergic skin reaction.
May damage fertility or the unborn child.

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wear protective gloves.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Calcium Carbonate	471-34-1	30 - 60
Polyethers (NJTS Reg. No. 04499600-6434)	Trade Secret*	15 - 40
Diisodecyl Phthalate	68515-49-1	10 - 20 Trade Secret *
Titanium Dioxide	13463-67-7	5 - 10 Trade Secret *
Fatty acids, C16-18, sodium salts	68424-38-4	< 3
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	1760-24-3	0.1 - 1 Trade Secret *
Hindered Amine	63843-89-0	< 1
Vinyltrimethoxysilane	2768-02-7	< 1
Tin, dioctylbis(2,4-pentanedionato-O,O')	54068-28-9	0.1 - 0.5 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

DO NOT USE WATER In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide

Irritant Vapors or Gases

Condition

During Combustion

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

Refer to Section 15 for additional information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

Refer to Section 15 for additional information

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m ³ ;TWA(Respirable finescale particles):2.5 mg/m ³	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m ³	
DUST, INERT OR NUISANCE	471-34-1	OSHA	TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m ³);TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m ³)	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	471-34-1	ACGIH	TWA(inhalable particulates):10 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	471-34-1	ACGIH	TWA(respirable particles):3 mg/m ³	
TIN, ORGANIC COMPOUNDS	54068-28-9	ACGIH	TWA(as Sn):0.1 mg/m ³ ;STEL(as Sn):0.2	A4: Not class. as human carcin, Danger of

			mg/m3	cutaneous absorption
TIN, ORGANIC COMPOUNDS	54068-28-9	OSHA	TWA(as Sn):0.1 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer to Section 15 for additional information

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
Color

Liquid
White

Specific Physical Form:

Paste

Odor

Slight Polyether

Odor threshold

No Data Available

pH

No Data Available

Melting point

Not Applicable

Boiling Point

Not Applicable

Flash Point

No flash point

Evaporation rate

Not Applicable

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

Vapor Pressure

Not Applicable

Vapor Density

Not Applicable

Density

1.3 - 1.5 g/ml

Specific Gravity

1.3 - 1.5 [Ref Std: WATER=1]

Solubility In Water

No Data Available

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Hazardous Air Pollutants

0 % weight

Molecular weight

No Data Available

Volatile Organic Compounds

16 g/l [Test Method: tested per EPA method 24]

Percent volatile

0.93 % weight

VOC Less H₂O & Exempt Solvents

16 g/l [Test Method: tested per EPA method 24]

VOC Less H₂O & Exempt Solvents

0.93 % [Test Method: tested per EPA method 24]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Alcohols

Amines

Water

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

<u>Name</u>	<u>Route</u>	<u>Species</u>	<u>Value</u>
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist	Rat	LC50 3 mg/l

	(4 hours)		
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Polyethers (NJTS Reg. No. 04499600-6434)	Ingestion	Rat	LD50 > 2,000 mg/kg
Polyethers (NJTS Reg. No. 04499600-6434)	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
Diisodecyl Phthalate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Diisodecyl Phthalate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 12.5 mg/l
Diisodecyl Phthalate	Ingestion	Rat	LD50 > 9,700 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Vinyltrimethoxysilane	Dermal	Rabbit	LD50 3,260 mg/kg
Vinyltrimethoxysilane	Inhalation-Vapor (4 hours)	Rat	LC50 16.8 mg/l
Vinyltrimethoxysilane	Ingestion	Rat	LD50 7,120 mg/kg
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Dermal	Rabbit	LD50 > 2,000 mg/kg
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.49, < 2.44 mg/l
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Ingestion	Rat	LD50 1,897 mg/kg
Tin, dioctylbis(2,4-pentanedionato-O,O')	Dermal	Rat	LD50 > 2,000 mg/kg
Tin, dioctylbis(2,4-pentanedionato-O,O')	Ingestion	Rat	LD50 > 2,000 mg/kg
Hindered Amine	Dermal	Rat	LD50 > 3,170 mg/kg
Hindered Amine	Ingestion	Rat	LD50 1,490 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Minimal irritation
Titanium Dioxide	Rabbit	No significant irritation
Vinyltrimethoxysilane	Rabbit	Minimal irritation
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Rabbit	Mild irritant
Tin, dioctylbis(2,4-pentanedionato-O,O')	Rabbit	No significant irritation
Hindered Amine	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation
Vinyltrimethoxysilane	Rabbit	No significant irritation
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Rabbit	Corrosive
Tin, dioctylbis(2,4-pentanedionato-O,O')	Rabbit	Mild irritant
Hindered Amine	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
Diisodecyl Phthalate	Guinea pig	Not classified
Titanium Dioxide	Human and animal	Not classified
Vinyltrimethoxysilane	Guinea pig	Some positive data exist, but the data are not sufficient for classification

1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Multiple animal species	Sensitizing
Tin, dioctylbis(2,4-pentanedionato-O,O')	Mouse	Sensitizing
Hindered Amine	Guinea pig	Not classified

Photosensitization

Name	Species	Value
Hindered Amine	Guinea pig	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Diisodecyl Phthalate	In Vitro	Not mutagenic
Diisodecyl Phthalate	In vivo	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Vinyltrimethoxysilane	In vivo	Not mutagenic
Vinyltrimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	In Vitro	Not mutagenic
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	In vivo	Not mutagenic
Tin, dioctylbis(2,4-pentanedionato-O,O')	In Vitro	Not mutagenic
Hindered Amine	In vivo	Not mutagenic
Hindered Amine	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Diisodecyl Phthalate	Ingestion	Not classified for female reproduction	Rat	NOAEL 927 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Not classified for male reproduction	Rat	NOAEL 929 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Toxic to development	Rat	NOAEL 38 mg/kg/day	2 generation
Vinyltrimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Vinyltrimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Vinyltrimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Vinyltrimethoxysilane	Inhalation	Not classified for development	Rat	NOAEL 1.8 mg/l	during organogenesis

1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	premating into lactation
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	28 days
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	during gestation
Tin, dioctylbis(2,4-pentanedionato-O,O')	Ingestion	Toxic to development	similar compounds	NOAEL not available	2 generation
Hindered Amine	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	premating into lactation
Hindered Amine	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	36 days
Hindered Amine	Ingestion	Not classified for development	Rat	NOAEL 10 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Diisodecyl Phthalate	Inhalation	respiratory system hematopoietic system liver	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Diisodecyl Phthalate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.5 mg/l	2 generation
Diisodecyl Phthalate	Ingestion	endocrine system	Not classified	Rat	NOAEL 686 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	liver kidney and/or bladder heart	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 320 mg/kg/day	90 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Vinyltrimethoxysilane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL mg/l	14 weeks
Vinyltrimethoxysilane	Inhalation	hematopoietic system eyes	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
Vinyltrimethoxysilane	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	40 days
Vinyltrimethoxysilane	Ingestion	endocrine system hematopoietic system liver immune system	Not classified	Rat	NOAEL 1,000 mg/kg/day	40 days
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Dermal	skin endocrine system hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 1,545 mg/kg/day	11 days
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated	Rat	NOAEL 0.015 mg/l	90 days

			exposure			
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Inhalation	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 0.044 mg/l	90 days
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Ingestion	hematopoietic system nervous system	Not classified	Rat	NOAEL 500 mg/kg/day	28 days
Tin, dioctylbis(2,4-pentanedionato-O,O')	Ingestion	immune system	Causes damage to organs through prolonged or repeated exposure	similar compounds	NOAEL not available	
Hindered Amine	Ingestion	gastrointestinal tract hematopoietic system liver immune system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 2 mg/kg/day	36 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

Refer to Section 15 for additional information

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

Additional TSCA Information

Components	CAS No	Additional Information
Tin, dioctylbis(2,4-pentanedionato-O,O')	54068-28-9	Allowed use(s): Catalyst. Required exposure controls when handling the LVE substance: Use in a well-ventilated area/ Appropriate general dilution and/or local exhaust ventilation; Gloves composed of material as determined by results of exposure assessment; sufficiently protective workclothes; impermeable gloves. Required environmental release controls for the LVE substance: Wastes and cleanup materials may be incinerated in a permitted facility or landfill.

15.2. State Regulations

Contact 3M for more information.

California Proposition 65**Ingredient**

Di-isodecyl phthalate (DIDP)

C.A.S. No.

68515-49-1

Listing

Developmental Toxin

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. One or more of the components in this material is not listed on the TSCA inventory, but is approved for specific commercial use(s) under a US EPA low volume exemption.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 28-8279-3

Issue Date: 02/21/25

Version Number: 3.03

Supersedes Date: 02/19/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com