



## Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 39-0698-9  
**Revision date:** 15/09/2025

**Version number:** 4.00  
**Supersedes date:** 31/01/2023

**Transportation version number:**

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

### IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

3M Scotch-Weld™ EC-9356 B/A FST - Structural Adhesive

#### Product Identification Numbers

UU-0082-9982-6      UU-0092-6411-8      UU-0111-4767-3

7100181415      7100186641      7100250368

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Product, Industrial use.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** ner-productstewardship@mmm.com

**Website:** [www.3M.com/uk](http://www.3M.com/uk)

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:**

38-9216-3, 38-9217-1

### TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

## KIT LABEL

### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### SIGNAL WORD

DANGER.

#### Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

#### Pictograms



#### Contains:

Acrylic copolymer; Titanium dioxide; Nitric acid, calcium salt, tetrahydrate; 1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane; bis-[4-(2,3-epoxipropoxy)phenyl]propane; Aluminium hydroxide; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); Oxide glass chemicals; Siloxanes and Silicones, di-Me, reaction products with silica; Amine terminated adduct; Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-([2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane; Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine ; red phosphorus

#### HAZARD STATEMENTS:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

#### Prevention:

P261A Avoid breathing vapours.

P273 Avoid release to the environment.

P280B Wear protective gloves and eye/face protection.

#### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTRE or doctor/physician.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

**For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**

### **<=125 ml Hazard statements**

H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.

## **<=125 ml Precautionary statements**

## Prevention:

P261A Avoid breathing vapours.  
P280B Wear protective gloves and eye/face protection.

## Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTRE or doctor/physician.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

## SUPPLEMENTAL INFORMATION:

### **Supplemental Hazard Statements:**

Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Refer to Safety Data Sheet for component % unknown values ([www.3M.com/msds](http://www.3M.com/msds)).

### Revision information:

GB Label: CLP Ingredients - kit components information was modified.  
Section 1: E-mail address information was modified.  
Section 1: Product use information information was modified.  
Section 2: <125ml Precautionary - Prevention information was modified.



## Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 38-9216-3  
**Revision date:** 18/12/2025

**Version number:** 10.00  
**Supersedes date:** 10/12/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M Scotch-Weld™ EC-9356 B/A FST Part A - Structural Adhesive

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Product

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** ner-productstewardship@mmm.com  
**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

This material has been tested for skin corrosion/irritation and the test results are reflected in the assigned classification.

#### CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

## 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

### SIGNAL WORD

DANGER.

### Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

### Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	1 - 35
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-(oxybis(ethane-2,1-diyloxy)]dipropan-1-amine		701-270-9	1 - 35
Nitric acid, calcium salt, tetrahydrate	13477-34-4	233-332-1	1 - 15

### HAZARD STATEMENTS:

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS

#### Prevention:

P261A	Avoid breathing vapours.
P273	Avoid release to the environment.
P280B	Wear protective gloves and eye/face protection.

#### Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 P333 + P313	Immediately call a POISON CENTRE or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

#### <=125 ml Hazard statements

H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

#### <=125 ml Precautionary statements

**Prevention:**

P261A

P280B

Avoid breathing vapours.

Wear protective gloves and eye/face protection.

**Response:**

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTRE or doctor/physician.

P333 + P313

If skin irritation or rash occurs: Get medical advice/attention.

30% of the mixture consists of components of unknown acute oral toxicity.

30% of the mixture consists of components of unknown acute dermal toxicity.

Contains 37% of components with unknown hazards to the aquatic environment.

**2.3. Other hazards**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

This material does not contain any substances that are assessed to be a PBT or vPvB

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Aluminium hydroxide	(CAS-No.) 21645-51-2 (EC-No.) 244-492-7	10 - 40	Substance with a national occupational exposure limit
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2	1 - 35	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethylene-2,1-diyloxy)]dipropan-1-amine	(EC-No.) 701-270-9	1 - 35	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
Amine terminated adduct	Trade Secret	5 - 30	Substance not classified as hazardous
Nitric acid, calcium salt, tetrahydrate	(CAS-No.) 13477-34-4 (EC-No.) 233-332-1	1 - 15	Acute Tox. 4, H302 Eye Dam. 1, H318
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	< 10	Substance with a national occupational exposure limit
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	<= 3	Substance with a national occupational exposure limit

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

### 4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO<sub>2</sub> (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Titanium dioxide	13463-67-7	UK HSE	TWA(respirable):4 mg/m <sup>3</sup> ;TWA(Inhalable):10 mg/m <sup>3</sup>	
Dust, inhalable dust	21645-51-2	UK HSE	TWA(as respirable dust):4 mg/m <sup>3</sup> ;TWA(as inhalable dust):10 mg/m <sup>3</sup>	
Silica, amorphous, inhalable dust	67762-90-7	UK HSE	TWA(as respirable dust):2.4 mg/m <sup>3</sup> ;TWA(as inhalable dust):6 mg/m <sup>3</sup>	

UK HSE : UK Health and Safety Commission

TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

#### Applicable Norms/Standards

Use eye/face protection conforming to EN 16321

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

#### Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	White
Odor	Light Amine
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	<i>Not applicable.</i>
Flammability	<i>Not applicable.</i>
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Flash point	> 93.3 °C [Test Method:Closed Cup]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	<i>Not applicable.</i>
Solubility- non-water	<i>Negligible</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>Not applicable.</i>
Density	1.1 - 1.5 g/cm <sup>3</sup> [Ref Std:WATER=1]
Relative density	1.3 [Ref Std:WATER=1]
Relative Vapour Density	<i>Not applicable.</i>
Particle Characteristics	<i>Not applicable.</i>

## 9.2. Other information

### 9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>Not applicable.</i>
Percent volatile	<i>No data available.</i>

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

None known.

### 10.5 Incompatible materials

Not determined

### 10.6 Hazardous decomposition products

**Substance**

None known.

**Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

#### Signs and Symptoms of Exposure

**Based on test data and/or information on the components, this material may produce the following health effects:**

##### **Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

##### **Skin contact**

May be harmful in contact with skin. Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

##### **Eye contact**

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

##### **Ingestion**

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

##### **Single exposure may cause target organ effects:**

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

##### **Additional information:**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg

Aluminium hydroxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium hydroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium hydroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Dermal	Rat	LD50 > 2,000 mg/kg
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	Rat	LD50 > 2,000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Dermal	similar compounds	LD50 > 2,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro data	Irritant
Aluminium hydroxide	Rabbit	No significant irritation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Rat	Irritant
Nitric acid, calcium salt, tetrahydrate	similar compounds	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

#### Serious Eye Damage/Irritation

Name	Species	Value
Aluminium hydroxide	Rabbit	No significant irritation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	In vitro data	Severe irritant
Nitric acid, calcium salt, tetrahydrate	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

#### Skin Sensitisation

Name	Species	Value
Aluminium hydroxide	Guinea pig	Not classified
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professional judgement	Sensitising
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Guinea pig	Sensitising

[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	pig	
Nitric acid, calcium salt, tetrahydrate	similar compounds	Not classified
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
Titanium dioxide	Human and animal	Not classified

### Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	In Vitro	Not mutagenic
Nitric acid, calcium salt, tetrahydrate	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
Aluminium hydroxide	Not specified.	Multiple animal species	Not carcinogenic
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

### Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Aluminium hydroxide	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesis
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for female reproduction	similar compound	NOAEL 1,500	prematuring into lactation

			ds	mg/kg/day	
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for male reproduction	similar compounds	NOAEL 1,500 mg/kg/day	28 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for development	similar compounds	NOAEL 1,500 mg/kg/day	pre mating into lactation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-(oxybis(ethane-2,1-diyloxy)dipropylamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-(oxybis(ethane-2,1-diyloxy)dipropylamine	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Ingestion	methemoglobinemia	Causes damage to organs	Human	NOAEL Not available	environmental exposure

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	gastrointestinal tract   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-(oxybis(ethane-2,1-diyloxy)dipropylamine	Ingestion	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days

		system   vascular system				
Nitric acid, calcium salt, tetrahydrate	Ingestion	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	similar compounds	NOAEL 1,500 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

### Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

## SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Aluminium hydroxide	21645-51-2	Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
3,3'-Oxybis(ethyleneoxybis(propylamine))	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
3,3'-Oxybis(ethyleneoxybis(propylamine))	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
3,3'-Oxybis(ethyleneoxybis(propylamine))	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
3,3'-Oxybis(ethyleneoxybis(propylamine))	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l

y)bis(propylamine)						
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-dioxy)]dipropylamine	701-270-9	Fathead minnow	Experimental	96 hours	LL50	2.16 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-dioxy)]dipropylamine	701-270-9	Green algae	Experimental	72 hours	EL50	0.43 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-dioxy)]dipropylamine	701-270-9	Water flea	Experimental	48 hours	EL50	0.57 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-dioxy)]dipropylamine	701-270-9	Green algae	Experimental	72 hours	NOEL	0.28 mg/l
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-dioxy)]dipropylamine	701-270-9	Activated sludge	Experimental	3 hours	EC50	410.3 mg/l
Amine terminated adduct	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Guppy	Estimated	96 hours	LC50	1,378 mg/l
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Fathead minnow	Estimated	30 days	NOEC	58 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium hydroxide	21645-51-2	Data not availbl-insufficient	N/A	N/A	N/A	N/A
3,3'-Oxybis(ethyleneoxybis(propylamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
3,3'-Oxybis(ethyleneoxybis(propylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	701-270-9	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301F - Manometric respirometry
Amine terminated adduct	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A

### 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Aluminium hydroxide	21645-51-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3,3'-Oxybis(ethyleneoxybis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	701-270-9	Modeled Bioconcentration		Bioaccumulation factor	42	Catalogic™
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine	701-270-9	Modeled Bioconcentration		Log Kow	11.7	Episuite™
Amine terminated adduct	Trade Secret	Estimated Bioconcentration		Bioaccumulation factor	2.9	
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	

## 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Modeled Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™
Reaction products of fatty acids, C18-unsaturated, dimers and trimers with 3,3'-(oxybis(ethane-2,1-dioxy))dipropylamine	701-270-9	Modeled Mobility in Soil	Koc	3,780,000,000 l/kg	

## 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

## 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

## SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
<b>14.1 UN number</b>	UN3077	UN3077	UN3077
<b>14.2 UN proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(FATTY ACIDS, C18-UNSATD, DIMERS, POLYMERS WITH 3,3-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(FATTY ACIDS, C18-UNSATD, DIMERS, POLYMERS WITH 3,3-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(FATTY ACIDS, C18-UNSATD, DIMERS, POLYMERS WITH 3,3-(OXYBIS(2,1-ETHANEDIYLOXY))BIS(1-

	(OXYBIS(2,1-ETHANEDIYLOXY))BIS(1-PROPANAMINE))	(OXYBIS(2,1-ETHANEDIYLOXY))BIS(1-PROPANAMINE))	PROPANAMINE))
<b>14.3 Transport hazard class(es)</b>	9	9	9
<b>14.4 Packing group</b>	III	III	III
<b>14.5 Environmental hazards</b>	Environmentally Hazardous	Not applicable	Marine Pollutant
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	C8	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<u>Carcinogenicity</u> <u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

### COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements

E1 Hazardous to the Aquatic environment	100	200
---	-----	-----

Seveso named dangerous substances, Annex 1, Part 2  
None

#### **Regulation (EU) No 649/2012, as amended for GB**

No chemicals listed

#### **15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

### **SECTION 16: Other information**

#### **List of relevant H statements**

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### **Revision information:**

No revision information

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M SDSs for Great Britain are available at [www.3M.com/uk](http://www.3M.com/uk)**

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



## Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	38-9217-1	<b>Version number:</b>	7.00
<b>Revision date:</b>	18/12/2025	<b>Supersedes date:</b>	07/02/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M Scotch-Weld™ EC-9356 B/A FST Part B - Structural Adhesive

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Product

#### 1.3. Details of the supplier of the safety data sheet

<b>Address:</b>	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
<b>Telephone:</b>	+44 (0)1344 858 000
<b>E Mail:</b>	ner-productstewardship@mmm.com
<b>Website:</b>	www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

#### CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

**2.2. Label elements****The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain****SIGNAL WORD**

WARNING.

**Symbols**

GHS07 (Exclamation mark) | GHS09 (Environment) |

**Pictograms**

Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	25 - 35
Aluminium hydroxide	21645-51-2	244-492-7	10 - 30
Acrylic copolymer	Trade Secret		7 - 13
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	14228-73-0	238-098-4	< 10
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane		701-263-0	< 10
red phosphorus	7723-14-0	231-768-7	3 - 7
Titanium dioxide	13463-67-7	236-675-5	3 - 7
Oxide glass chemicals	65997-17-3	266-046-0	0.5 - 1.5
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		0.5 - 1.5

**HAZARD STATEMENTS:**

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS****Prevention:**

P273	Avoid release to the environment.
P280E	Wear protective gloves.

**Response:**

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 P391	If skin irritation or rash occurs: Get medical advice/attention. Collect spillage.

**For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:****<=125 ml Hazard statements**

H317

May cause an allergic skin reaction.

## &lt;=125 ml Precautionary statements

**Prevention:**

P280E

Wear protective gloves.

**Response:**

P333 + P313

If skin irritation or rash occurs: Get medical advice/attention.

11% of the mixture consists of components of unknown acute oral toxicity.

Contains 12% of components with unknown hazards to the aquatic environment.

**2.3. Other hazards**

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	25 - 35	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Aluminium hydroxide	(CAS-No.) 21645-51-2 (EC-No.) 244-492-7	10 - 30	Substance with a national occupational exposure limit
Acrylic copolymer	Trade Secret	7 - 13	Substance not classified as hazardous
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	(CAS-No.) 14228-73-0 (EC-No.) 238-098-4	< 10	Aquatic Chronic 3, H412 Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1B, H317
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane	(EC-No.) 701-263-0	< 10	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411
red phosphorus	(CAS-No.) 7723-14-0 (EC-No.) 231-768-7	3 - 7	Flam. Sol. 1, H228 Aquatic Chronic 3, H412
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	3 - 7	Substance with a national occupational exposure limit

Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	0.5 - 1.5	Substance with a national occupational exposure limit
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	0.5 - 1.5	Substance with a national occupational exposure limit

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

### Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.

### 5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from amines.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
------------	---------	--------	------------	---------------------

Titanium dioxide	13463-67-7	UK HSE	TWA(respirable):4 mg/m <sup>3</sup> ;TWA(Inhalable):10 mg/m <sup>3</sup>
Dust, inhalable dust	21645-51-2	UK HSE	TWA(as respirable dust):4 mg/m <sup>3</sup> ;TWA(as inhalable dust):10 mg/m <sup>3</sup>
Dust, inhalable dust	65997-17-3	UK HSE	TWA(as respirable dust):4 mg/m <sup>3</sup> ;TWA(as inhalable dust):10 mg/m <sup>3</sup>
Oxide glass chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m <sup>3</sup> ;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m <sup>3</sup>
Silica, amorphous, inhalable dust	67762-90-7	UK HSE	TWA(as respirable dust):2.4 mg/m <sup>3</sup> ;TWA(as inhalable dust):6 mg/m <sup>3</sup>
red phosphorus	7723-14-0	UK HSE	TWA: 0.1 mg/m <sup>3</sup> ; STEL: 0.3 mg/m <sup>3</sup>

UK HSE : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

#### Applicable Norms/Standards

Use eye protection conforming to EN 16321

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

#### Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

### *Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter types A & P

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid.
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Pink
<b>Odor</b>	Light Epoxy
<b>Odour threshold</b>	<i>No data available.</i>
<b>Melting point/freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/boiling range</b>	<i>Not applicable.</i>
<b>Flammability</b>	<i>Not applicable.</i>
<b>Flammable Limits(LEL)</b>	<i>Not applicable.</i>
<b>Flammable Limits(UEL)</b>	<i>Not applicable.</i>
<b>Flash point</b>	No flash point
<b>Autoignition temperature</b>	<i>Not applicable.</i>
<b>Decomposition temperature</b>	<i>Not applicable.</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	<i>No data available.</i>
<b>Water solubility</b>	<i>Not applicable.</i>
<b>Solubility- non-water</b>	Negligible
<b>Partition coefficient: n-octanol/water</b>	<i>Not applicable.</i>
<b>Vapour pressure</b>	<i>Not applicable.</i>
<b>Density</b>	1.1 - 1.5 g/cm <sup>3</sup>
<b>Relative density</b>	<i>No data available.</i>
<b>Relative Vapour Density</b>	<i>Not applicable.</i>
<b>Particle Characteristics</b>	<i>Not applicable.</i>

### 9.2. Other information

#### 9.2.2 Other safety characteristics

<b>EU Volatile Organic Compounds</b>	<i>No data available.</i>
<b>Evaporation rate</b>	<i>Not applicable.</i>
<b>Percent volatile</b>	<i>No data available.</i>

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

None known.

### 10.5 Incompatible materials

Amines.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.  
Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Aluminium hydroxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium hydroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium hydroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	Dermal	Rat	LD50 > 2,000 mg/kg
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.19 mg/l
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Rat	LD50 1,098 mg/kg
red phosphorus	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
red phosphorus	Ingestion	Rat	LD50 > 15,000 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Aluminium hydroxide	Rabbit	No significant irritation
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	Rabbit	Irritant
Titanium dioxide	Rabbit	No significant irritation
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro data	Irritant
red phosphorus	Rabbit	No significant irritation
Oxide glass chemicals	Professional judgement	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
------	---------	-------

bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Aluminium hydroxide	Rabbit	No significant irritation
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro data	No significant irritation
red phosphorus	Rabbit	No significant irritation
Oxide glass chemicals	Professional judgement	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation

### Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human and animal	Sensitising
Aluminium hydroxide	Guinea pig	Not classified
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	Multiple animal species	Sensitising
Titanium dioxide	Human and animal	Not classified
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Mouse	Sensitising
red phosphorus	Guinea pig	Not classified
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified

### Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

### Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	In vivo	Not mutagenic
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vivo	Not mutagenic
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In Vitro	Some positive data exist, but the data are not sufficient for classification
red phosphorus	In Vitro	Not mutagenic
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium hydroxide	Not specified.	Multiple animal species	Not carcinogenic
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Aluminium hydroxide	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesis
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	33 days
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	premating into lactation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Reaction mass of 2,2'-(methylenebis(2,1-phenyleneoxymethylene))bis(oxirane) and 2,2'-(methylenebis(4,1-phenyleneoxymethylene))bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)\methyl)oxirane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
--	------------	------------------------	--	------------------------	---------------------	--

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propene	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3-epoxipropoxi)phenyl]propene	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxipropoxi)phenyl]propene	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-[2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy]methyl)oxirane	Ingestion	heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	endocrine system   gastrointestinal tract   liver   heart   hematopoietic system   immune system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 300 mg/kg/day	33 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure

### Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

## SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

## 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Aluminium hydroxide	21645-51-2	Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
1,4-Bis[(2,3-epoxypropoxy)met hyl]cyclohexane	14228-73-0	Bacteria	Estimated	18 hours	EC50	10,264 mg/l
1,4-Bis[(2,3-epoxypropoxy)met hyl]cyclohexane	14228-73-0	Green algae	Estimated	72 hours	EC50	26.7 mg/l
1,4-Bis[(2,3-epoxypropoxy)met hyl]cyclohexane	14228-73-0	Rainbow trout	Estimated	96 hours	LC50	10.1 mg/l
1,4-Bis[(2,3-epoxypropoxy)met hyl]cyclohexane	14228-73-0	Water flea	Estimated	48 hours	EC50	16.3 mg/l
1,4-Bis[(2,3-epoxypropoxy)met hyl]cyclohexane	14228-73-0	Green algae	Estimated	72 hours	EC10	21.4 mg/l
1,4-Bis[(2,3-epoxypropoxy)met hyl]cyclohexane	14228-73-0	Water flea	Estimated	21 days	NOEC	11.7 mg/l
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl	701-263-0	Green algae	Experimental	72 hours	EbC50	1.8 mg/l

xirane						
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	701-263-0	Rainbow trout	Experimental	96 hours	LC50	2 mg/l
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	701-263-0	Water flea	Experimental	48 hours	EC50	1.6 mg/l
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	701-263-0	Water flea	Analogous Compound	21 days	NOEC	0.3 mg/l
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(\{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	701-263-0	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
red phosphorus	7723-14-0	Activated sludge	Estimated	3 hours	NOEC	1,000 mg/l
red phosphorus	7723-14-0	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
red phosphorus	7723-14-0	Green algae	Experimental	72 hours	EL50	18.3 mg/l
red phosphorus	7723-14-0	Water flea	Experimental	48 hours	EL50	10.5 mg/l
red phosphorus	7723-14-0	Zebra Fish	Experimental	96 hours	EL50	2.5 mg/l

red phosphorus	7723-14-0	Green algae	Experimental	72 hours	EL10	6.6 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Aluminium hydroxide	21645-51-2	Data not availbl-insufficient	N/A	N/A	N/A	N/A
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	14228-73-0	Estimated Biodegradation	28 days	Dissolv. Organic Carbon Deplet	16.6 %removal of DOC	OECD 301F - Manometric respirometry
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxyethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxyethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\methyl)oxirane	701-263-0	Experimental Biodegradation	28 days	CO2 evolution	16 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxyethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxyethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\methyl)oxirane	701-263-0	Analogous Compound Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH

red phosphorus	7723-14-0	Experimental Hydrolysis		Hydrolytic half-life	8.3 years (t 1/2)	
Titanium dioxide	13463-67-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Oxide glass chemicals	65997-17-3	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A

### 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Aluminium hydroxide	21645-51-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	14228-73-0	Estimated Bioconcentration		Bioaccumulation factor	3	
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy\}methyl)oxirane	701-263-0	Experimental Bioconcentration		Log Kow	3.6	OECD 117 log Kow HPLC method
red phosphorus	7723-14-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

### 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite™
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	14228-73-0	Estimated Mobility in Soil	Koc	57 l/kg	Episuite™
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-	701-263-0	Experimental Mobility in Soil	Koc	4,460 l/kg	OECD 121 Estim. of Koc by HPLC

phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane					
---	--	--	--	--	--

## 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

## 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

## SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
<b>14.1 UN number</b>	UN3077	UN3077	UN3077
<b>14.2 UN proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(EPOXY RESIN)
<b>14.3 Transport hazard class(es)</b>	9	9	9
<b>14.4 Packing group</b>	III	III	III
<b>14.5 Environmental hazards</b>	Environmentally Hazardous	Not applicable	Marine Pollutant
<b>14.6 Special</b>	Please refer to the other	Please refer to the other	Please refer to the other sections of the

<b>precautions for user</b>	sections of the SDS for further information.	sections of the SDS for further information.	SDS for further information.
<b>14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	M7	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of Restriction

#### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**COMAH Regulation, SI 2015/483**

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2

None

**Regulation (EU) No 649/2012, as amended for GB**

No chemicals listed

**15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

**SECTION 16: Other information****List of relevant H statements**

H228	Flammable solid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

Section 1: E-mail address information was modified.

Label: CLP Supplemental Hazard Statements information was deleted.

Section 3: Composition/ Information of ingredients table information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 08: Personal Protection - Apron Statement information was added.

Section 8: Personal Protection - Skin/body information information was deleted.

Section 8: Skin protection - protective clothing information information was deleted.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M SDSs for Great Britain are available at [www.3M.com/uk](http://www.3M.com/uk)**

For Northern Ireland documents, please contact your 3M representative to obtain a copy.