

Safety Data Sheet

Copyright,2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-4454-6	Version number:	12.04
Revision date:	28/11/2024	Supersedes date:	24/02/2023
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier3M Scotch-Weld[™] EC-7256 B/A			
Product Identificati FS-9100-5178-8	on Numbers FS-9100-5491-5	FS-9100-5492-3	UU-0109-4246-2
7000080287	7100021468	7100022157	7100229938

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Product

1.3. Details of the supplier of the safety data sheet

Address:3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.Telephone:+44 (0)1344 858 000E Mail:tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number +44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

28-4446-2, 28-4437-1

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Contains:

Acrylic copolymer; 2,6-Di-tert-butyl-p-cresol; Nitric acid, calcium salt, tetrahydrate; bis-[4-(2,3-epoxipropoxi)phenyl]propane; [3-(2,3-epoxypropoxy)propyl]trimethoxysilane; Silane, triethoxy[3-(oxiranylmethoxy)propyl]-; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); Siloxanes and Silicones, di-Me, reaction products with silica; 2,2'-[(1-Methylethylidene)bis[4,1-phenyleneoxy[1-(butoxymethyl)ethylene]oxymethylene]]bisoxirane; 2,4,6-tris(dimethylaminomethyl)phenol

HAZARD STATEMENTS:H314Causes severe skin burns and eye damage.H317May cause an allergic skin reaction.H411Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention: P260A P273 P280D	Do not breathe vapours. Avoid release to the environment. Wear protective gloves, protective clothing, and eye/face protection.
Response:	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements	
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
<=125 ml Precautionary statemer	its

Prevention:P260ADo not breathe vapours.

P280D	Wear protective gloves, protective clothing, and eye/face protection.	
Response:		
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTRE or doctor/physician.	

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Section 1: Product use information information was modified.



Safety Data Sheet

Copyright,2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-4437-1	Version number:	8.00
Revision date:	26/11/2024	Supersedes date:	18/12/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld[™] EC-7256 B/A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Accelerator for two-part epoxy structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address:3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.Telephone:+44 (0)1344 858 000E Mail:tox.uk@mmm.comWebsite:www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Sensitization, Category 1 - Skin Sens. 1; H317

For full text of H phrases, see Section 16.

2.2. Label elements The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |



Ingredient	CAS Nbr	EC No.	% by Wt
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	50 - 70
Nitric acid, calcium salt, tetrahydrate	13477-34-4	233-332-1	7 - 13
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	202-013-9	7 - 13

HAZARD STATEMENTS:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention: P260A P280D	Do not breathe vapours. Wear protective gloves, protective clothing, and eye/face protection.
Response:	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements	
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention: P260A P280D	Do not breathe vapours. Wear protective gloves, protective clothing, and eye/face protection.
Response: P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
1010	Immediately call a POISON CENTRE or doctor/physician.

25% of the mixture consists of components of unknown acute oral toxicity.

Contains 27% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known. This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2	50 - 70	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with 3,3'-[oxybis(2,1- ethanediyloxy)]bis[1-propanamine]	(CAS-No.) 68585-28-4	20 - 30	Substance not classified as hazardous
Nitric acid, calcium salt, tetrahydrate	(CAS-No.) 13477-34-4 (EC-No.) 233-332-1	7 - 13	Acute Tox. 4, H302 Eye Dam. 1, H318
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9	7 - 13	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include: Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Amine compounds.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full face shield.

Indirect vented goggles.

Applicable Norms/Standards Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.7	=>8 hours

Fluoroelastomer	0.7	=>8 hours
Nitrile rubber.	0.4	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

. Information on basic physical and chemical prop	
Physical state	Solid.
Specific Physical Form:	Paste
Colour	White
Odor	Light Amine
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	Not applicable.
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	>=100 °C [Test Method:Closed Cup]
Autoignition temperature	Not applicable.
Decomposition temperature	No data available.
рН	substance/mixture is non-soluble (in water)
Kinematic Viscosity	27,273 mm ² /sec
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Density	1.1 g/ml
Relative density	1.09 - 1.12 [<i>Ref Std</i> :WATER=1]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds Evaporation rate Molecular weight Percent volatile No data available. No data available. No data available. <=1 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Strong acids. Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

<u>Condition</u>

Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000
-			mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000
-			mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
Nitric acid, calcium salt, tetrahydrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Dermal	similar	LD50 > 2,000 mg/kg
		compoun	
		ds	
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Nitric acid, calcium salt, tetrahydrate	similar	No significant irritation
	compoun	
	ds	
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Nitric acid, calcium salt, tetrahydrate	Rabbit	Corrosive
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive

Skin Sensitisation

Name Species Value

3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professio nal judgemen t	Sensitising
Nitric acid, calcium salt, tetrahydrate	similar compoun ds	Not classified
2,4,6-tris(dimethylaminomethyl)phenol	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
Nitric acid, calcium salt, tetrahydrate	In Vitro	Not mutagenic
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	premating into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for female reproduction	similar compoun ds	NOAEL 1,500 mg/kg/day	premating into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for male reproduction	similar compoun ds	NOAEL 1,500 mg/kg/day	28 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for development	similar compoun ds	NOAEL 1,500 mg/kg/day	premating into lactation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	2 generation
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Nitric acid, calcium salt, tetrahydrate	Ingestion	methemoglobinemi a	Causes damage to organs	Human	NOAEL Not available	environmental exposure
2,4,6- tris(dimethylaminomethyl) phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Ingestion	gastrointestinal tract heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	similar compoun ds	NOAEL 1,500 mg/kg/day	28 days
2,4,6- tris(dimethylaminomethyl) phenol	Dermal	skin	Not classified	Rat	NOAEL 25 mg/kg/day	4 weeks
2,4,6- tris(dimethylaminomethyl) phenol	Dermal	liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
2,4,6- tris(dimethylaminomethyl) phenol	Ingestion	heart endocrine system hematopoietic system liver muscles nervous system kidney and/or bladder respiratory system vascular system auditory system skin gastrointestinal tract bone, teeth, nails, and/or hair immune system eyes	Not classified	Rat	NOAEL 150 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Туре	Exposure	Test endpoint	Test result
3,3'-	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
Oxybis(ethyleneox			-			-
y)bis(propylamine)						
3,3'-	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
3,3'-	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
Oxybis(ethyleneox		_	-			-
y)bis(propylamine)						
3,3'-	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
3,3'-	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
Phenol, 4,4'-(1-	68585-28-4	N/A	Data not available	N/A	N/A	N/A
methylethylidene)b			or insufficient for			
is-, polymer with 2-			classification			
(chloromethyl)oxir						
ane, reaction						
products with 3,3'-						
[oxybis(2,1-						
ethanediyloxy)]bis[
1-propanamine]	12477.24.4			0.61	1.050	1.270 //
Nitric acid, calcium	134//-34-4	Guppy	Estimated	96 hours	LC50	1,378 mg/l
salt, tetrahydrate	12477.24.4			20.1	NOFO	50 //
Nitric acid, calcium	134//-34-4	Fathead minnow	Estimated	30 days	NOEC	58 mg/l
salt, tetrahydrate 2,4,6-	90-72-2	N/A	E	96 hours	LC50	719
2,4,0- tris(dimethylamino	90-72-2	IN/A	Experimental	96 nours	LC30	718 mg/l
methyl)phenol						
2.4.6-	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
z,4,0- tris(dimethylamino	90-72-2	Common Carp	Experimental	90 nours	LC30	>100 mg/1
methyl)phenol						
2,4,6-	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
tris(dimethylamino	122		Experimental	/ 2 110ur5		10.7 mg/1
methyl)phenol						
2.4.6-	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
tris(dimethylamino		, all the	2permientur	iouio	2000	100
methyl)phenol						
2,4,6-	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
tris(dimethylamino		Circon uigue		- nouro	1.020	
methyl)phenol						
meanynyphenor	I		1	1	1	1

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
3,3'-	4246-51-9	Experimental	25 days	CO2 evolution	-8 %CO2	OECD 301B - Modified
Oxybis(ethyleneox		Biodegradation	-		evolution/THCO2	sturm or CO2

y)bis(propylamine)					evolution	
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
Phenol, 4,4'-(1- methylethylidene)b is-, polymer with 2- (chloromethyl)oxir ane, reaction products with 3,3'- [oxybis(2,1- ethanediyloxy)]bis[1-propanamine]		Data not availbl- insufficient	N/A	N/A	N/A	N/A
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
Phenol, 4,4'-(1- methylethylidene)b is-, polymer with 2- (chloromethyl)oxir ane, reaction products with 3,3'- [oxybis(2,1- ethanediyloxy)]bis[1-propanamine]		Estimated Bioconcentration		Bioaccumulation factor	2.9	
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
3,3'- Oxybis(ethyleneoxy)bis(propylamine)		Modeled Mobility in Soil	Кос	1 l/kg	ACD/Labs ChemSketch™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and

handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09*Waste adhesives and sealants containing organic solvents or other dangerous substances20 01 27*Paint, inks, adhesives and resins containing dangerous substances

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3263	UN3263	UN3263
14.2 UN proper shipping name	CORROSIVE SOLID, BASIC, ORGANIC, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE))	CORROSIVE SOLID, BASIC, ORGANIC, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE))	CORROSIVE SOLID, BASIC, ORGANIC, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY)BIS(PRO PYLAMINE))
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	П	П	II
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	C8	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	18 - ALKALIS

SECTION 14: Transportation information

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H302	Harmful	if swallowed.			
11014	a	1 . 1	1	-	

- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.

Revision information:

Section 2: <125ml Precautionary - Prevention information was modified.

- Label: CLP Precautionary Prevention information was modified.
- Section 9: Flammability (solid, gas) information information was deleted.
- Section 09: Flammability information information was added.
- Section 09: Odor information was modified.
- Section 09: Particle Characteristics N/A information was added.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 11: Target Organs Single Table information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our

knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



Safety Data Sheet

Copyright,2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-4446-2	Version number:	10.03
Revision date:	21/11/2024	Supersedes date:	30/03/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld™ EC-7256 B/A Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Base component of two part Structural Adhesive

1.3. Details of the supplier of the safety data sheet

Address:3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.Telephone:+44 (0)1344 858 000E Mail:tox.uk@mmm.comWebsite:www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	65 - 75
2,2'-[(1-Methylethylidene)bis[4,1-phenyleneoxy[1- (butoxymethyl)ethylene]oxymethylene]]bisoxirane	71033-08-4	275-143-7	5 - 15
Acrylic copolymer	Trade Secret		< 15
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		1 - 3
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	219-784-2	< 1.5
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	2602-34-8	220-011-6	< 1.5
2,6-Di-tert-butyl-p-cresol	128-37-0	204-881-4	< 1

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:	
P280E	Wear protective gloves

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements	
H317	May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P280E

Wear protective gloves.

13% of the mixture consists of components of unknown acute oral toxicity.13% of the mixture consists of components of unknown acute dermal toxicity.97% of the mixture consists of components of unknown acute inhalation toxicity.Contains 27% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	65 - 75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Acrylic copolymer	Trade Secret	< 15	Substance not classified as hazardous
2,2'-[(1-Methylethylidene)bis[4,1- phenyleneoxy[1- (butoxymethyl)ethylene]oxymethylene]]bi soxirane	(CAS-No.) 71033-08-4 (EC-No.) 275-143-7	5 - 15	Skin Irrit. 2, H315 Skin Sens. 1, H317
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	1 - 3	Substance with a national occupational exposure limit
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2	< 1.5	Eye Dam. 1, H318 Aquatic Chronic 3, H412
Silane, triethoxy[3- (oxiranylmethoxy)propyl]-	(CAS-No.) 2602-34-8 (EC-No.) 220-011-6	< 1.5	Substance not classified as hazardous
2,6-Di-tert-butyl-p-cresol	(CAS-No.) 128-37-0 (EC-No.) 204-881-4	< 1	Aquatic Chronic 1, H410,M=1 Aquatic Acute 1, H400,M=1

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
		(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include: Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic

absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	
2,6-Di-tert-butyl-p-cresol	128-37-0	UK HSE	
Silicon dioxide	67762-90-7	UK HSE	

Limit type Additional comments TWA:10 mg/m³ TWA(as respirable dust):2.4 mg/m3;TWA(as inhalable dust):6 mg/m3

UK HSE : UK Health and Safety Commission TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material Polymer laminate **Thickness (mm)** No data available Breakthrough Time No data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties				
Physical state	Liquid.			
Specific Physical Form:	Paste			
Colour	White			
Odor	Light Epoxy			
Odour threshold	No data available.			
Melting point/freezing point	Not applicable.			
Boiling point/boiling range	> 121.1 °C			
Flammability	Not applicable.			
Flammable Limits(LEL)	No data available.			
Flammable Limits(UEL)	No data available.			
Flash point	>=122 °C [<i>Test Method</i> :Pensky-Martens Closed Cup]			
Autoignition temperature	No data available.			
Decomposition temperature	No data available.			
pH	substance/mixture is non-soluble (in water)			
Kinematic Viscosity	No data available.			

Water solubility	Nil	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Vapour pressure	Not applicable.	
Density	No data available.	
Relative density	1.11 - 1.15 [<i>Ref Std</i> :WATER=1]	
Relative Vapour Density	Not applicable.	
Particle Characteristics	Not applicable.	

9.2. Other information

9.2.2 Other safety characteristics
EU Volatile Organic Compounds
Evaporation rate
Molecular weight
Percent volatile

No data available. Not applicable. No data available. < 0.5 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

Condition

10.5 Incompatible materials

Amines. Strong acids. Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Vapours from heated material may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE $>1 - =5 \text{ mg/l}$
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
2,2'-[(1-Methylethylidene)bis[4,1-phenyleneoxy[1- (butoxymethyl)ethylene]oxymethylene]]bisoxirane	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
2,2'-[(1-Methylethylidene)bis[4,1-phenyleneoxy[1- (butoxymethyl)ethylene]oxymethylene]]bisoxirane	Ingestion	Rat	LD50 > 2,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	Dermal	Rabbit	LD50 4,250 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	Ingestion	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

3M Scotch-WeldTM EC-7256 B/A Part B

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
2,2'-[(1-Methylethylidene)bis[4,1-phenyleneoxy[1-	In vitro	Irritant
(butoxymethyl)ethylene]oxymethylene]]bisoxirane	data	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	Rabbit	No significant irritation
2,6-Di-tert-butyl-p-cresol	Human	Minimal irritation
	and	
	animal	

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
2,2'-[(1-Methylethylidene)bis[4,1-phenyleneoxy[1-	In vitro	No significant irritation
(butoxymethyl)ethylene]oxymethylene]]bisoxirane	data	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	Rabbit	No significant irritation
2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human and animal	Sensitising
2,2'-[(1-Methylethylidene)bis[4,1-phenyleneoxy[1- (butoxymethyl)ethylene]oxymethylene]]bisoxirane	Professio nal judgemen t	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	Guinea	Not classified
2,6-Di-tert-butyl-p-cresol	Human	Not classified

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,2'-[(1-Methylethylidene)bis[4,1-phenyleneoxy[1- (butoxymethyl)ethylene]oxymethylene]]bisoxirane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Some positive data exist, but the data are not sufficient for classification
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	In Vitro	Some positive data exist, but the data are not sufficient for classification

3M Scotch-Weld TM	EC-7256 B/A Part B
------------------------------	--------------------

Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	In vivo	Some positive data exist, but the data are not sufficient for classification
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic
Silane, triethoxy[3-(oxiranylmethoxy)propyl]-	Dermal	Mouse	Not carcinogenic
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2,2'-[(1- Methylethylidene)bis[4,1- phenyleneoxy[1- (butoxymethyl)ethylene]ox ymethylene]]bisoxirane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3- epoxypropoxy)propyl]trim ethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-Di-tert-butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks

Specific Target Organ Toxicity - repeated exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Туре	Exposure	Test endpoint	Test result

bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen	Activated sludge Rainbow trout Water flea Green algae	Analogous Compound Estimated Estimated	3 hours 96 hours	IC50	>100 mg/l 2 mg/l
y]]propane bis-[4-(2,3- epoxipropoxi)phen y]]propane bis-[4-(2,3- epoxipropoxi)phen y]]propane bis-[4-(2,3- epoxipropoxi)phen y]]propane bis-[4-(2,3- epoxipropoxi)phen y]]propane bis-[4-(2,3- poxipropoxi)phen y]]propane bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3-	Water flea	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3- 1675-54-3 epoxipropoxi)phen yl]propane bis-[4-(2,3- 1675-54-3	Water flea		96 hours	LC50	2 mg/l
epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(2,3- bis-[4-(3- bis-[4-(2,3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3- bis-[4-(3-(3-(3-(3-(3-(3-(3-(3-(3-(3-(3-(3-(3-					5
bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- l675-54-3		Estimated			
epoxipropoxi)phen yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- 1675-54-3		Estimated			
yl]propane bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- 1675-54-3	Green algae		48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane bis-[4-(2,3- 1675-54-3	Green algae				-
epoxipropoxi)phen yl]propane bis-[4-(2,3- 1675-54-3	Green algae				
yl]propane bis-[4-(2,3- 1675-54-3		Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- 1675-54-3					
epoxipropoxi)phen	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
yl]propane					
bis-[4-(2,3- 1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
epoxipropoxi)phen					
yl]propane			27/4	27/4	
2,2'-[(1-	N/A	Data not available	N/A	N/A	N/A
Methylethylidene)b		or insufficient for			
is[4,1- phenyleneoxy[1-		classification			
(butoxymethyl)ethy					
lene]oxymethylene					
]]bisoxirane					
Siloxanes and 67762-90-7	N/A	Data not available	N/A	N/A	N/A
Silicones, di-Me,	1 1 /A	or insufficient for	11/21	11/24	11/24
reaction products		classification			
with silica		classification			
[3-(2,3- 2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
epoxypropoxy)prop	common curp	Liperintental	<i>y</i> 0 110 415	2000	
yl]trimethoxysilane					
[3-(2,3- 2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
epoxypropoxy)prop	E E	1			6
yl]trimethoxysilane					
[3-(2,3- 2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
epoxypropoxy)prop					-
yl]trimethoxysilane					
[3-(2,3- 2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
epoxypropoxy)prop					
yl]trimethoxysilane					
[3-(2,3- 2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
epoxypropoxy)prop					
yl]trimethoxysilane					100 //
[3-(2,3- 2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
epoxypropoxy)prop					
yl]trimethoxysilane Silane, triethoxy[3- 2602-34-8	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
(oxiranylmethoxy)	Activated studge	Experimental	5 nours	NOEC	>=1,000 mg/1
propyl]-					
Silane, triethoxy[3- 2602-34-8	Green algae	Experimental	72 hours	EC50	>100 mg/l
(oxiranylmethoxy)	Green algae	Experimental	72 110013	LCSU	× 100 mg/1
propyl]-					
Silane, triethoxy[3- 2602-34-8	Water flea	Experimental	48 hours	EC50	>100 mg/l
(oxiranylmethoxy)	Water neu	Experimental	10 Hours	Leso	· ioo mg i
propyl]-					
Silane, triethoxy[3- 2602-34-8	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
(oxiranylmethoxy)		F			
propyl]-					
Silane, triethoxy[3- 2602-34-8	Green algae	Experimental	72 hours	NOEC	100 mg/l
(oxiranylmethoxy)					
propyl]-					
2,6-Di-tert-butyl-p- 128-37-0	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
cresol		-			
2,6-Di-tert-butyl-p- 128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
cresol					
2,6-Di-tert-butyl-p- 128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
cresol					

2,6-Di-tert-butyl-p- cresol	128-37-0	Zebra Fish	Experimental		No tox obs at lmt of water sol	>100 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Green algae	Experimental	72 hours	EC10	0.4 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
2,6-Di-tert-butyl-p- cresol	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
2,2'-[(1- Methylethylidene)b is[4,1- phenyleneoxy[1- (butoxymethyl)ethy lene]oxymethylene]]bisoxirane		Estimated Biodegradation	28 days	BOD	20 %BOD/ThOD	OECD 301F - Manometric respirometry
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane		Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Silane, triethoxy[3- (oxiranylmethoxy) propyl]-	2602-34-8	Experimental Biodegradation	28 days	BOD	53 %BOD/ThOD	OECD 301F - Manometric respirometry
Silane, triethoxy[3- (oxiranylmethoxy) propyl]-	2602-34-8	Experimental Hydrolysis		Hydrolytic half-life	36 hours (t 1/2)	
2,6-Di-tert-butyl-p- cresol	128-37-0	Data not availbl- insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
2,2'-[(1- Methylethylidene)b is[4,1- phenyleneoxy[1- (butoxymethyl)ethyl lene]oxymethylene]]bisoxirane		Estimated BCF - Other		Bioaccumulation factor	6.5	
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Experimental Bioconcentration		Log Kow	0.5	Episuite™
Silane, triethoxy[3- (oxiranylmethoxy)	2602-34-8	Estimated Bioconcentration		Bioaccumulation factor	2.5	

propyl]-						
2,6-Di-tert-butyl-p-	128-37-0	Experimental BCF	56 days	Bioaccumulation	1277	OECD305-Bioconcentration
cresol		- Fish		factor		

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)pheny l]propane		Modeled Mobility in Soil	Koc	450 l/kg	Episuite™
[3-(2,3- epoxypropoxy)prop yl]trimethoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite™
Silane, triethoxy[3- (oxiranylmethoxy)p ropyl]-	2602-34-8	Estimated Mobility in Soil	Koc	2,700 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09*Waste adhesives and sealants containing organic solvents or other dangerous substances20 01 27*Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
shipping name	HAZARDOUS	HAZARDOUS	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)

	1	1	
	N.O.S.(EPOXY RESIN)	N.O.S.(EPOXY RESIN)	
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity <u>Ingredient</u>	<u>CAS Nbr</u>	Classification	<u>Regulation</u>
2,6-Di-tert-butyl-p-cresol	128-37-0	Gr. 3: Not classifiable	International Agency for Research on Cancer
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements	
E2 Hazardous to the Aquatic environment	200	500	

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

GB Section 02: CLP Ingredient table information was modified.

GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was added.

GB Section 04: Information on toxicological effects information was modified.

Section 02: Label Elements: GB Percent Unknown information was added.

Section 3: Composition/ Information of ingredients table information was modified.

Section 8: Occupational exposure limit table information was modified.

OEL Reg Agency Desc information was modified.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Odor information was modified.

Section 09: Particle Characteristics N/A information was added.

- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 15: Seveso Hazard Category Text information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.