



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 08-0506-9
Issue Date: 11/13/25

Version Number: 20.00
Supersedes Date: 05/28/24

SECTION 1: Identification

1.1. Product identifier

3M™ Process Color 1805 Black

Product Identification Numbers

ID Number	UPC	ID Number	UPC
42-0016-6972-2		75-0300-4863-3	00-51138-64967-8
75-0300-4864-1	00-51138-64968-5		

7000129324

1.2. Recommended use and restrictions on use

Recommended use

Ink

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Commercial Branding and Transportation Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Liquid: Category 3.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 1.
Skin Sensitizer: Category 1.
Carcinogenicity: Category 2.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Corrosion | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

May cause respiratory irritation.

Precautionary statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating and lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid breathing vapors.

Wash exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves, eye protection, face protection, and if needed, respiratory protection (see SDS Section 8).

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Immediately call a POISON CENTER or doctor.

If skin irritation or rash occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

16% of the mixture consists of ingredients of unknown acute oral toxicity.

16% of the mixture consists of ingredients of unknown acute dermal toxicity.

16% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Cyclohexanone	108-94-1	15 - 40 Trade Secret *
Ethyl 3-ethoxypropionate	763-69-9	10 - 30
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Trade Secret*	10 - 30
Acrylic polymer	None	7 - 13
2-Butoxyethyl acetate	112-07-2	5 - 10 Trade Secret *
Carbon black	1333-86-4	3 - 7 Trade Secret *
Polymeric plasticizer	None	3 - 7
Synthetic crystalline-free silica gel	112926-00-8	1 - 5
Synthetic amorphous silica, fumed, crystalline free	112945-52-5	0.5 - 1.5
2,4-Dihydroxybenzophenone	131-56-6	< 1.0
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1 - 1 Trade Secret *
Heavy aromatic solvent naphtha (petroleum)	64742-94-5	0.1 - 1 Trade Secret *
Methyl Methacrylate	80-62-6	< 0.2
Toluene	108-88-3	< 0.2
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	< 0.06
Naphthalene	91-20-3	< 0.02

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide

Carbon dioxide

Hydrogen Chloride

Condition

During Combustion

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin.,Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
Cyclohexanone	108-94-1	ACGIH	TWA:20 ppm;STEL:50 ppm	A3: Confirmed animal carcin.,Danger of cutaneous absorption
Cyclohexanone	108-94-1	OSHA	TWA:200 mg/m3(50 ppm)	
2-Butoxyethyl acetate	112-07-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
Silica: Amorphous, including natural diatomaceous earth	112926-00-8	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Silica: Amorphous, including natural diatomaceous earth	112945-52-5	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Carbon black	1333-86-4	OSHA	TWA:3.5 mg/m3	
Methyl Methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	A4: Not class. as human carcin.,Dermal Sensitizer
Methyl Methacrylate	80-62-6	OSHA	TWA:410 mg/m3(100 ppm)	
Naphthalene	91-20-3	ACGIH	TWA:10 ppm	A3: Confirmed animal carcin.,Danger of cutaneous absorption
Naphthalene	91-20-3	OSHA	TWA:50 mg/m3(10 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Black
Odor	Moderate Solvent
Odor threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point/Initial boiling point/Boiling range	≥156.1 °C
Flash Point	45 °C [Test Method: Closed Cup]
Evaporation rate	≤0.23 [Ref Std: BUOAC=1]
Flammability	Flammable Liquid: Category 3.
Flammable Limits(LEL)	0.5 % volume
Flammable Limits(UEL)	8.7 %

Vapor Pressure	<=453.3 Pa [@ 20 °C]
Relative Vapor Density	>=3.4 [Ref Std: AIR=1]
Density	1 g/ml
Relative Density	1 [Ref Std: WATER=1]
Water solubility	Moderate
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Kinematic Viscosity	5,000 mm ² /sec
Volatile Organic Compounds	550 - 750 g/l [Details: as packaged]
Percent volatile	60 - 70 % volume
VOC Less H ₂ O & Exempt Solvents	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

Alkali and alkaline earth metals

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Naphthalene	91-20-3	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Naphthalene	91-20-3	Anticipated human carcinogen	National Toxicology Program Carcinogens

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Cyclohexanone	Dermal	Rabbit	LD50 >794, <3160 mg/kg
Cyclohexanone	Inhalation-Vapor (4 hours)	Rat	LC50 > 6.2 mg/l
Cyclohexanone	Ingestion	Rat	LD50 1,296 mg/kg

Ethyl 3-ethoxypropionate	Dermal	Rabbit	LD50 4,080 mg/kg
Ethyl 3-ethoxypropionate	Inhalation-Vapor (4 hours)	Rat	LC50 > 14.4 mg/l
Ethyl 3-ethoxypropionate	Ingestion	Rat	LD50 3,200 mg/kg
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Dermal	Rabbit	LD50 > 8,000 mg/kg
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Ingestion	Rat	LD50 > 8,000 mg/kg
2-Butoxyethyl acetate	Dermal	Rabbit	LD50 > 4,766 mg/kg
2-Butoxyethyl acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 2.66 mg/l
2-Butoxyethyl acetate	Ingestion	Rat	LD50 1,880 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
Synthetic crystalline-free silica gel	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic crystalline-free silica gel	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic crystalline-free silica gel	Ingestion	Rat	LD50 > 5,110 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Rat	LD50 > 5,110 mg/kg
2,4-Dihydroxybenzophenone	Dermal		LD50 estimated to be > 5,000 mg/kg
2,4-Dihydroxybenzophenone	Ingestion	Rat	LD50 8,600 mg/kg
Heavy aromatic solvent naphtha (petroleum)	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Heavy aromatic solvent naphtha (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Heavy aromatic solvent naphtha (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Dermal	Professional judgment	LD50 estimated to be 2,000 - 5,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	Rat	LD50 3,125 mg/kg
Methyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl Methacrylate	Inhalation-Vapor (4 hours)	Rat	LC50 29.8 mg/l
Methyl Methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Dermal	Professional judgment	LD50 estimated to be 2,000 - 5,000 mg/kg
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Rat	LD50 3,125 mg/kg
Naphthalene	Dermal	Human	LD50 estimated to be 2,000 - 5,000 mg/kg
Naphthalene	Inhalation-Vapor	Human	LC50 estimated to be 20 - 50 mg/l
Naphthalene	Ingestion	Human	LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Cyclohexanone	Rabbit	Irritant
Ethyl 3-ethoxypropionate	Rabbit	No significant irritation
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Professional	No significant irritation

	judgement	
2-Butoxyethyl acetate	Rabbit	Minimal irritation
Carbon black	Rabbit	No significant irritation
Synthetic crystalline-free silica gel	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
2,4-Dihydroxybenzophenone	Rabbit	No significant irritation
Heavy aromatic solvent naphtha (petroleum)	Rabbit	Minimal irritation
Toluene	Rabbit	Irritant
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Rabbit	Minimal irritation
Methyl Methacrylate	Rabbit	Irritant
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	Minimal irritation
Naphthalene	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Cyclohexanone	In vitro data	Corrosive
Ethyl 3-ethoxypropionate	Rabbit	Mild irritant
Vinyl polymer (New Jersey Trade Secret Registry # 04499600-5238P)	Professional judgement	No significant irritation
2-Butoxyethyl acetate	Rabbit	Mild irritant
Carbon black	Rabbit	No significant irritation
Synthetic crystalline-free silica gel	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline free	Rabbit	No significant irritation
2,4-Dihydroxybenzophenone	Rabbit	Severe irritant
Heavy aromatic solvent naphtha (petroleum)	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Rabbit	Mild irritant
Methyl Methacrylate	Rabbit	Mild irritant
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	Mild irritant
Naphthalene	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Cyclohexanone	Guinea pig	Not classified
Ethyl 3-ethoxypropionate	Guinea pig	Not classified
2-Butoxyethyl acetate	Guinea pig	Not classified
Synthetic crystalline-free silica gel	Human and animal	Not classified
Synthetic amorphous silica, fumed, crystalline free	Human and animal	Not classified
Heavy aromatic solvent naphtha (petroleum)	Guinea pig	Not classified
Toluene	Guinea pig	Not classified
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Guinea pig	Sensitizing
Methyl Methacrylate	Human and animal	Sensitizing
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Guinea pig	Sensitizing

Respiratory Sensitization

Name	Species	Value
------	---------	-------

Methyl Methacrylate	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Cyclohexanone	In Vitro	Not mutagenic
Cyclohexanone	In vivo	Not mutagenic
Ethyl 3-ethoxypropionate	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
Synthetic crystalline-free silica gel	In Vitro	Not mutagenic
Synthetic amorphous silica, fumed, crystalline free	In Vitro	Not mutagenic
Heavy aromatic solvent naphtha (petroleum)	In Vitro	Not mutagenic
Heavy aromatic solvent naphtha (petroleum)	In vivo	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	In vivo	Not mutagenic
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Methacrylate	In vivo	Not mutagenic
Methyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	In vivo	Not mutagenic
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Cyclohexanone	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic
Synthetic crystalline-free silica gel	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline free	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Heavy aromatic solvent naphtha (petroleum)	Not Specified	Not applicable	Carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Methyl Methacrylate	Ingestion	Rat	Not carcinogenic
Methyl Methacrylate	Inhalation	Human and animal	Not carcinogenic
Naphthalene	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Cyclohexanone	Inhalation	Not classified for female reproduction	Rat	NOAEL 4 mg/l	2 generation

Cyclohexanone	Ingestion	Not classified for development	Rabbit	NOAEL 500 mg/kg/day	during gestation
Cyclohexanone	Inhalation	Not classified for male reproduction	Rat	NOAEL 2 mg/l	2 generation
Cyclohexanone	Inhalation	Not classified for development	Rat	NOAEL 2.6 mg/l	during gestation
Synthetic crystalline-free silica gel	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic crystalline-free silica gel	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic crystalline-free silica gel	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Heavy aromatic solvent naphtha (petroleum)	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Heavy aromatic solvent naphtha (petroleum)	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Heavy aromatic solvent naphtha (petroleum)	Not Specified	Not classified for development	Rat	NOAEL Not available	2 generation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	Not classified for development	Rat	NOAEL 209 mg/kg/day	premating into lactation
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 804 mg/kg/day	premating into lactation
Methyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Methyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Methyl Methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 450 mg/kg/day	during gestation
Methyl Methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Not classified for development	Rat	NOAEL 209 mg/kg/day	premating into lactation
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 804 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Cyclohexanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Guinea pig	LOAEL 16.1 mg/l	6 hours
Cyclohexanone	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	
Cyclohexanone	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	

		system depression	dizziness	nal judgement	available	
2-Butoxyethyl acetate	Dermal	blood	Not classified	similar compounds	NOAEL Not available	
2-Butoxyethyl acetate	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	similar compounds	NOAEL Not available	
2-Butoxyethyl acetate	Inhalation	blood	Not classified	similar compounds	NOAEL Not available	
2-Butoxyethyl acetate	Ingestion	blood	Not classified	similar compounds	NOAEL Not available	
Heavy aromatic solvent naphtha (petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Methyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Naphthalene	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Cyclohexanone	Inhalation	liver	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	heart	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	skin	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	endocrine system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	immune system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	muscles	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	nervous system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	eyes	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	respiratory system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Inhalation	vascular system	Not classified	Rat	NOAEL 2.5 mg/l	13 weeks
Cyclohexanone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 407 mg/kg/day	3 months
Cyclohexanone	Ingestion	eyes	Not classified	Rat	NOAEL 407	3 months

					mg/kg/day	
Cyclohexanone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 407 mg/kg/day	3 months
Ethyl 3-ethoxypropionate	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	90 days
Ethyl 3-ethoxypropionate	Inhalation	nervous system	Not classified	Rat	NOAEL 6 mg/l	17 days
Ethyl 3-ethoxypropionate	Inhalation	heart	Not classified	Rat	NOAEL 6 mg/l	17 days
Ethyl 3-ethoxypropionate	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	17 days
Ethyl 3-ethoxypropionate	Inhalation	immune system	Not classified	Rat	NOAEL 6 mg/l	17 days
Ethyl 3-ethoxypropionate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 6 mg/l	17 days
Ethyl 3-ethoxypropionate	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	17 days
Ethyl 3-ethoxypropionate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethyl 3-ethoxypropionate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	17 days
Ethyl 3-ethoxypropionate	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	17 days
2-Butoxyethyl acetate	Dermal	blood	Not classified	similar compounds	NOAEL Not available	not available
2-Butoxyethyl acetate	Inhalation	blood	Not classified	similar compounds	NOAEL Not available	6 months
2-Butoxyethyl acetate	Ingestion	blood	Not classified	similar compounds	NOAEL Not available	13 weeks
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic crystalline-free silica gel	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic crystalline-free silica gel	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic amorphous silica, fumed, crystalline free	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Synthetic amorphous silica, fumed, crystalline free	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	auditory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	liver	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks

Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	28 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	liver	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	immune system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	heart	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	nervous system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl Methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
Methyl Methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl Methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure

Methyl Methacrylate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	heart	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	skin	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	endocrine system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	liver	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	muscles	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	nervous system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	respiratory system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	28 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	liver	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	immune system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	heart	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	nervous system	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
Naphthalene	Dermal	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Dermal	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Naphthalene	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.01 mg/l	13 weeks
Naphthalene	Inhalation	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Inhalation	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Naphthalene	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 500 mg/kg/day	15 days

Aspiration Hazard

Name	Value
Heavy aromatic solvent naphtha (petroleum)	Aspiration hazard

Toluene

Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Carcinogenicity

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**Ingredient**

2-Butoxyethyl acetate

C.A.S. No

112-07-2

% by Wt

Trade Secret 5 - 10

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**SECTION 16: Other information****NFPA Hazard Classification****Health: 3 Flammability: 2 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 08-0506-9**Version Number:** 20.00**Issue Date:** 11/13/25**Supersedes Date:** 05/28/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com