



Safety Data Sheet

Copyright, 2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-8618-0	Version number:	17.01
Revision date:	30/03/2026	Supersedes date:	04/12/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

Product Identification Numbers

62-1926-2640-6

7000028565

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone: +353 1 280 3555
E Mail: ner-productstewardship@mmm.com
Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
 Skin Sensitization, Category 1 - Skin Sens. 1; H317
 Carcinogenicity, Category 2 - Carc. 2; H351
 Reproductive Toxicity, Category 2 - Repr. 2; H361d
 Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
butanone	78-93-3	201-159-0	15 - 40
toluene	108-88-3	203-625-9	<= 5.5
antimony trioxide	1309-64-4	215-175-0	1 - 5
Quartz	14808-60-7	238-878-4	< 5
octhilinone (ISO)	26530-20-1	247-761-7	< 0.1
formaldehyde	50-00-0	200-001-8	< 0.02

HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260A	Do not breathe vapours.
P273	Avoid release to the environment.
P280K	Wear protective gloves and respiratory protection.

Response:

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313

If skin irritation or rash occurs: Get medical advice/attention.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066

Repeated exposure may cause skin dryness or cracking.

1% of the mixture consists of components of unknown acute oral toxicity.

Contains 2% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butanone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (REACH-No.) 01-2119457290-43	15 - 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Limestone	(CAS-No.) 1317-65-3 (EC-No.) 215-279-6	10 - 30	Substance with a national occupational exposure limit
Mica-group minerals	(CAS-No.) 12001-26-2	10 - 30	Substance with a national occupational exposure limit
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01-2119489379-17	7 - 13	Substance with a national occupational exposure limit
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9	<= 5.5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 3, H412
Acrylonitrile - butadiene polymer	(CAS-No.) 9003-18-	1 - 5	Substance not classified as hazardous

	3		
antimony trioxide	(CAS-No.) 1309-64-4 (EC-No.) 215-175-0	1 - 5	Carc. 2, H351 STOT RE 2, H373 Aquatic Chronic 3, H412
Feldspar-group minerals	(CAS-No.) 68476-25-5 (EC-No.) 270-666-7	< 5	Substance not classified as hazardous
Ammonia - o-cresol - formaldehyde - phenol polymer	(CAS-No.) 55185-45-0	1 - 5	Substance not classified as hazardous
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	(CAS-No.) 25085-50-1	1 - 5	Substance not classified as hazardous
Kaolin	(CAS-No.) 1332-58-7 (EC-No.) 310-194-1	< 5	Substance with a national occupational exposure limit
Quartz	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	< 5	STOT RE 1, H372
Alkanes, C20-28, chloro	(CAS-No.) 2097144-43-7	1 - 5	Substance not classified as hazardous
salicylic acid	(CAS-No.) 69-72-7 (EC-No.) 200-712-3	0.5 - 1.5	Acute Tox. 4, H302 Eye Dam. 1, H318 Repr. 2, H361d
propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (REACH-No.) 01-2119457558-25,01-2119457558-25-0208	0.5 - 1.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
heptane	(CAS-No.) 142-82-5 (EC-No.) 205-563-8	< 1.2	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1 Nota C
n-hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6	< 1	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 1, H372 Aquatic Chronic 2, H411
cyclohexane	(CAS-No.) 110-82-7 (EC-No.) 203-806-2	< 1	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336

			Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
zinc oxide	(CAS-No.) 1314-13-2 (EC-No.) 215-222-5 (REACH-No.) 01-2119463881-32	0.1 - 0.5	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
octhiline (ISO)	(CAS-No.) 26530-20-1 (EC-No.) 247-761-7	< 0.1	Acute Tox. 2, H330(LC50 = 0.27 mg/l ATE values per Annex VI) EUH071 Acute Tox. 3, H311(LD50 = 311 mg/kg ATE values per Annex VI) Acute Tox. 3, H301(LD50 = 125 mg/kg ATE values per Annex VI) Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400,M=100 Aquatic Chronic 1, H410,M=100
formaldehyde	(CAS-No.) 50-00-0 (EC-No.) 200-001-8	< 0.02	Acute Tox. 2, H330 EUH071 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Muta. 2, H341 Carc. 1B, H350 Nota B,D,F

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
octhiline (ISO)	(CAS-No.) 26530-20-1 (EC-No.) 247-761-7	(C >= 0.0015%) Skin Sens. 1A, H317
formaldehyde	(CAS-No.) 50-00-0 (EC-No.) 200-001-8	(C >= 25%)EUH071 (C >= 25%) Skin Corr. 1B, H314 (5% <= C < 25%) Skin Irrit. 2, H315 (C >= 25%) Eye Dam. 1, H318 (5% <= C < 25%) Eye Irrit. 2, H319 (5% <= C < 25%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include: Allergic skin reaction (redness, swelling, blistering, and itching). Dermal defatting (localized redness, itching, drying and cracking of skin). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons.
Carbon monoxide
Carbon dioxide.
Hydrogen Chloride
Oxides of antimony.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through

the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	Ireland OELs	TWA(8 hours):192 mg/m3(50 ppm);TWA(8 hours):50 ppm(192 mg/m3);STEL(15 minutes):384 mg/m3(100 ppm);STEL(15 minutes):100 ppm(384 mg/m3)	SKIN

n-hexane	110-54-3	Ireland OELs	TWA(8 hours):72 mg/m3(20 ppm);TWA(8 hours):20 ppm(72 mg/m3)	SKIN
cyclohexane	110-82-7	Ireland OELs	TWA(8 hours):700 mg/m3(200 ppm);TWA(8 hours):200 ppm(700 mg/m3)	
Mica-group minerals	12001-26-2	Ireland OELs	TWA(respirable fraction)(8 hours):3 mg/m3	
zinc oxide	1314-13-2	Ireland OELs	TWA(Respirable fraction & fume)(8 hours):2 mg/m3;STEL(Respirable fraction & fume)(15 minutes):10 mg/m3	
Limestone	1317-65-3	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m3;TWA(as respirable dust)(8 hours):4 mg/m3	
Kaolin	1332-58-7	Ireland OELs	TWA(as respirable dust)(8 hours):2 mg/m3	
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m3;TWA(as respirable dust)(8 hours):4 mg/m3	
heptane	142-82-5	Ireland OELs	TWA(8 hours):2085 mg/m3(500 ppm);TWA(8 hours):500 ppm(2085 mg/m3)	
Silica, crystalline, respirable dust (Cristobalite, Quartz, Tridymite, Tripoli)	14808-60-7	Ireland OELs	TWA(as respirable dust)(8 hours):0.1 mg/m3	
formaldehyde	50-00-0	Ireland OELs	TWA(8 hours):0.5 ppm(0.62 mg/m3);TWA(8 hours):0.37 mg/m3(0.3 ppm);STEL(15 minutes):0.6 ppm(0.738 mg/m3);STEL(15 minutes):0.738 mg/m3(0.6 ppm)	Respiratory/Dermal Sensitizer
propan-2-ol	67-63-0	Ireland OELs	TWA(8 hours):200 ppm;STEL(15 minutes):400 ppm	SKIN
butanone	78-93-3	Ireland OELs	TWA(8 hours):600 mg/m3(200 ppm);TWA(8 hours):200 ppm(600 mg/m3);STEL(15 minutes):900 mg/m3(300 ppm);STEL(15 minutes):300 ppm(900 mg/m3)	SKIN

Ireland OELs : Ireland. OELs
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation on open containers. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Safety glasses with side shields.
- Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 16321

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odor	Moderate Solvent

Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	>=80 °C [<i>Details:MEK</i>]
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	1.8 % volume
Flammable Limits(UEL)	12 % volume
Flash point	-6.7 °C [<i>Test Method:Closed Cup</i>]
Autoignition temperature	404 °C
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	166,667 mm ² /sec
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<=91 mm Hg [<i>@ 77 °F</i>]
Density	1.5 g/ml
Relative density	1.5 [<i>Ref Std:WATER=1</i>]
Relative Vapour Density	2.41 [<i>Ref Std:AIR=1</i>]
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate

2.7 [*Ref Std:ETHER=1*]

Molecular weight

No data available.

Percent volatile

<=36 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Ocular effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Dermal effects: Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
butanone	Dermal	Rabbit	LD50 > 8,050 mg/kg
butanone	Inhalation-Vapour (4 hours)	Rat	LC50 34.5 mg/l
butanone	Ingestion	Rat	LD50 2,737 mg/kg
Mica-group minerals	Dermal		LD50 estimated to be > 5,000 mg/kg
Mica-group minerals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg
Acrylonitrile - butadiene polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile - butadiene polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
antimony trioxide	Dermal	Rabbit	LD50 > 6,685 mg/kg
antimony trioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.76 mg/l
antimony trioxide	Ingestion	Rat	LD50 > 34,600 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
Feldspar-group minerals	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Feldspar-group minerals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Ammonia - o-cresol - formaldehyde - phenol polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Ammonia - o-cresol - formaldehyde - phenol polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Dermal		LD50 estimated to be > 5,000 mg/kg
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Ingestion	Rat	LD50 5,660 mg/kg
propan-2-ol	Dermal	Rabbit	LD50 12,870 mg/kg
propan-2-ol	Inhalation-Vapour (4 hours)	Rat	LC50 72.6 mg/l
propan-2-ol	Ingestion	Rat	LD50 4,710 mg/kg
heptane	Dermal	similar compound s	LD50 > 2,000 mg/kg
heptane	Inhalation-Vapour (4 hours)	similar compound s	LC50 > 33.5 mg/l
heptane	Ingestion	similar compound s	LD50 > 5,000 mg/kg

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

		ds	
n-hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
n-hexane	Inhalation-Vapour (4 hours)	Rat	LC50 170 mg/l
n-hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
cyclohexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 32.9 mg/l
cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
salicylic acid	Dermal	Rat	LD50 > 2,000 mg/kg
salicylic acid	Ingestion	Rat	LD50 891 mg/kg
zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
octhilinone (ISO)	Dermal	Rabbit	LD50 311 mg/kg
octhilinone (ISO)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.27 mg/l
octhilinone (ISO)	Ingestion	Rat	LD50 125 mg/kg
formaldehyde	Dermal	Rabbit	LD50 270 mg/kg
formaldehyde	Inhalation-Gas (4 hours)	Rat	LC50 470 ppm
formaldehyde	Ingestion	Rat	LD50 800 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
butanone	Rabbit	Minimal irritation
Limestone	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
toluene	Rabbit	Irritant
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
antimony trioxide	Human and animal	Minimal irritation
Quartz	Professional judgement	No significant irritation
Feldspar-group minerals	Professional judgement	No significant irritation
Kaolin	Professional judgement	No significant irritation
propan-2-ol	Multiple animal species	No significant irritation
heptane	Professional judgement	Mild irritant
n-hexane	Human and	Mild irritant

	animal	
cyclohexane	Rabbit	Mild irritant
salicylic acid	Rabbit	No significant irritation
zinc oxide	Human and animal	No significant irritation
oethylinone (ISO)	Rabbit	Corrosive
formaldehyde	official classification	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
butanone	Rabbit	Severe irritant
Limestone	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
toluene	Rabbit	Moderate irritant
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
antimony trioxide	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
propan-2-ol	Rabbit	Severe irritant
heptane	similar compounds	Mild irritant
n-hexane	Rabbit	Mild irritant
cyclohexane	Rabbit	Mild irritant
salicylic acid	Rabbit	Corrosive
zinc oxide	Rabbit	Mild irritant
oethylinone (ISO)	similar health hazards	Corrosive
formaldehyde	official classification	Corrosive

Skin Sensitisation

Name	Species	Value
Titanium dioxide	Human and animal	Not classified
toluene	Guinea pig	Not classified
antimony trioxide	Human	Not classified
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	Human	Some positive data exist, but the data are not sufficient for classification
propan-2-ol	Guinea pig	Not classified
heptane	similar compounds	Not classified
n-hexane	Human	Not classified
salicylic acid	Mouse	Not classified
zinc oxide	Guinea pig	Not classified
oethylinone (ISO)	Human and animal	Sensitising

formaldehyde	Guinea pig	Sensitising
--------------	------------	-------------

Photosensitisation

Name	Species	Value
salicylic acid	Mouse	Not sensitising

Respiratory Sensitisation

Name	Species	Value
formaldehyde	Human	Some positive data exist, but the data are not sufficient for classification

Germ Cell Mutagenicity

Name	Route	Value
butanone	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic
antimony trioxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
antimony trioxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
propan-2-ol	In Vitro	Not mutagenic
propan-2-ol	In vivo	Not mutagenic
heptane	In Vitro	Not mutagenic
n-hexane	In Vitro	Not mutagenic
n-hexane	In vivo	Not mutagenic
cyclohexane	In Vitro	Not mutagenic
cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
salicylic acid	In Vitro	Not mutagenic
salicylic acid	In vivo	Not mutagenic
zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
octhlinone (ISO)	In Vitro	Not mutagenic
octhlinone (ISO)	In vivo	Not mutagenic
formaldehyde	In Vitro	Some positive data exist, but the data are not sufficient for classification
formaldehyde	In vivo	Mutagenic

Carcinogenicity

Name	Route	Species	Value
butanone	Inhalation	Human	Not carcinogenic
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

antimony trioxide	Inhalation	Multiple animal species	Carcinogenic.
Quartz	Inhalation	Human and animal	Carcinogenic.
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
propan-2-ol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
n-hexane	Dermal	Mouse	Not carcinogenic
n-hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
formaldehyde	Not specified.	Human and animal	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
butanone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
antimony trioxide	Inhalation	Not classified for female reproduction	Rat	LOAEL 0.25 mg/l	prematuring & during gestation
propan-2-ol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
propan-2-ol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
propan-2-ol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
propan-2-ol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
n-hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
n-hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
n-hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
n-hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
salicylic acid	Ingestion	Toxic to development	Rat	NOAEL 75 mg/kg/day	during organogenesis

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	prematuring & during gestation
ochthilone (ISO)	Ingestion	Not classified for development	Rabbit	NOEL 20 mg/kg/day	during organogenesis
formaldehyde	Ingestion	Not classified for male reproduction	Rat	NOAEL 100 mg/kg	not applicable
formaldehyde	Inhalation	Not classified for development	Rat	NOAEL 10 ppm	during gestation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
butanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
butanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
butanone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
butanone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
antimony trioxide	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
propan-2-ol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propan-2-ol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
propan-2-ol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
propan-2-ol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
n-hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
n-hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
n-hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours

cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
oethilnone (ISO)	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL Not available	
formaldehyde	Inhalation	respiratory system	Causes damage to organs	Rat	LOAEL 128 ppm	6 hours
formaldehyde	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
butanone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
butanone	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
butanone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
butanone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
Mica-group minerals	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the	Rat	NOAEL 625	13 weeks

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

			data are not sufficient for classification		mg/kg/day	
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
antimony trioxide	Dermal	skin	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
antimony trioxide	Inhalation	pulmonary fibrosis	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.002 mg/l	1 years
antimony trioxide	Inhalation	liver	Not classified	Rat	NOAEL 0.043 mg/l	1 years
antimony trioxide	Inhalation	blood	Not classified	Rat	NOAEL 0.004 mg/l	not available
antimony trioxide	Inhalation	pneumoconiosis	Not classified	Human	LOAEL 0.01 mg/l	occupational exposure
antimony trioxide	Inhalation	heart	Not classified	Rat	NOAEL 0.02 mg/l	1 years
antimony trioxide	Ingestion	blood liver	Not classified	Rat	NOAEL 418 mg/kg/day	not available
antimony trioxide	Ingestion	heart	Not classified	Rat	NOAEL Not available	not available
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
propan-2-ol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
propan-2-ol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
propan-2-ol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
heptane	Inhalation	nervous system	Not classified	Rat	NOAEL 6.15 mg/l	30 weeks
heptane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 12.5 mg/l	16 weeks
heptane	Inhalation	hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
n-hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
n-hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
n-hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
n-hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
n-hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
n-hexane	Inhalation	auditory system immune system eyes	Not classified	Human	NOAEL Not available	occupational exposure
n-hexane	Inhalation	heart skin endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
n-hexane	Ingestion	peripheral nervous	Some positive data exist, but the	Rat	NOAEL	90 days

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

		system	data are not sufficient for classification		1,140 mg/kg/day	
n-hexane	Ingestion	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
salicylic acid	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	3 days
zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
zinc oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
formaldehyde	Dermal	respiratory system	Not classified	Mouse	NOAEL 80 mg/kg/day	60 weeks
formaldehyde	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 ppm	28 months
formaldehyde	Inhalation	liver	Not classified	Rat	NOAEL 20 ppm	13 weeks
formaldehyde	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 15 ppm	3 weeks
formaldehyde	Inhalation	nervous system	Not classified	Mouse	NOAEL 10 ppm	13 weeks
formaldehyde	Inhalation	endocrine system immune system muscles kidney and/or bladder	Not classified	Rat	NOAEL 15 ppm	28 months
formaldehyde	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 15 ppm	2 years
formaldehyde	Inhalation	eyes vascular system	Not classified	Rat	NOAEL 14.3 ppm	2 years
formaldehyde	Inhalation	heart	Not classified	Mouse	NOAEL 14.3 ppm	2 years
formaldehyde	Ingestion	liver	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
formaldehyde	Ingestion	immune system	Not classified	Rat	NOAEL 20 mg/kg/day	4 weeks
formaldehyde	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 15 mg/kg/day	24 months
formaldehyde	Ingestion	nervous system	Not classified	Rat	NOAEL 109 mg/kg/day	2 years
formaldehyde	Ingestion	heart endocrine system hematopoietic system respiratory system vascular system	Not classified	Rat	NOAEL 300 mg/kg/day	2 years
formaldehyde	Ingestion	skin muscles eyes	Not classified	Rat	NOAEL 109 mg/kg/day	2 years

Aspiration Hazard

Name	Value
toluene	Aspiration hazard
heptane	Aspiration hazard

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

n-hexane	Aspiration hazard
cyclohexane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
butanone	78-93-3	Fathead minnow	Experimental	96 hours	LC50	2,993 mg/l
butanone	78-93-3	Green algae	Experimental	96 hours	ErC50	2,029 mg/l
butanone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
butanone	78-93-3	Green algae	Experimental	96 hours	ErC10	1,289 mg/l
butanone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
butanone	78-93-3	Bacteria	Experimental	16 hours	LOEC	1,150 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
Mica-group minerals	12001-26-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Acrylonitrile - butadiene polymer	9003-18-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Alkanes, C20-28, chloro	2097144-43-7	Rainbow trout	Estimated	96 hours	No tox obs at lmt of water sol	>100 mg/l
Alkanes, C20-28, chloro	2097144-43-7	Water flea	Estimated	24 hours	No tox obs at lmt of water sol	>100 mg/l
Alkanes, C20-28, chloro	2097144-43-7	Rainbow trout	Estimated	60 days	No tox obs at lmt of water sol	>100 mg/l
Alkanes, C20-28, chloro	2097144-43-7	Water flea	Estimated	21 days	No tox obs at lmt of water sol	>100 mg/l
Ammonia - o-cresol - formaldehyde - phenol polymer	55185-45-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
antimony trioxide	1309-64-4	Green algae	Endpoint not reached	72 hours	ErC50	>100 mg/l
antimony trioxide	1309-64-4	Fathead minnow	Estimated	96 hours	LC50	17.2 mg/l
antimony trioxide	1309-64-4	Fish	Estimated	96 hours	LC50	8.3 mg/l
antimony trioxide	1309-64-4	Invertebrate	Estimated	96 hours	EC50	2.12 mg/l
antimony trioxide	1309-64-4	Green algae	Estimated	72 hours	NOEC	2.53 mg/l
antimony trioxide	1309-64-4	Rainbow trout	Estimated	28 days	LC10	0.188 mg/l
antimony trioxide	1309-64-4	Water flea	Estimated	21 days	NOEC	2.08 mg/l
antimony trioxide	1309-64-4	Activated sludge	Estimated	4 hours	NOEC	6.1 mg/l
Feldspar-group minerals	68476-25-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Quartz	14808-60-7	Green algae	Estimated	72 hours	EC50	440 mg/l
Quartz	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l
Quartz	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

Quartz	14808-60-7	Green algae	Estimated	72 hours	NOEC	60 mg/l
propan-2-ol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
propan-2-ol	67-63-0	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
propan-2-ol	67-63-0	Invertebrate	Experimental	24 hours	LC50	>10,000 mg/l
propan-2-ol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
propan-2-ol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
propan-2-ol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
propan-2-ol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l
salicylic acid	69-72-7	Green algae	Experimental	72 hours	EC50	>100 mg/l
salicylic acid	69-72-7	Medaka	Experimental	96 hours	LC50	>100 mg/l
salicylic acid	69-72-7	Water flea	Experimental	48 hours	EC50	870 mg/l
salicylic acid	69-72-7	Water flea	Experimental	21 days	NOEC	10 mg/l
salicylic acid	69-72-7	Activated sludge	Experimental	3 hours	EC50	>3,200
salicylic acid	69-72-7	Bacteria	Experimental	18 hours	EC10	465
heptane	142-82-5	Water flea	Experimental	48 hours	EC50	1.5 mg/l
heptane	142-82-5	Water flea	Estimated	21 days	NOEC	0.17 mg/l
cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
n-hexane	110-54-3	Fathead minnow	Experimental	96 hours	LC50	2.5 mg/l
n-hexane	110-54-3	Water flea	Experimental	48 hours	LC50	3.9 mg/l
zinc oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	EC50	0.052 mg/l
zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	NOEC	0.006 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l
octhiline (ISO)	26530-20-1	Diatom	Experimental	72 hours	EC50	0.0015 mg/l
octhiline (ISO)	26530-20-1	Green algae	Experimental	72 hours	EC50	0.084 mg/l
octhiline (ISO)	26530-20-1	Mysid Shrimp	Experimental	96 hours	LC50	0.071 mg/l
octhiline (ISO)	26530-20-1	Rainbow trout	Experimental	96 hours	LC50	0.036 mg/l
octhiline (ISO)	26530-20-1	Sheepshead Minnow	Experimental	96 hours	LC50	0.18 mg/l
octhiline (ISO)	26530-20-1	Water flea	Experimental	48 hours	EC50	0.42 mg/l

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

octhilonone (ISO)	26530-20-1	Diatom	Experimental	72 hours	NOEC	0.00068 mg/l
octhilonone (ISO)	26530-20-1	Green algae	Experimental	72 hours	NOEC	0.0156 mg/l
octhilonone (ISO)	26530-20-1	Water flea	Experimental	21 days	NOEC	0.0016 mg/l
octhilonone (ISO)	26530-20-1	Activated sludge	Experimental	3 hours	EC50	30.4 mg/l
octhilonone (ISO)	26530-20-1	Bobwhite quail	Experimental	14 days	LD50	384 ppm diet
octhilonone (ISO)	26530-20-1	Lettuce	Experimental	17 days	EC50	45 mg/kg (Dry Weight)
octhilonone (ISO)	26530-20-1	Redworm	Experimental	14 days	LC50	866 mg/kg (Dry Weight)
octhilonone (ISO)	26530-20-1	Soil microbes	Experimental	28 days	EC50	84.1 mg/kg (Dry Weight)
formaldehyde	50-00-0	Green algae	Experimental	72 hours	ErC50	4.89 mg/l
formaldehyde	50-00-0	Striped bass	Experimental	96 hours	LC50	6.7 mg/l
formaldehyde	50-00-0	Water flea	Experimental	48 hours	EC50	5.8 mg/l
formaldehyde	50-00-0	Medaka	Experimental	28 days	NOEC	>=48 mg/l
formaldehyde	50-00-0	Water flea	Experimental	21 days	NOEC	>=6.4 mg/l
formaldehyde	50-00-0	Activated sludge	Experimental	3 hours	EC50	19

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
butanone	78-93-3	Experimental Biodegradation	28 days	BOD	98 %BOD/ThOD	OECD 301D - Closed bottle test
Limestone	1317-65-3	Data not available/insufficient	N/A	N/A	N/A	N/A
Mica-group minerals	12001-26-2	Data not available/insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available/insufficient	N/A	N/A	N/A	N/A
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Acrylonitrile - butadiene polymer	9003-18-3	Data not available/insufficient	N/A	N/A	N/A	N/A
Alkanes, C20-28, chloro	2097144-43-7	Estimated Biodegradation	25 days	BOD	7.5 %BOD/ThOD	
Ammonia - o-cresol - formaldehyde - phenol polymer	55185-45-0	Data not available/insufficient	N/A	N/A	N/A	N/A
antimony trioxide	1309-64-4	Data not available/insufficient	N/A	N/A	N/A	N/A
Feldspar-group minerals	68476-25-5	Data not available/insufficient	N/A	N/A	N/A	N/A
Kaolin	1332-58-7	Data not available/insufficient	N/A	N/A	N/A	N/A
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	
Quartz	14808-60-7	Data not available/insufficient	N/A	N/A	N/A	N/A
propan-2-ol	67-63-0	Experimental Biodegradation	14 days	BOD	86 %BOD/ThOD	OECD 301C - MITI test (I)
salicylic acid	69-72-7	Experimental Biodegradation	14 days	BOD	88.1 %BOD/ThOD	OECD 301C - MITI test (I)

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

heptane	142-82-5	Experimental Biodegradation	28 days	BOD	101 %BOD/ThOD	OECD 301C - MITI test (I)
heptane	142-82-5	Experimental Photolysis		Photolytic half-life (in air)	4.24 days (t 1/2)	
cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 %BOD/ThOD	OECD 301F - Manometric respirometry
cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.3 days (t 1/2)	
n-hexane	110-54-3	Experimental Bioconcentration	28 days	BOD	100 %BOD/ThOD	OECD 301C - MITI test (I)
n-hexane	110-54-3	Experimental Photolysis		Photolytic half-life (in air)	5.4 days (t 1/2)	
zinc oxide	1314-13-2	Data not available or insufficient	N/A	N/A	N/A	N/A
octhilonone (ISO)	26530-20-1	Experimental Biodegradation	28 days	BOD	< 10 %BOD/ThOD	OECD 301D - Closed bottle test
octhilonone (ISO)	26530-20-1	Experimental Aquatic Inherent Biodegrad.	59 days	Dissolv. Organic Carbon Deplet	88 %removal of DOC	OECD 303A - Simulated Aerobic
formaldehyde	50-00-0	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	99 %removal of DOC	OECD 301A - DOC Die Away Test
formaldehyde	50-00-0	Experimental Biodegradation	160 days	BOD	99.5 %BOD/COD	OECD 303A - Simulated Aerobic

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
butanone	78-93-3	Experimental Bioconcentration		Log Kow	0.3	OECD 117 log Kow HPLC method
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mica-group minerals	12001-26-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	
Acrylonitrile - butadiene polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Alkanes, C20-28, chloro	2097144-43-7	Estimated BCF - Fish	60 days	Bioaccumulation factor	37.6	
Alkanes, C20-28, chloro	2097144-43-7	Estimated Bioconcentration		Log Kow	≥7.63	
Ammonia - o-cresol - formaldehyde - phenol polymer	55185-45-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
antimony trioxide	1309-64-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Feldspar-group minerals	68476-25-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Formaldehyde, polymer with 4-(1,1-dimethylethyl) phenol	25085-50-1	Estimated Bioconcentration		Bioaccumulation factor	7.4	
Quartz	14808-60-7	Data not available or insufficient for	N/A	N/A	N/A	N/A

3M Scotch-Weld™ Tamper Proof Sealant EC-1252 White

		classification				
propan-2-ol	67-63-0	Experimental Bioconcentration		Log Kow	0.05	
salicylic acid	69-72-7	Experimental Bioconcentration		Log Kow	2.26	
heptane	142-82-5	Estimated Bioconcentration		Bioaccumulation factor	105	
cyclohexane	110-82-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	129	OECD305-Bioconcentration
cyclohexane	110-82-7	Experimental Bioconcentration		Log Kow	3.44	
n-hexane	110-54-3	Modeled Bioconcentration		Bioaccumulation factor	50	Catalogic™
zinc oxide	1314-13-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	≤217	OECD305-Bioconcentration
oathilone (ISO)	26530-20-1	Experimental Bioconcentration		Log Kow	2.92	OECD 117 log Kow HPLC method
formaldehyde	50-00-0	Experimental Bioconcentration		Log Kow	0.35	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
toluene	108-88-3	Experimental Mobility in Soil	Koc	37-160 l/kg	
salicylic acid	69-72-7	Modeled Mobility in Soil	Koc	<1 l/kg	Episuite™
cyclohexane	110-82-7	Modeled Mobility in Soil	Koc	970 l/kg	Episuite™
oathilone (ISO)	26530-20-1	Experimental Mobility in Soil	Koc	604-1297 l/kg	835.1110 Sludge Sorp Isotherm
formaldehyde	50-00-0	Estimated Mobility in Soil	Koc	15.9 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	UN1866	UN1866	UN1866
14.2 UN proper shipping name	RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	II	II	II
14.5 Environmental hazards	Environmentally Hazardous	Not applicable.	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	F1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity****Ingredient****CAS Nbr****Classification****Regulation**

antimony trioxide	1309-64-4	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
antimony trioxide	1309-64-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
formaldehyde	50-00-0	Carc. 1B	Regulation (EC) No. 1272/2008, Table 3.1
formaldehyde	50-00-0	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Quartz	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
cyclohexane	110-82-7
toluene	108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Authorization status under REACH:

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

<u>Ingredient</u>	<u>CAS Nbr</u>
n-hexane	110-54-3

Authorization status: listed in the Candidate List of Substances of Very High Concern for Authorization

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500
P5c FLAMMABLE LIQUIDS*	5000	50000

*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements

formaldehyde	50-00-0	5	50
--------------	---------	---	----

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

List of Relevant Notas

Nota B	Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.
Nota C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Nota D	Certain substances which are susceptible to spontaneous polymerisation or decomposition are

	generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words ‘non-stabilised’.
Nota F	This substance may contain a stabiliser. If the stabiliser changes the hazardous properties of the substance, as indicated by the classification in Part 3, classification and labelling should be provided in accordance with the rules for classification and labelling of hazardous mixtures.

Revision information:

- Section 14 - Not Hazardous for Transportation information was added.
- EU Section 14 - Table Data information was added.
- EU Section 14 - Table Headers information was added.
- CLP: Ingredient table information was modified.
- Label: Graphic information was modified.
- Section 3: Composition/ Information of ingredients table information was modified.
- Section 03: SCL table information was modified.
- Section 8: Occupational exposure limit table information was modified.
- Section 9: Vapour pressure value information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Carcinogenicity Table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Respiratory Sensitization Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs - Repeated Table information was modified.
- Section 11: Target Organs - Single Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Mobility in soil information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12: Biocumulative potential information information was modified.
- Section 14 Classification Code – Main Heading information was deleted.
- Section 14 Classification Code – Regulation Data information was deleted.
- Section 14 Control Temperature – Main Heading information was deleted.
- Section 14 Control Temperature – Regulation Data information was deleted.
- Section 14 Emergency Temperature – Main Heading information was deleted.
- Section 14 Emergency Temperature – Regulation Data information was deleted.
- Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.
- Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.
- Section 14 Other Dangerous Goods – Main Heading information was deleted.
- Section 14 Other Dangerous Goods – Regulation Data information was deleted.
- Section 14 Packing Group – Main Heading information was deleted.
- Section 14 Packing Group – Regulation Data information was deleted.
- Section 14 Proper Shipping Name information was deleted.
- Section 14 Regulations – Main Headings information was deleted.
- Section 14 Segregation – Regulation Data information was deleted.
- Section 14 Segregation Code – Main Heading information was deleted.
- Section 14 Special Precautions – Main Heading information was deleted.
- Section 14 Special Precautions – Regulation Data information was deleted.
- Section 14 Transport in bulk – Regulation Data information was deleted.
- Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was deleted.
- Section 14 UN Number Column data information was deleted.
- Section 14 UN Number information was deleted.
- Section 15: Authorization status under REACH: SVHC Authorization ingredient information information was added.
- Section 15: Carcinogenicity information information was modified.
- Section 15: Seveso Substance Text information was modified.

Section 16: Two-column table displaying the unique list of Notas for all components of the given material. information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com