



## Safety Data Sheet

Copyright, 2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	29-4187-0	<b>Version number:</b>	5.00
<b>Revision date:</b>	13/02/2026	<b>Supersedes date:</b>	28/11/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M Beige Multi-Purpose Seam Sealer PN 50740

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Sprayable sealant

#### 1.3. Details of the supplier of the safety data sheet

<b>Address:</b>	3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
<b>Telephone:</b>	+353 1 280 3555
<b>E Mail:</b>	ner-productstewardship@mmm.com
<b>Website:</b>	www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

##### CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

**CLP REGULATION (EC) No 1272/2008**

**SIGNAL WORD**

WARNING.

**Symbols**

GHS07 (Exclamation mark) |

**Pictograms**



**HAZARD STATEMENTS:**

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H412 Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**SUPPLEMENTAL INFORMATION:**

**Supplemental Hazard Statements:**

EUH208 Contains Trimethoxyvinylsilane. May produce an allergic reaction.

16% of the mixture consists of components of unknown acute oral toxicity.

Contains 16% of components with unknown hazards to the aquatic environment.

**2.3. Other hazards**

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Limestone	(CAS-No.) 1317-65-3 (EC-No.) 215-279-6	40 - 70	Substance with a national occupational exposure limit
Silylated prepolymer	Trade Secret	10 - 30	Substance not classified as hazardous
Diisodecyl phthalate	(CAS-No.) 26761-40-0	5 - 10	Substance with a national occupational

	(EC-No.) 247-977-1		exposure limit
Distillates (petroleum), hydro- treated light	(CAS-No.) 64742-47-8 (EC-No.) 265-149-8	5 - 10	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336
Calcium oxide	(CAS-No.) 1305-78-8 (EC-No.) 215-138-9	< 3	EUH071 Skin Corr. 1C, H314 Eye Dam. 1, H318
Trimethoxyvinylsilane	(CAS-No.) 2768-02-7 (EC-No.) 220-449-8	< 0.8	Skin Sens. 1B, H317 Flam. Liq. 3, H226 Acute Tox. 4, H332
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	(CAS-No.) 52829-07-9 (EC-No.) 258-207-9	< 0.3	Acute Tox. 3, H331 Eye Dam. 1, H318 Repr. 2, H361f Aquatic Acute 1, H400,M=1 Aquatic Chronic 2, H411

Please see section 16 for the full text of any H statements referred to in this section

**Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
Calcium oxide	(CAS-No.) 1305-78-8 (EC-No.) 215-138-9	(C >= 50%)EUH071 (C >= 50%) Skin Corr. 1C, H314 (10% =< C < 50%) Skin Irrit. 2, H315 (C >= 3%) Eye Dam. 1, H318 (1% =< C < 3%) Eye Irrit. 2, H319 (20% =< C < 50%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

The most important symptoms and effects based on the CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Serious irritation to the eyes (significant redness,

swelling, pain, tearing, and impaired vision).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide	During combustion.

#### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Calcium oxide	1305-78-8	Ireland OELs	TWA(respirable fraction)(8 hours):1 mg/m <sup>3</sup> ;TWA(respirable fraction)(8 hours):1 mg/m <sup>3</sup> ;STEL(respirable fraction)(15 minutes):4 mg/m <sup>3</sup> ;STEL(respirable fraction)(15 minutes):4 mg/m <sup>3</sup>	
Limestone	1317-65-3	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m <sup>3</sup> ;TWA(as respirable dust)(8 hours):4 mg/m <sup>3</sup>	
Diisodecyl phthalate	26761-40-0	Ireland OELs	TWA(8 hours):5 mg/m <sup>3</sup>	

Ireland OELs : Ireland. OELs  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**Recommended monitoring procedures:**Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

#### *Applicable Norms/Standards*

Use eye protection conforming to EN 16321

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Neoprene.	>0.30	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

#### *Applicable Norms/Standards*

Use gloves tested to EN 374

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### *Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter types A & P

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Beige
<b>Odor</b>	Light Odour
<b>Odour threshold</b>	<i>No data available.</i>
<b>Melting point/freezing point</b>	<i>No data available.</i>
<b>Boiling point/boiling range</b>	> 190 °C
<b>Flammability</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>

<b>Flash point</b>	> 70 °C
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	<i>No data available.</i>
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Density</b>	1.66 g/ml [ @ 20 °C ]
<b>Relative density</b>	1.66 [Ref Std: WATER=1]
<b>Relative Vapour Density</b>	<i>No data available.</i>
<b>Particle Characteristics</b>	<i>Not applicable.</i>

## 9.2. Other information

### 9.2.2 Other safety characteristics

<b>EU Volatile Organic Compounds</b>	<i>No data available.</i>
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Percent volatile</b>	8 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

### 10.5 Incompatible materials

Accelerators

Strong acids.

Strong bases.

Strong oxidising agents.

Reducing agents.

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Water

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

#### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Distillates (petroleum), hydro- treated light	Inhalation-Vapour	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Distillates (petroleum), hydro- treated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydro- treated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), hydro- treated light	Dermal	similar compounds	LD50 > 2,000 mg/kg
Diisodecyl phthalate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Diisodecyl phthalate	Inhalation-	Rat	LC50 > 12.5 mg/l

	Dust/Mist (4 hours)		
Diisodecyl phthalate	Ingestion	Rat	LD50 > 9,700 mg/kg
Calcium oxide	Ingestion	Rat	LD50 > 2,500 mg/kg
Calcium oxide	Dermal	similar compoun ds	LD50 > 2,500 mg/kg
Trimethoxyvinylsilane	Dermal	Rabbit	LD50 3,260 mg/kg
Trimethoxyvinylsilane	Inhalation- Vapour (4 hours)	Rat	LC50 16.8 mg/l
Trimethoxyvinylsilane	Ingestion	Rat	LD50 7,120 mg/kg
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Dermal	Rat	LD50 > 3,170 mg/kg
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.5 mg/l
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Ingestion	Rat	LD50 3,700 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Limestone	Rabbit	No significant irritation
Distillates (petroleum), hydro- treated light	Rabbit	Irritant
Diisodecyl phthalate	Rabbit	Minimal irritation
Calcium oxide	Human	Corrosive
Trimethoxyvinylsilane	Rabbit	Minimal irritation
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Rabbit	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Limestone	Rabbit	No significant irritation
Distillates (petroleum), hydro- treated light	Rabbit	Mild irritant
Diisodecyl phthalate	Rabbit	Mild irritant
Calcium oxide	Rabbit	Corrosive
Trimethoxyvinylsilane	Rabbit	No significant irritation
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Rabbit	Corrosive

### Skin Sensitisation

Name	Species	Value
Distillates (petroleum), hydro- treated light	Guinea pig	Not classified
Diisodecyl phthalate	Guinea pig	Not classified
Trimethoxyvinylsilane	Guinea pig	Some positive data exist, but the data are not sufficient for classification
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Guinea pig	Not classified

### Photosensitisation

Name	Species	Value
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Guinea pig	Not sensitising

### Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Distillates (petroleum), hydro- treated light	In Vitro	Not mutagenic
Diisodecyl phthalate	In Vitro	Not mutagenic
Diisodecyl phthalate	In vivo	Not mutagenic
Calcium oxide	In Vitro	Not mutagenic
Trimethoxyvinylsilane	In vivo	Not mutagenic
Trimethoxyvinylsilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Distillates (petroleum), hydro- treated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Diisodecyl phthalate	Ingestion	Not classified for female reproduction	Rat	NOAEL 927 mg/kg/day	2 generation
Diisodecyl phthalate	Ingestion	Not classified for male reproduction	Rat	NOAEL 929 mg/kg/day	2 generation
Diisodecyl phthalate	Ingestion	Toxic to development	Rat	NOAEL 38 mg/kg/day	2 generation
Trimethoxyvinylsilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Trimethoxyvinylsilane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Trimethoxyvinylsilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Trimethoxyvinylsilane	Inhalation	Not classified for development	Rat	NOAEL 1.8 mg/l	during organogenesis
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 430 mg/kg/day	2 generation
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Ingestion	Not classified for development	Rat	NOAEL 130 mg/kg/day	2 generation
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 130 mg/kg/day	2 generation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Distillates (petroleum), hydro- treated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydro- treated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydro- treated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Calcium oxide	Inhalation	respiratory irritation	May cause respiratory irritation	Not available	NOAEL Not available	occupational exposure
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Dermal	photoirritation	Not classified	Mouse	NOAEL not available	
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Diisodecyl phthalate	Inhalation	respiratory system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Diisodecyl phthalate	Ingestion	endocrine system	Not classified	Rat	NOAEL 686 mg/kg/day	90 days
Diisodecyl phthalate	Ingestion	liver   kidney and/or bladder   heart	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Diisodecyl phthalate	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 320 mg/kg/day	90 days
Trimethoxyvinylsilane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL mg/l	14 weeks
Trimethoxyvinylsilane	Inhalation	hematopoietic system   eyes	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
Trimethoxyvinylsilane	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	40 days
Trimethoxyvinylsilane	Ingestion	endocrine system   hematopoietic system   liver   immune system	Not classified	Rat	NOAEL 1,000 mg/kg/day	40 days
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Ingestion	heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 261 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
Distillates (petroleum), hydro- treated light	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**11.2. Information on other hazards**

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
Diisodecyl phthalate	26761-40-0	Green algae	Estimated	96 hours	EC50	>100 mg/l
Diisodecyl phthalate	26761-40-0	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Diisodecyl phthalate	26761-40-0	Water flea	Estimated	48 hours	EC50	>100 mg/l
Diisodecyl phthalate	26761-40-0	Green algae	Estimated	96 hours	NOEC	100 mg/l
Diisodecyl phthalate	26761-40-0	Water flea	Estimated	21 days	NOEC	100 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Green algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Rainbow trout	Estimated	96 hours	LL50	2 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Water flea	Estimated	48 hours	EL50	1.4 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Green algae	Estimated	72 hours	NOEL	1 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Water flea	Estimated	21 days	NOEL	0.48 mg/l
Calcium oxide	1305-78-8	Common Carp	Experimental	96 hours	LC50	1,070 mg/l
Trimethoxyvinylsilane	2768-02-7	Bacteria	Experimental	5 hours	EC10	1.1 mg/l
Trimethoxyvinylsilane	2768-02-7	Green algae	Experimental	72 hours	EC50	>957 mg/l
Trimethoxyvinylsilane	2768-02-7	Rainbow trout	Experimental	96 hours	LC50	191 mg/l
Trimethoxyvinylsilane	2768-02-7	Water flea	Experimental	48 hours	EC50	169 mg/l
Trimethoxyvinylsilane	2768-02-7	Green algae	Experimental	72 hours	NOEC	957 mg/l
Trimethoxyvinylsilane	2768-02-7	Water flea	Experimental	21 days	NOEC	28 mg/l
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Bluegill	Experimental	96 hours	LC50	4.4 mg/l
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Green algae	Experimental	72 hours	EC50	0.705 mg/l
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Water flea	Experimental	48 hours	EC50	8.58 mg/l
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Green algae	Experimental	72 hours	EC10	0.188 mg/l
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Water flea	Experimental	21 days	NOEC	0.23 mg/l
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Activated sludge	Experimental	3 hours	IC50	>100

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Limestone	1317-65-3	Data not available/insufficient	N/A	N/A	N/A	N/A
Diisodecyl phthalate	26761-40-0	Estimated Biodegradation	28 days	BOD	74 %BOD/ThOD	OECD 301F - Manometric respirometry
Distillates (petroleum), hydro- treated light	64742-47-8	Data not available/insufficient	N/A	N/A	N/A	N/A
Calcium oxide	1305-78-8	Data not available/insufficient	N/A	N/A	N/A	N/A
Trimethoxyvinylsilane	2768-02-7	Experimental Biodegradation	28 days	BOD	51 %BOD/ThOD	OECD 301F - Manometric respirometry
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Experimental Biodegradation	28 days	Percent degraded	24 %CO <sub>2</sub> evolution/THC O <sub>2</sub> evolution	OECD 301B - Modified Sturm or CO <sub>2</sub>
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	56.6 days (t <sub>1/2</sub> )	OECD 111 Hydrolysis function of pH

**12.3 : Bioaccumulative potential**

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diisodecyl phthalate	26761-40-0	Experimental BCF - Fish	56 days	Bioaccumulation factor	<14.4	OECD305-Bioconcentration
Distillates (petroleum), hydro- treated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Calcium oxide	1305-78-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Trimethoxyvinylsilane	2768-02-7	Estimated Bioconcentration		Log Kow	-2	
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Experimental Bioconcentration		Log Kow	0.35	OECD 107 log Kow shake flask mtd

**12.4. Mobility in soil**

Material	Cas No.	Test type	Study Type	Test result	Protocol
Trimethoxyvinylsilane	2768-02-7	Estimated Mobility in Soil	Koc	650 l/kg	Episuite™
bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	52829-07-9	Experimental Mobility in Soil	Koc	780-16000 l/kg	OECD 106 Adsp-Desb Batch Equil

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Endocrine disrupting properties**

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

**SECTION 14: Transportation information**

Not hazardous for transportation.

	<b>Ground Transport (ADR)</b>	<b>Air Transport (IATA)</b>	<b>Marine Transport (IMDG)</b>
<b>14.1 UN number or ID number</b>	No data available.	No data available.	No data available.
<b>14.2 UN proper shipping name</b>	No data available.	No data available.	No data available.
<b>14.3 Transport hazard class(es)</b>	No data available.	No data available.	No data available.
<b>14.4 Packing group</b>	No data available.	No data available.	No data available.
<b>14.5 Environmental hazards</b>	No data available.	No data available.	No data available.
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.

<b>ADR Classification Code</b>	No data available.	No data available.	No data available.
<b>IMDG Segregation Code</b>	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

#### Ingredient

Diisodecyl phthalate

#### CAS Nbr

26761-40-0

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

#### Global inventory status

Contact 3M for more information.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

#### Regulation (EU) No 649/2012

No chemicals listed

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

### List of relevant H statements

EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

Section 1: Address information was modified.

Section 1: E-mail address information was modified.

Section 1: Product identification numbers information was deleted.

Section 01: SAP Material Numbers information was deleted.

Section 3: Composition/ Information of ingredients table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Odor information was modified.

Section 09: Particle Characteristics N/A information was added.

Section 11: Acute Toxicity table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Photosensitisation Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M Ireland MSDSs are available at [www.3M.com](http://www.3M.com)**