Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	46-3716-1	**Version Number:**	1.01
Issue Date:	05/28/26	**Supersedes Date:**	03/30/26

Product identifier
3M™ Scotch-Weld™ Structural Plastic Adhesive DP8115NS, Off-White, 490mL Kit

ID Number(s):

62-2971-3630-1

7100416674

Recommended use
Adhesive

Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

46-3715-3, 46-3713-8

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	46-3713-8	**Version Number:**	1.03
Issue Date:	09/14/26	**Supersedes Date:**	09/08/26

SECTION 1: Identification

1.1. Product identifier
3M™ Scotch-Weld™ Structural Plastic Adhesive DP8115NS, Off-White, Part A

Product Identification Numbers
LA-D100-3914-9, LA-D100-3915-0

1.2. Recommended use and restrictions on use

Recommended use
Adhesive

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification
Acute Toxicity (oral): Category 4.
Acute Toxicity (dermal): Category 4.
Acute Toxicity (inhalation): Category 4.
Skin Corrosion/Irritation: Category 1B.
Serious Eye Damage/Irritation: Category 1.
Skin Sensitizer: Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Corrosion |Exclamation mark |

Pictograms



Hazard Statements

Harmful if swallowed, in contact with skin or if inhaled.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.

Precautionary statements

Prevention:
Do not breathe vapors.
Wash exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves, protective clothing, eye protection, and face protection.

Response:
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Immediately call a POISON CENTER or doctor.
If skin irritation or rash occurs: Get medical attention.
Take off contaminated clothing and wash it before reuse.

Storage:
Store locked up.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Hazards not otherwise classified
May cause chemical gastrointestinal burns.

Supplemental Information:
Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

38% of the mixture consists of ingredients of unknown acute oral toxicity.
38% of the mixture consists of ingredients of unknown acute dermal toxicity.
12% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Benzoate ester	27138-31-4	45 - 70
Proprietary polymer#1	Trade Secret*	9 - 25
Benzoate esters	None	3 - 10.5

Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	148861-07-8	5 - 10 Trade Secret *
Amorphous silica	67762-90-7	<= 5
Proprietary polymer#2	Trade Secret*	0.15 - 1.25
1,3-Propanediamine	109-76-2	0.1 - 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:
Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:
Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Amine Compounds	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Silica: Amorphous, including natural diatomaceous earth	67762-90-7	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Full Face Shield
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Color	Off-White
Odor	Acrylic
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*No Data Available*
Boiling Point	> 250 ºF
Flash Point	>=201 ºF [*Test Method:*Closed Cup]
Evaporation rate	*No Data Available*
Flammability	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapor Pressure	*No Data Available*

Relative Vapor Density	*No Data Available*
Density	1.078 g/ml
Relative Density	1.078 [*Ref Std:*WATER=1]
Solubility in Water	Negligible
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	5,882 mm2/sec
Hazardous Air Pollutants	0 % weight
Molecular weight	*No Data Available*
VOC Less H2O & Exempt Solvents	<=4 g/l [*Test Method:*calculated SCAQMD rule 443.1] [*Details:*as supplied]
VOC Less H2O & Exempt Solvents	<=10 g/l [*Test Method:*calculated SCAQMD rule 443.1] [*Details:*When used as intended with Part B]
Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials
Strong acids
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction in sensitive people: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin Contact:
Harmful in contact with skin. Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:
Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Additional Information:
Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >1,000 - =2,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >10 - =20 mg/l
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
Benzoate ester	Dermal	Rat	LD50 > 2,000 mg/kg
Benzoate ester	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Benzoate ester	Ingestion	Rat	LD50 3,295 mg/kg
Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	Dermal	similar compounds	LD50 178 mg/kg
Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	Inhalation-Vapor (4 hours)	similar compounds	LC50 1.4 mg/l
Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	Ingestion	similar compounds	LD50 235 mg/kg
Amorphous silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous silica	Ingestion	Rat	LD50 > 5,110 mg/kg
1,3-Propanediamine	Dermal	Rabbit	LD50 178 mg/kg
1,3-Propanediamine	Inhalation-Vapor (4 hours)	Rat	LC50 > 20 mg/l
1,3-Propanediamine	Ingestion	Rat	LD50 311 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Benzoate ester	Rabbit	No significant irritation
Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	similar compounds	Corrosive
Amorphous silica	Rabbit	No significant irritation
1,3-Propanediamine	In vitro data	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Benzoate ester	Rabbit	No significant irritation
Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	similar compounds	Corrosive
Amorphous silica	Rabbit	No significant irritation
1,3-Propanediamine	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Benzoate ester	Guinea pig	Not classified
Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	similar compounds	Sensitizing
Amorphous silica	Human and animal	Not classified
1,3-Propanediamine	similar compounds	Sensitizing

Respiratory Sensitization

Name	Species	Value
Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	similar compounds	Some positive data exist, but the data are not sufficient for classification
1,3-Propanediamine	similar compounds	Some positive data exist, but the data are not sufficient for classification

Germ Cell Mutagenicity

Name	Route	Value
Benzoate ester	In Vitro	Not mutagenic
Amorphous silica	In Vitro	Not mutagenic
1,3-Propanediamine	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Amorphous silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration

Benzoate ester	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Benzoate ester	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Benzoate ester	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Amorphous silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Boron, triethyl(1,3-propanediamine-N)-, (T-4)-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
1,3-Propanediamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Benzoate ester	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Benzoate ester	Ingestion	liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Amorphous silica	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Amorphous silica	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not Applicable.

Health Hazards
Acute toxicity
Hazard Not Otherwise Classified (HNOC)
Respiratory or Skin Sensitization
Serious eye damage or eye irritation
Skin Corrosion or Irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	46-3713-8	**Version Number:**	1.03
Issue Date:	09/14/26	**Supersedes Date:**	09/08/26

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	46-3715-3	**Version Number:**	1.05
Issue Date:	09/14/26	**Supersedes Date:**	09/14/26

SECTION 1: Identification

1.1. Product identifier
3M™ Scotch-Weld™ Structural Plastic Adhesive DP8115NS, Off-White, Part B

Product Identification Numbers
LA-D100-3915-3, LA-D100-3915-4

1.2. Recommended use and restrictions on use

Recommended use
Adhesive, Industrial use

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification
Skin Sensitizer: Category 1.

2.2. Label elements
Signal word
Warning

Symbols
Exclamation mark |

Pictograms



Hazard Statements

May cause an allergic skin reaction.

Precautionary statements

Prevention:
Avoid breathing vapors.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves.

Response:
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical attention.
Take off contaminated clothing and wash it before reuse.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

33% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Benzyl methacrylate	2495-37-6	40 - 50
2-Ethylhexyl methacrylate	688-84-6	10 - 30 Trade Secret *
Proprietary polymer	Trade Secret*	10 - 30
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	1 - 7
Amorphous silica	67762-90-7	<= 2
Acrylic copolymer	Trade Secret*	<= 1.5
Proprietary component	Trade Secret*	<= 1.5
Phosphate methacrylate	1627542-04-4	<= 0.9
HEMA	868-77-9	<= 0.28
Methyl Methacrylate	80-62-6	<= 0.25

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

5.3. Special protective actions for fire-fighters
Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Silica: Amorphous, including natural diatomaceous earth	67762-90-7	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Methyl Methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	A4: Not class. as human carcin, Dermal Sensitizer
Methyl Methacrylate	80-62-6	OSHA	TWA:410 mg/m3(100 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection
None required.

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection
None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Color	Off-White
Odor	Acrylate
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*No Data Available*
Boiling Point	*Not Applicable*
Flash Point	> 250 ºF [*Test Method:*Closed Cup]
Evaporation rate	*Not Applicable*
Flammability	Not Applicable
Flammable Limits(LEL)	*Not Applicable*
Flammable Limits(UEL)	*Not Applicable*
Vapor Pressure	*No Data Available*
Relative Vapor Density	*Not Applicable*
Density	1.006 g/ml
Relative Density	1.006 [*Ref Std:*WATER=1]
Solubility in Water	Nil
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	8,100 mm2/sec
Molecular weight	*Not Applicable*
VOC Less H2O & Exempt Solvents	<=7 g/l [*Test Method:*tested per EPA method 24] [*Details:*When used as intended with Part A]
Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials
Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
No known health effects.

Skin Contact:
Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:
No known health effects.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Benzyl methacrylate	Dermal	Rat	LD50 > 2,000 mg/kg
Benzyl methacrylate	Ingestion	Rat	LD50 4,820 mg/kg
2-Ethylhexyl methacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2-Ethylhexyl methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Dermal	Rat	LD50 > 2,000 mg/kg
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	Rat	LD50 > 5,000 mg/kg
Amorphous silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous silica	Ingestion	Rat	LD50 > 5,110 mg/kg

Phosphate methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Phosphate methacrylate	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
HEMA	Dermal	Rabbit	LD50 > 5,000 mg/kg
HEMA	Ingestion	Rat	LD50 5,564 mg/kg
Methyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl Methacrylate	Inhalation-Vapor (4 hours)	Rat	LC50 29.8 mg/l
Methyl Methacrylate	Ingestion	Rat	LD50 7,900 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Benzyl methacrylate	Rabbit	Minimal irritation
2-Ethylhexyl methacrylate	Rabbit	Minimal irritation
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Rabbit	No significant irritation
Amorphous silica	Rabbit	No significant irritation
Phosphate methacrylate	Professional judgement	No significant irritation
HEMA	Rabbit	Minimal irritation
Methyl Methacrylate	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Benzyl methacrylate	Rabbit	No significant irritation
2-Ethylhexyl methacrylate	Rabbit	No significant irritation
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Rabbit	No significant irritation
Amorphous silica	Rabbit	No significant irritation
Phosphate methacrylate	Professional judgement	Corrosive
HEMA	Rabbit	Moderate irritant
Methyl Methacrylate	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
Benzyl methacrylate	Mouse	Sensitizing
2-Ethylhexyl methacrylate	Guinea pig	Sensitizing
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Mouse	Not classified
Amorphous silica	Human and animal	Not classified
Phosphate methacrylate	Professional judgement	Sensitizing
HEMA	Human and animal	Sensitizing
Methyl Methacrylate	Human and animal	Sensitizing

Respiratory Sensitization

Name	Species	Value

Methyl Methacrylate	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Benzyl methacrylate	In Vitro	Not mutagenic
2-Ethylhexyl methacrylate	In Vitro	Not mutagenic
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	In vivo	Not mutagenic
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	In Vitro	Some positive data exist, but the data are not sufficient for classification
Amorphous silica	In Vitro	Not mutagenic
Phosphate methacrylate	In Vitro	Not mutagenic
HEMA	In vivo	Not mutagenic
HEMA	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Methacrylate	In vivo	Not mutagenic
Methyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Amorphous silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Methyl Methacrylate	Ingestion	Rat	Not carcinogenic
Methyl Methacrylate	Inhalation	Human and animal	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Benzyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	premating into lactation
Benzyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	33 days
Benzyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	premating into lactation
2-Ethylhexyl methacrylate	Ingestion	Not classified for male reproduction		NOAEL 1,000 mg/kg/day	49 days
2-Ethylhexyl methacrylate	Ingestion	Not classified for female reproduction		NOAEL 300 mg/kg/day	premating into lactation
2-Ethylhexyl methacrylate	Ingestion	Not classified for development		NOAEL 300 mg/kg/day	during gestation
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	premating into lactation
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	56 days
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Amorphous silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
HEMA	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
HEMA	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days

HEMA	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Methyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Methyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Methyl Methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 450 mg/kg/day	during gestation
Methyl Methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Phosphate methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Methyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Benzyl methacrylate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	33 days
Benzyl methacrylate	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	33 days
Benzyl methacrylate	Ingestion	nervous system	Not classified	Rat	NOAEL 500 mg/kg/day	33 days
Benzyl methacrylate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	33 days
2-Ethylhexyl methacrylate	Ingestion	heart	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
2-Ethylhexyl methacrylate	Ingestion	endocrine system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
2-Ethylhexyl methacrylate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
2-Ethylhexyl methacrylate	Ingestion	liver	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
2-Ethylhexyl methacrylate	Ingestion	immune system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
2-Ethylhexyl methacrylate	Ingestion	nervous system	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
2-Ethylhexyl methacrylate	Ingestion	eyes	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
2-Ethylhexyl methacrylate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 360 mg/kg/day	90 days
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	nervous system	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	eyes	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Amorphous silica	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Amorphous silica	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Dermal	peripheral nervous	Not classified	Human	NOAEL Not	occupational

		system			available	exposure
Methyl Methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
Methyl Methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl Methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	heart	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	skin	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	endocrine system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	liver	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	muscles	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	nervous system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Methyl Methacrylate	Ingestion	respiratory system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not Applicable.

Health Hazards
Respiratory or Skin Sensitization

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	46-3715-3	**Version Number:**	1.05
Issue Date:	09/14/26	**Supersedes Date:**	09/14/26

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer

may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com