



## Safety Data Sheet

Copyright,2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	07-9764-7	<b>Version number:</b>	21.04
<b>Revision date:</b>	19/03/2026	<b>Supersedes date:</b>	17/10/2025

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M™ Adhesion Promoter No. 86A

#### Product Identification Numbers

70-0707-4280-7

7000002051

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2  
**Telephone:** +353 1 280 3555  
**E Mail:** ner-productstewardship@mmm.com  
**Website:** www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

##### CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318  
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

## 2.2. Label elements

### CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### Symbols

GHS02 (Flame) |GHS05 (Corrosion) |GHS07 (Exclamation mark) |

#### Pictograms



#### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
propan-2-ol	67-63-0	200-661-7	40 - 60
propan-1-ol	71-23-8	200-746-9	30 - 45

#### HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.

#### PRECAUTIONARY STATEMENTS

##### Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261A	Avoid breathing vapours.
P280A	Wear eye/face protection.

##### Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

## 2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (REACH-No.) 01-2119457558-25,01-2119457558-25-0208	40 - 60	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
propan-1-ol	(CAS-No.) 71-23-8 (EC-No.) 200-746-9 (REACH-No.) 01-2119486761-29	30 - 45	Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336
POLYIMIDE RESIN	Trade Secret	5 - 10	Substance not classified as hazardous
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	< 4	Substance not classified as hazardous
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	(CAS-No.) 68411-46-1 (EC-No.) 270-128-1	< 0.25	Repr. 2, H361f Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).  
Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Hydrocarbons.  
Carbon monoxide  
Carbon dioxide.  
Oxides of nitrogen.

#### Condition

During combustion.  
During combustion.  
During combustion.  
During combustion.

### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
propan-2-ol	67-63-0	Ireland OELs	TWA(8 hours):200 ppm;STEL(15 minutes):400 ppm	SKIN
propan-1-ol	71-23-8	Ireland OELs	TWA(8 hours):100 ppm	SKIN

Ireland OELs : Ireland. OELs  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
propan-2-ol		Agricultural soil	28 mg/kg d.w.
propan-2-ol		Concentration in marine fish for secondary poisoning	160 mg/kg w.w.
propan-2-ol		Freshwater	140.9 mg/l
propan-2-ol		Freshwater sediments	552 mg/kg d.w.
propan-2-ol		Intermittent releases to water	140.9 mg/l
propan-2-ol		Marine Water	140.9 mg/l
propan-2-ol		Marine water sediments	552 mg/kg d.w.
propan-2-ol		Sewage Treatment Plant	2,251 mg/l

**Recommended monitoring procedures:** Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

## 8.2. Exposure controls

In addition, refer to the annex for more information.

### 8.2.1. Engineering controls

Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

#### *Applicable Norms/Standards*

Use eye protection conforming to EN 16321

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.5	=>8 hours
Fluoroelastomer	0.4	=>8 hours
Nitrile rubber.	0.35	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

#### *Applicable Norms/Standards*

Use gloves tested to EN 374

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### *Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter types A & P

### 8.2.3. Environmental exposure controls

Refer to Annex

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Colourless
Odor	Slight Solvent
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	approximately 82.8 °C
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	2 % volume
Flammable Limits(UEL)	12.7 % volume
Flash point	11.7 °C [ <i>Test Method: Closed Cup</i> ]
Autoignition temperature	398.9 °C
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-polar/aprotic</i>
Kinematic Viscosity	91.5 mm <sup>2</sup> /sec
Water solubility	Appreciable
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	33 mm Hg [ <i>@ 68 °F</i> ]
Density	<i>No data available.</i>
Relative density	0.82 [ <i>Ref Std: WATER=1</i> ]
Relative Vapour Density	2.1 [ <i>Ref Std: AIR=1</i> ]
Particle Characteristics	<i>Not applicable.</i>

## 9.2. Other information

## 9.2.2 Other safety characteristics

EU Volatile Organic Compounds

741 g/l

Evaporation rate

*No data available.*

Molecular weight

*No data available.*

## SECTION 10: Stability and reactivity

## 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

## 10.2 Chemical stability

Stable.

## 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## 10.4 Conditions to avoid

Sparks and/or flames.

## 10.5 Incompatible materials

Strong oxidising agents.

## 10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

##### Skin contact

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

##### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

##### Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

##### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

##### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

##### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg

propan-2-ol	Dermal	Rabbit	LD50 12,870 mg/kg
propan-2-ol	Inhalation-Vapour (4 hours)	Rat	LC50 72.6 mg/l
propan-2-ol	Ingestion	Rat	LD50 4,710 mg/kg
propan-1-ol	Dermal	Rabbit	LD50 4,000 mg/kg
propan-1-ol	Inhalation-Vapour (4 hours)	Rat	LC50 > 34 mg/l
propan-1-ol	Ingestion	Rat	LD50 estimated to be 2,000 - 5,000 mg/kg
POLYIMIDE RESIN	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
POLYIMIDE RESIN	Ingestion	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Dermal	Rat	LD50 > 2,000 mg/kg
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
propan-2-ol	Multiple animal species	No significant irritation
propan-1-ol	Rabbit	Minimal irritation
POLYIMIDE RESIN	Professional judgement	No significant irritation
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
propan-2-ol	Rabbit	Severe irritant
propan-1-ol	Rabbit	Severe irritant
POLYIMIDE RESIN	Professional judgement	No significant irritation
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Rabbit	Mild irritant

**Skin Sensitisation**

Name	Species	Value
propan-2-ol	Guinea pig	Not classified
propan-1-ol	Guinea pig	Not classified
POLYIMIDE RESIN	Professional judgement	Not classified
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
propan-2-ol	In Vitro	Not mutagenic
propan-2-ol	In vivo	Not mutagenic
propan-1-ol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
propan-2-ol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
propan-1-ol	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
propan-2-ol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
propan-2-ol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
propan-2-ol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
propan-2-ol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
propan-1-ol	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.6 mg/l	6 weeks
propan-1-ol	Inhalation	Not classified for development	Rat	NOAEL 8.6 mg/l	during gestation
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Not classified for male reproduction	Rat	NOAEL 54 mg/kg/day	2 generation
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Not classified for development	Rat	NOAEL 18 mg/kg/day	2 generation
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	Toxic to female reproduction	Rat	NOAEL 54 mg/kg/day	2 generation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
propan-2-ol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propan-2-ol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
propan-2-ol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
propan-2-ol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
propan-1-ol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Mouse	NOAEL 5 mg/l	4 hours
propan-1-ol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	
propan-1-ol	Ingestion	central nervous	May cause drowsiness or	Professio	NOAEL Not	

		system depression	dizziness	nal judgement	available	
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
propan-2-ol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
propan-2-ol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
propan-2-ol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
propan-1-ol	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 70 mg/kg/day	83 weeks
propan-1-ol	Ingestion	liver	Not classified	Rat	LOAEL 70 mg/kg/day	83 weeks
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 54 mg/kg/day	98 days
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Ingestion	endocrine system   liver   kidney and/or bladder   heart   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles   eyes   respiratory system	Not classified	Rat	NOAEL 225 mg/kg/day	28 days

### Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

## SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
propan-2-ol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
propan-2-ol	67-63-0	Green algae	Experimental	72 hours	EC50	>1,000 mg/l

propan-2-ol	67-63-0	Invertebrate	Experimental	24 hours	LC50	>10,000 mg/l
propan-2-ol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
propan-2-ol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
propan-2-ol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
propan-2-ol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l
propan-1-ol	71-23-8	Activated sludge	Experimental	3 hours	IC50	>1,000 mg/l
propan-1-ol	71-23-8	Algae or other aquatic plants	Experimental	96 hours	EC50	4,480 mg/l
propan-1-ol	71-23-8	Fathead minnow	Experimental	96 hours	LC50	4,555 mg/l
propan-1-ol	71-23-8	Fish	Experimental	96 hours	LC50	3,000 mg/l
propan-1-ol	71-23-8	Water flea	Experimental	48 hours	EC50	3,642 mg/l
propan-1-ol	71-23-8	Water flea	Experimental	21 days	NOEC	100 mg/l
POLYIMIDE RESIN	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Water flea	Experimental	24 hours	EC50	0.82 mg/l
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Zebra Fish	Experimental	96 hours	LC50	>47.05 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
propan-2-ol	67-63-0	Experimental Biodegradation	14 days	BOD	86 %BOD/ThOD	OECD 301C - MITI test (I)
propan-1-ol	71-23-8	Experimental Biodegradation	20 days	BOD	73 %BOD/ThOD	OECD 301D - Closed bottle test
POLYIMIDE RESIN	Trade Secret	Data not available or insufficient	N/A	N/A	N/A	N/A
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Experimental Biodegradation	28 days	CO2 evolution	<=1 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2

## 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
propan-2-ol	67-63-0	Experimental Bioconcentration		Log Kow	0.05	
propan-1-ol	71-23-8	Experimental Bioconcentration		Log Kow	0.2	
POLYIMIDE RESIN	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1	Analogous Compound BCF - Fish	42 days	Bioaccumulation factor	1730	

## 12.4. Mobility in soil

No test data available.

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Endocrine disrupting properties**

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

070104\* Other organic solvents, washing liquids and mother liquors  
20 01 13\* Solvents

**SECTION 14: Transportation information**

	<b>Ground Transport (ADR)</b>	<b>Air Transport (IATA)</b>	<b>Marine Transport (IMDG)</b>
<b>14.1 - UN Number or ID number</b>	UN1987	UN1987	UN1987
<b>14.2 UN proper shipping name</b>	ALCOHOLS, N.O.S.(ISOPROPYL ALCOHOL; PROPYL ALCOHOL)	ALCOHOLS, N.O.S.(ISOPROPYL ALCOHOL; PROPYL ALCOHOL)	ALCOHOLS, N.O.S.(ISOPROPYL ALCOHOL; PROPYL ALCOHOL)
<b>14.3 Transport hazard class(es)</b>	3	3	3
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	Not Environmentally Hazardous	Not applicable.	Not a Marine Pollutant

<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	F1	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

\*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

None

#### Regulation (EU) No 649/2012

No chemicals listed

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No

1907/2006, as amended.

**SECTION 16: Other information****List of relevant H statements**

H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Revision information:**

EU Section 14 - Table Data information was added.

EU Section 14 - Table Headers information was added.

Industrial Use of Coatings: Section 16: Annex information was modified.

Label: Graphic information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 8: PNEC table row information was added.

Section 9: Vapour pressure value information was modified.

Section 14 Classification Code – Main Heading information was deleted.

Section 14 Classification Code – Regulation Data information was deleted.

Section 14 Control Temperature – Main Heading information was deleted.

Section 14 Control Temperature – Regulation Data information was deleted.

Section 14 Emergency Temperature – Main Heading information was deleted.

Section 14 Emergency Temperature – Regulation Data information was deleted.

Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.

Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.

Section 14 Other Dangerous Goods – Main Heading information was deleted.

Section 14 Other Dangerous Goods – Regulation Data information was deleted.

Section 14 Packing Group – Main Heading information was deleted.

Section 14 Packing Group – Regulation Data information was deleted.

Section 14 Proper Shipping Name information was deleted.

Section 14 Regulations – Main Headings information was deleted.

Section 14 Segregation – Regulation Data information was deleted.

Section 14 Segregation Code – Main Heading information was deleted.

Section 14 Special Precautions – Main Heading information was deleted.

Section 14 Special Precautions – Regulation Data information was deleted.

Section 14 Transport in bulk – Regulation Data information was deleted.

Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was deleted.

Section 14 UN Number Column data information was deleted.

Section 14 UN Number information was deleted.

**Annex**

<b>1. Title</b>	
<b>Substance identification</b>	propan-2-ol; EC No. 200-661-7; CAS Nbr 67-63-0;
<b>Exposure Scenario Name</b>	Industrial Use of Coatings
<b>Lifecycle Stage</b>	Use at industrial sites

<b>Contributing activities</b>	PROC 07 -Industrial spraying PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
<b>Processes, tasks and activities covered</b>	Application of product with a roller or brush. (PROC 10) Spraying of substances/mixtures. (PROC 7,11) Transfers with dedicated controls, including loading, filling, dumping, bagging. (PROC 8b) Transfers without dedicated controls, including loading, filling, dumping, bagging. (PROC 8a)
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day;  <b>Task: Indoor spraying;</b> Indoors with enhanced general ventilation; Indoors with good general ventilation;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed; ; The following task-specific risk management measures apply in addition to those listed above: <b>Task: PROC07;</b> <b>Human Health;</b> Laminar Flow Booth;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at [www.3M.com](http://www.3M.com)